PROJECT DEVELOPMENT PHASE SPRINT-3

Date	12 November 2022
Team ID	PNT2022TMID49939
Project Name	Smart farmer- IoT based smart farming application.

Code:

```
#include <ESP8266WiFi.h>
#include <ESP8266HTTPClient.h>
String thingSpeakAddress= "http://api.thingspeak.com/update?";
String writeAPIKey;
String tsfield1Name;
String request_string,request_string1;
HTTPClient http;
#include <DHT.h>
#include <ESP8266WiFi.h>
String apiKey = "77921LPMGM2OAGQE";
char *ssid = "DESKTOP";
char *pass = "asdfghjkl";
char* server = "api.thingspeak.com";
#define DHTPIN 0
dht(DHTPIN, DHT11);
WiFiClient client;
void setup()
dht.begin();
Serial.begin(115200);
delay(3000);
WiFi.disconnect();
Serial.println("START");
WiFi.begin("DESKTOP", "asdfghjkl");
while ((!(WiFi.status() == WL_CONNECTED)))
delay(300);
Serial.println("...");
Serial.println("I AM CONNECTED");
void loop()
if (client.connect("api.thingspeak.com",80))
request_string = thingSpeakAddress;
request_string += "key=";
```

```
request_string += "77921LPMGM2OAGQE";
request_string += "&";
request_string += "field3";
request_string += "=";
request string += analogRead(A0);
http.begin(request_string);
http.GET();
http.end();
delay(10);
float h = dht.readHumidity();
float t = dht.readTemperature();
if (isnan(h) || isnan(t))
Serial.println("Failed to read from DHT sensor!");
return;
if (client.connect(server,80))
String postStr = apiKey;
postStr +="&field1=";
postStr += String(t);
postStr +="&field2=";
postStr += String(h);
postStr += "\langle r \rangle r \rangle r;
client.print("POST /update HTTP/1.1\n");
client.print("Host: api.thingspeak.com\n");
client.print("Connection: close\n");
client.print("X-THINGSPEAKAPIKEY: "+apiKey+"\n");
client.print("Content-Type: application/x-www-form-urlencoded\n"); client.print("Content-
Length: ");
client.print(postStr.length());
client.print("\n\n");
client.print(postStr);
Serial.print("Temperature: ");
Serial.print(t);
Serial.print(" degrees Celcius, Humidity: ");
Serial.print(h);
Serial.print(" Soil Sensor ");
Serial.print(A0);
Serial.println("%. Send to Thingspeak.");
client.stop();
Serial.println("Waiting...");
delay(10);
}
```