

1952. Minimum Sideway Jumps

Difficulty : Medium

<https://leetcode.com/problems/minimum-sideway-jumps>

There is a **3 lane road** of length n that consists of $n + 1$ **points** labeled from 0 to n . A frog **starts** at point 0 in the **second** lane and wants to jump to point n . However, there could be obstacles along the way.

You are given an array `obstacles` of length $n + 1$ where each `obstacles[i]` (**ranging from 0 to 3**) describes an obstacle on the lane `obstacles[i]` at point i . If `obstacles[i] == 0`, there are no obstacles at point i . There will be **at most one** obstacle in the 3 lanes at each point.

- For example, if `obstacles[2] == 1`, then there is an obstacle on lane 1 at point 2.


The frog can only travel from point i to point $i + 1$ on the same lane if there is not an obstacle on the lane at point $i + 1$. To avoid obstacles, the frog can also perform a **side jump** to jump to **another** lane (even if they are not adjacent) at the **same** point if there is no obstacle on the new lane.

- For example, the frog can jump from lane 3 at point 3 to lane 1 at point 3.

Return the **minimum number of side jumps** the frog needs to reach **any lane** at point n starting from lane 2 at point 0 .

Note: There will be no obstacles on points 0 and n .

Example 1:




Input: `obstacles = [0,1,2,3,0]`

Output: 2

Explanation: The optimal solution is shown by the arrows above. There are 2 side jumps (red arrows). Note that the frog can jump over obstacles only when making side jumps (as shown at point 2).

Example 2:




Input: `obstacles = [0,1,1,3,3,0]`

Output: 0

Explanation: There are no obstacles on lane 2. No side jumps are required.

Example 3:



Input: obstacles = [0,2,1,0,3,0]

Output: 2

Explanation: The optimal solution is shown by the arrows above. There are 2 side jumps.

Constraints:

- obstacles.length == n + 1
- 1 <= n <= 5 * 10⁵
- 0 <= obstacles[i] <= 3
- obstacles[0] == obstacles[n] == 0