

2131. Smallest Missing Genetic Value in Each Subtree

Difficulty : Hard

<https://leetcode.com/problems/smallest-missing-genetic-value-in-each-subtree>


There is a **family tree** rooted at 0 consisting of n nodes numbered 0 to $n - 1$. You are given a **0-indexed** integer array `parents`, where `parents[i]` is the parent for node i . Since node 0 is the **root**, `parents[0] == -1`.

There are 10^5 genetic values, each represented by an integer in the **inclusive** range $[1, 10^5]$. You are given a **0-indexed** integer array `nums`, where `nums[i]` is a **distinct** genetic value for node i .

Return an array `ans` of length n where `ans[i]` is the **smallest** genetic value that is **missing** from the subtree rooted at node i .

The **subtree** rooted at a node x contains node x and all of its **descendant** nodes.

Example 1:




Input: `parents = [-1,0,0,2]`, `nums = [1,2,3,4]`

Output: `[5,1,1,1]`

Explanation: The answer for each subtree is calculated as follows:

- 0: The subtree contains nodes `[0,1,2,3]` with values `[1,2,3,4]`. 5 is the smallest missing value.
- 1: The subtree contains only node 1 with value 2. 1 is the smallest missing value.
- 2: The subtree contains nodes `[2,3]` with values `[3,4]`. 1 is the smallest missing value.
- 3: The subtree contains only node 3 with value 4. 1 is the smallest missing value.

Example 2:



Input: `parents = [-1,0,1,0,3,3]`, `nums = [5,4,6,2,1,3]`

Output: `[7,1,1,4,2,1]`

Explanation: The answer for each subtree is calculated as follows:

- 0: The subtree contains nodes `[0,1,2,3,4,5]` with values `[5,4,6,2,1,3]`. 7 is the smallest missing value.
- 1: The subtree contains nodes `[1,2]` with values `[4,6]`. 1 is the smallest missing value.
- 2: The subtree contains only node 2 with value 6. 1 is the smallest missing value.
- 3: The subtree contains nodes `[3,4,5]` with values `[2,1,3]`. 4 is the smallest missing value.
- 4: The subtree contains only node 4 with value 1. 2 is the smallest missing value.
- 5: The subtree contains only node 5 with value 3. 1 is the smallest missing value.

Example 3:

Input: `parents = [-1,2,3,0,2,4,1]`, `nums = [2,3,4,5,6,7,8]`

Output: `[1,1,1,1,1,1,1]`

Explanation: The value 1 is missing from all the subtrees.

Constraints:

- $n == \text{parents.length} == \text{nums.length}$
- $2 \leq n \leq 10^5$

- $0 \leq \text{parents}[i] \leq n - 1$ for $i \neq 0$
- $\text{parents}[0] == -1$
- parents represents a valid tree.
- $1 \leq \text{nums}[i] \leq 10^5$
- Each $\text{nums}[i]$ is distinct.