

2300™ Process Module

Facility

PM BOM Version 571-800096-002

2300 Software Version 1.4.3

System Version 2300

PUBLISHED BY

Publications Department
Lam Research Corporation
4650 Cushing Parkway
Fremont, California 94538-6470
E-mail: pubs@lamrc.com

Copyright ©2001 by Lam Research Corporation. Printed in the United States of America. All Rights Reserved.

The information conveyed in this document has been carefully checked and is believed to be reliable at the time of printing. However, Lam Research Corporation makes no warranty regarding the information set forth in this document and assumes no responsibility for any errors or inaccuracies contained herein. Lam Research Corporation is not obligated to update or correct any information contained in this document. Lam Research Corporation reserves the right to change products or specifications at any time without notice.

Modifications to Lam products may affect their safe operation and may also affect compliance with various laws and regulations governing their operation. To reduce the likelihood of interference, RF transmitters (cellular telephones, CB radios, cordless telephones) should not be used in the vicinity of Lam products.

Lam recommends that customers check with local fire departments within their jurisdictions to ensure all marking requirements are satisfied.

No part of this document may be reproduced in any form for any purpose without the prior written permission of Lam Research Corporation.

2300, 384T, 4520XLE, Advanced Capability Rainbow, Alliance, AutoEtch, Classic, CoolPORT, Continuum, DSS, DSS-150, DSS-200, Deep SubMicron and DSP, EndPoint Plus, Envision, Envoy, Exelan, the Lam logo, Oxide, Rainbow, Synergy, Synergy Integra, Teres, Transformer Coupled Plasma, TCP, and Versys are trademarks of Lam Research Corporation. All other trademarks or registered trademarks are the property of their respective holders. Mention of third-party products or services is for informational purposes only, and does not constitute an endorsement or recommendation.

Revision A
October 2001

2300 Process Module Facility Legend:

This manual combines into one manual the process module facility information from the following process module types: 2300 Metal, Silicon, and Exelan. This manual replaces all previous process module type manuals.

Contents

253-800096-001, Revision D, 300MM TCP PM Facility Specification 1

253-810068-001, Revision J, 300MM Facility Requirements Drawing 7

251-800096-001, Revision C, 300MM PM P&ID Diagram 21

224-800096-001, Revision D, 300MM Process Module Interconnect Diagram 27

224-800096-002, Revision E, 300MM PM AC DC Interconnect Diagram 29

224-800096-003, Revision D, 300MM PM Heaters Interconnect Diagram 31

224-800096-004, Revision D, 300MM PM Thermocouples Interconnect Diagram 33

224-800096-005, Revision D, 300MM PM Overtemp Interconnect Diagram 35

224-800096-006, Revision E, 300MM PM Communications Interconnect Diagram 37

224-800096-007, Revision E, 300MM PM Hardware Interlock Interconnect Diagram 39

224-800096-008, Revision E, 300MM PM Node 1 Interconnect Diagram 41

224-800096-009, Revision E, 300MM PM Node 5 Interconnect Diagram 43

224-800096-402, Revision A, DFC PM AC DC Distribution Interconnect Diagram 45


224-800096-406, Revision A, DFC PM Communication Interconnect Diagram 47


224-800096-407, Revision A, DFC PM Interlock Interconnect Diagram 49

224-800096-408, Revision A, DFC PM Node 1 Interconnect Diagram 51

224-800096-409, Revision A, DFC Node 5 Interconnect Diagram 53

253-802968-002, Revision B, Installation Template for 2300 Process Module 55








CHART #1 GAS BOX TO PM PLUMBING		
DESCRIPTION	GAS LINE FITTING	DBL CONTAINMENT FITTING
PROCESS GAS DELIVERY LINE	1/4 MVCR	1.0" OD TUBE (FOR CONNECTION OF 1.0" ID CORRUGATED HOSE W/HOSE CLAMP)
PROCESS GAS DELIVERY LINE	1/4 MVCR	1.0" OD TUBE (FOR CONNECTION OF 1.0" ID CORRUGATED HOSE W/HOSE CLAMP)

TABLE 1 ENVIRONMENT					
DESCRIPTION	TEMPERATURE		HUMIDITY	VIBRATION	
	°C	±	%	SENSITIVE	EMISSION
PROCESS MODULE	25	5	<50	SLIGHT	NO

TABLE 2 THERMAL OUTPUT				
DESCRIPTION	(BTU/hr)			
	CARRIED BY WATER	CARRIED BY EXHAUST	DISPERSED TO ENVIRONMENT	TOTAL OUTPUT
PROCESS MODULE	9K	8K	20K	37.4K

TABLE 3 PROCESS COOLING WATER FLOW SPECIFICATIONS						
DESCRIPTION	FLOW		FITTING	PRESSURE		TEMP
	GPM	L/MIN	SIZE	ΔPSI	MAX	
PROCESS MODULE	4.5	17.04	1/2" HOSE BARB	40	100	15-25°C
2300 EXELAN	9	34.07				

TABLE 4 CDA							
DESCRIPTION	PRESSURE		FITTING		SOURCE	USAGE	FLOW (LPM)
	PSI	±	SIZE	TYPE			
PROCESS MODULE	90	5	3/8"	COMPRESSION	TM	INTER-MITTENT	10

TABLE 5 HOUSE N2							
DESCRIPTION	PRESSURE		FITTING		SOURCE	USAGE	FLOW
	PSI	±	SIZE	TYPE			
TURBOMOLECULAR PUMP PURGE & FORELINE BALLAST	50	2	1/4"	VCR (MALE)	TM	CONT	100 SCCM (MIN)

TABLE 6 SYSTEM EXHAUST REQUIREMENTS									
DESCRIPTION	DRAW (CFM)	H2O IN	SYSTEM	HAZARD	DUCT	SIZE	FLANGE TYPE	OIL CONTENT	REMOVABLE CONNECTION
UPPER ENCLOSURE	150	.50	SCRUBBER	POSSIBLE *	4.0	10.2	TUBE	NO	YES
DUCT MATERIAL	FLEXIBLE MATERIAL OR SPIRAL WIRE REINFORCED PVC FUME DUCT (WITH V-ø FLAMMABILITY RATING UNDER UL-94 AND UL RECOGNITION)								

*ONLY IN THE EVENT OF A PRIMARY CONTAINMENT FAILURE, EXHAUST PROVIDES SECONDARY BACKUP CONTAINMENT.
*IT IS RECOMMENDED THAT THE DRAW BE MEASURED AT A POINT FOUR DUCT DIAMETERS DOWNSTREAM OF THE EXHAUST PORT.

TABLE 7 POWER REQUIREMENTS							
DESCRIPTION	VOLTS (AC)	Hz	PHASE	WIRE	TYPE	AMPS	CONDUIT REQUIRED
MAIN POWER	208 +10% -10%	50/60	3	4	DELTA	VERSYS	50
						2300 EXELAN	70

SINGLE POWER INPUT FOR SYSTEM. REQUIRES AN 8-FOOT EARTH GROUND COPPER-CLAD ROD.

TABLE 8 HELIUM							
DESCRIPTION	PRESSURE		FITTING		FLOW	SOURCE	USAGE
	PSI	±	SIZE	TYPE			
WAFER COOLING	10	2	1/4"	VCR (MALE)	50 SCCM MIN	TM	INTER-MITTENT

TABLE 16 WEIGHT	
TOTAL WEIGHT LBS (KG)	1500 (680)
LOAD PER LEVELING PAD *A* LBS (KG)	375 (170)

TABLE 16 PHYSICAL DIMENSIONS							
DESCRIPTION	WIDTH IN	MAX CM	DEPTH IN	MAX CM	HEIGHT IN	MAX CM	CENTER OF GRAVITY x,y,z FROM 0,0
300mm PM	34.22	86.9	29.59	75.1	76.95	195.3	1.05, 15.87, 31.34

TABLE 16 SEISMIC TIE DOWN	
ATTACHMENT FEATURE	1/2-13 UNC X .68 MAX

PROPRIETARY INFORMATION NOTICE
THE NOTICE SET FORTH ON SHEET 1 IS INCORPORATED HEREIN BY REFERENCE.


		FREMONT, CA	
SIZE	DRAWING NO.	REV	D
D	253-800096-001		D
SCALE	NONE	SHEET 5 OF 6	

TABLE 9 ENVIRONMENT				
DESCRIPTION	TEMP	HUMIDITY	VIBRATION SENSITIVITY	EMISSION
CHILLER (EDWARDS 40/80*)	10-26°C	NON-CONDENSING	NONE	SLIGHT
ROUGHING PUMP (IH 600)	5-40°C	NON-CONDENSING 90% RA	NONE	YES

TABLE 10 THERMAL OUTPUT (BTU/HR)				
DESCRIPTION	WATER	EXHAUST	ENVIROMENT	TOTAL
CHILLER (EDWARDS 40/80*)	12.5K	N/A	2.5K	15K
ROUGHING PUMP (IH 600)	3.2K	3K	7K	16K

TABLE 11 PROCESS COOLING WATER FLOW SPECIFICATION					
DESCRIPTION	FLOW	PRESSURE Δ AT COMPONENT	MAX PRESSURE	FILTRATION	CONNECTION
CHILLER (EDWARDS 40/80*)	3-6 GPM (11.5-23 LPM)	40 PSI (MIN)	100 PSI	<200 μ	1/2" BARBED FITING
ROUGHING PUMP (IH 600)	4 LPM MIN	15 PSI	100 PSI	<200 μ	3/8" BSP FEMALE OUTLET 3/8" BSP MAL INLET


TABLE 12 HOUSE N2				
DESCRIPTION	FLOW	PRESSURE	FILTRATION	CONNECTION
ROUGHING PUMP (IH 600)	60 LPM MAX. 44 TYP	20-100 PSI	<30 μ	1/4" TUBE COMPRESSION FTG (MULTIPLE LOCATION ON THE PUMP)

TABLE 13 SCRUBBED EXHAUST REQUIREMENTS FOR BACKING PUMP			
DESCRIPTION	FLOW	CONNECTION	EXHAUST HAZARDS
ROUGHING PUMP (IH 600)	40 CFM BURST (ON PUMP DOWN) 1 LPM SCCM AVG	NW40	TOXIC, CORROSIVE, CONDENSABLE

TABLE 14 ELECTRICAL POWER REQUIREMENTS		
DESCRIPTION	POWER	HOOUP CONNECTION
CHILLER (EDWARDS 40/80*)	208 +10% -15% VAC 3ø 50/60 HZ 30 AMP	FITTED WITH 10" POWER CORD WITH 5 PIN TWIST LOCK (L21-30 P) PLUG
ROUGHING PUMP (IH 600)	208 +10% -10% VAC 3ø 50/60 HZ 26 AMP	TERMINAL BLOCK


TABLE 15 BACKING PUMP & PUMPLINE SPECIFICATIONS		
DESCRIPTION	PUMPING SPEED REQUIRED PM (OUTLET & TURBO)	PUMPLINE CONDUCTANCE- PM TO ROUGHING PUMP
BACKING PUMP (IH 600)	20 CFM 1 TORR	≥ 50 CFM 1 TORR

PROPRIETARY INFORMATION NOTICE
THE NOTICE SET FORTH ON SHEET 1 IS INCORPORATED HEREIN BY REFERENCE.


Lam
RESEARCH

FREMONT, CA


SIZE D	DRAWING NO. 253-800096-001	REV D
SCALE NONE	SHEET 6 OF 6	




Released
Printed: Wed Aug 8 17:05:45 GMT 2001
See ECO File (MF, L, 220) for Current Rev Status




Released
Printed: Wed Aug 8 17:05:53 GMT 2001
See ECO File (MF, L, 220) for Current Rev Status







Released
Printed: Wed Aug 8 17:06:00 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




Released
Printed: Wed Aug 8 17:06:07 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




Released
Printed: Wed Aug 8 17:06:22 GMT 2001
See ECO File (MF/L/220) for Current Rev Status




Released
Printed: Wed Aug 8 17:06:29 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




Released
Printed: Wed Aug 8 17:06:44 GMT 2001
See ECO File (MF,L,220) for Current Rev Status





Released
Printed: Wed Aug 8 17:06:51 GMT 2001
See ECO File (MF,L,220) for Current Rev Status



Released
Printed: Wed Aug 8 17:06:58 GMT 2001
See ECO File (MF,L,220) for Current Rev Status

TRANSPORT MODULE FACILITY REQUIREMENTS

TABLE 1. SYSTEM POWER REQUIREMENTS									
DESCRIPTION	SUPPLY POINT INTERCONNECT	VOLTS (AC)	Hz	PHASE	WIRE	TYPE	AMPS (MAX)	MAIN CB RATING	CONDUIT REQUIRED
MAIN SYSTEM POWER	----	208 +10% -10%	50/60	3	4	DELTA	350	400 AMPS	ø3"

- NOTE: 1. SINGLE POWER INPUT FOR SYSTEM. REQUIRES AN 8-FOOT EARTH GROUND COPPER-CLAD ROD.
2. MAIN POWER CABLE IS PROVIDED BY A CUSTOMER.
3. DEPTH OF WORKING SPACE SHALL NOT BE LESS THAN 36".
4. MAIN CB IS INSTALLED WITH LINE TERMINALS DOWN AND LOAD TERMINALS UP.

TABLE 3. FACILITY GAS REQUIREMENTS											
REF.	GAS REQUIRED	SUPPLY POINT INTERCONNECT	PRESSURE (PSIG)	INLET TEMPERATURE (°F)	REGULATOR REQUIRED	CLEANLINESS REQUIREMENT (QUALITY)	MAX FLOW	FITTING MATERIAL	FITTING SIZE (IN)	FITTING TYPE	MIN. FILTRATION (μ)
FOR TM/PM	CDA	TBD	90 ±5	AMBIENT	NO	NONE	10 LPM + 10 LPM/PM	BRASS	3/8	COMPRESSION	0.05
FOR TM/PM	N2	TBD	50 ±2	AMBIENT	NO	PROCESS GRADE	30 LPM	SST	1/4	MALE VCR	0.05
FOR WAFER COOLING	He	TBD	50 ±2	AMBIENT	NO	PROCESS GRADE	*50 SCFM MIN	SST	1/4	MALE VCR	0.05

*MULTIPLY FLOW BY NUMBER OF PMS FOR SYSTEM HE CONSUMPTION.

TABLE 5. COOLING WATER REQUIREMENTS									
DESCRIPTION	LIQUID REQUIRED	SUPPLY POINT INTERCONNECT	SUPPLY TEMPERATURE	FLOW (GPM)	PRESSURE Δ	PRESSURE MAX	FILTER (μ)	CONNECTION	THERMAL OUTPUT
TM VAC PUMP (EDWARDS 1PX 100)	H2O	TBD	35°C MAX	0.528 TO 0.793	30 PSI MIN	100 PSIG	<45	QUICK RELEASE: 3/8" BSP FEMALE INLET 3/8" BSP MALE	6824 BTU/HR TYPICAL

TABLE 6. FACILITY VACUUM REQUIREMENTS							
DESCRIPTION	SUPPLY POINT INTERCONNECT	DRAW (scfm)	VACUUM (in H2O)	AVG. FLOW (LPM)	CONNECTION	MATERIAL	EXHAUST HAZARDS
TM VAC PUMP (EDWARDS 1PX 100)	TBD	47	≤.7	18	NW 25	SST	TOXIC, CORROSIVE, CONDENSABLE
LOAD PORT/ROBOT	TBD	---	321	CLAMP ONLY	3/8 PUSH TO CONNECT	BRASS	NONE

NOTE: THE DRAW REQUIREMENT IS SPECIFIED AT THE VACUUM PUMP INTERFACE CONNECTING POINT (I.E. WITHOUT 90° ADAPTER OR FLEX SECTION).

TABLE 8. ENVIRONMENTAL REQUIREMENTS				
DESCRIPTION	TEMPERATURE (°C)	HUMIDITY (%)	VIBRATION	
			SENSITIVITY	EMISSION
TRANSPORT MODULE	25 ±5	<50	SLIGHT	NONE

TABLE 9. TM WEIGHT	
DESCRIPTION	WEIGHT LBS (KG)
TRANSPORT MODULE	4,039 (1,832)
LOAD PER LEVELING PAD	1,413 (641) MAX

TABLE 10. TM DIMENSIONS			
DESCRIPTION	WIDTH IN (CM)	DEPTH IN (CM)	HEIGHT IN (CM)
TRANSPORT MODULE	113 (287)	80 (203)	92.6 (235)

TABLE 11. THERMAL OUTPUT		
DESCRIPTION	DISPERSED TO ENVIRONMENT	TOTAL
	10.2 kBTU/hr	10.2 kBTU/hr



TM TO PM & RPDB CONNECTIONS


TABLE 12. POWER REQUIREMENTS FROM TM POWER CONTROL RACK							
DESCRIPTION	VOLTS (AC)	Hz	PHASE	WIRE	TYPE	AMPS (MAX)	CONDUIT REQUIRED
PROCESS MODULE	208 +10% -10%	50/60	3	4	DELTA	50	ø1.25"
REMOTE POWER DISTRIBUTION BOX	208 +10% -10%	50/60	3	4	DELTA	200 AMP CB	ø2"

NOTE: POWER CABLE FROM POWER CONTROL RACK TO RPDB IS PROVIDED BY A CUSTOMER.


TABLE 13. TM TO PM GAS CONNECTIONS	
DESCRIPTION	CONNECTION
HELIUM	1/4 MALE VCR
HOUSE N2	1/4 MALE VCR
CDA	3/8 COMPRESSION


		FREMONT, CA	
SIZE D	DRAWING NO. 253-810068-001	REV G	
SCALE NONE	SHEET 12 OF 12		

Released
Printed: Wed Apr 25 22:07:03 GMT 2001
See ECO File (MP, L, 220) for Current Rev Status




Released
Printed: Wed Aug 8 17:07:12 GMT 2001
See ECO File (MP, L, 220) for Current Rev Status






Released
Printed: Wed Apr 25 22:04:38 GMT 2001
See ECO File (MF,L,220) for Current Rev Status



Released
Printed: Wed Apr 25 22:04:46 GMT 2001
See ECO File (MF, L, 230) for Current Rev Status




PROPRIETARY INFORMATION NOTICE
THE NOTICE SET FORTH ON SHEET 1 IS INCORPORATED HEREIN BY REFERENCE.

DOC. CONTROL
DEC 07 2000
RELEASED


POLY


Lam		FREMONT, CA	
SIZE D	DRAWING NO. 251-800096-001	REV B	
SCALE NONE	SHEET 4 OF 6		

Released
Printed: Wed Apr 25 22:04:54 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




Released
Printed: Wed Apr 25 22:07:13Z GMT 2001
See ECO File (MF,L,220) for Current Rev Status







Released
Printed: Wed Apr 25 22:07:48 GMT 2001
See ECO File (MP,L,220) for Current Rev Status




Released
Printed: Wed Apr 25 22:07:55 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




Released
Printed: Wed Apr 25 22:08:09 GMT 2001
See ECO File (MP, L, 220) for Current Rev Status



Released
Printed: Wed Apr 25 22:08:21 GMT 2001
See ECO File (Mr.L,220) for Current Rev Status




Released
Printed: Wed Apr 25 22:08:33 GMT 2001
See ECO File (HF,L,220) for Current Rev Status




Released
Printed: Wed Apr 25 22:08:46 GMT 2001
See ECO File (MP, L, 220) for Current Rev Status


Released
Printed: Wed Apr 25 22:09:00 GMT 2001
See ECO File (MF,L,220) for Current Rev Status




LAM PROPRIETARY INFORMATION
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF LAM AND SHALL NOT BE REPRODUCED, THE INFORMATION CONTAINED HEREIN SHALL NOT BE DISCLOSED TO PERSONS EXCEPT THOSE NECESSARY TO PRODUCE THE PART OR PRODUCT OR USE THE PROCESS HEREIN SPECIFIED FOR LAM, NOR SHALL THE NUMBER BY THIS DOCUMENT BE LICENSED TO MANUFACTURE SUCH PART OR PRODUCT OR USE SUCH PROCESS EXCEPT IN THE QUANTITIES ORDERED BY LAM PURCHASE ORDERS. ANY EXCEPTION TO THE FOREGOING CONDITIONS MUST BE APPROVED BY ADVANCE WRITTEN AGREEMENT SIGNED BY AN AUTHORIZED REPRESENTATIVE OF LAM.



Released
Printed: Wed Apr 25 22:09:13 GMT 2001
See ECO File (MF,L,220) for Current Rev Status



Released
Printed: Wed Apr 25 22:09:28 GMT 2001
See ECO File (MF,L,220) for Current Rev Status



LAM PROPRIETARY INFORMATION
THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN
ARE CONFIDENTIAL TO, AND THE PROPERTY OF, LAM RE-
SEARCH CORPORATION. THIS DOCUMENT SHALL BE DISCLOSED
TO ONLY AS NECESSARY TO CARRY OUT THE PURPOSE FOR
WHICH IT WAS DISCLOSED AND IN A MANNER TO PROTECT
ITS CONFIDENTIALITY. NO OTHER USE IS PERMITTED.
THIS DOCUMENT SHALL BE RETURNED IMMEDIATELY UPON
LAM'S REQUEST.

REVISIONS						
REV	ZONE	DESCRIPTION	INC BY	CHECK	APVD	DATE
A		INITIAL RELEASE	BLT	12-4-00	CL	12/6/00




ORIGIN	INITIAL	DATE
B. TAJI	CL	12/6/00
CHECKED	CL	12/6/00
ELECT. ENGINEER	J. RASNIER	12/6/00
MECH. ENGINEER		


ALL DIMENSIONS ARE IN INCHES
DIMENSIONS IN PARENTS ARE MILLIMETERS.

SIZE	D	DRAWING NO.	224-800096-402	RIV	A
SCALE	NONE	SHEET	1 OF 1		


Released
Printed: Mon Apr 30 17:02:44 GMT 2001
See ECO File (MF, L, 220) for Current Rev Status




Released
Printed: Mon Apr 30 17:02:56 GMT 2001
See ECO File (HF,L,220) for Current Rev Status



Released
Printed: Mon Apr 30 17:03:11 GMT 2001
See ECO file (MF,L,220) for Current Rev Status



Released
Printed: Mon Apr 30 17:03:25 GMT 2001
See ECO File (Hr,L,220) for Current Rev Status



Released 2000/12/01-17:06:20:492 253-802968-002
Printed: Tue May 1 22:03:22 GMT 2001
See ECO File (MF,L,220) for Current Rev Status

