
Use Cases

for

<Project>

Version 1.0 approved

Prepared by <author>

<organization>

<date created>

Revision History

Name	Date	Reason For Changes	Version

Guidance for Use Case Template

Document each use case using the template shown in the Appendix. This section provides a description of each section in the use case template.

1. Use Case Identification

1.1. Use Case ID

Give each use case a unique numeric identifier, in hierarchical form: X.Y. Related use cases can be grouped in the hierarchy. Functional requirements can be traced back to a labeled use case.

1.2. Use Case Name

State a concise, results-oriented name for the use case. These reflect the tasks the user needs to be able to accomplish using the system. Include an action verb and a noun. Some examples:

- View part number information.
- Manually mark hypertext source and establish link to target.
- Place an order for a CD with the updated software version.

1.3. Use Case History

1.3.1. Created By

Supply the name of the person who initially documented this use case.

1.3.2. Date Created

Enter the date on which the use case was initially documented.

1.3.3. Last Updated By

Supply the name of the person who performed the most recent update to the use case description.

1.3.4. Date Last Updated

Enter the date on which the use case was most recently updated.

2. Use Case Definition

2.1. Actor

An actor is a person or other entity external to the software system being specified who interacts with the system and performs use cases to accomplish tasks. Different actors often correspond to different user classes, or roles, identified from the customer community that will use the product. Name the actor(s) that will be performing this use case.

2.2. Description

Provide a brief description of the reason for and outcome of this use case, or a high-level description of the sequence of actions and the outcome of executing the use case.

2.3. Preconditions

List any activities that must take place, or any conditions that must be true, before the use case can be started. Number each precondition. Examples:

1. User's identity has been authenticated.
2. User's computer has sufficient free memory available to launch task.

2.4. Postconditions

Describe the state of the system at the conclusion of the use case execution. Number each postcondition. Examples:

1. Document contains only valid SGML tags.
2. Price of item in database has been updated with new value.

2.5. Priority

Indicate the relative priority of implementing the functionality required to allow this use case to be executed. The priority scheme used must be the same as that used in the software requirements specification.

2.6. Frequency of Use

Estimate the number of times this use case will be performed by the actors per some appropriate unit of time.

2.7. Flow of Events

Provide a detailed description of the user actions and system responses that will take place during execution of the use case under normal, expected conditions. This dialog sequence will ultimately lead to accomplishing the goal stated in the use case name and description. This description may be written as an answer to the hypothetical question, "How do I <accomplish the task stated in the use case name>?" This is best done as a numbered list of actions performed by the actor, alternating with responses provided by the system.

2.8. Alternative Flows

Document other, legitimate usage scenarios that can take place within this use case separately in this section. State the alternative course, and describe any differences in the sequence of steps that take place. Number each alternative course using the Use Case ID as a prefix, followed by "AC" to indicate "Alternative Course". Example: X.Y.AC.1.

2.9. Exceptions

Describe any anticipated error conditions that could occur during execution of the use case, and define how the system is to respond to those conditions. Also, describe how the system is to respond if the use case execution fails for some unanticipated reason. Number each exception using the Use Case ID as a prefix, followed by "EX" to indicate "Exception". Example: X.Y.EX.1.

2.10. Includes

List any other use cases that are included ("called") by this use case. Common functionality that appears in multiple use cases can be split out into a separate use case that is included by the ones that need that common functionality.

2.11. Special Requirements

Identify any additional requirements, such as nonfunctional requirements, for the use case that may need to be addressed during design or implementation. These may include performance requirements or other quality attributes.

2.12. Assumptions

List any assumptions that were made in the analysis that led to accepting this use case into the product description and writing the use case description.

2.13. Notes and Issues

List any additional comments about this use case or any remaining open issues or TBDs (To Be Determineds) that must be resolved. Identify who will resolve each issue, the due date, and what the resolution ultimately is.

Use Case Template

Use Case ID:	UC.2		
Use Case Name:	Select Industry		
Created By:	Gan Sui	Last Updated By:	Gan Sui
Date Created:	21/2/26	Date Last Updated:	15/3/26

Actor:	Job seeker
Description:	This use case allows a Job Seeker to select an industry from the Top 10 industry list displayed on the dashboard. The outcome of this use case is that the selected industry is highlighted and stored, and the system proceeds to retrieve relevant courses for that industry.
Preconditions:	1. The system has successfully displayed the Top 10 industries (UC.1). 2. The user has access to the system through a supported web browser.
Postconditions:	1. The selected industry is highlighted with a red light bar. 2. The selected industry is stored in the system state. 3. The system initiates course retrieval for the selected industry (UC.3).
Priority:	High
Frequency of Use:	High

Flow of Events:	1. The Job Seeker views the Top 10 industries displayed on the dashboard. 2. The Job Seeker clicks on an industry card. 3. The system highlights the selected industry using a red light bar to indicate selection. 4. The system stores the selected industry in the application state. 5. The system initiates UC.3 to retrieve and display courses related to the selected industry.
Alternative Flows:	UC.2.AC.1: The Job Seeker changes the selected industry 1. The Job Seeker clicks on a different industry after making a previous selection. 2. The system removes the red highlight from the previously selected industry. 3. The system applies the red highlight to the newly selected industry. 4. The system updates the stored selection and re-triggers UC.3.
Exceptions:	UC.2.EX.1: Invalid selection state 1. The system detects that the selected industry is invalid or unavailable. 2. The system resets the selection and prompts the user to select a valid industry.
Includes:	UC.3 – Retrieve and Display Courses
Special Requirements:	1. The system must highlight the selected industry using a red light bar. 2. The system must allow the user to change their selection at any time.

Assumptions:	1. The user interacts with the system through a graphical user interface. 2. Only one industry can be selected at any given time.
Notes and Issues:	1. The visual feedback timing for selection may require further user experience testing.