

# IBM Education Assistance for z/OS V2R1

Item: Migration Throughput Enhancements

Element/Component: DFSMSHsm



## Agenda

- Trademarks
- Presentation Objectives
- Overview
- Usage & Invocation
- Presentation Summary
- Appendix



## Trademarks

- See url <http://www.ibm.com/legal/copytrade.shtml> for a list of trademarks.



## Presentation Objectives

- Describe improvements
- Identify how to configure
- Discuss setup requirements



## Overview

### ▪ Problem Statement / Need Addressed:

- Throughput of DFSMSHsm migration function is relatively low in comparison to copy utilities like DFSMSdss or IEBGENER.
  - Multiple tasks supported but operations such as pre-processing, data movement, and post-processing of each data set during migration are performed sequentially.

### ▪ Solution:

- Allow a migration task to migrate multiple data sets concurrently
  - Subtasks can then perform pre-processing, data movement, and post-processing of multiple data sets concurrently with other subtasks.
  - Still only one concurrent data movement to tape per migration task


### ▪ Benefit:

- Throughput of volume migration functions (Primary Space Management, Interval Migration, On Demand Migration) increased from concurrently running data set migrations as sub-tasks of the migration task.




## Overview

### Pre-V2R1



### Migration Subtasking



- Data movement to tape (only one concurrently per migration task)
- Pre- & Post-Processing (Eligibility checking, Enqueue, CDS Updates, Catalog, Scratch)



## Usage & Invocation

- User can select if DFSMSHsm should enable migration subtasks during PSM, ODM, and IM (L0 to ML1/ML2 only) via the following command.

SETSYS:

```
> _____>
|
|      _YES_
|  _MIGRATIONSUBTASKS_ ( _ _ _ ) _
|  _MIGSBTSKS_         | _YES_ | _ADDITIONALSUBTASKS (nn) _ _ |
|                     | _NO_  | _ADDSBTSKS_                 |
```

- MIGRATIONSUBTASKS(YES) enables the function and can only be specified on startup.
- A default number of subtasks will be used unless ADDITIONALSUBTASKS(nn) is specified which allows additional amount of concurrency. Allows users to increase throughput if additional CPU is available. May impact below-the-line storage usage.
- The default number of subtasks is a patchable value which is initially set to 5. Internal testing found this to be an ideal balance of throughput and CPU usage.



## Presentation Summary

- DFSMSHsm migration throughput is generally worse than data copy utilities (ie. DFSMSdss, IEBGENER)
- Allowing concurrent migration subtasks can increase throughput
- SETSYS MIGRATIONSUBTASKS(YES) enables the function with default number of concurrent subtasks
- Functions supported: PSM, IM, and ODM (L0 to ML1/ML2 migrations).





## Appendix

- Publications:
  - *DFSMSHsm Storage Administration* (SC23-6871-0)

