



Complete Solution for ELISA & EIA Tests

readwell Touch

Automatic ELISA Plate Analyser





((

Features

- Accommodates different microplate geometries U, V & Flat
- Plate shaking facility with variable speed and duration
- Ability to read plate within seconds
- Digital light control with unique circuit for long lamp life
- Bichromatic readings
- Flexible controls and calibrators positioning
- Storage of calibration curves & controls
- External printer connectivity
- Patient report with PID & name

- Various Graph curve fit mode: Linear, Point to Point, 4 parameter log regression, Cubic Spline, Polynomial with scales such as Log Abs / Conc, Logit Abs / Log Conc, Abs / Conc, Log Abs / Log Conc etc.
- Matrix mode for result printing
- Storage of plate results
- Data transfer to computer with easy view of results in Excel format

Technical Specifications

OPTICAL SYSTEM

Linear measurement range: 0.000 to 3.500 absorbance units(A)

Photometric accuracy: ± 1 % or 0.007 whichever is higher from 0 to 1.5 A,

 \pm 2 % from 1.5 A to 3.5 A

Drift: <0.005 A/hr Resolution: 0.001 Light source: Halogen

FILTERS

Type of filter: High quality narrow band interference **Wavelength**: 405, 450, 492, 630 nm & two optional

Half bandwidth: < 10 nm

Selection: Automatic by stepper motor

MEMORY

Programs: 250 tests

Results: 9600 patient results retrieval Assay wise, Patient wise

PRINTER: On board thermal 52 columns, maintenance free

DISPLAY

Human machine interface : TOUCH PANEL & KEYPAD,
7" Graphics Color Display

POWER

Voltage: $115 - 230 \text{ Volts} \pm 10\%$, 50 - 60 Hz

COMPUTER INTERFACE

RS232 Serial Port: 9600 baud, 8 data, 1 stop, no parity bits

USB

ANALYSIS MODES: Absorbance, Cut-off, Multi-standard,

% Absorbance, Single standard, Uptake, Ratio

Curve Plotting: Graphical representation on printer & display Plate Carrier Movement: Precisely through stepper motor Dimensions in mm (lxbxh): 405 x 380 x 280 (Approx)


Weight: 10 kgs. (Approx)



Printer



Display



Graph

Due to continuous development, specifications are subject to change without prior notice.



ROBONIK (INDIA) PVT. LTD.

Plot No. 3 & 4, MIDC Industrial Area, Morivali, Near Ladhi Naka, Ambernath (West) - 421 501, District Thane, Maharashtra, INDIA

Tel.: +91 (251) 2689000,

National Sales : marketing@robonikindia.com, International Sales : export@robonikindia.com



Authorised Distributor