| No | Quantity Designator   | Comment  | Description                                | Package        |
|----|---|--|--|----------------|
| 1  | 4 C1, C2, C4, C7  | 1uF  | 10V-5% Ceramic                             | CASE 0402      |
| 2  | 15 C3, C5, C6, C8, C9, C10, C11, C12, C13, C14, C15, C16, C17, C25, C34 | 0.1uF  | 50V-5% Ceramic                             | CASE 0402      |
| 3  | 1 C18   | 22uF   | 10V-10%Ceramic                             | CASE 0805      |
| 4  | 2 C26, C27  | 15pF   | 50V-5% Ceramic                             | CASE 0402      |
| 5  | 1 D1  | BAT60A   | Silicon Schottky Diode                     | SOD-323        |
| 6  | 2 J1, J2  | 2.54mm 1x20 Pin Header DIP   | 2.54mm 1x20 Pin Header DIP, Male           | DIP            |
| 7  | 1 J3  | 2.54mm 1x3 Pin Header DIP  | 2.54mm 1x3 Pin Header DIP                  | DIP            |
| 8  | 1 J4  | 2.54mm 1x4 Pin Header DIP  | 2.54mm 1x4 Pin Header DIP                  | DIP            |
| 9  | 1 LD1   | Red  | SMD Red LED                                | CASE 0603      |
| 10 | 1 LD2   | Green  | SMD Green LED                              | CASE 0603      |
| 11 | 1 M1  | WizFi360   | WIZnet Wi-Fi Module                        | SMD            |
| 12 | 1 P1  | Micro 5P B DBX 6.4   | Micro USB B Connector SMD                  | SMD            |
| 13 | 1 Q1  | 2N7002   | N-Channel 60-V (D-S) MOSFET                | SOT23          |
| 14 | 2 R1, R11   | 470R   | 1/10W-1% SMD                               | CASE 0402      |
| 15 | 1 R2  | 5.6K   | 1/10W-1% SMD                               | CASE 0402      |
| 16 | 2 R3, R8  | 100K   | 1/10W-1% SMD                               | CASE 0402      |
| 17 | 1 R4  | 10K  | 1/10W-1% SMD                               | CASE 0402      |
| 18 | 1 R5  | 200K   | 1/10W-1% SMD                               | CASE 0402      |
| 19 | 2 R6, R9  | 27R  | 1/10W-1% SMD                               | CASE 0402      |
| 20 | 1 R7  | 200R   | 1/10W-1% SMD                               | CASE 0402      |
| 21 | 1 R10   | 1R   | 1/10W-1% SMD                               | CASE 0402      |
| 22 | 1 R12   | 4.7K   | 1/10W-1% SMD                               | CASE 0402      |
| 23 | 2 R13, R25  | NC   | 1/10W-1% SMD                               | CASE 0402      |
| 24 | 1 R15   | 0R   | 1/10W-1% SMD                               | CASE 0402      |
| 25 | 7 R14, R16, R17, R18, R19, R26, R31                                     | 1K   | 1/10W-1% SMD                               | CASE 0402      |
| 26 | 2 SW1, SW2  | 1185SA(2.0)  | TACT Switch (SMD)                          | SMD            |
| 27 | 1 U1  | LM8805SF5-33V  | 600mA CMOS LDO Regulator                   | SOT-23-5L      |
| 28 | 1 U2  | RP2040   | Raspverry Pi, Dual ARM Cortex-M0+ @ 133MHz | QFN56          |
| 29 | 1 U4  | W25Q16JVZPIM   | 3V 16M-BIT SERIAL FLASH MEMORY             | WSON-8         |
| 30 | 1 Y1  | 12MHz  | X-tal 12MHz,3.2x2.5 SMD, CL=18pF           | SMD3225, 4-PAD |
| 31 | 1   | 75 x 21 (mm), 2-layer, 1.0T, 1oz, FR-4, OSP, PCB: Green, Silk: White |  |                |