

# WIZ505SR-RP V100 Partlist

| No | Quantity | Designator   | Comment   | Description  | Package        |
|----|----------|--|---|--|----------------|
| 1  | 3        | C1, C4, C17  | 1uF   | 10V-5% Ceramic   | CASE 0402      |
| 2  | 23       | C2, C3, C5, C6, C7, C8, C9, C10, C11, C12, C13, C14, C15, C16, C18, C19, C20, C21, C22, C23, C24, C28, C31 | 0.1uF   | 50V-5% Ceramic   | CASE 0402      |
| 3  | 1        | C25  | 1nF/2kV   | 1nF/2kV Ceramic  | CASE 1808      |
| 4  | 2        | C26, C27   | 18pF  | 50V-5% Ceramic   | CASE 0402      |
| 5  | 2        | C29, C30   | 15pF  | 50V-5% Ceramic   | CASE 0402      |
| 6  | 1        | J1   | 2.54mm 1x6 Pin Header DIP   | 2.54mm 1x6 Pin Header DIP                                    | DIP            |
| 7  | 1        | J2   | 2.54mm 2x7 Pin Header DIP   | 2.54mm 2x7 Pin Header DIP                                    | DIP            |
| 8  | 2        | J3, J4   | 2.54mm 1x2 Pin Header DIP   | 2.54mm 1x2 Pin Header DIP                                    | DIP            |
| 9  | 3        | L1, L2, L3   | HH-1M1608-121JT   | Bead for Power Line, 120[ohm]                                | CASE 0603      |
| 10 | 3        | LD3, LD4, LD5  | Green   | Green SMD LED  | CASE 0603      |
| 11 | 1        | LD2  | Red   | Red SMD LED  | CASE 0603      |
| 12 | 1        | P1   | J1B1211CCD  | Cetus Single RJ-45 Connector with Magnetics                  | DIP            |
| 13 | 1        | R1   | 200R  | 1/10W-1% SMD   | CASE 0402      |
| 14 | 1        | R2   | 1R  | 1/10W-1% SMD   | CASE 0402      |
| 15 | 1        | R3   | 4.7K  | 1/10W-1% SMD   | CASE 0402      |
| 16 | 9        | R4, R5, R8, R10, R16, R17, R18, R25, R33   | 0R  | 1/10W-1% SMD   | CASE 0402      |
| 17 | 4        | R6, R7, R9, R11  | 3.3R  | 1/10W-1% SMD   | CASE 0402      |
| 18 | 4        | R12, R13, R14, R15   | 49.9R   | 1/10W-1% SMD   | CASE 0402      |
| 19 | 1        | R19  | 1M  | 1/10W-1% SMD   | CASE 0402      |
| 20 | 1        | R20  | 12K/1%  | 1/10W-1% SMD   | CASE 0402      |
| 21 | 1        | R21  | 300R  | 1/10W-1% SMD   | CASE 0402      |
| 22 | 6        | R22, R23, R26, R27, R28, R29   | 470R  | 1/10W-1% SMD   | CASE 0402      |
| 23 | 3        | R24, R31, R32  | 1K  | 1/10W-1% SMD   | CASE 0402      |
| 24 | 1        | R30  | NC  | Not Mount  | CASE 0402      |
| 25 | 1        | SW1  | 1185SA(2.0)   | TACT Switch (SMD)  | SMD            |
| 26 | 1        | U1   | RP2040  | Raspberry Pi, Dual ARM Cortex-M0+ @ 133MHz                   | QFN56          |
| 27 | 1        | U2   | W5100S  | WIZnet Hardwired TCP/IP Chip                                 | LQFP48         |
| 28 | 1        | U3   | TPD4S009DCKR  | 4-Channel ESD Solution for High-Speed Differential Interface | SC70-6L        |
| 29 | 1        | U4   | W25Q16JVZPIM  | 3V 16M-BIT SERIAL FLASH MEMORY WITH DUAL/QUAD SPI            | WSO8           |
| 30 | 1        | Y1   | S3225A-025000-F18   | X-tal 25MHz,3.2x2.5 SMD, CL=18pF                             | SMD3225, 4-PAD |
| 31 | 1        | Y2   | S3225A-012000-F18   | X-tal 12MHz,3.2x2.5 SMD, CL=20pF                             | SMD3225, 4-PAD |
| 32 | 1        | PCB  | 40 X 62 (MM), 4-Layer, 1.6T, 1oz, FR-4, OSP, PCB: Matt Black, Silk: White |  |                |