

Generative Adversarial Networks (GAN)

Speaker: Guanyu Hu
School of Computer Science and Technology
Xi'an Jiaotong University

■ Generative Model

- What Are Generative Models
- Types of Deep Generative Models

■ Generative Adversarial Networks (GAN)


- Discriminator
- Generator
- BCE Cost Function
- Training GANs

What Are Generative Models



Discriminative Models

VS.



Generative Models

What Are Generative Models

Discriminative Models

How:

- 直接根据特征 X ，来对 Y 建模，划定一个整体判别边界，每新来一个数据 X ，就根据这个边界来判断它应该属于哪一类。
- 获得样本 X 属于类别 Y 的概率分布，是一个条件概率 $P(Y|X)$

Goal:

- 给定一组 feature X 来判定它是属于哪个分类 Y 的

Generative Models

How:

- 观察训练数据 X 与 Y 的整体分布，求得联合概率分布 $P(X,Y)$ ，每新来一个数据 X ，求出 X 与不同分类 Y 之间的联合概率分布，将 X 分为联合概率大的那一类。


Goal:

- 给定一组 feature X 计算出与不同分类的联合概率 $P(X,Y)$

Methods:

- 朴素贝叶斯方法，隐马尔可夫模型

What Are Generative Models



- Take some random input represented by the noise
- From these inputs, to generate a set of features X that look like a realistic representation of class Y

■ **Generative Model**

- **What Are Generative Models**
- Types of Deep Generative Models

■ **Generative Adversarial Networks (GAN)**

- Discriminator
- Generator
- BCE Cost Function
- Training GANs

■ Generative Model

- What Are Generative Models
- **Types of Deep Generative Models**


■ Generative Adversarial Networks (GAN)

- Discriminator
- Generator
- BCE Cost Function
- Training GANs


Variational Autoencoders (VAE)




Variational Autoencoders (VAE)



Variational



Generative Adversarial Networks (GAN)



■ Generative Model

- What Are Generative Models
- **Types of Deep Generative Models**

■ Generative Adversarial Networks (GAN)

- Discriminator
- Generator
- BCE Cost Function
- Training GANs


- **Generative Model**

- What Are Generative Models
- Types of Deep Generative Models


- **Generative Adversarial Networks (GAN)**

- **Discriminator**
- Generator
- BCE Cost Function
- Training GANs

Discriminator for Classification



Discriminator for Generation



$$P(\underset{\text{Class}}{\text{Y}} \mid \underset{\text{Features}}{\text{X}}) \longrightarrow P(\underset{\text{Class}}{\text{Fake}} \mid \underset{\text{Features}}{\text{Image}}) = 0.85 \longrightarrow \boxed{\text{Fake}}$$

- **Generative Model**

- What Are Generative Models
- Types of Deep Generative Models

- **Generative Adversarial Networks (GAN)**

- **Discriminator**
- Generator
- BCE Cost Function
- Training GANs

- **Generative Model**


- What Are Generative Models
- Types of Deep Generative Models

- **Generative Adversarial Networks (GAN)**

- Discriminator
- **Generator**
- BCE Cost Function
- Training GANs

Generative Adversarial Networks (GAN)

Generator



- **Generative Model**

- What Are Generative Models
- Types of Deep Generative Models

- **Generative Adversarial Networks (GAN)**

- Discriminator
- **Generator**
- BCE Cost Function
- Training GANs

- **Generative Model**

- What Are Generative Models
- Types of Deep Generative Models

- **Generative Adversarial Networks (GAN)**

- Discriminator
- Generator
- **BCE Cost Function**
- Training GANs

Binary Cross Entropy function Cost Function

$$J(\theta) = -\frac{1}{m} \sum_{i=1}^m [y^{(i)} \log h(x^{(i)}, \theta) + (1 - y^{(i)}) \log (1 - h(x^{(i)}, \theta))]$$

- h : predictions made by the model
- y : is the labels for the different examples, true label of real fake
- x : feature passed in through the prediction, could be an image
- θ : parameters to model the classifier h

- **Generative Model**


- What Are Generative Models
- Types of Deep Generative Models

- **Generative Adversarial Networks (GAN)**

- Discriminator
- Generator
- BCE Cost Function
- **Training GANs**


Generative Adversarial Networks (GAN)

Training Discriminator



Generative Adversarial Networks (GAN)

Training Generator



Use Saved Model

