

Terminal Dev Environment: Cheatsheet tmux · zsh/fzf · Neovim · git · Antigravity CLI

OLD pre-existing workflow NEW added workflow Where multiple ways exist to do the same thing, all are listed: pick whichever fits the moment.

Git	aliases (existing, kept)
gs	status
gl	pull
ga	add
gc "msg"	commit -m
gp	push
gamend	commit --amend --no-edit
gsw / gsm	switch / switch master
gb	branch
gco / gcm	checkout / checkout main
gcl	clone
glog	log --oneline --graph --all
gd	diff
gundo	reset --soft HEAD~1

Git	aliases (new)
gwl	worktree list
gwa	worktree add
gwr	worktree remove
gcp	cherry-pick
gst / gstp	stash / stash pop
grb main	rebase -i main
grbc / grba	rebase --continue / --abort

gwt() function (left) is the fast path vs manual gwa+cd.

Git	lazygit (lg)
1..5	switch panel
Space	stage/unstage file or hunk
a	stage all
c	commit
P / p	push / pull
d	discard (careful)
e	edit file in \$EDITOR
Space (conflict)	pick ours/theirs/both
M	external merge tool

Alt for staging/commit vs gitsigns hunk-stage in Neovim.

Shell	fzf-git.sh (Ctrl-g ...)
Ctrl-g Ctrl-f	files
Ctrl-g Ctrl-b	branches
Ctrl-g Ctrl-t	tags
Ctrl-g Ctrl-r	remotes
Ctrl-g Ctrl-h	commit hashes
Ctrl-g Ctrl-s	stash entries
Ctrl-g Ctrl-l	reflog

All-NEW. Inserts token at cursor with live preview.

tmux	prefix Ctrl-a
" / %	split horizontal / vertical
h j k l	move between panes NEW
o	next pane (arrow-key style) OLD
H J K L	resize pane NEW
Ctrl+arrow	resize pane OLD
x	kill pane
c	new window
[num]	go to window [num]
n / p	next / prev window
,	rename window
&	kill window
s / w	choose session / window from list
f	tmux-sessionizer (new window) NEW
F	tmux-fzf menu (sess/win/pane) NEW
A	launch Antigravity CLI window NEW
d	detach
r	reload tmux.conf NEW
q	show pane numbers
?	show all keybindings
:	command prompt

Neovim	git : diffview / fugitive (new)
leader gv / gV	Diffview open / close
leader gh / gH	file history: file / repo
leader gl	Flog: git log graph
:Git	fugitive status window (s/u stage)
:Git blame	full-file blame (A cycle, Enter open)
:Git commit/push	git commands in-editor

Neovim	merge conflicts (new)
]x / [x	next / prev conflict (diffview)
leader co	choose ours
leader ct	choose theirs
leader cb	choose base
leader ca	choose all
:diffget //2 //3	theirs / ours (native, no plugin)

Two ways to do it : quick map	
Find a file	Ctrl-t (shell) · leader ff (nvim) · fcd/z (dirs)
Switch branch	gco/gsw (manual) · gcof (fuzzy) · lazygit panel
View a diff	gd/gdiff (shell) · leader gv (nvim) · lg (lazygit)
Stage changes	ga . (manual) · leader gs (hunk, nvim) · lg Space (lazygit)
Resolve conflict	leader co/ct (diffview) · :diffget //2/3 (native) · lg Space
New project session	tn (manual) · ts/tm (fuzzy)
Jump panes	o (cycle) · h j k l (directional)
Kill a process	kill -9 <pid> (manual) · fkill (fuzzy)
Work on 2 branches	git stash + checkout (manual) · gwt/worktree (parallel dirs)
AI help	claudecode.nvim (in-file) · agy (repo-wide/async)

tmux	Copy Mode (vi keys)
[	enter copy mode
]	paste buffer
v	begin selection NEW
Space	begin selection OLD (legacy)
y	copy → system clipboard NEW
Enter	copy selection OLD (legacy)
r	toggle rectangle select NEW
q	exit copy mode

Neovim	navigation (new)
s	Flash jump (any visible loc)
S	Flash treesitter node jump
/ then Enter	native search (still works)
C-h/j/k/l	cross Neovim splits AND tmux panes

Neovim	leader = Space (existing)
,s	w (save)
space e	diagnostic float
[d /]d	prev/next diagnostic
space q	diagnostics loclist
gd / gi / K	definition / impl / hover
space t / rn	type def / rename
-	Oil: parent dir
^	Oil: open cwd
; / m	Arrow bookmarks (global/buffer)
{ / }	Aerial prev/next symbol
leader a	Aerial toggle (overloaded w/ Claude grp)
C-K (insert)	expand snippet
leader se/sa	edit / add snippet
leader ss/sl/sd	session save/load/delete
leader ,	copy filename to clipboard
leader y / wy	yank sel/word to system clip
,s / ,d	vsplit / split

Neovim	worktrees & diagnostics (new)
leader gwc	create worktree
leader gwL	list/switch worktree
leader xx	Trouble: workspace diagnostics
leader xd	Trouble: buffer diagnostics
leader xr	Trouble: LSP references
leader xq	Trouble: quickfix list

Antigravity CLI	: agy (new)
agy	launch interactive TUI
agy -p "-"	one-shot headless prompt
agy -p "-" --output-format json	structured output for piping
/agent "-"	dispatch async background subagent
Ctrl-I	command mode (inline, from TUI)
/usage	check quota (subagents run in parallel)
/logout	clear saved credentials
ag / agp / agy?	shell aliases → agy / agy -p / agy -p
tmux prefix A	open in dedicated tmux window

Use in-editor claudecode.nvim for scoped in-file review; agy for repo-wide/async tasks.

Shell	functions & helpers
fkilL	fuzzy pick+kill process
fcd [root]	fuzzy cd w/ tree preview
mkcd <dir>	mkdir -pv + cd (alt: ' mkdir -pv' alias OLD)
extract <f>	universal archive extract
gcof	fuzzy git checkout (local+remote)
gdifff [ref]	fuzzy pick changed file → diff
gwt <branch>	create/attach sibling worktree
fdocker	fuzzy exec into container
fdlogs	fuzzy follow container logs

All-NEW additions layered on existing aliases below.

Shell	fzf core
Ctrl-t	insert fuzzy file path NEW
Ctrl-r	fuzzy history search NEW
Alt-c	fuzzy cd NEW
**<Tab>	fuzzy-complete any arg NEW
z <name>	zoxide frecency-jump (aliased as cd) NEW
cdd	real 'cd' escape hatch NEW

Neovim	Telescope (existing)
leader ff	find files
leader fg	live grep
leader fb	buffers

Same picker style as fzf-git.sh in shell: consistent UX.

Shell	Sessions (tmux)
tn <name>	new session OLD
ta <name>	attach session OLD
tl	list sessions OLD
tk / tks	kill session / server OLD
tm [name]	attach-or-create NEW
ts	tmux-sessionizer: fuzzy project → session NEW

ts/tm are the fast path; tn/ta/tl/tk still work for manual control.

Neovim	git : gitsigns (new)
]c / [c	next / prev hunk
leader gs	stage hunk (v: stage selection)
leader gr	reset hunk
leader gp	preview hunk
leader gS / gR	stage / reset whole buffer
leader gb	blame line (full)
leader gd	diff this file

Neovim	claudecode.nvim (existing)
leader ac	toggle Claude
leader af	focus Claude
leader ar / ac	resume / continue
leader am	select model
leader ab	add current buffer
leader as	send selection (v) / add file (tree)
leader aa / ad	accept / deny diff