

Predict the Output

Conditional operator and switch statement practice for Lecture 07.01

For each example, predict exactly what the program prints before running it. Pay attention to which branch executes, whether a case matches, and where break appears.

Name: _____ Date: _____

1. Simple conditional choice

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    int age = 20;
    string label = age >= 18 ? "adult" : "minor";

    cout << label << endl;
}
```

2. Numeric conditional expression

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    int items = 3;
    double shipping = items >= 3 ? 0.0 : 5.99;

    cout << shipping << endl;
}
```

3. Conditional operator inside output

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    bool member = false;

    cout << (member ? "Discount applied" : "Regular price") << endl;
}
```

4. Nested conditional operator

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    int score = 85;

    string grade =
        score >= 90 ? "A" :
        score >= 80 ? "B" :
        score >= 70 ? "C" : "D";

    cout << grade << endl;
}
```

5. switch with a matching case

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    char code = 'E';

    switch (code) {
        case 'S':
            cout << "Standard";
            break;
        case 'E':
            cout << "Express";
            break;
        case 'P':
            cout << "Pickup";
            break;
        default:
            cout << "Unknown";
    }
}
```

6. switch with default

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    int choice = 4;

    switch (choice) {
    case 1:
        cout << "Deposit";
        break;
    case 2:
        cout << "Withdraw";
        break;
    case 3:
        cout << "Balance";
        break;
    default:
        cout << "Invalid choice";
    }
}
```

7. switch without a break

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    char size = 'M';

    switch (size) {
        case 'S':
            cout << "Small ";
            break;
        case 'M':
            cout << "Medium ";
        case 'L':
            cout << "Large ";
            break;
        default:
            cout << "Unknown";
    }
}
```

8. Multiple cases sharing one result

Predicted output: _____

```
#include <iostream>
using namespace std;

int main() {
    int day = 6;

    switch (day) {
        case 1:
        case 2:
        case 3:
        case 4:
        case 5:
            cout << "Weekday";
            break;
        case 6:
        case 7:
            cout << "Weekend";
            break;
        default:
            cout << "Invalid day";
    }
}
```