IPHONE 13 DISPLAY FPC DIODE READINGS & POWER RAILS

Display Connector Pinout & Touch IC Traces | Sheet 1 of 2

FPC CONNECTOR J5700 DIODE VALUE MAP

Pins 1 to 20 Reading Matrix (Multimeter Red Probe on GND)

Pin 1 (GND): 0.000 (Beep) | Clean ground reference return

Pin 2 (PP_VAR_SOC_DSI): 460mV | Dynamic OLED core supply

Pin 3 (MIPI_DSI_DATA0_P): 375mV | High-speed differential positive

Pin 4 (MIPI_DSI_DATA0_N): 375mV | High-speed differential negative

Pin 7 (PP5V7_DISPLAY_AVDD_PLUS): 530mV | +5.7V analog display rail

Pin 9 (PP5V7_DISPLAY_AVDD_MINUS): 540mV | -5.7V inverted analog display rail

CONFIDENTIAL - SALEN MOBILE GURU CHIP-LEVEL HARDWARE LAB

IPHONE 13 DISPLAY FPC DIODE READINGS & POWER RAILS

Display Connector Pinout & Touch IC Traces | Sheet 2 of 2

TOUCH CONTROLLER & EEPROM LINES

True Tone & Ambient Light Sensor Integration

Pin 12 (TOUCH_RESET_L): 590mV | 1.8V Touch reset line

Pin 14 (SPI_TOUCH_MOSI): 490mV | 24MHz Serial peripheral data in

Pin 15 (SPI_TOUCH_MISO): 490mV | 24MHz Serial peripheral data out

Pin 18 (I2C_DISPLAY_EEPROM_SDA): 480mV | Encrypted True Tone serialization code

Pin 19 (I2C_DISPLAY_EEPROM_SCL): 480mV | Clock line to display micro-EEPROM

Grinding Rule: Grind touch IC to 0.12mm without puncturing OLED flex substrate

CONFIDENTIAL - SALEN MOBILE GURU CHIP-LEVEL HARDWARE LAB