

```

-- Schema
CREATE SCHEMA IF NOT EXISTS public;

-- Timestamp update trigger
CREATE OR REPLACE FUNCTION set_updated_at()
RETURNS trigger AS $$
BEGIN
    NEW.updated_at = NOW();
    RETURN NEW;
END;
$$ LANGUAGE plpgsql;

-----
-- TABLE: customer
-----
CREATE TABLE IF NOT EXISTS public.customer (
    customer_id      BIGSERIAL PRIMARY KEY,
    customer_name    text NOT NULL,
    last_name        text NOT NULL,
    first_name       text NOT NULL,
    street_number    text NOT NULL,
    postal_code      text NOT NULL,
    city             text NOT NULL,
    phone            varchar(20),
    cellphone        varchar(20),
    created_at       timestampz NOT NULL DEFAULT now(),
    updated_at       timestampz NOT NULL DEFAULT now()
);

-----
-- TABLE: users
-----
CREATE TABLE IF NOT EXISTS public.users (
    user_id          SERIAL PRIMARY KEY,
    email            text NOT NULL UNIQUE,
    password_hash    text,
    name             text NOT NULL,
    role             varchar(50) NOT NULL,
    is_active        boolean NOT NULL DEFAULT true,
    street_number    text NOT NULL,
    postal_code      text NOT NULL,
    city             text NOT NULL,
    created_at       timestampz NOT NULL DEFAULT now(),
    updated_at       timestampz NOT NULL DEFAULT now()
);

-----
-- TABLE: vehicle
-----
CREATE TABLE IF NOT EXISTS public.vehicle (
    vehicle_id       BIGSERIAL PRIMARY KEY,
    license_plate    varchar(20) NOT NULL UNIQUE,
    brand            text NOT NULL,
    model            text,

```

```

        color            text,
        capacity_kg       numeric(10,0),
        fuel_type         text NOT NULL,
        is_active         boolean NOT NULL DEFAULT true,
        created_at        timestampz NOT NULL DEFAULT now(),
        updated_at        timestampz NOT NULL DEFAULT now()
    );

```

```

-----
-- TABLE: product
-----

```

```

CREATE TABLE IF NOT EXISTS public.product (
    product_id BIGSERIAL PRIMARY KEY,
    weight_kg   numeric(10,0),
    product_name varchar(255) NOT NULL,
    created_at  timestampz NOT NULL DEFAULT now(),
    updated_at  timestampz NOT NULL DEFAULT now()
);

```

```

-----
-- TABLE: purchase_orders
-----

```

```

CREATE TABLE IF NOT EXISTS public.purchase_orders (
    order_id BIGSERIAL PRIMARY KEY,
    payment_status text NOT NULL,
    delivery_address text NOT NULL,
    customer_id integer NOT NULL,
    delivery_phone varchar(20) NOT NULL,
    delivery_window_start timestampz NOT NULL,
    delivery_window_end timestampz NOT NULL,
    total_weight_kg numeric(10,0) NOT NULL,
    order_status text NOT NULL,
    lat numeric(10,6),
    lng numeric(10,6),
    created_at timestampz NOT NULL DEFAULT now(),
    updated_at timestampz NOT NULL DEFAULT now(),
    CONSTRAINT fk_purchase_orders_customer
        FOREIGN KEY (customer_id)
        REFERENCES public.customer(customer_id)
);

```

```

-----
-- TABLE: route
-----

```

```

CREATE TABLE IF NOT EXISTS public.route (
    route_id BIGSERIAL PRIMARY KEY,
    driver_id integer NOT NULL,
    vehicle_id integer NOT NULL,
    created_by_user_id integer NOT NULL,
    route_date date NOT NULL,
    route_status text NOT NULL,
    started_at timestampz,
    completed_at timestampz,
    driver_day_comment text,

```

```

        created_at          timestampz NOT NULL DEFAULT now(),
        updated_at          timestampz NOT NULL DEFAULT now(),
        CONSTRAINT fk_route_driver      FOREIGN KEY (driver_id)          REFERENCES
public.users(user_id),
        CONSTRAINT fk_route_creator    FOREIGN KEY (created_by_user_id) REFERENCES
public.users(user_id),
        CONSTRAINT fk_route_vehicle    FOREIGN KEY (vehicle_id)         REFERENCES
public.vehicle(vehicle_id)
);

```

```

-----
-- TABLE: order_item
-----

```

```

CREATE TABLE IF NOT EXISTS public.order_item (
    order_item_id BIGSERIAL PRIMARY KEY,
    order_id       integer NOT NULL,
    product_id     integer NOT NULL,
    quantity       integer NOT NULL,
    created_at     timestampz NOT NULL DEFAULT now(),
    CONSTRAINT fk_order_item_order
        FOREIGN KEY (order_id) REFERENCES public.purchase_orders(order_id)
        ON DELETE CASCADE,
    CONSTRAINT fk_order_item_product
        FOREIGN KEY (product_id) REFERENCES public.product(product_id)
);

```

```

-----
-- TABLE: route_delivery
-----

```

```

CREATE TABLE IF NOT EXISTS public.route_delivery (
    route_delivery_id BIGSERIAL PRIMARY KEY,
    route_id          integer NOT NULL,
    order_id          integer NOT NULL,
    sequence          integer NOT NULL,
    delivery_status    text,
    delivery_at        timestampz,
    delivery_comment    text,
    created_at         timestampz NOT NULL DEFAULT now(),
    updated_at         timestampz NOT NULL DEFAULT now(),
    CONSTRAINT fk_route_delivery_route
        FOREIGN KEY (route_id) REFERENCES public.route(route_id),
    CONSTRAINT fk_route_delivery_order
        FOREIGN KEY (order_id) REFERENCES public.purchase_orders(order_id)
);

```

```

-----
-- Triggers: updated_at automatisch bijwerken
-----

```

```

CREATE TRIGGER trg_customer_updated
BEFORE UPDATE ON public.customer
FOR EACH ROW EXECUTE FUNCTION set_updated_at();

```

```

CREATE TRIGGER trg_users_updated

```

```
BEFORE UPDATE ON public.users  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

```
CREATE TRIGGER trg_vehicle_updated  
BEFORE UPDATE ON public.vehicle  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

```
CREATE TRIGGER trg_product_updated  
BEFORE UPDATE ON public.product  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

```
CREATE TRIGGER trg_purchase_orders_updated  
BEFORE UPDATE ON public.purchase_orders  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

```
CREATE TRIGGER trg_route_updated  
BEFORE UPDATE ON public.route  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```

```
CREATE TRIGGER trg_route_delivery_updated  
BEFORE UPDATE ON public.route_delivery  
FOR EACH ROW EXECUTE FUNCTION set_updated_at();
```