



BigBuy API (1.0.0)

Download OpenAPI specification: [Download](#)

Generated SDK's

- [Php](#)
- [Java](#)
- [Python](#)

Rate Limit

In this section, you learn how to check your rate limits and request exceptions.

Check your rate limits with BigBuy rate limit headers

- X-RateLimit-Limit - the rate limit ceiling that is applicable for the current request.

For example:

```
HTTP/1.1 200 OK
X-RateLimit-Limit: 1200
```

Authentication

BigBuy API offers one form of authentication in header:

Authorization: Bearer API_KEY

Attribute

Attribute

Returns all attributes.

Rate Limit

Max Requests	Period
24	1 h

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format

required

string json

QUERY PARAMETERS

isoCode

string

es by default

page

integer

Default 0

pageSize

integer

Default 0

Responses

- > 200 Returned when successful
- 409 Returned when no attributes were found in cache.
- 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/attributes.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogAttributes($format, $page, $page
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeApi->getRestCatalogAttributes: '
* }
* ?>
```

Response samples

200

409

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": 123456,
    "attributeGroup": 14,
    "name": "Red",
    "isoCode": "en"
  }
]
```

Returns attribute.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

QUERY PARAMETERS

| | |
|---------|-------------------------|
| isoCode | string
es by default |
|---------|-------------------------|

Responses

- > 200 Returned when successful
- 404 Returned when no attribute was found.
- 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/attribute/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogAttributeId($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeApi->getRestCatalogAttributeId:
* }
* ?>
```

Response samples

200

404

415

429

Content type

application/json

Copy

```
{
  "id": 123456,
  "attributeGroup": 14,
```

```
"name": "Red",
"isoCode": "en"
}
```

Returns a single attribute all languages.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

Responses

- > 200 Returned when successful
- 404 Returned when no attribute was found.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

```
GET /rest/catalog/attributealllanguages/{id}.{format}
```

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogAttributealllanguages($id, $form
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeApi->getRestCatalogAttributealll
* }
* ?>
```

Response samples

200

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": 123456,
    "attributeGroup": 14,
    "name": "Red",
    "isoCode": "en"
  }
]
```

AttributeGroup

AttributeGroup

Returns all attribute groups.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

`format`
required string `json`

QUERY PARAMETERS

`isoCode` string
es by default

`page` integer
Default 0

`pageSize` integer
Default 0

Responses

- > **200** Returned when successful
- **409** Returned when no attributeGroups were found in cache.
- **415** Returned on invalid Content-Type header.
- **429** Exceeded requests limits.

GET /rest/catalog/attributegroups.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeGroupApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogAttributegroups($format, $page,
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeGroupApi->getRestCatalogAttribut
* }
* ?>
*
```

Response samples

[200](#)[409](#)[415](#)[429](#)

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
[
  - {
    "id": 123456,
    "name": "Color",
    "isoCode": "en"
  }
]
```

Returns attribute group by id.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

QUERY PARAMETERS

| | |
|---------|-------------------------|
| isoCode | string
es by default |
|---------|-------------------------|

Responses

- > 200 Returned when successful
- 404 Returned when no attributeGroup found with id X.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/catalog/attributegroup/{id}.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeGroupApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogAttributegroup($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeGroupApi->getRestCatalogAttribut
* }
* ?>
*
```

Response samples

[200](#)[404](#)[415](#)[429](#)

Content type

application/json

[Copy](#)

```
{
  "id": 123456,
  "name": "Color",
  "isoCode": "en"
}
```

Returns single attribute group all languages.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

Responses

- > 200 Returned when successful
- 404 Returned when no attributeGroup found with id X.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/catalog/attributegroupalllanguages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\AttributeGroupApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogAttributegroupId($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling AttributeGroupApi->getRestCatalogAttribut
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": 123456,
    "name": "Color",
    "isoCode": "en"
  }
]
```

Category

Category

Lists all categories. Deprecated

Deprecated: Use /taxonomies instead

*

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--|---|
| <code>format</code>
required | string <code>json</code>
JSON or XML |
|--|---|

QUERY PARAMETERS

| | |
|----------------------|-------------------------|
| <code>isoCode</code> | string
es by default |
|----------------------|-------------------------|

| | |
|-------------------|----------------------|
| <code>page</code> | integer
Default 0 |
|-------------------|----------------------|

| | |
|-----------------------|----------------------|
| <code>pageSize</code> | integer
Default 0 |
|-----------------------|----------------------|

Responses

> **200** Returned when successful

— **409** Returned when no categories were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/categories.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\CategoryApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogCategories($format, $iso_code, $
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling CategoryApi->getRestCatalogCategories: ',
* }
* ?>
```

Response samples

200

409

415

429

Content type

application/json

```
[
  - {
    "id": 123456,
    "name": "Home and Garden",
    "url": "home-garden",
    "parentCategory": 789456,
    "dateAdd": "2016-05-13 11:35:40",
    "dateUpd": "2023-05-13 11:35:40",
    + "urlImages": [ ... ],
    "isoCode": "en"
  }
]
```

Returns the selected category by id. Deprecated

Deprecated: Use /taxonomy/{id} instead
*

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id
required string \d+

format
required string json

Responses

> 200 Returned when successful

— 404 Returned when no category found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/category/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\CategoryApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogCategory($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling CategoryApi->getRestCatalogCategory: ', $
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": 123456,
  "name": "Home and Garden",
  "url": "home-garden",
  "parentCategory": 789456,
  "dateAdd": "2016-05-13 11:35:40",
  "dateUpd": "2023-05-13 11:35:40",
  - "urlImages": [
    "https://cdnbigbuy.com/images/category/2595_header.jpg"
  ],
  "isoCode": "en"
}
```

Returns the selected category all languages. Deprecated

Deprecated: Use /taxonomyalllanguages/{id} instead
*

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

Responses

- > 200 Returned when successful
- 404 Returned when no category found with id X.
- 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/categoryalllanguages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\CategoryApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogCategoryAllLanguages($id, $forma
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling CategoryApi->getRestCatalogCategoryAllLan
* }
* ?>
```

Response samples

200

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": 123456,
    "name": "Home and Garden",
    "url": "home-garden",
    "parentCategory": 789456,
    "dateAdd": "2016-05-13 11:35:40",
    "dateUpd": "2023-05-13 11:35:40",
    + "urlImages": [ ... ],
    "isoCode": "en"
  }
]
```

Returns all products categories. Deprecated

Deprecated: Use /productstaxonomies instead
*

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 2 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

QUERY PARAMETERS

| | |
|----------------|-----------------------------|
| page | integer
Default 0 |
| pageSize | integer
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

> **200** Returned when successful

— **409** Returned when no productCategories were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productscategories.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\CategoryApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsCategories($format, $pag
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling CategoryApi->getRestCatalogProductsCatego
* }
* ?>
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "product": 789456,
    "category": 123456,
    "position": 0
  }
]
```

Returns all categories for a given product. Deprecated

Deprecated: Use /producttaxonomies/{id} instead
*

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--------------------|---------------------------|
| id
required | integer \d+
Product id |
| format
required | string json |

Responses

> 200 Returned when successful

— **404** Returned when no productCategories found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productcategories/{id}.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\CategoryApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 56; // int | Product id
* $format = 'format_example'; // string | Response format, defaults to j
*
* try {
* $result = $apiInstance->getRestCatalogProductCategories($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling CategoryApi->getRestCatalogProductCategor
* }
* ?>
```

Response samples

[200](#)[404](#)[415](#)[429](#)

Content type

application/json

Copy

```
{
  "id": 123456,
  "product": 789456,
  "category": 123456,
  "position": 0
}
```

Language

Language

Returns all languages.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|----------------------------|
| format
required | string json
JSON or XML |
|--------------------|----------------------------|

Responses

> 200 Returned when successful

— 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/languages.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\LanguageApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
*
* try {
* $result = $apiInstance->getRestCatalogLanguages($format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling LanguageApi->getRestCatalogLanguages: ',
* }
* ?>
*
```

Response samples

200

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "name": "English",
    "isoCode": "en"
  }
]
```

Manufacturer

Manufacturer

Returns all manufacturers.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 5 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|----------------------------------|--------------------|
| format
<i>required</i> | string <i>json</i> |
|----------------------------------|--------------------|

QUERY PARAMETERS

| | |
|-----------------------|-----------------------------|
| page | integer
Default 0 |
| pageSize | integer
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

➤ **200** Returned when successful

— **409** Returned when no manufacturers were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/manufacturers.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ManufacturerApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogManufacturers($format, $page, $p
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ManufacturerApi->getRestCatalogManufactur
* }
* ?>
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    "name": "BigBuy",
    "urlImage": "https://cdnbigbuy.com/images/brand/1_mini.png",
    "reference": 1234
  }
]
```

Returns a single manufacturer.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id
required

string \d+
Manufacturer id

format
required

string json

Responses

- > 200 Returned when successful
- 404 Returned when no manufacturer found with id X.
- 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/manufacture/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ManufacturerApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string | Manufacturer id
*
* try {
* $result = $apiInstance->getRestCatalogManufacturer($format, $id);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ManufacturerApi->getRestCatalogManufactur
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

Copy

```
{
  "id": 1234,
```

```
"name": "BigBuy",
"urlImage": "https://cdnbigbuy.com/images/brand/1_mini.png",
"reference": 1234
}
```

Compliance

Compliance

Get a single Product Compliance.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

id
required string
productId

format
required string *json*

QUERY PARAMETERS

isoCode string
es by default

Responses

> **200** Returned when successful

— **404** Returned when no product compliances found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productcompliance/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ComplianceApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string | productId
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogProductCompliancesId($id, $forma
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ComplianceApi->getRestCatalogProductCompl
* }
* ?>
```

Response samples

200

404

415

429

Content type
application/json

```
{
  "id": 1234,
  "sku": "S12435678",
  - "generalProductSafetyRegulations": [
    + { ... }
  ],
  - "productComplianceDocuments": [
    + { ... }
  ]
}
```

Product

Product

New or republished products

New or republished products in the last 7 days. Updated only once a day

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 2 | 1 h |

Maximum page size is 10000

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

QUERY PARAMETERS

page integer
Default 0

| | |
|----------------|-----------------------------|
| pageSize | integer
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

> **200** Returned when successful

— **409** Returned when no products were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/new-products.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductNew($format, $page, $page
```

```
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductNew: ',
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "manufacturer": 1234,
    "id": 1234567,
    "sku": "S12435678",
    "ean13": "7569000752751",
    "weight": 158,
    "height": 23,
    "width": 55,
    "depth": 10,
    "dateUpd": "2016-05-13 11:35:40",
    "category": 12450,
    "dateUpdDescription": "2016-05-13 11:35:40",
    "dateUpdImages": "2016-05-13 11:35:40",
    "dateUpdStock": "2016-05-13 11:35:40",
    "wholesalePrice": "50.47",
    "retailPrice": "64.20",
    "taxonomy": 11548,
    "dateAdd": "2016-05-13 11:35:40",
    "video": "0",
    "active": 1,
    "attributes": true,
    "categories": true,
    "images": true,
    "taxRate": 21,
    "taxId": 21,
    "inShopsPrice": 76,
    "condition": "New",
    "logisticClass": "A",
    "tags": true,
    "dateUpdProperties": "2016-05-13 11:35:40",
    "dateUpdCategories": "2016-05-13 11:35:40",
    + "priceLargeQuantities": [ ... ],
    "intrastat": null,
    "partNumber": "1234ABC",
    "canon": 0
  }
]
```

Returns all products.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

Maximum page size is 10000

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

`format`
required string `json`

QUERY PARAMETERS

| | |
|-----------------------------|-----------------------------|
| <code>page</code> | integer
Default 0 |
| <code>pageSize</code> | integer
Default 0 |
| <code>parentTaxonomy</code> | integer
Taxonomy Tree Id |

Responses

- > **200** Returned when successful
- **409** Returned when no products were found in cache.
- **415** Returned on invalid Content-Type header.
- **429** Exceeded requests limits.

GET `/rest/catalog/products.{format}`

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProduct($format, $page, $page_si
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProduct: ', $e-
* }
* ?>
*
```

Response samples

200

409

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "manufacturer": 1234,
    "id": 1234567,
    "sku": "S12435678",
    "ean13": "7569000752751",
    "weight": 158,
    "height": 23,
    "width": 55,
    "depth": 10,
    "dateUpd": "2016-05-13 11:35:40",
    "category": 12450,
    "dateUpdDescription": "2016-05-13 11:35:40",
    "dateUpdImages": "2016-05-13 11:35:40",
    "dateUpdStock": "2016-05-13 11:35:40",
    "wholesalePrice": "50.47",
    "retailPrice": "64.20",
    "taxonomy": 11548,
    "dateAdd": "2016-05-13 11:35:40",
    "video": "0",
    "active": 1,
    "attributes": true,
    "categories": true,
    "images": true,
    "taxRate": 21,
    "taxId": 21,
    "inShopsPrice": 76,
    "condition": "New",
    "logisticClass": "A",
    "tags": true,
    "dateUpdProperties": "2016-05-13 11:35:40",
    "dateUpdCategories": "2016-05-13 11:35:40",
    + "priceLargeQuantities": [ ... ],
    "intrastat": null,
    "partNumber": "1234ABC",
    "canon": 0
  }
]
```

Get a single product.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|---------------------------|--------------------|
| id
required | string |
| format
required | string <i>json</i> |

Responses

> **200** Returned when successful

— **404** Returned when no product found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/product/{id}.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
```

```
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogProductId($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductId: ', $
* }
* ?>
*
```

Response samples

200**404****415****429**

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "manufacturer": 1234,
  "id": 1234567,
  "sku": "S12435678",
  "ean13": "7569000752751",
  "weight": 158,
  "height": 23,
  "width": 55,
  "depth": 10,
  "dateUpd": "2016-05-13 11:35:40",
  "category": 12450,
  "dateUpdDescription": "2016-05-13 11:35:40",
  "dateUpdImages": "2016-05-13 11:35:40",
  "dateUpdStock": "2016-05-13 11:35:40",
  "wholesalePrice": "50.47",
  "retailPrice": "64.20",
  "taxonomy": 11548,
  "dateAdd": "2016-05-13 11:35:40",
  "video": "",
  "active": 1,
  "attributes": true,
  "categories": true,
  "images": true,
  "taxRate": 21,
```



```
    "taxId": 21,
    "inShopsPrice": 76,
    "condition": "New",
    "logisticClass": "A",
    "tags": true,
    "dateUpdProperties": "2016-05-13 11:35:40",
    "dateUpdCategories": "2016-05-13 11:35:40",
    - "priceLargeQuantities": [
      + { ... }
    ],
    "intrastat": null,
    "partNumber": "1234ABC",
    "canon": 0
  }
```

Returns all products information.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|-------------|
| format
required | string json |
|--------------------|-------------|

QUERY PARAMETERS

| | |
|----------------|-----------------------------|
| isoCode | string
es by default |
| pageSize | string
Default 0 |
| page | string
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

> **200** Returned when successful

— **409** Returned when no products information were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

```
GET /rest/catalog/productsinformation.{format}
```

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

```
<?php
```

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
* $page_size = 'page_size_example'; // string | Default 0
* $page = 'page_example'; // string | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsInformation($format, $is
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductsInforma
* }
```

* ?>
*

Response samples

- 200
- 409
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    "sku": "S12435678",
    "name": "Wire Scalp Massager",
    "description": "<p>Do you constantly live under the effects of stress?",
    "url": "wire-scalp-massager",
    "isoCode": "en",
    "dateUpdDescription": "2016-05-13 11:35:40"
  }
]
```

Get a single product information.

Rate Limit

Max Requests	Period
1	5 s

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id required	string
format required	string json

QUERY PARAMETERS

isoCode

string
es by default

Responses

> **200** Returned when successful

— **404** Returned when no product found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

```
GET /rest/catalog/productinformation/{id}.{format}
```

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string |
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogProductInformationId($format, $i
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductInformat
```

* }
* ?>
*

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy

```
{  
  "id": 1234,  
  "sku": "S12435678",  
  "name": "Wire Scalp Massager",  
  "description": "<p>Do you constantly live under the effects of stress? No  
  "url": "wire-scalp-massager",  
  "isoCode": "en",  
  "dateUpdDescription": "2016-05-13 11:35:40"  
}
```

Get a single product information languages.

Rate Limit

Max Requests	Period
1	5 s

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id required	string product id
format required	string json

Responses

> **200** Returned when successful

— **404** Returned when no products information with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productinformationalllanguages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string | product id
*
* try {
* $result = $apiInstance->getRestCatalogProductInformationAllLanguagesId
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductInformat
* }
* ?>
*
```

Response samples

200

404

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    "sku": "S12435678",
    "name": "Wire Scalp Massager",
    "description": "<p>Do you constantly live under the effects of stress?",
    "url": "wire-scalp-massager",
    "isoCode": "en",
    "dateUpdDescription": "2016-05-13 11:35:40"
  }
]
```

Get a single product information by sku.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

sku
required string
product sku

format
required string *json*

QUERY PARAMETERS

isoCode string
es by default

Responses

➤ **200** Returned when successful

— **404** Returned when no product found with sku X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productinformationbysku/{sku}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ProductApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $sku = 'sku_example'; // string | product sku
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogProductInformationBySku($format,
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ProductApi->getRestCatalogProductInformat
* }
* ?>
```

Response samples

200

404

415

429

Content type
application/json

Copy

```
{
  "id": 1234,
  "sku": "S12435678",
  "name": "Wire Scalp Massager",
  "description": "<p>Do you constantly live under the effects of stress? No
  "url": "wire-scalp-massager",
  "isoCode": "en",
  "dateUpdDescription": "2016-05-13 11:35:40"
}
```

Image

Image

Returns all products images.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required

string json

QUERY PARAMETERS

pageSize

string
Default 0

| | |
|----------------|-----------------------------|
| page | string
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

- > 200 Returned when successful
- 409 Returned when no products images were found in cache.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/catalog/productsimages.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ImageApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page_size = 'page_size_example'; // string | Default 0
* $page = 'page_example'; // string | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsimages($format, $page_si
```

```
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ImageApi->getRestCatalogProductsimages: '
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
- {
  "id": 1234,
  + "images": [ ... ]
}
]
```

Get a single product images.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|----------------------|
| id
required | string
Product Id |
| format
required | string json |

Responses

> **200** Returned when successful

— **404** Returned when no product images found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productimages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ImageApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string | Product Id
*
* try {
* $result = $apiInstance->getRestCatalogProductimagesId($format, $id);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ImageApi->getRestCatalogProductimagesId:
* }
* ?>
*
```

Response samples

200

404

415

429

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": 1234,
  - "images": [
    + { ... }
  ]
}
```

Price

Price

Returns all product pricing info.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string json

QUERY PARAMETERS

includePriceLargeQuantities none
Include the volume discounts

page integer
Default 0

pageSize

integer

Default 0

parentTaxonomy

integer

First level taxonomy ID

Responses

> **200** Returned when successful

— **409** Returned when no results found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productprices.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\PriceApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductprices($format, $page, $p
```

```
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling PriceApi->getRestCatalogProductprices: ',
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    "sku": "S1243567",
    "wholesalePrice": 0.1,
    "retailPrice": 0.1,
    "inShopsPrice": 0.1,
    + "priceLargeQuantities": [ ... ]
  }
]
```

Returns all product variation pricing info.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required

string json

QUERY PARAMETERS

`includePriceLargeQuantities` none
Include the volume discounts

`page` integer
Default 0

`pageSize` integer
Default 0

`parentTaxonomy` integer
Taxonomy Tree Id

Responses

> **200** Returned when successful

— **409** Returned when no results found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET `/rest/catalog/productvariationprices.{format}`

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\PriceApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
```



```
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
*   $result = $apiInstance->getRestCatalogProductvariationprices($format,
*   print_r($result);
* } catch (Exception $e) {
*   echo 'Exception when calling PriceApi->getRestCatalogProductvariationp
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
- {
  "id": 1234,
  "sku": "S1243567",
  "wholesalePrice": 0.1,
  "retailPrice": 0.1,
  "inShopsPrice": 0.1,
+ "priceLargeQuantities": [ ... ]
}
]
```

Stock

Stock

Returns all products stock by handling days.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

QUERY PARAMETERS

page integer
Default 0

pageSize integer
Default 0

parentTaxonomy integer
Taxonomy Tree Id

Responses

- > **200** Returned when successful
- **409** Returned when no products stock by handling days were found in cache.
- **415** Returned on invalid Content-Type header.
- **429** Exceeded requests limits.

GET /rest/catalog/productsstockbyhandlingdays.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
```

```
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\StockApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsstockbyhandlingdays($for
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling StockApi->getRestCatalogProductsstockbyha
* }
* ?>
*
```

Response samples

200

409

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
- {
  "id": 1234,
  "sku": "S12435678",
+ "stocks": [ ... ]
}
]
```

Get a single product stock by handling days.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|---------------------------|--------------------|
| id
required | string |
| format
required | string <i>json</i> |

Responses

> **200** Returned when successful

— **404** Returned when no product stock found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productstockbyhandlingdays/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\StockApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
```

```
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
*   $result = $apiInstance->getRestCatalogProductStockByHandlingDaysById($
*   print_r($result);
* } catch (Exception $e) {
*   echo 'Exception when calling StockApi->getRestCatalogProductStockByHan
* }
* ?>
*
```

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": 1234,
  "sku": "S12435678",
  - "stocks": [
    + { ... }
  ]
}
```

Returns all products variation stock by handling days.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
requiredstring json

QUERY PARAMETERS

| | |
|----------------|-----------------------------|
| page | integer
Default 0 |
| pageSize | integer
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

- > 200 Returned when successful
- 409 Returned when no products variations stock were found in cache.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/catalog/productsvariationsstockbyhandlingdays.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\StockApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttpClient` will be used as default.
* new GuzzleHttpClient(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
```

```
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsvariationsstockbyhandlin
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling StockApi->getRestCatalogProductsvariation
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
- {
  "id": 1234,
  "sku": "S12435678",
+ "stocks": [ ... ]
}
]
```

Returns product variations stock by handling days by id.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id
requiredstring

format
required

string json

Responses

> **200** Returned when successful

— **404** Returned when no product variations stock found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productvariationsstockbyhandlingdays/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\StockApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogProductVariationsStockByHandling
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling StockApi->getRestCatalogProductVariations
* }
```


* ?>
*

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": 1234,
  "sku": "S12435678",
  - "stocks": [
    + { ... }
  ]
}
```

Tag

Tag

Lists all product tags.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

QUERY PARAMETERS

| | |
|----------------|-----------------------------|
| isoCode | string
es by default |
| pageSize | string
Default 0 |
| page | string
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

> **200** Returned when successful

— **409** Returned when no products tags were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productstags.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)**<?php**

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TagApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
```

```
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
* $page_size = 'page_size_example'; // string | Default 0
* $page = 'page_example'; // string | Default 0
*
* try {
*   $result = $apiInstance->getRestCatalogProductsTags($format, $iso_code,
*   print_r($result);
* } catch (Exception $e) {
*   echo 'Exception when calling TagApi->getRestCatalogProductsTags: ', $e
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
- {
  "id": 1234,
  "sku": "S12435678",
+ "tag": { ... }
}
]
```

Get a single ProductTag.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|----------------|---------------------|
| id
required | string
productId |
|----------------|---------------------|

| | |
|--------------------|-------------|
| format
required | string json |
|--------------------|-------------|

QUERY PARAMETERS

| | |
|---------|-------------------------|
| isoCode | string
es by default |
|---------|-------------------------|

Responses

> **200** Returned when successful

— **404** Returned when no product tags found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/producttags/{id}.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

```
<?php
```

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TagApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string | productId
```

```
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogProductTagsId($id, $format, $iso
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TagApi->getRestCatalogProductTagsId: ', $
* }
* ?>
*
```

Response samples

200

404

415

429

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": 1234,
  "sku": "S12435678",
  - "tag": {
    "id": 123456,
    "name": "animals",
    "linkRewrite": "animals",
    "language": "en"
  }
}
```

Lists all tags.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required

string json

QUERY PARAMETERS

isoCode

string
es by default

Responses

> **200** Returned when successful

— **409** Returned when no tags were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/tags.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TagApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
```

```
* $result = $apiInstance->getRestCatalogTags($format, $iso_code);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TagApi->getRestCatalogTags: ', $e->getMes
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "name": "animals",
    "linkRewrite": "animals",
    "language": "en"
  }
]
```

Get a single Tag.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id
requiredstring \d+

format
requiredstring json

QUERY PARAMETERS

isoCode

string
es by default

Responses

> **200** Returned when successful

— **404** Returned when no tag found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/tag/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TagApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string |
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogTag($format, $id, $iso_code);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TagApi->getRestCatalogTag: ', $e->getMess
```


* }
* ?>
*

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy

```
{  
  "id": 123456,  
  "name": "animals",  
  "linkRewrite": "animals",  
  "language": "en"  
}
```

Get a single Tag languages.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

Responses

> 200 Returned when successful

— **404** Returned when no tag languages found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/tagalllanguages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TagApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogTagAllLanguages($format, $id);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TagApi->getRestCatalogTagAllLanguages: ',
* }
* ?>
```

Response samples

200

404

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "name": "animals",
    "linkRewrite": "animals",
    "language": "en"
  }
]
```

Taxonomy

Taxonomy

Returns all products taxonomies.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 5 | 1 h |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--------------------|--------------------------|
| format
required | string <code>json</code> |
|--------------------|--------------------------|

QUERY PARAMETERS

| | |
|------|----------------------|
| page | integer
Default 0 |
|------|----------------------|

| | |
|----------|----------------------|
| pageSize | integer
Default 0 |
|----------|----------------------|

parentTaxonomy

integer

Taxonomy Tree Id

Responses

> **200** Returned when successful

— **409** Returned when no products taxonomies were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productstaxonomies.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TaxonomyApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $page = 56; // int | Default 0
* $page_size = 56; // int | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsTaxonomies($format, $pag
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TaxonomyApi->getRestCatalogProductsTaxono
```

* }
* ?>
*

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "taxonomy": 123456,
    "product": 654321
  }
]
```

Returns all taxonomies for a given product.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

id
required

integer \d+
Product id

format
required

string json

Responses

> **200** Returned when successful

— **404** Returned when no product taxonomies found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/producttaxonomies/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TaxonomyApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 56; // int | Product id
* $format = 'format_example'; // string | Response format, defaults to j
*
* try {
* $result = $apiInstance->getRestCatalogProductTaxonomies($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TaxonomyApi->getRestCatalogProductTaxonom
* }
* ?>
*
```

Response samples

200

404

415

429

Content type
application/json

Copy

```
{
  "id": 123456,
  "taxonomy": 123456,
  "product": 654321
}
```

Lists all taxonomies.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|--------------------|----------------------------|
| format
required | string json
JSON or XML |
|--------------------|----------------------------|

QUERY PARAMETERS

| | |
|------------|--|
| isoCode | string
es by default |
| firstLevel | integer
Send this parameter if only want to take first level categories |

Responses

- > 200 Returned when successful
- 409 Returned when no taxonomies were found in cache.
- 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

GET /rest/catalog/taxonomies.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TaxonomyApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogTaxonomies($format, $iso_code);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TaxonomyApi->getRestCatalogTaxonomies: ',
* }
* ?>
*
```

Response samples

200

409

415

429

Content type

application/json

Copy

Expand all

Collapse all


```
[
  - {
    "id": 1234,
    "name": "Home and Garden",
    "url": "home-garden",
    "parentTaxonomy": 6543,
    "dateAdd": "2016-05-13 11:35:40",
    "dateUpd": "2016-05-13 11:35:40",
    "urlImages": "https://cdnbigbuy.com/images/home-garden-00.jpg",
    "isoCode": "en"
  }
]
```

Returns the selected taxonomy all languages.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 24 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|---------------------------|-----------------------------------|
| format
required | string <i>json</i>
JSON or XML |
|---------------------------|-----------------------------------|

| | |
|-----------------------|-------------------|
| id
required | string <i>\d+</i> |
|-----------------------|-------------------|

QUERY PARAMETERS

| | |
|----------------|-------------------------|
| isoCode | string
es by default |
|----------------|-------------------------|

Responses

> **200** Returned when successful

— **404** Returned when no taxonomy found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/taxonomyalllanguages/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TaxonomyApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $id = 'id_example'; // string |
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestCatalogTaxonomyalllanguages($format, $i
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TaxonomyApi->getRestCatalogTaxonomyalllan
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

```
[
  - {
    "id": 1234,
    "name": "Home and Garden",
    "url": "home-garden",
    "parentTaxonomy": 6543,
    "dateAdd": "2016-05-13 11:35:40",
    "dateUpd": "2016-05-13 11:35:40",
    "urlImages": "https://cdnbigbuy.com/images/home-garden-00.jpg",
    "isoCode": "en"
  }
]
```

Variation

Variation

Returns all products variations.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
requiredstring json

QUERY PARAMETERS

pageSizestring
Default 0

| | |
|----------------|-----------------------------|
| page | string
Default 0 |
| parentTaxonomy | integer
Taxonomy Tree Id |

Responses

> **200** Returned when successful

— **409** Returned when no products variations were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/productsvariations.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)

```
<?php
```

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\VariationApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string |
* $page_size = 'page_size_example'; // string | Default 0
* $page = 'page_example'; // string | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogProductsVariations($format, $pag
```

```
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling VariationApi->getRestCatalogProductsVaria
* }
* ?>
*
```

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
- {
  "id": 1234,
  "sku": "S12435678",
  "ean13": "7569000752751",
  "extraWeight": 10,
  "product": 6543,
  "wholesalePrice": 50,
  "retailPrice": 64.55,
  "inShopsPrice": 76,
  "width": 22.7,
  "height": 10.56,
  "depth": 5.28,
+ "priceLargeQuantities": [ ... ],
  "logisticClass": "A",
  "partNumber": "1234ABC",
  "canon": 0
}
]
```

Get a single product variations.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|---------------------------|--------------------|
| id
required | string |
| format
required | string <i>json</i> |

Responses

> **200** Returned when successful

GET /rest/catalog/productvariations/{id}.{format}

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    "sku": "S12435678",
    "ean13": "7569000752751",
    "extraWeight": 10,
    "product": 6543,
    "wholesalePrice": 50,
    "retailPrice": 64.55,
    "inShopsPrice": 76,
    "width": 22.7,
    "height": 10.56,
    "depth": 5.28,
    + "priceLargeQuantities": [ ... ],
    "logisticClass": "A",
    "partNumber": "1234ABC",
    "canon": 0
  }
]
```

Returns all variations.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 10 | 1 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
requiredstring json

QUERY PARAMETERS

pageSizestring
Default 0

pagestring
Default 0

parentTaxonomy

integer

Taxonomy Tree Id

Responses

> **200** Returned when successful

— **409** Returned when no variations were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/variations.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\VariationApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string |
* $page_size = 'page_size_example'; // string | Default 0
* $page = 'page_example'; // string | Default 0
*
* try {
* $result = $apiInstance->getRestCatalogVariations($format, $page_size,
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling VariationApi->getRestCatalogVariations: '
```


* }
* ?>
*

Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 1234,
    + "attributes": [ ... ]
  }
]
```

Get a single variation.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 5 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|--------------------|-------------|
| id
required | string \d+ |
| format
required | string json |

Responses

> 200 Returned when successful

— **404** Returned when no variation found with id X.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/catalog/variation/{id}.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\VariationApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id = 'id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestCatalogVariation($id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling VariationApi->getRestCatalogVariation: ',
* }
* ?>
```

Response samples

200

404

415

429

Content type
application/json

Copy Expand all Collapse all

```
{
  "id": 1234,
  - "attributes": [
    + { ... }
  ]
}
```

Order

Order

Submit an order

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

REQUEST BODY SCHEMA: application/json

order > object (CustomerOrder)

Responses

> **201** Returned when successful. To retrieve the created order ID, parse the location header.

— **400** Returned when validation errors has been found.

— **404** Returned when no carriers/products has been found.

— **409** Returned when there are constrain conflicts.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

POST `/rest/order/create.{format}`

Request samples

Payload

PHP

Java

Python

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "order": {
    "internalReference": "123456789",
    "language": "en",
    "paymentMethod": "paypal",
    + "carriers": [ ... ],
    + "shippingAddress": { ... },
    + "products": [ ... ]
  }
}
```

Response samples

201

400

404

409

415

429

Content type

application/json

Copy

```
{
  "order_id": "123456"
}
```

Check/simulate an order and return the total order to paid.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

REQUEST BODY SCHEMA: application/json

order > object (CustomerOrder)

Responses

- > 200 Returned when successful.
- 400 Returned when validation errors has been found.
- 404 Returned when no carriers/products has been found.
- 409 Returned when there are constrain conflicts.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

POST /rest/order/check.{format}

Request samples

Payload

PHP

Java

Python

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "order": {
    "internalReference": "123456789",
    "language": "en",
    "paymentMethod": "paypal",
    + "carriers": [ ... ],
    + "shippingAddress": { ... },
    + "products": [ ... ]
  }
}
```

Response samples

200

400

404

409

415

429

Content type

application/json

Copy

```
{
  "totalWithoutTaxesAndWithoutShippingCost": 20.77,
  "totalWithoutTaxes": 27.45,
  "total": 32.56
}
```

Get order information by customer reference.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

| | |
|-----------------------|-------------|
| reference
required | string |
| format
required | string json |

Responses

> **200** Returned when successful

— **404** Returned when no order were found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/order/reference/{reference}.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\OrderApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
```

```
* );
* $reference = 'reference_example'; // string |
* $format = 'format_example'; // string |
*
* try {
*   $result = $apiInstance->getRestOrderOrderReference($reference, $format
*   print_r($result);
* } catch (Exception $e) {
*   echo 'Exception when calling OrderApi->getRestOrderOrderReference: ',
* }
* ?>
*
```

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy

```
{
  "id": "123456",
  "totalPaidTaxIncl": "44.56"
}
```

Get order statuses.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required

string json

QUERY PARAMETERS

language

string

isoCode language

Responses

> **200** Returned when successful

— **400** Returned when validation errors has been found.

— **404** Returned when not found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/order/orderstatuses.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\OrderApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | Response format, defaults to j
* $language = 'language_example'; // string | isoCode language
*
* try {
* $result = $apiInstance->getRestOrderOrderStatuses($format, $language);
* print_r($result);
* } catch (Exception $e) {
```

```
* echo 'Exception when calling OrderApi->getRestOrderOrderStatuses: ', $
* }
* ?>
*
```

Response samples

- 200
- 400
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "name": "In process"
  }
]
```

Get order information.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|---------------------|-------------|
| orderId
required | string |
| format
required | string json |

Responses

> 200 Returned when successful

- **404** Returned when no order were found.
- **415** Returned on invalid Content-Type header.
- **429** Exceeded requests limits.

GET /rest/order/{orderId}.{format}

Request samples

[PHP](#)[Java](#)[Python](#)[Copy](#)**<?php**

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\OrderApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $order_id = 'order_id_example'; // string |
* $format = 'format_example'; // string |
*
* try {
* $result = $apiInstance->getRestOrderOrderId($order_id, $format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling OrderApi->getRestOrderOrderId: ', $e->get
* }
* ?>
```

Response samples

[200](#)[404](#)[415](#)[429](#)

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "id": 123456,
  "internalReference": "123456789",
  "dateAdd": "2023-05-13 11:35:40",
  "totalPaidTaxIncl": 64.59,
  "totalPaidTaxExcl": 55.82,
  "totalShippingTaxExcl": 5.23,
  "totalShippingTaxIncl": 7.66,
  "status": "In process",
  - "carriers": [
    + { ... }
  ],
  - "shippingAddress": {
    "id": 123456,
    "firstName": "Alejandro",
    "lastName": "Lopez Garcia",
    "country": "Spain",
    "postcode": 46011,
    "town": "Valencia",
    "address": "Road 17",
    "phone": 123456789,
    "email": "example@gmail.com",
    "vatNumber": "21",
    "companyName": "Company",
    "comment": "Comment example"
  },
  - "products": [
    + { ... }
  ]
}
```

Upload a base64-encoded invoice to an order in PENDING INVOICE status.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

REQUEST BODY SCHEMA: application/json

| | |
|----------------------|--|
| idOrder
required | string |
| file
required | string |
| mimeType
required | string
Enum: "application/pdf" "image/png" "image/jpeg" |
| amount
required | number <float> |
| concept
required | string |
| invoiceDetail > | object or null |

Responses

- 200 Returned when successful. To retrieve the created order ID, parse the location header
- 400 Returned when validation errors has been found.
- 409 Returned when there are constrain conflicts.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

POST /rest/order/upload_invoice

Request samples

Payload

PHP

Java

Python

Content type
application/json

Copy

```
{
  "idOrder": 123456,
  "file": "JVBERi0xLjMNCi...Xi48/JSVFT0YNCg==",
  "mimeType": "mimeType",
  "amount": 44.53,
  "concept": "Concept example",
  "invoiceDetail": "Invoice detail"
}
```

Response samples

200

400

409

415

429

Content type
application/json

Copy

```
[
  true
]
```

Submit an order multishipping.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required

string json

REQUEST BODY SCHEMA: application/json

order >

object (CustomerOrder)

Responses

> **201** Returned an order created.

— **400** Returned when validation errors has been found.

— **409** Returned when there are constrain conflicts.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

POST `/rest/order/create/multishipping.{format}`

Request samples

Payload

PHP

Java

Python

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "order": {
    "internalReference": "123456789",
    "language": "en",
    "paymentMethod": "paypal",
    + "carriers": [ ... ],
    + "shippingAddress": { ... },
    + "products": [ ... ]
  }
}
```

Response samples

201**400****409****415****429**

Content type
application/json

Copy Expand all Collapse all

```
{
  - "orders": [
    + { ... }
  ],
  - "errors": [
    + { ... }
  ]
}
```

Check/simulate an order and return order multishipping.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

REQUEST BODY SCHEMA: application/json

order > object (CustomerOrder)

Responses

- > 200 Returned when successful.
- 400 Returned when validation errors has been found.
- 409 Returned when there are constrain conflicts.

— 415 Returned on invalid Content-Type header.

— 429 Exceeded requests limits.

POST /rest/order/check/multishipping.{format}

Request samples

- Payload
- PHP
- Java
- Python

Content type
application/json

Copy Expand all Collapse all

```
{
  - "order": {
    "internalReference": "123456789",
    "language": "en",
    "paymentMethod": "paypal",
    + "carriers": [ ... ],
    + "shippingAddress": { ... },
    + "products": [ ... ]
  }
}
```

Response samples

- 200
- 400
- 409
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
{
  - "orders": [
    + { ... }
  ],
  - "errors": [
    + { ... }
  ]
}
```

Get delivery notes for the order

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

orderId
required string

Responses

> **200** Returned when successful.

— **403** Returned when order does not belong to the user

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/order/delivery-notes/{orderId}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
```

```
*
* $apiInstance = new Swagger\Client\Api\OrderApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $order_id = 'order_id_example'; // string |
*
* try {
* $result = $apiInstance->getRestOrderDeliveryNotesByOrder($order_id);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling OrderApi->getRestOrderDeliveryNotesByOrde
* }
* ?>
*
```

Response samples

200

403

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
{
  "reference": "WH/OUT/0000001",
  "order": "10000001",
  "status": "SHIPPED",
  "carrier": "GLS",
  "numberOfPackages": 2,
  - "products": [
    + { ... }
  ]
}
```

Shipping

Shipping

Get the list of available carriers.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

Responses

> **200** Returned when successful

— **404** Returned when no carriers were found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/shipping/carriers.{format}

Request samples

PHP

Java

Python

Copy

```
<?php
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ShippingApi(
```

```
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
*
* try {
* $result = $apiInstance->getRestShippingCarriers($format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ShippingApi->getRestShippingCarriers: ',
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "id": "1234",
    "name": "GLS",
    + "shippingServices": [ ... ],
    + "shippingCountries": [ ... ],
    + "excludedProductReferences": [ ... ],
    + "excludedCategoryIds": [ ... ]
  }
]
```

Returns the lowest shipping cost for a product reference when sent to the provided country.

IMPORTANT: Carriers that do not offer proof of delivery (POD), such as Correos International or Postal Service, are excluded

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

REQUEST BODY SCHEMA: application/json

productCountry > object (ProductCountry)

Responses

- > 200 Returned when successful
- 400 Returned when validation errors has been found.
- 404 Returned when no carriers were found.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

POST /rest/shipping/lowest-shipping-cost-by-country.{format}

Request samples

Payload

PHP

Java

Python

Content type
application/json

Copy Expand all Collapse all

```
{
  - "productCountry": {
    "reference": "S12435678",
    "countryIsoCode": "en"
  }
}
```

Response samples

- 200
- 400
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "shippingCost": 4.56,
    + "carrier": { ... }
  }
]
```

Returns the lowest shipping cost for every product when being shipped to the provided country.

IMPORTANT: Carriers that do not offer proof of delivery (POD), such as Correos International or Postal Service, are excluded

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 36 | 6 h |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|----------------|------------|
| countryIsoCode | string |
| required | example es |

| | |
|----------|-------------|
| format | string json |
| required | |

Responses

> **200** Returned when successful

— **409** Returned when no shippingCosts were found in cache.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

```
GET /rest/shipping/lowest-shipping-costs-by-country/{countryIsoCode}.{...
```

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\ShippingApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
* $country_iso_code = 'country_iso_code_example'; // string | example es
*
* try {
* $result = $apiInstance->getRestShippingLowestShippingCostByCountryCoun
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling ShippingApi->getRestShippingLowestShippin
* }
* ?>
*
```


Response samples

200

409

415

429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "reference": "S12435678",
    "cost": "4.76",
    "carrierId": "1234",
    "carrierName": "GLS"
  }
]
```

Get shipping costs for an order.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

REQUEST BODY SCHEMA: application/json

order > object (OrderCartShippingOption)

Responses

> 200 Returned when successful

— **400** Returned when validation errors has been found.

— **404** Returned when no carriers were found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

POST /rest/shipping/orders.{format}

Request samples

Payload

PHP

Java

Python

Content type

application/json

Copy

Expand all

Collapse all

```
{
  - "order": {
    + "products": [ ... ],
    + "delivery": { ... }
  }
}
```

Response samples

200

400

404

415

429

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    + "shippingOptions": [ ... ]
  }
]
```

Tracking

Tracking

Get the list of available carriers.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required

string json

Responses

- > 200 Returned when successful
- 404 Returned when no carriers were found.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/tracking/carriers.{format}

Request samples

PHP

Java

Python

[Copy](#)

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TrackingApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
*
* try {
* $result = $apiInstance->getRestTrackingCarriers($format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TrackingApi->getRestTrackingCarriers: ',
* }
* ?>
*
```

Response samples

200

404

415

429

Content type

application/json

[Copy](#)[Expand all](#)[Collapse all](#)

```
[
  - {
    "id": "1234",
    "name": "GLS"
  }
]
```

Get the list of available trackings for the passed orders.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > *Bearer*

PATH PARAMETERS

format
required string *json*

QUERY PARAMETERS

isoCode string
es by default

REQUEST BODY SCHEMA: application/json

track > object (Track)

Responses

- > **200** Returned when successful
- **400** Invalid order tracking format.
- **404** Returned when no carriers were found.
- **415** Returned on invalid Content-Type header.
- **429** Exceeded requests limits.

POST /rest/tracking/orders.{format}

Request samples

Payload

PHP

Content type
application/json

Copy Expand all Collapse all

```
{
  - "track": {
    + "orders": [ ... ]
  }
}
```

Response samples

- 200
- 400
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "reference": 789456123,
    + "trackings": [ ... ]
  }
]
```

Get the list of available trackings.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

| | |
|---------------------|--------------------|
| idOrder
required | string
Order id |
| format
required | string json |

QUERY PARAMETERS

isoCode

string
es by default

Responses

> **200** Returned when successful

— **404** Returned when no trackings were found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

```
GET /rest/tracking/order/{idOrder}.{format}
```

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\TrackingApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $id_order = 'id_order_example'; // string | Order id
* $format = 'format_example'; // string |
* $iso_code = 'iso_code_example'; // string | es by default
*
* try {
* $result = $apiInstance->getRestTrackingOrderTrackingById($id_orde
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling TrackingApi->getRestTrackingOrderTracking
```

* }
* ?>
*

Response samples

- 200
- 404
- 415
- 429

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "id": 123456,
    "reference": 789456123,
    + "trackings": [ ... ]
  }
]
```

User

User

Get the ammount of money available in the purse.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
required string json

Responses

> **200** Returned when successful

— **404** Returned when not available ammount of money available were found.

— **415** Returned on invalid Content-Type header.

— **429** Exceeded requests limits.

GET /rest/user/purse.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\UserApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string | JSON or XML
*
* try {
* $result = $apiInstance->getRestUserPurse($format);
* print_r($result);
* } catch (Exception $e) {
* echo 'Exception when calling UserApi->getRestUserPurse: ', $e->getMess
* }
* ?>
```

Response samples

200

404

415

429

Content type
application/json

Copy

"12234"

Get the auth status from user.

Rate Limit

| Max Requests | Period |
|--------------|--------|
| 1 | 1 s |

AUTHORIZATIONS: > Bearer

PATH PARAMETERS

format
requiredstring json

Responses

- 200 Returned when successful
- 404 Returned when not not user were found.
- 415 Returned on invalid Content-Type header.
- 429 Exceeded requests limits.

GET /rest/user/auth/status.{format}

Request samples

PHP

Java

Python

Copy

<?php

```
* require_once(__DIR__ . '/vendor/autoload.php');
* // Configure HTTP bearer authorization: Bearer
* $config = Swagger\Client\Configuration::getDefaultConfiguration()
* ->setAccessToken('YOUR_ACCESS_TOKEN');
*
* $apiInstance = new Swagger\Client\Api\UserApi(
* // If you want use custom http client, pass your client which implemen
* // This is optional, `GuzzleHttp\Client` will be used as default.
* new GuzzleHttp\Client(),
* $config
* );
* $format = 'format_example'; // string |
*
* try {
*     $apiInstance->getRestUserAuthStatus($format);
* } catch (Exception $e) {
*     echo 'Exception when calling UserApi->getRestUserAuthStatus: ', $e
* }
* ?>
```

Response samples

200

404

415

429

Content type

application/json

Copy

```
{
  "code": 200,
  "message": "Returned when successful"
}
```