



U_PERIPHERAL_PORT_IO
PERIPHERAL_PORT_IO.SchDoc

U_RAM
RAM.SchDoc

U_LOGIC_FPGA
LOGIC_FPGA.SchDoc

U_POWER_SUPPLY
POWER_SUPPLY.SchDoc

U_FPGA_POWER_AND_CONFIGURATION
FPGA_POWER_AND_CONFIGURATION.SchDoc

U_DIGITAL_IO
DIGITAL_IO.SchDoc

LOGi-Bone Top Level			
Revision:	R1.0	Sheet	1 of 7
Date:	5/27/2014	Engineer:	MJones

ValentF(X) ELECTRONICS INNOVATION

Power: By Default Power will be supplied by the Beaglebone.

Optionally power can be supplied through FPGA VIN header J1.



1 x Auxillary Power output Headers



LOGI-LOGO-600
LOGO3

VALENTFX-LOGO-750
Logo5

LOGI-LOGO-750
LOGO4

Title	Power Supply		
Revision:	R1.0	Sheet	2 of 7
Date:	5/27/2014	Engineer:	MJones

















Decoupling cap configuration recommended by Xilinx UG393 (V1.2) for Spartan 6 power distribution



Title	FPGA Configuration		
Revision:	R1.0	Sheet	3 of 7
Date:	5/27/2014	Engineer:	MJones

ValentF(X) ELECTRONICS INNOVATION



















FPGA EXT Oscillator: 50Mhz





Title	FPGA Logic		
Revision:	R1.0	Sheet	4 of 7
Date:	5/27/2014	Engineer:	MJones

ValentF(x) ELECTRONICS INNOVATION

Beaglebone Configuration EEPROM



CAT24C256YI-G

Address Selection DIP SW

If the DIP SW is NOT installed the eerpom will hold the low address 0x54 (highest priority) for capes and be used for the bone pin configuration in the case multiple installed of capes

Arduino Header - Arduino Shield Expansion



GPIO Expander - Handling of General Control Pins



Beaglebone P8



Value
SAM1197-23-ND

Beaglebone P9



Value





Title	Peripheral Port IO		
Revision:	R1.0	Sheet	5 of 7
Date:	5/27/2014	Engineer:	MJones

ValentF(X) ELECTRONICS INNOVATION

FPGA Digital IO



USER PUSH BUTTON

SATA HIGH BANDWITH EXPANSION

PMOD1 PORT

PMOD2 PORT

Title	Digital IO		
Revision:	R1.0	Sheet	6 of 7
Date:	5/27/2014	Engineer:	MJones

ValentF(X) ELECTRONICS INNOVATION

SDRAM



Title	RAM
Revision:	R1.0
Sheet	7 of 7
Date:	5/27/2014
Engineer:	MJones

ValentF(X) ELECTRONICS INNOVATION