CSE 2010, HW4

Due Thu Mar 9 at the start of your lab section; Submit Server: class = cse2010, assignment = hw4SxIndividual Due Thu Mar 9 at the end of your lab section; Submit Server: class = cse2010, assignment = hw4SxGroupHelp x is 14, 23, or c—your merged section number or c.

To add an element of surprise/excitement (and perhaps more revenue), an online retail/auction site tries to sell multiple items of the same product at random times over a period of time (e.g. 1,000 items at random times over 24 hours). How would you design an efficient system to match items to bids from customers?

The goal of HW4 is to design a system that can efficiently match items with the highest bidding price at different times. The system allows customers to enter bids. Each bid consists of a price and quantity. For simplicity, each customer can have one bid and there is only one product. If two bids have the same price, the earlier bid has a higher priority (assume the timestamp of a bid is unique). Also, to not lose money, the site does not sell an item if the highest bidding price is lower than the minimum acceptable price, which can be updated over time by the retailer (e.g. higher at the beginning).

To manage and find the highest bid efficiently, use a priority queue implemented with a heap. Each entry of the priority queue has: bid price (key), timestamp (secondary key), and customer name (value). Assume at most 100 entries. A tie in the price is broken by the timestamp. Functions/methods include:

- insert(entry)
- \bullet remove Max() // return and remove entry with the maximum key
- getMax() // return entry with the maximum key
- isFull()
- isEmpty()

To implement the priority queue, you may modify/rewrite Code Fragment 9.8 on pp. 377-378 (Programs 9.20 and 9.21 on pp. 352-355 in Standish) We will be evaluating your submission on code01.fit.edu; we strongly recommend you to ensure that your submission functions properly on code01.fit.edu.

Input: The command-line argument for HW4.java (hw4.c) is the name of the input file, which has:

- EnterBid time name price quantity
- UpdateMinimumAcceptablePrice time price
- SellOneItem time
- DisplayHighestBid time

Time is an integer in HHMM format, where HH is 00-23 and MM is 00-59 (leading zeros are optional). Sample input files are on the course website. You may assume names are unique.

Output: Output goes to the standard output (screen), each line corresponds to an action:

- EnterBid time name price quantity
- ullet UpdateMinimumAcceptablePrice $time\ price$

- SellOneItem $time\ name\ price\ [NoBids\ /\ HighestBidding-PriceIsTooLow]$
- DisplayHighestBid time name bidTime price quantity

Sample output is on the course website.

Extra Credit (10 pts): Separate submission via HW4Extra.java (hw4extra.c). Consider the customers are also allowed to update bids. Additional possible input action is:

• UpdateBid time name price quantity

and output result is:

• UpdateBid time name price quantity [customerNot-Found]

Although the priority queue is designed to find the highest bid quickly, it is not designed to find a customer quickly [faster than O(N), where N is the number of customers].

- 1. Design and implement an additional data structure that can help find a customer and update the priority queue faster than O(N).
- 2. In the comments at the top of your program (or in a separate PDF file):
 - (a) explain why your additional data structure can help UpdateBid become faster than O(N) with an analysis of the time complexity of UpdateBid.
 - (b) for UpdateBid, discuss the different cases and how the heap (priority queue) needs to be adjusted.
 - (c) explain why EnterBid becomes slower than $O(\log N)$ [It's OK for now; it can be can be remedied with data structures to be discussed later in the course.]

Submission: Submit HW4.java (hw4.c) that has the main method and other program files. Submissions for Individual and GroupHelp have the same guidelines as HW1.

Note the late penalty on the syllabus if you submit after the due date and time as specified at the top of the assignment.

For extra credit, submit HW4Extra.java (hw4extra.c) that has the main method and other program files. GroupHelp submission is not applicable to extra credit. Late submission for extra credit is not accepted.