# REAL – TIME EMOTION – ADAPTIVE HUMAN – ROBOT – INTERACTION SYSTEM FOR INTELLIGENT WORKSPACE ASSISTANCE

23BAI1563 | Joelle Mary Suji

23BAI1569 | Nikita Elizabeth Chacko

23BRS1015 | Ananth S Mahadev

# PROJECT ABSTRACT

Human – Robot Interaction (HRI) has advanced significantly with the development of artificial intelligence, emotion recognition, and natural language processing. However, most existing systems focus only on detecting user emotions and provide limited personalized assistance in real – world environments. This project proposes a **real – time emotion – adaptive intelligent desk robot** that combines **facial emotion recognition, speech emotion recognition, multimodal emotion fusion, long – term conversational memory, and IoT – based smart workspace control** to create a personalized study and work companion. The robot continuously analyses the user's emotional and cognitive state through facial expressions, speech, attention level, and eye fatigue. Based on this understanding, it responds through natural conversations, expressive gestures, and intelligent actions such as break reminders, adaptive lighting, and screen brightness adjustment. The system also maintains long – term memory of user preferences and previous interactions to deliver personalized assistance over time. By integrating multimodal perception, explainable decision – making, and adaptive workspace automation into a single humanoid platform, the proposed system aims to provide a more natural, intelligent, and human – centred workspace assistant.

# LITERATURE REVIEW

# – EMOTION RECOGNITION –

| I | Deep Facial Expression Recognition : A Survey (Shan Li, Wiehong Deng) |
|---|---|

## RESEARCH OBJECTIVE

Review the development of deep learning-based facial expression recognition and identify its challenges and future directions.

## METHODOLOGY

- Reviewed the deep FER pipeline from face detection to emotion classification.
- Discussed deep learning architectures (CNN, VGG, ResNet, DenseNet) and their training strategies.
- Reviewed benchmark datasets (FER2013, CK+, RAF-DB, AffectNet) and their applications.

## RESEARCH GAP FOUND

Existing deep FER systems mainly focus on facial expressions and do not incorporate behavioral cues for more effective emotion analysis.

| II | A survey on facial emotion recognition techniques: A state-of-the-art literature review (Felipe Zago Canal, Tobias Rossi Müller) |
|---|---|

## RESEARCH OBJECTIVE

Compare existing classical and deep learning techniques used for facial emotion recognition.

## METHODOLOGY

- Reviewed 51 research papers consisting of 94 FER methods.
- Compared classical machine learning approaches (SVM, Random Forest, KNN, LBP, HOG) with deep learning approaches (CNN, Transfer Learning).
- Reviewed popular FER datasets (FER2013, CK+, JAFFE, MMI, AffectNet, RAF-DB) and compared their strengths and limitations.

## RESEARCH GAP FOUND

Existing FER techniques still struggle to generalize across diverse real – world environments due to small, lab – controlled datasets.

| III | **Advances in Facial Expression Recognition: A Survey of Methods, Benchmarks, Models, and Datasets (Thomas Kopalidis, Vassilios Solachidis, Nicholas Vretos, Petros Daras)** |
|---|---|

## RESEARCH OBJECTIVE

Analyze latest FER methods, benchmark datasets, evaluation methods, and recent advances in FER.

## METHODOLOGY

- Reviewed the evolution of FER from traditional approaches to Transformer – based models.
- Compared accuracy of FER models (CNN, ResNet, DenseNet, EfficientNet, Vision Transformer, FER-Former, TransFER).
- Analyzed performance across popular FER datasets (FER2013, FER+, JAFFE, AFEW, CK+).

## RESEARCH GAP FOUND

Existing FER models achieve high benchmark accuracy but still face challenges in efficient real – time deployment for intelligent systems.

| IV | Multi-Face Emotion Detection for Effective Human-Robot Interaction (Mohamed Ala Yahyaoui et al.) |
|---|---|

## RESEARCH OBJECTIVE

Develop a real – time multi – face emotion detection system for improving human – robot – interaction.

## METHODOLOGY

- Developed a facial emotion detection interface integrated with a mobile humanoid robot.
- Compared different deep learning FER models to select the most efficient one in terms of both accuracy as well as memory required.
- Enabled real – time emotion detection of multiple people through a graphical user interface.

## RESEARCH GAP FOUND

Focuses only on real – time emotion detection of multiple users and does not consider personalized cognitive state analysis or adaptive workspace assistance.

| V | Dawn of the Transformer Era in Speech Emotion Recognition: Closing the Valence Gap (Johannes Wagner et al.) |
|---|---|

## RESEARCH OBJECTIVE

Evaluate the effectiveness of Transformer – based models in improving Speech Emotion Recognition (SER), particularly for detecting emotional valence.

## METHODOLOGY

- Used Transformer – based models to recognize emotions from speech pattern datasets.
- Compared their performance with deep learning models (CNN, LSTM, RNN).
- Measured and evaluated their emotion recognition accuracy.

## RESEARCH GAP FOUND

Existing SER systems only analyze vocal emotions and do not combine speech with other behavioral cues for a more complete understanding of the user's emotional state.

| VI | Multimodal Emotion Detection via Attention-Based Fusion of Extracted Facial and Speech Features (Dilnoza Mamieva et al.) |
|---|---|

## RESEARCH OBJECTIVE

Improve emotion recognition by combining facial expressions and speech features using an attention – based fusion approach.

## METHODOLOGY

- Extracted emotion features from facial images and speech signals.
- Combined both modals using an attention – based fusion model.
- Evaluated the multimodal model against single modal approaches to improve emotion recognition accuracy.

## RESEARCH GAP FOUND

Existing multimodal emotion recognition systems end at emotion classification, and do not support intelligent decision making or personalized workspace assistance and IoT integration.

| VII | A Comprehensive Review of Facial Expression Recognition Techniques<br>R. Rashmi Adyapady & B. Annappa |
|---|---|

## RESEARCH OBJECTIVE

Review recent facial expression recognition techniques, their advantages, challenges, and future research directions.

## METHODOLOGY

- Reviewed recent facial expression recognition algorithms.
- Compared different FER approaches used in laboratory and real – world environments.
- Analyzed the advantages, limitations, and applications of existing FER techniques.

## RESEARCH GAP FOUND

Existing FER systems are affected by variations such as lighting, head pose, and occlusions in real-world environments.

# – CONTEXT AND MEMORY –

| I | Self Context-Aware Emotion Perception on Human–Robot Interaction (Lin, Cruz & Sandoval) |
|---|---|

## RESEARCH OBJECTIVE

Improve emotion perception in human–robot interaction by considering the user's contextual information instead of emotions alone.

## METHODOLOGY

- Proposed a Self Context-Aware Model (SCAM) for emotion recognition.
- Combined audio, visual, and multimodal information with contextual information.
- Evaluated the model by comparing emotion recognition accuracy across different modalities.

## RESEARCH GAP FOUND

Existing context-aware emotion recognition improves emotion detection but does not provide intelligent workspace adaptation or personalized robotic assistance.

| II | Real-Time Emotion Generation in Human – Robot Dialogue Using Large Language Models (Chinmaya Mishra et al.) |
|---|---|

## RESEARCH OBJECTIVE

Use LLMs to generate appropriate emotions for robots during real – time conversations.

## METHODOLOGY

- Used GPT-3.5 to predict the robot's emotions from the conversation.
- Displayed the predicted emotions using the robot's facial expressions.
- Evaluated the robot through user interaction experiments to measure human perception and engagement.

## RESEARCH GAP FOUND

The robot generates appropriate emotional responses but does not understand the user's emotional and cognitive state using multimodal inputs.

| III | Evaluating Very Long-Term Conversational Memory of LLM Agents (Adyasha Maharana et al.) |
|---|---|

## RESEARCH OBJECTIVE

Evaluate how well LLMs remember and understand conversations over long periods of time.

## METHODOLOGY

- Developed LOCOMO, a dataset containing long-term conversations over multiple sessions.
- Evaluated LLMs on question answering, conversation summarization, and multimodal dialogue generation.
- Compared LLM performance with human performance in long-term conversational memory.

## RESEARCH GAP FOUND

Existing LLMs struggle to maintain long – term conversational memory and personalize interactions with context.

| IV | On Memory Construction and Retrieval for Personalized Conversational Agents (Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang) |
|---|---|

## RESEARCH OBJECTIVE

Improve long – term memory retrieval for personalized conversational agents.

## METHODOLOGY

- Analyzed different memory construction methods (turn – level, session – level, and summarization – based).
- Proposed SECOM, a segment – based memory retrieval framework.
- Evaluated SECOM on long – term conversation benchmarks (LOCOMO, Long-MT-Bench+).

## RESEARCH GAP FOUND

Existing conversational agents still struggle to retrieve relevant long – term memories accurately during personalized interactions.

| V | Retrieval – Augmented Generation for Knowledge – Intensive NLP Tasks (Patrick Lewis et al.) |
|---|---|

## RESEARCH OBJECTIVE

Improve the accuracy of language models by combining them with external knowledge retrieval.

## METHODOLOGY

- Proposed the Retrieval-Augmented Generation (RAG) framework.
- Retrieved relevant information from an external knowledge base (Wikipedia) before generating responses.
- Compared RAG with traditional language models on knowledge – intensive NLP tasks.

## RESEARCH GAP FOUND

Traditional language models rely mainly on internal knowledge and struggle to retrieve accurate, up – to – date information during conversations.

| VI | From Human Memory to AI Memory: A Survey on Memory Mechanisms in the Era of LLMs (Yaxiong Wu, Sheng Liang, Chen Zhang) |
|---|---|

## RESEARCH OBJECTIVE

Review existing AI memory mechanisms and explore how human memory can inspire better memory systems for LLMs.

## METHODOLOGY

- Reviewed different AI memory mechanisms used in LLMs.
- Compared human memory with AI memory and categorized existing memory approaches.
- Discussed open challenges and future directions for long – term AI memory.

## RESEARCH GAP FOUND

Existing AI memory systems still do not effectively imitate human memory for long – term learning and personalized interactions.

# – EXPLAINABILITY AND INTEGRATION –

| I | Overcoming Catastrophic Forgetting in Neural Networks (James Kirkpatrick et al.) |
|---|---|

## RESEARCH OBJECTIVE

Enable neural networks to learn new tasks without forgetting previously learned knowledge.

## METHODOLOGY

- Proposed Elastic Weight Consolidation (EWC) to reduce catastrophic forgetting.
- Protected important neural network weights while learning new tasks.
- Evaluated the approach on MNIST handwritten digit classification and Atari 2600 games.

## RESEARCH GAP FOUND

Existing continual learning methods still struggle to retain knowledge while adapting to new tasks over long periods.

| II | A Comprehensive Survey of Continual Learning: Theory, Method and Application (Liyuan Wang et al.) |
|---|---|

## RESEARCH OBJECTIVE

Review the theory, methods, challenges, and applications of continual learning.

## METHODOLOGY

- Reviewed existing continual learning techniques and their theoretical foundations.
- Classified different continual learning strategies and compared their advantages and limitations.
- Analyzed practical applications and discussed future research directions.

## RESEARCH GAP FOUND

Existing continual learning methods still face challenges in balancing learning new knowledge while retaining previously learned information efficiently.

| III | Learning without Forgetting<br>(Zhizhong Li & Derek Hoiem) |
|---|---|

## RESEARCH OBJECTIVE

Enable neural networks to learn new tasks without forgetting previous tasks, even when old training data is unavailable.

## METHODOLOGY

- Proposed the Learning without Forgetting (LwF) method.
- Trained the model using only new task data while preserving previously learned knowledge.
- Compared LwF with fine – tuning, feature extraction, and multitask learning approaches.

## RESEARCH GAP FOUND

Existing learning methods often require access to previous training data, making it difficult to continuously learn new tasks efficiently.

| IV | A Continual Learning Survey: Defying Forgetting in Classification Tasks (Matthias De Lange et al.) |
|---|---|

## RESEARCH OBJECTIVE

Review and compare state – of – the – art continual learning methods for classification tasks.

## METHODOLOGY

- Reviewed and categorized 11 state – of – the – art continual learning methods.
- Evaluated them on multiple benchmarks (Tiny ImageNet, iNaturalist, recognition datasets).
- Compared methods based on accuracy, memory usage, computation time, and stability–plasticity trade-off.

## RESEARCH GAP FOUND

Existing continual learning methods involve trade-offs between accuracy, memory usage, and computational efficiency, making them difficult to optimize simultaneously.

| V | "Help Me Help the AI": Understanding How Explainability Can Support Human-AI Interaction (Sunnie S. Y. Kim, Elizabeth Anne Watkins) |
|---|---|

## RESEARCH OBJECTIVE

Understand how explainable AI (XAI) can improve human – AI interaction and user trust.

## METHODOLOGY

- Conducted a mixed – methods user study with 20 users of the Merlin Bird ID application.
- Collected users' opinions on different AI explanation methods.
- Analyzed how explainability influences trust, collaboration, and user behavior.

## RESEARCH GAP FOUND

Existing explainable AI methods provide technical explanations but offer limited support for intuitive and user – friendly human – AI interaction.

| VI | Towards A Rigorous Science of Interpretable Machine Learning (Finale Doshi-Velez & Been Kim) |
|---|---|

## RESEARCH OBJECTIVE

Establish a structured framework for defining and evaluating interpretability in machine learning.

## METHODOLOGY

- Reviewed existing interpretability methods and their limitations.
- Proposed a taxonomy for evaluating interpretability (application – grounded, human – grounded, and functionally – grounded evaluation).
- Discussed challenges and future research directions for interpretable machine learning.

## RESEARCH GAP FOUND

There is no standardized way to define and evaluate interpretability across different machine learning applications.

| VII | "Why Should I Trust You?": Explaining the Predictions of Any Classifier (Marco Tulio Ribeiro, Sameer Singh, Carlos Guestrin) |
|---|---|

## RESEARCH OBJECTIVE

Develop a method that explains the predictions of any machine learning classifier and improves user trust.

## METHODOLOGY

- Proposed LIME (Local Interpretable Model – Agnostic Explanations) for explaining individual predictions.
- Applied LIME to different machine learning models (Random Forests, Neural Networks, Text and Image Classifiers).
- Evaluated whether explanations helped users trust, compare, and improve machine learning models.

## RESEARCH GAP FOUND

Existing machine learning models often make accurate predictions but provide little explanation for individual decisions, reducing user trust.

# CRITICAL SYNTHESIS

**There is a lack of an integrated, real-time HRI system that combines multimodal user-state perception, contextual reasoning, long-term personalization, continual adaptation, explainable decision-making, and smart workspace control.**

# PROBLEM DEFINITION

# PROBLEM DEFINITION

Current AI assistants have limited ability to understand and retain the user's evolving context across interactions. They often rely on explicit commands and isolated interactions, resulting in limited awareness of user state, workspace context, preferences, and previous experiences. This makes it difficult to provide assistance that is consistently personalized, context-aware, adaptive, and relevant over time.

# KEY ASSUMPTIONS & KEY CONSTRAINTS

## KEY ASSUMPTIONS

- Designed for a **desk-based, single-user environment**.
- Camera and microphone provide **adequate input quality.**
- Users provide **consent** for sensing and personalization

## KEY CONSTRAINTS

- **Limited computational resources** for real-time AI inference.
- Limited availability of **synchronized multimodal datasets.**
- **Privacy requirements** for personal and behavioral data.
- **Response latency** must remain suitable for real-time interaction

# PROBLEM STATEMENT

Current AI assistants often operate as **reactive, session-based systems with limited ability to maintain meaningful context across interactions.** While they can process individual inputs, they may **lack a unified understanding of the user's emotional state, preferences, workspace context, and interaction history,** resulting in assistance that can feel **generic or repetitive**.

There is therefore a need for an AI workspace assistant that can **combine information from multiple modalities, retain relevant personal context, adapt to changing user needs, and provide understandable decisions and responses while operating within practical computational, privacy, hardware, and real-time constraints.**

# SDG ALIGNMENT

**SDG 3 — Good Health & Well-Being**

Encourages healthy work habits through fatigue/attention awareness and break recommendations.

**SDG 4 — Quality Education**

Supports personalized and adaptive study assistance.

**SDG 8 — Decent Work & Economic Growth**

Promotes productive and user-aware work environments.

**SDG 9 — Industry, Innovation & Infrastructure**


Demonstrates integration of AI, robotics and IoT technologies.

# PROPOSED SYSTEM

- Multimodal Perception — Capture facial, speech, behavioral, and workspace cues through camera and microphone inputs.
- User-State Understanding — Combine these signals to estimate the user's emotional, cognitive, and interaction state.
- Personalized Long-Term Memory — Store and retrieve relevant user preferences, past interactions, and experiences.
- Context-Aware Reasoning — Combine current user state, conversation context, and retrieved memories to determine appropriate responses.
- Adaptive Assistance — Adjust conversations, recommendations, and workspace actions according to the user's changing needs.
- Explainable Decisions — Provide understandable reasons behind important recommendations or actions.
- Interactive Workspace Integration — Connect the AI system with the physical robot and smart workspace devices to enable real-world assistance.

# SYSTEM ARCHITECTURE

# COMPLETE SYSTEM ARCHITECTURE



# TECHNOLOGY STACK

| Module | Technology |
|---|---|
| Facial Emotion Recognition | MediaPipe + CNN / ViT |
| Speech Emotion Recognition | Whisper + Wav2Vec2 / HuBERT |
| Eye Fatigue Detection | MediaPipe Face Mesh |
| Attention Detection | Head Pose Estimation + MediaPipe |
| Multimodal Fusion | PyTorch |
| Large Language Model (LLM) | Llama 3 / Gemma / GPT API |
| Long – Term Memory | ChromaDB / FAISS |
| Retrieval Augmented Generation (RAG) | LangChain |
| Continual Learning | LoRA |
| Explainable AI | LIME |
| Internet of Things (IoT) | ESP32 + MQTT |
| Robot | Raspberry Pi 5 |

# FEASIBILITY ANALYSIS

# TECHNICAL FEASIBILITY

- **Python + PyTorch** for AI model development and integration.
- **Pre-trained models** reduce training requirements and development time.
- **Modular architecture** enables independent development and testing.
- Initial development can run on a **laptop**; heavier models can later use a **GPU workstation**.
- **Raspberry Pi + ESP32** handle robot and IoT control, while computation-intensive AI runs separately.

# OPERATIONAL FEASIBILITY

- Designed for a **controlled desk/workspace environment**.
- **Voice and visual interaction** provide natural user inputs.
- Modular components allow **gradual system integration.**
- User remains able to **override or reject system actions**

# RESOURCE & ECONOMIC FEASIBILITY

- **Open-source frameworks and pre-trained models** reduce development cost.
- Existing laptop, camera and microphone support **initial prototyping**.
- Hardware can be **integrated incrementally** as resources become available

# IMPLEMENTATION FEASIBILITY

Begin with **software-only modules** before hardware integration.

Develop and validate **individual components independently**.

Integrate the **robot and IoT devices after the core AI pipeline is validated**.

Modular design allows components to be **replaced or optimized** if required.

# ETHICAL AND PRIVACY CONSIDERATIONS

# ETHICAL AND PRIVACY CONSIDERATIONS

- **CONSENT** – User approval before sensing & personalization.
- **DATA MINIMIZATION** – Collect only necessary information.
- **PRIVACY & SECURITY** – Local processing + protected memory + deletion control.
- **RESPONSIBLE AI** – Probabilistic predictions + no high-stakes use + transparent recommendations.

# REQUIREMENT ANALYSIS

# FUNCTIONAL REQUIREMENTS

- Detect facial emotions.
- Detect emotions from speech.
- Detect eye fatigue.
- Monitor attention.
- Maintain long – term user memory.
- Generate personalized responses.
- Control IoT devices.
- Explain its recommendations.
- Learn user preferences over time.

# NON – FUNCTIONAL REQUIREMENTS

- Real-time response (<2–3 seconds)
- Privacy (local processing where possible)
- High reliability
- Easy to use
- Scalable
- Secure storage of user data

# METHODOLOGY

# PROPOSED METHODOLOGY

- 1. Multimodal Input – capture facial, speech, behavioral and contextual signals.
- 2. Perception – extract relevant user-state features from incoming data.
- 3. Multimodal Fusion – combine information from multiple modalities into a common representation of the user's current state.
- 4. Context & Memory – retrieve relevant preferences, previous interactions and contextual information.
- 5. Context-Aware Reasoning – combine current state, context and memory to determine an appropriate response or action.
- 6. Explainability & Adaptation – provide understandable reasoning and adapt future interactions based on user feedback and history.
- 7. Action & Feedback – execute appropriate assistance and use subsequent user interactions as feedback for future adaptation.

# DEVELOPMENT ROADMAP

# PROPOSED METHODOLOGY

- **Phase 1 — Foundation**
  Development environment setup
  Dataset preparation
  Implement basic facial and speech analysis
  Establish baseline models
- **Phase 2 — Multimodal Perception**
  Integrate facial, speech and behavioral cues
  Develop multimodal fusion
  Validate user-state estimation
- **Phase 3 — Memory & Personalization**
  Implement user profiles and build long-term memory storage
  Develop memory retrieval / RAG
  Test personalized responses
- **Phase 4 — Reasoning & Adaptation**
  Integrate LLM-based reasoning
  Develop context-aware decision making with explainability
  Incorporate user feedback for adaptation
- **Phase 5 — Hardware & Workspace Integration**
  Integrate robot controller
  Connect IoT devices via ESP32/MQTT
  Implement workspace actions and connect software pipeline to physical interface
- **Phase 6 — Integration & Evaluation**
  End-to-end system integration with performance and latency testing
  Memory/retrieval evaluation
  User interaction testing
  Optimization, documentation and final demonstration

# EXPECTED OUTCOMES & EVALUATION METRICS

## OUTCOMES

- **Multimodal perception**
- **User-state estimation**
- **Long-term memory**
- **Personalized reasoning**
- **Adaptive assistance**
- **Explainable decisions**
- **Robot + IoT prototype**

## EVALUATION

- **Recognition: F1 / Accuracy**
- **Fusion: vs. single modality**
- **Memory: Retrieval relevance**
- **Personalization: Response relevance**
- **XAI: User-rated clarity**
- **System: Latency + successful actions**
- **Overall: User evaluation**

# — THANK YOU —

23BAI1563 | Joelle Mary Suji

23BAI1569 | Nikita Elizabeth Chacko

23BRS1015 | Ananth S Mahadev