List of Errata to

Massive MIMO Networks: Spectral, Energy, and Hardware Efficiency

Updated: October 12, 2018.

This documents lists typos detected in the published manuscript of:

Emil Björnson, Jakob Hoydis and Luca Sanguinetti (2017), "Massive MIMO Networks: Spectral, Energy, and Hardware Efficiency", Foundations and Trends® in Signal Processing: Vol. 11: No. 3-4, pp 154-655. http://dx.doi.org/10.1561/2000000093

This document will be updated if further typos are discovered and the latest version is available at:
`https://massivemimobook.com`

All the typos listed in this document have been corrected in the authors' version of the manuscript, which you can download as a free PDF from `https://massivemimobook.com`.

If you discover a potential typo that is not listed in the latest version of this document, we appreciate if you report it to us. You can send an email to emil.bjornson@liu.se

List of Errata

1. In the paragraph before Eq. (1.23), "horizontal ULA with antenna spacing d_{H}" should be "horizontal ULA with antenna spacing $d_{\mathrm{H}} \in (0, 0.5]$".

2. In Section 1.3.5, the statement "the same as that of sending M additional UL pilot signals" is only true if $M \geq K$. To make it more accurate, the statement should instead be "the same as that of sending $\max(M, K)$ additional UL pilot signals" and the following sentence should be added to the footnote on the same page: "More precisely, with the multiplexing gain $\min(M, K)$ of SDMA, we need $\max(M, K)$ symbol transmissions to feed back the MK channel coefficients."

   Consequently, the average pilot overhead of the FDD protocol is $\frac{M+K+\max(M,K)}{2}$ and not $M + \frac{K}{2}$ (which is only correct for $M \geq K$). This error is found at several places in this section. Moreover, Figure 1.22 is shown as


   but should be

3. In Eq. (2.17), the final expression $\frac{\text{tr}\left((\mathbf{R}_{jk}^j)^2\right)}{(M_j\beta_{lk}^j)^2}$ should be $\frac{\text{tr}\left((\mathbf{R}_{jk}^j)^2\right)}{(M_j\beta_{jk}^j)^2}$.

4. Figure 2.6 is shown as

but should be

This error was a consequence of insufficient accuracy in the computation of the covariance matrices. The related sentence

"In fact, a uniform angular distribution makes 66% of the eigenvalues 50 dB smaller than in the reference case, while this happens for around 40% of the eigenvalues with Gaussian and Laplace distributions."

should read as

"In fact, a uniform angular distribution makes 68% of the eigenvalues 30 dB smaller than in the reference case, while this happens for 40% of the eigenvalues with Gaussian distribution and 19% with Laplace distribution."

5. In the first paragraph of Section 3.3.3, $\mathbf{h}_{li}^j \sim \mathcal{N}_{\mathbb{C}}(\mathbf{0}_M, \mathbf{R}_{li}^j)$ should be $\mathbf{h}_{li}^j \sim \mathcal{N}_{\mathbb{C}}(\mathbf{0}_{M_j}, \mathbf{R}_{li}^j)$.

6. In Eq. (3.36), $\mathbf{I}_M$ should be $\mathbf{I}_{M_j}$. This typo also appears on the row right above Eq. (3.37).

7. In Eq. (3.38), $\frac{1}{p_{li}} \left(\mathbf{\Psi}_{li}^j \right)^{-1}$ should be $\frac{1}{p_{li}\tau_p} \left(\mathbf{\Psi}_{li}^j \right)^{-1}$.

8. In Eq. (4.29), σ_{UL}^2 should be σ_{DL}^2.

9. In Section 6.1.2, after Eq. (6.7), the statement "LTE only requires $\mathsf{EVM} \leq 0.0175$" should be "LTE only requires $\mathsf{EVM} \leq 0.175$"

10. The subsection title "7.4.1 Physical Array Size and Antenna Spacing" should be "7.4.1 Preliminaries on Physical Array Size".

11. Figure 7.26 is shown as

but should be

12. Figure 7.27 is shown as

but should be

In the paragraph that describes this figure, the sentence "However, going from $S = 1$ to $S = 16$ improves the median of β by around 9 dB; increasing this number to $S = 256$ adds another 5 dB." should read as: "However, going from $S = 1$ to $S = 16$ improves the median of β by around 12.5 dB; increasing this number to $S = 256$ adds another 9.5 dB."

13. In the paragraph after (C.63), $\mathbf{A} = \tau_p \mathbf{\Psi}_{jk}^{j}$ should be $\mathbf{A} = \tau_p (\mathbf{\Psi}_{jk}^{j})^{-1}$.