

※ Create a directory for the paths showed in the following table and configure the permission to match the “Permission” Column  
Make sure that the shared directory can be accessed from other servers

Path	Permission	Shared target server							Remarks
		DBMS	backyard	Ansible	Ansible Tower	Cobbler	Terraform	Web/AP	
/(Free directory)/data_relay_storage/symphony	777		●	●	●			●	Required
/(Free directory)/data_relay_storage/conductor	777		●	●	●			●	Required
/(Free directory)/data_relay_storage/ansible_driver	777		●	●	●			●	Required if installing Ansible-Driver
/(Free directory)/data_relay_storage/cobbler_driver	777		●			●		●	Required if installing Cobbler-Driver
/(Free directory)/ita_sessions	777							●	Required
/(Free directory)/ita-root/temp	777		●					●	Required
/(Free directory)/ita-root/uploadfiles	777		●					●	Required
/(Free directory)/ita-root/webroot/uploadfiles	777		●					●	Required
/(Free directory)/ita-root/webroot/menus/sheets	755		●					●	Required
/(Free directory)/ita-root/webroot/menus/users	755		●					●	Required
/(Free directory)/ita-root/webconfs/sheets	755		●					●	Required
/(Free directory)/ita-root/webconfs/users	755		●					●	Required
/(Free directory)/ita-root/repositorys	755		●						Required if installing CI/CD For IaC function
/(DB File directory)	778	●							Create if you are installing MariaDB Database Files