

Procedure				The necessary packages are as listed below									
HA Construction (DBMS)				MariaDB、MariaDB-server、expect									
※ Please change the the version number (x.x.x) written under “Settings” or “Remarks” to match the version of ITA being installed. Please also change text such as “ITA Installation directory name” , Backyard Server host name” to fit your environment.													
No.	Goal	Goal						Settings	Remarks				
		Common	Menu create	Host group	Ansible	Cobbler	Terraform			CI/CD for IaC			
Unpack ITA Installation files													
1	Unpack ITA Installation files	●						Deploy the ITA file exastro-it-automation-x.x.x.tar.gz to the installation file directory. cd / (Install file unpack directory) ls -l exastro-it-automation-x.x.x.tar.gz	“The install files can be unpacked in any directory. For online, uesr the following command to gather them. wget https://github.com/exastro-suite/it-automation/releases/download/vx.x.x/exastro-it-automation-x.x.x.tar.gz ※Use the following command for v1.10.1 and later versions. curl -OL https://github.com/exastro-suite/it-automation/releases/download/vx.x.x_tag/exastro-it-automation-x.x.x.tar.gz”				
2								Unpack the ITA Installation files tar xzf exastro-it-automation-x.x.x.tar.gz					
3								Configure ITA Installation directory find it-automation-x.x.x -type f xargs -I{} sed -i -e “s:%%ITA_DIRECTORY%%:/ (ITA Install directory):g” {}					
Install yum-utils													
4	【For CentOS7 and RHEL7】 Install yum-utils	●						Install the following package(s) yum-utils	For online environments, please install using the following command. yum install -y yum-utils				
Configure common directory (DB file storage location)													
5	Create a directory where the Maria DB Database files will be saved. ※Only if you are going to move DB Files to an external storage.	●						mkdir -p / (DB File storage directory)	Example: mkdir -p /data/mysql				
6	Configure Common directory. ※Only if you are going to move DB Files to an external storage.	●						Configure the external storage common directory settings to be as bellow.					
								DBMS server common directory		External storage common directory			
								/ (DB file storage directory)		/ (DB File storage directory)			
Install MariaDB													
7	Install MariaDB	●						Install the following packages 【For CentOS7, RHEL7】 MariaDB MariaDB-server expect 【For CentOS8, RHEL8】 mariadb mariadb-server expect	For online environments, use the following command to activate respositories 【For CentOS7, RHEL7】 curl -sS https://downloads.mariadb.com/MariaDB/mariadb_repo_setup bash 【For CentOS8, RHEL8】 No repository will be added For online, use the following commands to install. 【For CentOS7, RHEL7】 yum install -y MariaDB MariaDB-server expect 【For CentOS8, RHEL8】 yum install -y mariadb mariadb-server expect				
8	Move MariaDB database files to external storage ※Only if you are going to move DB files to an external storage.	●						cp -pr /var/lib/mysql/* / (DB File storage directory)	Example : cp -pr /var/lib/mysql/* /data/mysql				
9		●						rm -rf /var/lib/mysql					
10		●						ln -s / (DB File storage directory) /var/lib/mysql	Example : ln -s /data/mysql /var/lib/mysql				
11	Configure Maria DB automatic startup settings and run Maria DB	●						systemctl enable mariadb systemctl start mariadb					

No.	Goal	Goal							Settings	Remarks
		Common	Menu create	Host group	Ansible	Cobbler	Terraform	CI/CD for IaC		
12	Configure Maria DB root password	●							mysql_secure_installation The rest is set up interactively.	※The password can only contain half-width characters and symbols
13	Deploy MariaDB Settings files.	●							【For CentOS7, RHEL7】 cp -p / (Install file unzip location) /it-automation-x.x.x/ita_install_package/ext_files_for_CentOS7.x/etc_my.cnf.d/server.cnf /etc/my.cnf.d/server.cnf 【For CentOS8, RHEL8】 cp -p / (Install file unzip location) /it-automation-x.x.x/ita_install_package/ext_files_for_CentOS8.x/etc_my.cnf.d/server.cnf /etc/my.cnf.d/server.cnf	
14	Restart MariaDB	●							systemctl restart mariadb	
Create DB for ITA										
15	Connect to MariaDB	●							mysql -uroot -p(MariaDB root password)	
16	Create MariaDB User	●							CREATE USER '(user name)' IDENTIFIED BY '(password)'; CREATE USER '(user name)'@'localhost' IDENTIFIED BY '(password)';	※The password can only contain half-width characters and symbols
17	Create Database for ITA	●							CREATE DATABASE (TA Database name) CHARACTER SET utf8;	
18	Configure User permission	●							GRANT ALL ON (ITA Database name).* TO '(User name)'@'%' WITH GRANT OPTION; GRANT ALL ON (ITA Database name).* TO '(User name)'@'localhost' WITH GRANT OPTION;	
19	Exit MariaDB	●							exit	
20	Create ita_base table	●							mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-a.sql	
21	Create createparam table		●						mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-m.sql	
22	Create hostgroup table			●					mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-n.sql	
23	Create ansible_driver table				●				mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-c.sql	
24	Create ansible_driver table (collect function) ※Only if you are installing createparam and Ansible_driver.		●		●				mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-m2.sql	
25	Create cobbler_driver table					●			mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-d.sql	
26	Create terraform_driver table						●		mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-o.sql	
27	Create cicd_for_iac table							●	mysql -u (User name) -p(Password) (ITA Database name) < /tmp/it-automation-x.x.x/ita_install_package/ITA/ita-sqlscripts/en_US_mysql_ita_model-o.sql	