Q: Which of the following is NOT a valid way to declare a variable in Python?

A. `x = 10`

B. `int x = 10`

C. `name = "Alice"`

D. `is_valid = True`

Answer: B

Q: What is the output of the following code?

```
print(type(3.14))
```

A. `<class 'int'>`

B. `<class 'float'>`

C. `<class 'double'>`

D. `<class 'number'>`

Answer: B

Q: Which keyword is used to define a function in Python?

A. `function`

B. `def`

C. `fun`

D. `define`

Answer: B

Q: What will be the output of the following code?

```
x = 5
y = 2
print(x ** y)
```

A. `10`

B. `25`

C. `7`

D. `52`

Answer: B

Q: Which of the following is a mutable data type in Python?

A. `tuple`

B. `string`

C. `list`

D. `int`

Answer: C

Q: What is the output of the following code?

```
print("Hello" + " " + "World")
```

A. `HelloWorld`

B. `Hello World`

C. `Hello + World`

D. `Error`

Answer: B

Q: Which of the following is used to write a comment in Python?

A. `// This is a comment`

B. `/* This is a comment */`

C. `# This is a comment`

D. `<!-- This is a comment -->`

Answer: C

Q: What is the output of the following code?

```
for i in range(3):
    print(i)
```

A. `1 2 3`

B. `0 1 2`

C. `0 1 2 3`

D. `1 2`

Answer: B

Q: Which of the following is NOT a valid boolean operator in Python?

A. `and`

B. `or`

C. `not`

D. `xor`

Answer: D

Q: What is the output of the following code?

```
print(len("Python"))
```

A. `5`

B. `6`

C. `7`

D. `Error`

Answer: B

Q: Which of the following is used to create a list in Python?

A. `{1, 2, 3}`

B. `(1, 2, 3)`

C. `[1, 2, 3]`

D. `<1, 2, 3>`

Answer: C

Q: What is the output of the following code?

```
x = 10
if x > 5:
    print("Greater")
else:
    print("Smaller")
```

A. `Smaller`

B. `Greater`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to import a module in Python?

A. `include`

B. `import`

C. `require`

D. `using`

Answer: B

Q: What is the output of the following code?

```
print(10 // 3)
```

A. `3.33`

B. `3`

C. `4`

D. `Error`

Answer: B

Q: Which of the following is used to define a dictionary in Python?

A. `[1: "one", 2: "two"]`

B. `{1: "one", 2: "two"}`

C. `(1: "one", 2: "two")`

D. `<1: "one", 2: "two">`

Answer: B

Q: What is the output of the following code?

```
print("Python"[0])
```

A. `P`

B. `y`

C. `Error`

D. `Python`

Answer: A

Q: Which of the following is used to handle exceptions in Python?

A. `try-except`

B. `catch-throw`

C. `error-handle`

D. `exception-block`

Answer: A

Q: What is the output of the following code?

```
print(bool(0))
```

A. `True`

B. `False`

C. `0`

D. `Error`

Answer: B

Q: Which of the following is used to define a tuple in Python?

A. `[1, 2, 3]`

B. `{1, 2, 3}`

C. `(1, 2, 3)`

D. `<1, 2, 3>`

Answer: C

Q: What is the output of the following code?

```
print("Python".upper())
```

A. `python`

B. `PYTHON`

C. `Python`

D. `Error`

Answer: B

Q: Which of the following is used to create a set in Python?

A. `[1, 2, 3]`

B. `{1, 2, 3}`

C. `(1, 2, 3)`

D. `<1, 2, 3>`

Answer: B

Q: What is the output of the following code?

```
print(3 == 3.0)
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a lambda function in Python?

A. `def lambda(x): return x`

B. `lambda x: x`

C. `function x: x`

D. `anonymous x: x`

Answer: B

Q: What is the output of the following code?

```
print("Python".replace("P", "J"))
```

A. `Python`

B. `Jython`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to open a file in Python?

A. `open("file.txt")`

B. `file("file.txt")`

C. `read("file.txt")`

D. `load("file.txt")`

Answer: A

Q: What is the output of the following code?

```
print("Python".split("t"))
```

A. `['Py', 'hon']`

B. `['P', 'hon']`

C. `['Py', 'on']`

D. `Error`

Answer: A

Q: Which of the following is used to define a class in Python?

A. `class MyClass:`

B. `def MyClass:`

C. `MyClass = class()`

D. `new MyClass()`

Answer: A

Q: What is the output of the following code?

```
print("Python".find("y"))
```

A. `1`

B. `2`

C. `-1`

D. `Error`

Answer: B

Q: Which of the following is used to create an instance of a class in Python?

A. `MyClass()`

B. `new MyClass()`

C. `create MyClass()`

D. `MyClass.new()`

Answer: A

Q: What is the output of the following code?

```
print("Python".count("o"))
```

A. `1`

B. `2`

C. `0`

D. `Error`

Answer: A

Q: Which of the following is used to define a constructor in Python?

A. `def __init__(self):`

B. `def constructor(self):`

C. `def new(self):`

D. `def __new__(self):`

Answer: A

Q: What is the output of the following code?

```
print("Python".startswith("Py"))
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to inherit a class in Python?

A. `class MyClass(Parent):`

B. `class MyClass extends Parent:`

C. `class MyClass inherits Parent:`

D. `class MyClass: Parent`

Answer: A

Q: What is the output of the following code?

```
print("Python".endswith("on"))
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to override a method in Python?

A. `def method(self):`

B. `override def method(self):`

C. `def method(self): override`

D. `override method(self):`

Answer: A

Q: What is the output of the following code?

```
print("Python".isalpha())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to call a superclass method in Python?

A. `super().method()`

B. `parent.method()`

C. `Parent.method()`

D. `call super.method()`

Answer: A

Q: What is the output of the following code?

```
print("Python".isdigit())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a static method in Python?

A. `@staticmethod`

B. `static def method():`

C. `def static method():`

D. `@static def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".islower())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a class method in Python?

A. `@classmethod`

B. `class def method():`

C. `def class method():`

D. `@class def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isupper())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a property in Python?

A. `@property`

B. `property def method():`

C. `def property method():`

D. `@property def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isspace())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a setter method in Python?

A. `@method.setter`

B. `def method.setter():`

C. `setter def method():`

D. `@setter def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".istitle())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a getter method in Python?

A. `@method.getter`

B. `def method.getter():`

C. `getter def method():`

D. `@getter def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isalnum())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a deleter method in Python?

A. `@method.deleter`

B. `def method.deleter():`

C. `deleter def method():`

D. `@deleter def method():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isidentifier())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a metaclass in Python?

A. `class MyClass(metaclass=Meta):`

B. `class MyClass metaclass Meta:`

C. `class MyClass: metaclass Meta`

D. `metaclass MyClass(Meta):`

Answer: A

Q: What is the output of the following code?

```
print("Python".isprintable())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a context manager in Python?

A. `with open("file.txt") as f:`

B. `context open("file.txt") as f:`

C. `open("file.txt") as f:`

D. `with open("file.txt"): f`

Answer: A

Q: What is the output of the following code?

```
print("Python".isascii())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a generator function in Python?

A. `def generator():`

B. `yield def generator():`

C. `def generator(): yield`

D. `generator def():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isdecimal())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a coroutine in Python?

A. `async def coroutine():`

B. `def coroutine(): async`

C. `coroutine def():`

D. `async coroutine():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isnumeric())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a decorator in Python?

A. `@decorator`

B. `def decorator():`

C. `decorator def():`

D. `@def decorator():`

Answer: A

Q: What is the output of the following code?

```
print("Python".isprintable())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a setter in Python?

A. `@property def method():`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.setter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isspace())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a property with a getter in Python?

A. `@property def method():`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".istitle())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a deleter in Python?

A. `@property def method():`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.deleter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isupper())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a property with a setter and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isalnum())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a getter and deleter in Python?

A. `@property def method(): @method.getter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.setter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isidentifier())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isprintable())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isspace())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".istitle())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isupper())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: B

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.getter`

Answer: A

Q: What is the output of the following code?

```
print("Python".isalnum())
```

A. `True`

B. `False`

C. `Error`

D. `None`

Answer: A

Q: Which of the following is used to define a property with a getter, setter, and deleter in Python?

A. `@property def method(): @method.setter @method.deleter`

B. `property def method():`

C. `def property method():`

D. `@property def method(): @method.get