

COA LAB**Experiment – 2**

Problem Statement: Write an assembly language program to compute the average of two numbers.

Algorithm:

- Step 1:** Define the Base Register Address value during the program creation.
- Step 2:** Move the first operand in the General-Purpose Register R1.
- Step 3:** Move the second operand in the General-Purpose Register R2.
- Step 4:** Perform the addition operation with the values in the registers.
- Step 5:** Result will be stored in the destination register.
- Step 6:** Divide the destination register value by 2, and the result will be stored in the destination register.
- Step 7:** Store the resultant value in a data memory location.
- Step 8:** Terminate the program.

Assembly Language code:

MOV #6, R01 ;Store value of 6 in register R01

MOV #4, R02 ;Store value of 4 in register R02

ADD R01, R02 ;Add the register R01 and R02 values and store the resultant value in register R02

DIV #2, R02 ;Divide register R02 by value 2 and store the resultant value in register R02

STB R01, 00 ;Store the resultant value of R01 in memory location 00

HLT ;Stop the simulator

Result:




Fig. 1: CPU Simulator Window




Fig. 2: Data Memory Window

Step 01	
PC	6
IR	MOV #6, R01
MAR	0
MDR	MOV #6, R01
R01	6
Step 02	

PC	12
IR	MOV #4, R02
MAR	6
MDR	MOV #4, R02
R01	6
R02	4
Step 03	
PC	17
IR	ADD R01, R02
MAR	12
MDR	ADD R01, R02
R01	6
R02	10
Step 04	
PC	23
IR	DIV #2, R02
MAR	17
MDR	DIV #2, R02
R01	6
R02	5
00	05
Step 05	
PC	29
IR	STB R02, 00
MAR	0
MDR	5
R01	6
R02	5
00	05
Step 06	
PC	30
IR	HLT
MAR	29
MDR	HLT
R01	6
R02	5
00	05