

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD		LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method		(Page 1 of 20)
Project Name:	MF8 MF8 _IndSupply_IndExhaust_SZHP_HRV	Date Prepared: 2026-05-22

A. General Information					
1	Project Name	MF8 MF8 _IndSupply_IndExhaust_SZHP_HRV			
2	Run Title	MF8 Individual Supply + Individual Exhaust (SZHP-HRV)			
3	Project Location	Street			
4	City	Los Angeles	5	Standards Version	Compliance 2025
6	Zip code	95837	7	Compliance Software (version)	CBECC 2025.2.0.1 (1395)
8	Climate Zone	9	9	Building Orientation (deg)	0
10	Building Type(s)	• Multifamily 3 stories or less	11	Weather File	CA_Title24_2025_LOS-ANGELES-USC.epw
12	Project Scope	• New complete scope	13	Number of Dwelling Units	8
14	Total Conditioned Floor Area in Scope (ft²)	7320	15	Total # of hotel/motel rooms	0
16	Total Unconditioned Floor Area (ft²)	0	17	Fuel Type	Natural gas
18	Is Natural Gas Available per Section 100.1?	Yes	19	Nonresidential Conditioned Floor Area	0
20	Total # of Stories (Habitable Above Grade)	2	21	Residential Conditioned Floor Area	7320

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 2 of 20)

B. PROJECT SUMMARY							
Table B shows which building components are included in the performance calculation. If indicated as not included, the project must show compliance prescriptively if within the permit application.							
Building Components Complying via Performance					Building Components Complying Prescriptively		
Envelope (See Table G)	Nonres	Not Included	Solar Thermal Water Heating (See Table I3)	☐	Performance	The following building components are ONLY eligible for prescriptive compliance and should be documented on the LMCC form listed if within the scope of the permit application (i.e. compliance will not be shown on the LMCC-PRF-E).	
	MultiFam	Performance		☒	Not Included		
Mechanical (See Table H)	Nonres	Not Included	Covered Process: Commercial Kitchens (see Table J)	☐	Performance	Indoor Lighting (Unconditioned) 140.6 & 170.2(e)	LMCC-LTI-01E is required
	MultiFam	Performance		☒	Not Included	Outdoor Lighting 140.7 & 170.2(e)	LMCC-LTO-01E is required
Domestic Hot Water (See Table I)	Nonres	Not Included	Covered Process: Laboratory Exhaust (see Table J)	☐	Performance	Sign Lighting 140.8 & 170.2(e)	LMCC-LTS-01E is required
	MultiFam	Performance		☒	Not Included	Building Components Complying with Mandatory Measures	
Lighting (Indoor Conditioned, see Table K)	Nonres	Not Included	Photovoltaics (see Table F)	☒	Performance	Electrical power systems, commissioning, solar ready, elevator and escalator requirements are mandatory and should be documented on the LMCC form listed if applicable (i.e. compliance will not be shown on the LMCC-PRF-E.)	
	MultiFam	Performance		☐	Not Included	Electrical Power Distribution 110.11	LMCC-ELC-01E is required
			Battery (see Table F)	☐	Performance	Commissioning 120.8	LMCC-CXR-01E is required
				☒	Not Included	Solar and Battery 110.10	LMCC-SAB-01E is required

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 3 of 20)

C1. COMPLIANCE SUMMARY			
DOES NOT COMPLY *			
	Long-term System Cost (LSC) ¹		Source Energy Use
	Efficiency ² (\$/ft ² -yr)	Total ³ (\$/ft ² -yr)	Total ³ (kBtu/ft ² -yr)
Standard Design	8.92	-9.33	7.24
Proposed Design	9.18	-9.11	0.23
Compliance Margins	-0.26	-0.22	7.01
	Fail	Fail	Pass
¹ Long-term System Cost (LSC) is a 30-year present value cost to California's energy system. LSC is not a predicted utility bill. ² Efficiency measures include energy efficiency improvements such as better building envelope and more efficient mechanical equipment ³ Compliance Totals include efficiency, photovoltaics and batteries * New Construction: Building complies when Proposed Design is equal to or less than Standard Design in all compliance categories and unmet load hour limits are not exceeded. Complete Addition Scope and Existing, Addition and Alteration Scope: Building complies when efficiency compliance margin is greater than or equal to zero and unmet load hour limits are not exceeded.			

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 4 of 20)

C2. LSC ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual LSC Energy Use, \$/ft²-yr)			
DOES NOT COMPLY			
Energy Component	Standard Design (LSC)	Proposed Design (LSC)	Compliance Margin (LSC)¹
Space Heating	0.11	0	0.11
Space Cooling	1.71	2.06	-0.35
Indoor Fans	1.59	1.67	-0.08
Heat Rejection	0	0	0
Pumps & Misc.	0.03	0.03	0
Domestic Hot Water	5.48	5.42	0.06
Indoor Lighting	0	0	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	8.92	9.18	-0.26 (-2.9%)
Photovoltaics	-18.25	-18.29	0.04
Batteries	---	---	---
TOTAL COMPLIANCE	-9.33	-9.11	-0.22 (0%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

C3. LSC ENERGY RESULTS FOR NON-REGULATED COMPONENTS ¹			
Non-Regulated Energy Component	Standard Design (LSC)	Proposed Design (LSC)	Compliance Margin (LSC) ²
Receptacle	11.33	11.33	---
Process	11.73	11.83	-0.1
Other Ltg	2.05	2.05	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	15.78	16.1	-0.32 (-2%)
¹ Notes: This table is not used for Energy Code Compliance.			
² Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 6 of 20)

C4. SOURCE ENERGY COMPLIANCE RESULTS FOR PERFORMANCE COMPONENTS (Annual SOURCE Energy Use, kBtu/ft² /yr)			
DOES NOT COMPLY			
Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE)¹
Space Heating	0.05	0	0.05
Space Cooling	0.24	0.31	-0.07
Indoor Fans	0.37	0.38	-0.01
Heat Rejection	0	0	0
Pumps & Misc.	0.02	0.01	0.01
Domestic Hot Water	8.37	1.34	7.03
Indoor Lighting	0	0	0
Flexibility	---	---	---
EFFICIENCY COMPLIANCE TOTAL	9.05	2.04	7.01 (77.5%)
Photovoltaics	-1.81	-1.81	---
Batteries	---	---	---
TOTAL COMPLIANCE	7.24	0.23	7.01 (96.8%)
¹ Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

C5. SOURCE ENERGY RESULTS FOR NON-REGULATED COMPONENTS ¹			
Non-Regulated Energy Component	Standard Design (SOURCE)	Proposed Design (SOURCE)	Compliance Margin (SOURCE) ²
Receptacle	3.01	3.01	---
Process	2.74	2.77	-0.03
Other Ltg	0.59	0.59	---
Process Motors	---	---	---
TOTAL (TOTAL COMPLIANCE + NON-REGULATED COMPONENTS)	13.58	6.6	6.98 (51.4%)
¹ Notes: This table is not used for Energy Code Compliance.			
² Notes: This number in parenthesis following the Compliance Margin in column 4, represents the Percent Better than Standard.			

C6. 'ABOVE CODE' QUALIFICATIONS	
☐ This project is pursuing CalGreen Tier 1	☐ This project is pursuing CalGreen Tier 2

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 8 of 20)

C7. ENERGY USE SUMMARY						
Energy Component	Standard Design Site (MWh)	Proposed Design Site (MWh)	Margin (MWh)	Standard Design Site (MBtu)	Proposed Design Site (MBtu)	Margin (MBtu)
Space Heating	0.1	---	---	---	---	---
Space Cooling	1.9	2.3	-0.4	---	---	---
Indoor Fans	1.7	1.8	-0.1	---	---	---
Heat Rejection	---	---	---	---	---	---
Pumps & Misc.	0	0	0	---	---	---
Domestic Hot Water	6.1	6	0.1	---	---	---
Indoor Lighting	---	---	---	---	---	---
Flexibility	---	---	---	---	---	---
EFFICIENCY TOTAL	9.8	10.1	-0.3	0	0	0
Photovoltaics	-25	-25.1	0.1	---	---	---
Batteries	---	---	---	---	---	---
ENERGY USE SUBTOTAL	-15.2	-15	-0.2	0	0	0
Receptacle	12.1	12.1	0	---	---	---
Process	13.2	13.3	-0.1	---	---	---
Other Ltg	2.1	2.1	0	---	---	---
Process Motors	---	---	---	---	---	---
ENERGY USE TOTAL	12.2	12.5	-0.3	0	0	0

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 9 of 20)

C8. ENERGY USE INTENSITY (EUI)				
	Standard Design (kBtu/ft² / yr)	Proposed Design (kBtu/ft² / yr)	Margin (kBtu/ft² / yr)	Margin Percentage
GROSS EUI ¹	17.34	17.53	-0.19	-1.1
NET EUI ¹	5.69	5.83	-0.14	-2.46
¹ Notes: Gross EUI is Energy Use Total (not including PV)/Total Building Area. Net EUI is Energy Use Total (including PV)/Total Building Area.				

D1. EXCEPTIONAL CONDITIONS
Verify project meets the requirements for Vestibules as per Section 120.7(e).

D2. MULTIFAMILY REQUIRED SPECIAL FEATURES
- Indoor air quality, balanced fan - IAQ Ventilation System Heat Recovery: minimum 70 SRE and 70 ASRE - IAQ Ventilation System: supply outside air inlet, filter, and H/ERV cores accessible per RACM Reference Manual - IAQ Ventilation System: fault indicator display - Cool roof - Non-standard duct location (any location other than attic) - Northwest Energy Efficiency Alliance (NEEA) rated heat pump water heater; specific brand/model, or equivalent, must be installed

E1. ECC FEATURE SUMMARY
The following is a summary of the features that must be field-verified by a certified ECC Rater as a condition for meeting the modeled energy performance for this computer analysis. Additional detail is provided in the building tables below. Registered LMCI's and LMCV's are required to be completed in the ECC Registry.
Building-level Verifications: - Quality insulation installation (QII) - Indoor air quality ventilation - Kitchen range hood Cooling System Verifications: - Minimum Airflow - Verified Refrigerant Charge - Fan Efficacy Watts/CFM Heating System Verifications: -- None -- HVAC Distribution System Verifications: - Duct leakage testing - Ducts located entirely in conditioned space confirmed by duct leakage testing Domestic Hot Water System Verifications: -- None --

F1. REQUIRED PV SYSTEMS											
01	02	03	04	05	06	07	08	09	10	11	12
DC System Size (kWdc)	Exception ¹	Module Type	Array Type	Power Electronics	CFI	Azimuth (deg)	Tilt Input	Array Angle (deg)	Tilt: (x in 12)	Inverter Eff. (%)	Annual Solar Access (%)
15.4		Standard (14-17%)	Fixed	none	true	150-270	N/A	N/A	<=7:12	96	98
¹ See Table D1 for any PV exceptions used.											

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 11 of 20)

F1B. PV BATTERY BUILDING TYPE(S)		
01	02	03
Building Occupancy Type* (From Table 140.10-A/B and 170.2-U/V)	Conditioned Floor Area (ft²)	Unconditioned Floor Area (ft²)
Events and Exhibits	0	0
Library	0	0
Hotel/Motel	0	0
Office, Financial Institutions, Unleased Tenant Space, Medical Office Building/Clinic	0	0
Restaurants	0	0
Retail, Grocery	0	0
School	0	0
Warehouse	0	0
Religious Worship	0	0
Sports and Recreation	0	0
Multifamily greater than 3 stories	0	0
None	0	0
<i>*Building Occupancy Types are defined in Section 100.1 of the Energy Code</i>		

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft²)	Total Fenestration Area (ft²)	Window to Wall Ratio (%)
North-Facing ¹	2074	329.4	15.88
East-Facing ²	510	81	15.88
South-Facing ³	2074	329.4	15.88
Notes ¹ North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW), ² East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE), ³ South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE), ⁴ West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),			

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 12 of 20)

G1. ENVELOPE GENERAL INFORMATION (conditioned spaces only)			
01	02	03	04
Opaque Surfaces & Orientation	Total Gross Surface Area (ft ²)	Total Fenestration Area (ft ²)	Window to Wall Ratio (%)
West-Facing ⁴	510	81	15.88
Total	5168	820.8	15.88
Roof	0	0	0
Notes ¹ North-Facing is oriented to within 45 degrees of true north, including 4500'00" east of north (NE), but excluding 4500'00" west of north (NW), ² East-Facing is oriented to within 45 degrees of true east, including 4500'00" south of east (SE), but excluding 4500'00" north of east (NE), ³ South-Facing is oriented to within 45 degrees of true south, including 4500'00" west of south (SW), but excluding 4500'00" east of south (SE), ⁴ West-Facing is oriented to within 45 degrees of true west, including 4500'00" north of west (NW), but excluding 4500'00" south of west (SW),			

G2B. ROOFING PRODUCT SUMMARY (MULTIFAMILY AND COMMON AREAS)					
01	02	03	04	05	06
Name	Roof Pitch	Roof Rise (x in 12)	Aged Solar Reflectance	Thermal Emittance	SRI
Attic	Steep slope	5	0.2	0.75	N/A

G3. ATTIC			
01	02	03	04
Name	Construction	Type	Radiant Barrier
Attic	Attic Roof Cons	Ventilated	Yes

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 13 of 20)

G5. OPAQUE SURFACE ASSEMBLY SUMMARY										
01	02	03	04	05	06		07	08	09	10
Surface Name	Construction Type	Area (ft²)	Framing Type	Cavity R-Value	Continuous R-Value		Units	Value	Description of Assembly Layers	Status¹
					Interior	Exterior				
Exterior Wall Cons	Exterior Walls	5,168	Wood Framed Wall	21	0	4	U-factor	0.0509	Inside Finish: Gypsum Board Cavity / Frame: R-21 / 2x6 Sheathing / Insulation: R-4 Sheathing Exterior Finish: Synthetic Stucco	N
Ceiling Below Attic Cons	Ceilings (below attic)	3,660	Wood Framed Ceiling	38	0	0	U-factor	0.0253	Over Ceiling Joists: R-28.9 insul. Cavity / Frame: R-9.1 / 2x4 Btm Chrd Inside Finish: Gypsum Board	N
Attic Roof Cons	Attic Roofs	3,660	Wood Framed Ceiling	0	0	0	U-factor	0.4003	Roofing: 10 PSF (RoofTileAirGap) Tile Gap: present Roof Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x4	N
Interior Floor	Interior Floors	3,660	Wood Framed Floor	0	0	0	U-factor	0.1957	Floor Surface: Carpeted Floor Deck: Wood Siding/sheathing/decking Cavity / Frame: no insul. / 2x12 Ceiling Below Finish: Gypsum Board	N
¹ Status: N - New, A - Altered, E - Existing										

G6B. OPAQUE DOOR SUMMARY (MULTIFAMILY AND COMMON AREAS)			
01	02	03	04
Name	Area (ft ²)	Overall U-factor	Status ¹
Zone1DoorFront	80	0.2	N
Zone2DoorFront	80	0.2	N
¹ Status: N - New, A - Altered, E - Existing			

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 14 of 20)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status¹
Zone1WinFront	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone1WallFront	0	10.98	164.7	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone1WinLeft	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone1WallLeft	90	2.7	40.5	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone1WinBack	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone1WallBack	180	10.98	164.7	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone1WinRight	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone1WallRight	270	2.7	40.5	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone2WinFront	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone2WallFront	0	10.98	164.7	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone2WinLeft	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone2WallLeft	90	2.7	40.5	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
Zone2WinBack	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone2WallBack	180	10.98	164.7	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 15 of 20)

G7B. FENESTRATION SUMMARY (MULTIFAMILY AND COMMON AREAS)												
01	02	03	04	05	06	07	08	09	10	11	12	13
Fenestration Name	Fenestration Type/ Product Type / Frame Type	Parent Surface	Azimuth	Multiplier	Area (ft ²)	Overall U-factor	U-factor Source	Overall SHGC	SHGC Source	Overall VT	Exterior Shading	Status ¹
Zone2WinRig ht	Vertical fenestration Architectural Window - Operable (Multifamily only) N/A	Zone2WallRig ht	270	2.7	40.5	0.3	NFRC	0.23	NFRC	N/A	Standard bug screens	N
¹ Status: N - New, A - Altered, E - Existing												

H2. DWELLING UNIT HVAC HEATING AND COOLING SYSTEMS														
01	02	03	04	05	06	07	08	09	10	11	12	13	14	15
Dwelling Unit Type	Equipment Name	Equipment Type	Quantity	Air Distribution System Name	Fan System name	Heating					Cooling			
						Heat Output at 47	Heat Output at 17	Efficiency Unit	Efficiency	Backup	Total Cooling Output	Efficiency Unit	Efficiency	Variable Speed
1-Bed Type Z1	Split SZHP System	Central split HP N/A	4	Air Distribution System - Res	Heat Pump Fan	36,000	22,536	HSPF2	7.5	Electric	N/A	EER2 SEER2	11.7 14.3	☐
2-Bed Type Z1	Split SZHP System	Central split HP N/A	4	Air Distribution System - Res	Heat Pump Fan	36,000	22,536	HSPF2	7.5	Electric	N/A	EER2 SEER2	11.7 14.3	☐

H3a. MULTIFAMILY / COMMON USE AREA FAN SYSTEMS SUMMARY				
01	02	03	04	05
Name	Type	Power	Power Units	Status
Heat Pump Fan	Fixed speed	0.45	W/cfm	N/A

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 16 of 20)

H3b. MULTIFAMILY / COMMON USE AREA IAQ FAN SYSTEMS SUMMARY					
01	02	03	04	05	06
Name	Type	Airflow (CFM)	Power	Power Units	Status
IAQ Bal Fan HRV - 1BR	Balanced HRV	37.5	0.4	W/cfm	N/A
IAQ Bal Fan HRV - 2BR	Balanced HRV	54.9	0.4	W/cfm	N/A

H4. MULTIFAMILY HVAC DISTRIBUTION							
01	02	03	04	05	06	07	08
Name	Type	Duct Ins. R-value Supply	Duct Ins. R-value Return	Duct Location Supply	Duct Location Return	Verified Duct Design Surface Area	
						Supply	Return
Air Distribution System - Res	Conditioned space-entirely (Non-Verified)	R-4.2	R-4.2	Conditioned Zone	Conditioned Zone	N/A	N/A

H4b. MULTIFAMILY HVAC DISTRIBUTION – ECC VERIFICATION								
01	02	03	04	05	06	07	08	09
Name	Duct Leakage Verification	Duct Leakage Target (%)	Verified Duct Location	Verified Duct Design	Buried Ducts	Deeply Buried Ducts	Low-leakage Air Handler	Low Leakage Ducts Entirely in Conditioned Space
Air Distribution System - Res	Yes	total leakage <= 12.0 or leakage to outdoors <= 6.0	Required	Not Required	Not Required	Credit not taken	Not Required	No

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 17 of 20)

H10. MULTIFAMILY DWELLING UNIT TYPE CENTRAL / INDIVIDUAL VENTILATION												
01	02	03	04	05	06	07	08	09	10	11	12	13
Dwelling Unit Type	IAQ Option	Central Fan (If applicable)					Individual Fan (if applicable)					
		IAQ Fan Type Type	Supply Airflow CFM	Supply Fan Efficacy W/CFM	Exhaust CFM	Exhaust Fan Efficacy W/CFM	IAQ Fan Type	Count	Airflow CFM	Fan Efficacy W/CFM	Recovery Efficiency SRE	Recovery Efficiency ASRE
1-Bed Type Z1	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Balanced	1	37.5	0.4	70	70
2-Bed Type Z1	Individual IAQ Fan	N/A	N/A	N/A	N/A	N/A	Balanced	1	54.9	0.4	70	70

I1. WATER HEATER EQUIPMENT SUMMARY													
01	02	03	04	05	06	07	08	09	10	11	12	13	14
Name	Heater Element Type	Tank Type	Qty	Tank Vol (gal)	Rated Input	Rated Input Unit	Efficiency	Efficiency Unit	Tank Insulation R-value Int/Ext	Standby Loss Fraction	1st Hr. Rating or Flow Rate (gal)	Heat Pump Type	Tank Location or Ambient Condition
Heat Pump	Heat Pump	Storage	8	50	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Residential (NEEA RATED) PRODUCT	Tank Zone

I2. MULTI-FAMILY WATER HEATING SYSTEM DETAIL							
01	02	03	04	05	06	07	08
System Name	Configuration	Type	Qty in System	Dwelling Unit Distribution Type	Water Heater Name	Solar Heating System	Is Compact Distribution
DHWHeatpump	Domestic Hot Water (DHW)	Unitary	1	Standard Distribution System	Heat Pump	N/A	No

K4. INDOOR CONDITIONED LIGHTING MANDATORY LIGHTING CONTROL
See LMCC-LTI01-E for mandatory controls

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 18 of 20)

L. DWELLING UNIT INFORMATION			
01	02	03	04
Dwelling Unit Name	Dwelling Unit Type	Zone	Zone Group Multiplier
1BR - First Floor-(1/2)	1-Bed Type Z1	Zone1	1
1BR - First Floor-(2/2)	1-Bed Type Z1	Zone1	1
2BR - First Floor-(1/2)	2-Bed Type Z1	Zone1	1
2BR - First Floor-(2/2)	2-Bed Type Z1	Zone1	1
1BR - Second Floor-(1/2)	1-Bed Type Z1	Zone2	1
1BR - Second Floor-(2/2)	1-Bed Type Z1	Zone2	1
2BR - Second Floor-(1/2)	2-Bed Type Z1	Zone2	1
2BR - Second Floor-(2/2)	2-Bed Type Z1	Zone2	1

M. DWELLING UNIT TYPES						
01	02	03	04	05	06	07
Name	CFA (ft ²)	Number of Bedrooms	Number in Building	Space Conditioning Systems Assigned	DHW System Name	IAQ Vent Fan Name
1-Bed Type Z1	750	1	4	1-Bed Type Z1 :Split SZHP System:Air Distribution System - Res:Heat Pump Fan:2:3	DHWHeatpump	Individual IAQ Fans
2-Bed Type Z1	1080	2	4	2-Bed Type Z1 :Split SZHP System:Air Distribution System - Res:Heat Pump Fan:2:3	DHWHeatpump	Individual IAQ Fans
1-Bed Type Z2	750	1	0		DHWHeatpump	Individual IAQ Fans
2-Bed Type Z2	1080	2	0		DHWHeatpump	Individual IAQ Fans

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 19 of 20)

N. DECLARATION OF REQUIRED CERTIFICATES OF INSTALLATION	
<i>Selections made by Documentation Author indicate which Certificates of Installation must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online</i>	
Building Component	Form/Title
Envelope	NRCI-ENV-E - Envelope (for all buildings)
Plumbing	NRCI-PLB-E - For all buildings with Plumbing Systems
Solar and Battery	NRCI-SAB-E - Solar Water Heating, PV and Battery Storage Systems
Indoor Lighting	NRCI-LTI-E - Indoor Lighting (for all buildings)

O. DECLARATION OF REQUIRED CERTIFICATES OF ACCEPTANCE	
<i>Selections made by Documentation Author indicate which Certificates of Acceptance must be submitted for the features to be recognized for compliance. These documents must be provided to the building inspector during construction. Lighting controls and mechanical NRCA's must be completed through an Acceptance Test Technician Certification Provider (ATTCP).</i>	
Building Component ¹	Form/Title System Name(s)
Envelope	NRCA-ENV-02-F - NRFC label verification for fenestration
¹ Refer to other prescriptive NRCC forms applicable to the project for additional NRCA tests required that are not included in the NRCC-PRF-E form	

P. DECLARATION OF REQUIRED CERTIFICATES OF VERIFICATION
<i>Selections made by Documentation Author indicate which Certificates of Verification must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online</i>
<i>Selections made by Documentation Author indicate which Certificates of Verification must be submitted for the features to be recognized for compliance. These documents must be retained and provided to the building inspector during construction and can be found online</i>
There are no certificates applicable to this project

CERTIFICATE OF COMPLIANCE - LOWRISE MULTIFAMILY PERFORMANCE COMPLIANCE METHOD	LMCC-PRF-01-E
Lowrise Multifamily Mixed Use Performance Compliance Method	(Page 20 of 20)

Documentation Author's Declaration Statement

1. I certify that this Certificate of Compliance documentation is accurate and complete.	
Documentation Author Name:	Documentation Author Signature:
Company:	Signature Date:
Address:	CEA/AEA/ECC Certification Identification (if applicable):
City/State/Zip: ,	Phone:

Responsible Person's Declaration statement

I certify the following under penalty of perjury, under the laws of the State of California: - The information provided on this Certificate of Compliance is true and correct. - I am eligible under Division 3 of the Business and Professions Code to accept responsibility for the building design or system design identified on this Certificate of Compliance (responsible designer). - The energy features and performance specifications, materials, components, and manufactured devices for the building design or system design identified on this Certificate of Compliance conform to the requirements of Title 24, Part 1 and Part 6 of the California Code of Regulations. - The building design features or system design features identified on this Certificate of Compliance are consistent with the information provided on other applicable compliance documents, worksheets, calculations, plans and specifications submitted to the enforcement agency for approval with this building permit application. - I understand that a registered copy of this Certificate of Compliance shall be made available with the building permit(s) issued for the building and shall be made available to the enforcement agency for all applicable inspections. I will take the necessary steps to fulfill this requirement. - I understand that a registered copy of this Certificate of Compliance is required to be included with the documentation the builder provides to the building owner at occupancy. I will take the necessary steps to fulfill this requirement.	
Responsible Designer Name:	Responsible Designer Signature:
Company:	Date Signed:
Address:	License #:
City/State/Zip:	Title:
Phone:	Scope:

Registration Number:

CA Building Energy Efficiency Standards
2025 Lowrise Multifamily Compliance

Registration Date/Time:

Report Version: 2025.0.000
Schema Version: rev 20250101

ECC Provider:

Report Generated: 2026-05-22 12:53:25