

## Lab: Skills - JUnit and EclEmma in Eclipse

**Getting Ready:** Before going any further, you should:

1. Setup your development environment.
2. Download the following files:  
[GiftCard.java](#)  
to an appropriate directory/folder. (In most browsers/OSs, the easiest way to do this is by right-clicking/control-clicking on each of the links above.)
3. If you don't already have one from earlier in the semester, create a project named `eclipseskills`.
4. Drag the file `GiftCard.java` into the default package (using the "Copy files" option).
5. Open `GiftCard.java`.

**Part 1. JUnit Basics:** JUnit is an open-source testing framework. It provides a way to write, organize, and run repeatable test. This part of the lab will help you become familiar with JUnit.

1. Create an empty JUnit test named `GiftCardTest` in the default package by clicking on `File>New>JUnit Test Case`. Use the most recent version of JUnit; if necessary, add JUnit to the build path when asked.

Note: Normally, you should put tests in their own package(s). To keep things simple, we will break that rule.

2. Copy the following code into `GiftCardTest`.

```
import static org.junit.Assert.assertEquals;
import org.junit.Test;
import org.junit.rules.ExpectedException;

public class GiftCardTest
{
    @Test
    public void getIssuingStore()
    {
        double      balance;
        GiftCard     card;
        int          issuingStore;

        issuingStore = 1337;
        balance      = 100.00;
        card = new GiftCard(issuingStore, balance);

        assertEquals("getIssuingStore()",
                    issuingStore, card.getIssuingStore());
    }
}
```

3. A JUnit test suite is a class, much like any other class. Tests are methods that are preceded with the annotation `@Test`. (Note: An annotation provides information about a program but is not part of the program. Annotations have no effect on the operation of the program. Instead, they are used to provide information to tools that might use the program as input.)

How many tests are in the test suite `GiftCardTest`?

**There is one test in the test suite `GiftCardTest`: `getIssuingStore()` method**

4. JUnit has an `Assert` class that has a static `assertEquals()` method with the following signature that is used to compare expected and actual results:

```
public static void assertEquals(String description, int expected, int actual)
```

where `description` is a human-readable `String` describing the test, `expected` is the expected result, and `actual` is the result of actually running the code being tested.

How would you call this method and pass it the `String "getIssuingStore()",` the `int issuingStore,` and the `int` returned by the `card` object's `getIssuingStore()` method?

```
Assert.assertEquals("getIssuingStore()",  
    issuingStore, card.getIssuingStore());
```

5. How is this method actually being called in `GiftCardTest`?

```
assertEquals("getIssuingStore()", issuingStore, card.getIssuingStore());
```


6. Why isn't the class name needed?

`Org.junit.Assert.assertEquals` has a static modifier that tells the compiler that the class name can be left out from the calls to static methods

7. Execute `GiftCardTest`. Why is it somewhat surprising that you can execute `GiftCardTest` without a main method?


**We have been only able to execute classes that have a `main()` method**

8. What output was generated?



**None, just the test results, and that all of the tests passed**

9. To see what happens when a test fails, modify the `getIssuingStore()` method in the `GiftCard` class so that it returns `issuingStore + 1`, compile `GiftCard.java`, and re-run the test suite. Now what happens?




```
3 import org.junit.test;
4 import static org.junit.jupiter.api.Assertions.*;
5 import org.junit.rules.ExpectedException;
6
7
8 public class GiftCardTest{
9     @Test
10     public void getIssuingStore() {
11         double balance;
12         GiftCard card;
13         int issuingStore;
14
15         issuingStore =1337;
16         balance = 100.00;
17         card = new GiftCard(issuingStore+1, balance);
```

**The test fails**

10. In the "Failure Trace", interpret the line:

`java.lang.AssertionError: getIssuingStore() expected:<1337> but was:<1338>`

Note: You may have to scroll the "Failure Trace" window to the right to see the whole message.



```
java.lang.AssertionError: getIssuingStore() expected:<1337> but was:<1338>
```

**The result should have been 1337 but was 1338, `getIssuingStore()` was runned**

11. What mechanism is JUnit using to indicate an abnormal return?

**Throwing an exception**

12. Before you forget, correct the fault in the `getIssuingStore()` method.

13. The `Assert` class in JUnit also has a static `assertEquals()` method with the following signature:  
`public static void assertEquals(String description, double expected, double actual, double tolerance)`

where `tolerance` determines how close to double values have to be in order to be considered "approximately equal".

Add a test named `getBalance()` that includes a call to `assertEquals()` that can be used to test the `getBalance()` method in the card class (with a tolerance of `0.001`).

```

@Test
public void getBalance(){
    double balance;
    GiftCard card;
    int issuingStore;

    issuingStore = 1337;
    balance = 100.00;
    card = new GiftCard(issuingStore, balance);

    assertEquals("getBalance()",
                 balance, card.getBalance(), 0.001);
}

```

ns: 2/2      Errors: 0      Failures: 0

---

GiftCardTest [Runner: JUnit 5] (0.000 s)

- getIssuingStore (0.000 s)
- getBalance (0.000 s)

14. How many tests are in your test suite now?

**There is two tests now**

15. Suppose you had put both calls to `assertEquals()` in one method (named, say, `getIssuingStore()`). How many tests would be in your test suite?

**Technically one**

16. Re-compile and re-execute the test suite. How many tests were run?


**Two tests. Both passed**

17. The Assert class in JUnit also has a static `assertEquals()` method with the following signature:  
`public static void assertEquals(String description, String expected, String actual)`  
Using JUnit terminology, add a test named `deduct()` to your test suite that can be used to test the `deduct()` method in the `GiftCard` class. Note: Be careful, the variables that are declared in the `getIssuingStore()` method are local.

```
public void deduct_RemainingBalance()
{
    double    balance;
    GiftCard   card;
    int        issuingStore;
    String     s;

    issuingStore = 1337;
    balance      = 100.00;
    card = new GiftCard(issuingStore, balance);

    s = "Remaining Balance: " + String.format("%6.2f", 90.00);
    assertEquals("deduct(10.00)",
                 s, card.deduct(10.0));
}
```



The image shows a screenshot of JUnit test results. At the top, there is a green bar indicating success. Below it, a list of test results is shown: 'GiftCardTest [Runner: JUnit 5] (0.005 s)' is the total time. Underneath, four individual tests are listed, each with a green checkmark icon and its execution time: 'deduct\_RemainingBalance (0.001 s)', 'getIssuingStore (0.001 s)', and 'getBalance (0.003 s)'. The 'getIssuingStore' test is highlighted with a blue background.

```
GiftCardTest [Runner: JUnit 5] (0.005 s)
  deduct_RemainingBalance (0.001 s)
  getIssuingStore (0.001 s)
  getBalance (0.003 s)
```

18. Execute the test suite.

**Part 2. Coverage:** This part of the lab will help you understand coverage tools and coverage metrics.

1. Read Eclipse\_EclEmma.pdf.
2. Run GiftCardTest using EclEmma, click on the "Coverage" tab and expand the directories/packages until you can see GiftCard.java and GiftCardTest.java.  
Why is the coverage of GiftCardTest.java 100% and why is this uninteresting/unimportant?
3. How many of the tests passed?

**Three tests passed**

4. Does this mean that the GiftCard class is correct?

**For the current tests, yes**

5. What is the statement coverage for GiftCard.java?

eclipseskills		34.5 %
▼ src		34.5 %
▼ eclipseskills		34.5 %
> PhoneDriver.java		0.0 %
> PhoneCard.java		0.0 %
> GiftCard.java		55.7 %
> GiftCardTest.java		100.0 %
nent		
	Coverage	C
eclipseskills		34.5 %
> src		34.5 %

6. Select the tab containing the source code for GiftCard.java. What is different about it?

**Statements are highlighted**

7. What do you think it means when a statement is highlighted in red?

**Statement wasn't executed by the other tests**

8. Hover your mouse over the icon to the left of the first if statement in the constructor. What information appears?

**2 of 4 branches missed**

9. Add tests to your test suite so that it covers all of the statements and branches in the deduct() method in the GiftCard class.

```

public void deduct_AmountDue()
{
    double        balance;
    GiftCard       card;
    int            issuingStore;
    String         s;

    issuingStore = 1337;
    balance      = 100.00;
    card = new GiftCard(issuingStore, balance);

    s = "Amount Due: " + String.format("%.2f", 10.00);
    assertEquals("deduct 10.00 from 100.00",
        s, card.deduct(10.0));
}

```



```


public void deduct_InvalidTransaction()
{
    double        balance;
    GiftCard       card;
    int            issuingStore;
    String         s;






    issuingStore = 1337;
    balance      = 100.00;
    card = new GiftCard(issuingStore, balance);

    s = "Invalid Transaction";
    assertEquals("deduct -10.00 from 100.00",
        s, card.deduct(-10.0));
}

```

Runs: 5/5     Errors: 0     Failures: 0

 GiftCardTest [Runner: JUnit 5] (0.002 s)
 

-  deduct\_AmountDue (0.000 s)
-  deduct\_RemainingBalance (0.000 s)
-  getIssuingStore (0.000 s)
-  getBalance (0.000 s)
-  deduct\_InvalidTransaction (0.002 s)

10. Your test suite still does not cover every statement in the `GiftCard` class. What is different about the statements that remain untested?

**They involve exceptions**



**Part 3. Testing Methods that Throw Exceptions:** This part of the lab will help you learn how to test methods that throw exceptions.

1. The easiest (though not the most flexible) way to test for exceptions is to use the optional `expected` parameter of the `@Test` annotation. For example, add the following test to your test suite.

```
@Test(expected = IllegalArgumentException.class)
public void constructor_IncorrectBalance() throws IllegalArgumentException
{
    new GiftCard(1, -100.00);
}
```

Note: `IllegalArgumentException` is an unchecked exception. Hence, the code will compile even if it isn't re-thrown. If you are testing for a checked exception then the method must specify the exception.

2. Add a test to your test suite named `constructor_IncorrectID_Low()` that covers the case when the `storeID` is less than 0.

```
    }, card.deduct(-10.0));
}
@Test(expected = IllegalArgumentException.class)
public void constructor_IncorrectBalance() throws IllegalArgumentException
{
    new GiftCard(1, -100.00);
}
@Test(expected = IllegalArgumentException.class)
public void constructor_IncorrectID_Low()
{
    new GiftCard(-1, 100.00);
}
}
```

**Part 4. Coverage and Completeness:** This part of the lab will help you better understand code coverage and the completeness of test suites.

1. Run EclEmman on your current test suite. What is the statement coverage for `GiftCard.java` now?

100%

2. What branch does the test suite fail to test?

`storeID > MAX_ID` branch

3. Add a test to your test suite named `constructor_IncorrectID_High()` that covers the other branch.

```
@Test(expected = IllegalArgumentException.class)
public void constructor_IncorrectID_High()
{
    new GiftCard(100000, 100.00);
}
```

4. Run EcEmma. What is the branch coverage now?

**All branches are covered**

5. From a "white box" testing perspective, is your test suite complete? Conversely, can you think of tests that should be added?

**Each one was handled properly**

6. From a "black box" testing perspective, is your test suite complete? Conversely, can you think of tests that could be added?

**Big or small numbers can cause issues**