

ASSIGNMENT 6

Insert/Delete/Truncate/Drop

In this lab you will use SQL statements that fall in both the DDL and DML category. In this lab you will be storing new information in the database. You will be using the tables from your previous assignment as such: (Make sure that your tables contain the following columns along with the appropriate constraints)

Student

SSN primary key
lname
fname
dob
salary check > 10000
(lname and fname are a composite candidate key)

Class

Class code primary key
Class description (Create an index on this column using the create index command)

Student_class

SSN Foreign key
Class Code Foreign key
(SSN and class code are a composite primary key)

You must execute the statements in the order in which the questions are being asked.

Suggestions:

- 1) Do not create a spool file. This lab will probably take several days. Since you cannot guarantee that the work that you did on my home computer or the lab computers on campus will be there the next time you open up the SQLPlus session, I would make the following suggestion: Store all your SQL statements in a text file. Then you can just copy and paste your SQL statements into the SQLPlus session and get back to where you left off.
- 2) I would also suggest that you drop all your tables in the beginning of the text file just in case the tables are still there so that you don't get any error messages



All the tables that you create should be prefixed with the first five letters of your lastname such as sabze_patient

What to turn in:

- 1) You will turn in this word document only. I do not want any other files
- 2) Paste a printscreen of either the **SQLPlus session** or **SQL Developer** showing only the SQL command and the results from the database engine. Some of the SQL statements that you issue may cause an error and may actually be the expected result. Do not assume that just because you are not getting an error message, everything is okay.
- 3) When typing in your SQL statements, make sure that the **keywords are all in uppercase**. The identifiers that you come up with such as **table names, column names or constraint names should all be in lower case**.
- 4) Make sure that you prefix your table names with the **first five letters of your last name**.
- 5) Make sure that you **only provide a printscreen of the snippet that pertains to the question (NOTHING MORE)**.


Suggestion: you can use the snipping tool in windows 7 or you can download this open source program <http://getgreenshot.org/> for printscreens. Provide only the printscreen



that pertains to the question. I do not want to see your trial and errors or things that pertain to other questions.

	SQLPlus	or	SQLDeveloper	(Your choice)
Example	Display the contents of the dual table			
	<pre>SQL> SELECT * FROM dual;</pre> <pre>D</pre> <pre>-</pre> <pre>X</pre> <pre>1 row selected.</pre>			
Next Example	Create a table called test			
	<pre>SQL> CREATE TABLE sabze_test</pre> <pre>2 (</pre> <pre>3 col CHAR</pre> <pre>4);</pre> <pre>Table created.</pre>			


All the tables that you create must be prefixed with the first five letters of your last name such as sabze_student.





The order in which you insert data into your tables is different from the order in which the questions have been asked. **Questions 1a, 1b and 1c should not give you any error messages**


1A	Insert three rows of valid data into the student_class table		
	<pre>INSERT INTO chave_student_class VALUES ('123456789',0);</pre> <pre>INSERT INTO chave_student_class VALUES ('123456789',1);</pre> <pre>INSERT INTO chave_student_class VALUES ('132567586',1);</pre> 		
1B	Insert two rows of valid data into the class table according to the following. Make sure that you provide a value for every column.		
	<pre>INSERT INTO chave_class VALUES (0,'MATH 100');</pre> <pre>INSERT INTO chave_class VALUES (1,'CSC 134');</pre>		

		 <pre>1 rows inserted. 1 rows inserted.</pre>
1C	<p>Insert two rows of valid data into the student table according to the following. Provide a value for every column.</p> <p>For the 1st row:</p> <p>Use the to_date function to insert into the DOB column in the format (yyddmm)</p> <p>For the 2nd row</p> <p>Use the default date format (Do not use to_date function) (use default)</p>	<pre>INSERT INTO chavestudent VALUES('123456789','Smith','John',(TO_DATE('602506','YYDDMM')),'15000'); INSERT INTO chavestudent VALUES('132567586','Ross','Boss','01-FEB-1989',30000);</pre>  <pre>1 rows inserted. 1 rows inserted.</pre>

Do the questions in the order in which they appear. You may get error messages which of course is valid

2A	Insert a row of invalid data into student table such that it violates the primary key
	<pre>INSERT INTO chavestudent VALUES('13256758695834598','Trane','Thomas','10-FEB-1980',30000);</pre>  <pre>Error starting at line : 68 in command - INSERT INTO chavestudent VALUES('13256758695834598','Trane','Thomas','10-FEB-1980',30000) Error report - SQL Error: ORA-12899: value too large for column "CSUS"."CHAVE_STUDENT"."SSN" (actual: 17, maximum: 9) 12899. 00000 - "value too large for column %s (actual: %s, maximum: %s)" *Cause: An attempt was made to insert or update a column with a value which is too wide for the width of the destination column. The name of the column is given, along with the actual width of the value, and the maximum allowed width of the column. Note that widths are reported in characters if character length semantics are in effect for the column, otherwise widths are reported in bytes. *Action: Examine the SQL statement for correctness. Check source and destination column data types. Either make the destination column wider, or use a subset of the source column (i.e. use substring).</pre>
2B	Insert a row of invalid data into student table such that it violates the candidate key
	<pre>INSERT INTO chavestudent VALUES('135304389','Ross','Boss','10-FEB-1980',20000);</pre>





	 <p>Task completed in 0.081 seconds</p> <p>Error starting at line : 72 in command - INSERT INTO chavestudent VALUES('135304389','Ross','Boss','10-FEB-1980',20000) Error report - SQL Error: ORA-00001: unique constraint (CSUS.CHAVE_STUDENT_LNAME_FNAME_UK) violated 00001. 00000 - "unique constraint (%s.%s) violated" *Cause: An UPDATE or INSERT statement attempted to insert a duplicate key. For Trusted Oracle configured in DBMS MAC mode, you may see this message if a duplicate entry exists at a different level. *Action: Either remove the unique restriction or do not insert the key.</p>
2C	Insert a row of invalid data into student table such that it violates a check constraint
	<pre>INSERT INTO chavestudent VALUES('132567582','Trane','Thomas','10-FEB-1980',9000);</pre>  <p>Task completed in 0.141 seconds</p> <p>Error starting at line : 76 in command - INSERT INTO chavestudent VALUES('132567582','Trane','Thomas','10-FEB-1980',9000) Error report - SQL Error: ORA-02290: check constraint (CSUS.CHAVE_STUDENT_SALARY_CK) violated 02290. 00000 - "check constraint (%s.%s) violated" *Cause: The values being inserted do not satisfy the named check *Action: do not insert values that violate the constraint.</p>
2D	Insert a row of invalid data into the student_class table such that it violates the foreign key to the class table
	<pre>INSERT INTO chavestudent_class VALUES('123495334',0);</pre>  <p>Task completed in 0.13 seconds</p> <p>Error starting at line : 80 in command - INSERT INTO chavestudent_class VALUES('123495334',0) Error report - SQL Error: ORA-02291: integrity constraint (CSUS.CHAVE_STUDENT_CLASS_SSN_FK) violated - parent key not found 02291. 00000 - "integrity constraint (%s.%s) violated - parent key not found" *Cause: A foreign key value has no matching primary key value. *Action: Delete the foreign key or add a matching primary key.</p>
2E	Insert a row of invalid data into the student_class table such that it violates the foreign key to the student table
	<pre>INSERT INTO chavestudent_class VALUES('245306649',5);</pre>  <p>Task completed in 0.096 seconds</p> <p>Error starting at line : 84 in command - INSERT INTO chavestudent_class VALUES('245306649',5) Error report - SQL Error: ORA-02291: integrity constraint (CSUS.CHAVE_STUDENT_CLASS_CLASS_CODE_FK) violated - parent key not found 02291. 00000 - "integrity constraint (%s.%s) violated - parent key not found" *Cause: A foreign key value has no matching primary key value. *Action: Delete the foreign key or add a matching primary key.</p>
2F	Insert a row of invalid data into the student_class table such that it violates the primary key in the student_class table.

	<pre>INSERT INTO chave_student_class VALUES('123456789',0);</pre>  <p>Query Result x Script Output x</p> <p>Task completed in 0.084 seconds</p> <p>Error starting at line : 88 in command - INSERT INTO chave_student_class VALUES('123456789',0) Error report - SQL Error: ORA-00001: unique constraint (CSUS.CHAVE_STUDENT_CLASS_SSN_CLASS_CODE_PK) violated 00001. 00000 - "unique constraint (%s.%s) violated" *Cause: An UPDATE or INSERT statement attempted to insert a duplicate key. For Trusted Oracle configured in DBMS MAC mode, you may see this message if a duplicate entry exists at a different level. *Action: Either remove the unique restriction or do not insert the key.</p>
--	--

Do the questions in the order in which they appear. You may get error messages which of course is valid

3A	<p>Disable the foreign key constraint to the student table</p> <pre>ALTER TABLE chave_student_class DISABLE CONSTRAINT chave_student_class_ssn_fk;</pre>  <p>Query Result x Script Output x</p> <p>Task completed in 0.031 seconds</p> <p>table CHAVE_STUDENT_CLASS altered.</p>
3B	<p>Insert a rows of data into the student_class table such that it would violate the foreign key constraint if the above constraint to the student table was enabled</p> <pre>INSERT INTO chave_student_class VALUES('987654321',0);</pre>  <p>Query Result x Script Output x</p> <p>Task completed in 0.027 seconds</p> <p>1 rows inserted.</p>
3C	<p>Enable the foreign key constraint</p> <pre>ALTER TABLE chave_student_class ENABLE CONSTRAINT chave_student_class_ssn_fk;</pre>  <p>Query Result x Script Output x</p> <p>Task completed in 0.061 seconds</p> <p>Error starting at line : 99 in command - ALTER TABLE chave_student_class ENABLE CONSTRAINT chave_student_class_ssn_fk Error report - SQL Error: ORA-02298: cannot validate (CSUS.CHAVE_STUDENT_CLASS_SSN_FK) - parent keys not found 02298. 00000 - "cannot validate (%s.%s) - parent keys not found" *Cause: an alter table validating constraint failed because the table has child records. *Action: Obvious</p>

Do the questions in the order in which they appear. You may get error messages which of course is valid

4A	Delete the data from the student_class table
	<pre>DELETE FROM chave_student_class;</pre>  <p>The screenshot shows a SQL query execution window with tabs for 'Query Result' and 'Script Output'. Below the tabs are icons for a pin, pencil, save, print, and a green flag. The text 'Task completed in 0.054 seconds' is displayed. The main area shows the result: '4 rows deleted.'</p>
4B	Truncate the student table
	<pre>TRUNCATE TABLE chave_student;</pre> <p>table CHAVE_STUDENT truncated.</p>
4C	drop the index that you created on the student table
	<pre>DROP INDEX chave_student_ssn_dob_idx;</pre>  <p>The screenshot shows a SQL query execution window with tabs for 'Query Result' and 'Script Output'. Below the tabs are icons for a pin, pencil, save, print, and a green flag. The text 'Task completed in 0.152 seconds' is displayed. The main area shows the result: 'index CHAVE_STUDENT_SSN_DOB_IDX dropped.'</p>
4D	Drop the foreign key constraints
	<pre>ALTER TABLE chave_student_class DROP CONSTRAINT chave_student_class_ssn_fk; ALTER TABLE chave_student_class DROP CONSTRAINT chave_student_class_class_code_fk;</pre>  <p>The screenshot shows a SQL query execution window with tabs for 'Query Result' and 'Script Output'. Below the tabs are icons for a pin, pencil, save, print, and a green flag. The text 'Task completed in 0.121 seconds' is displayed. The main area shows two lines of results: 'table CHAVE_STUDENT_CLASS altered.' and 'table CHAVE_STUDENT_CLASS altered.'</p>
4E	Drop the student table.
	<pre>DROP TABLE chave_student;</pre>  <p>The screenshot shows a SQL query execution window with tabs for 'Query Result' and 'Script Output'. Below the tabs are icons for a pin, pencil, save, print, and a green flag. The text 'Task completed in 0.14 seconds' is displayed. The main area shows the result: 'table CHAVE_STUDENT dropped.'</p>