

StrongSwan VPN

Project Overview

This project focused on designing and implementing a **secure IPsec VPN tunnel** using **StrongSwan** between two virtual machines in an enterprise-style network. The VPN provided encrypted communication between internal and DMZ environments, ensuring confidentiality and integrity of data in transit.

Additionally, the VPN server was integrated with **Splunk Enterprise** to collect, monitor, and analyze VPN logs, providing real-time visibility into connection attempts, authentications, and potential anomalies.

This project demonstrates practical skills in **secure network configuration, firewall and routing management**, and **SIEM integration** for log visibility and threat detection.

Objectives

- Configure **StrongSwan IPsec VPN** for secure host-to-host communication.
 - Assign and manage static IP addresses for VPN endpoints.
 - Update DNS configurations and DHCP services for proper routing.
 - Forward VPN logs to **Splunk Enterprise** for monitoring.
 - Validate encryption through **Wireshark** traffic analysis.
 - Apply **UFW firewall rules** to restrict SSH access within the DMZ.
-

Implementation Steps

1. Lab Preparation and Environment Setup

- Cloned the existing *Client2-DMZ* virtual machine to create *StrongSwan-DMZ*.
 - Enabled “Reinitialize MAC addresses” during cloning to prevent conflicts.
 - Verified network connectivity and booted the **Outside-Firewall** before powering on *StrongSwan-DMZ*.
-

2. Hostname and Static IP Configuration

- Changed the hostname from `client2-dmz` to `strongswan-dmz`:
 - `sudo nano /etc/hostname`
 - `sudo nano /etc/hosts`
 - `sudo hostname strongswan-dmz`
 - Assigned a static IP (192.168.4.60) under the **IPv4 Settings** tab using “Manual” configuration.
 - Set **DNS Server** to 192.168.4.1 to align with internal DNS routing.
 - Restarted the network interface to apply changes:
 - `sudo ifconfig enp0s3 down`
 - `sudo ifconfig enp0s3 up`
-

3. Fixing DNS Configuration and DHCP Server

- Updated **pfSense DHCP settings** on *Inside-Firewall* to distribute the correct DNS server (192.168.4.1).
 - Navigated to:
Services → DHCP Server → Servers
 - Replaced Google DNS (8.8.8.8) with local DNS (192.168.4.1).
 - Saved and applied changes.
 - Confirmed that *Inside-Firewall* and *Outside-Firewall* continued to route internal traffic correctly.
-

4. Installing and Configuring StrongSwan VPN Server

- Installed required StrongSwan packages:
- `sudo apt update`
- `sudo apt install strongswan strongswan-pki -y`
- Configured `/etc/ipsec.conf`:(`sudo nano /etc/ipsec.conf`)
 - `config setup`
 - `conn %default`
 - `ikelifetime=60m`
 - `keylife=20m`
 - `rekeymargin=3m`
 - `keyingtries=1`
 - `keyexchange=ikev2`
 - `authby=secret`
 - `mobike=no`
 - `conn host-host`
 - `keyexchange=ikev2`
 - `ike=aes256-sha384-ecp384-prfsha384!`
 - `esp=aes256gcm128-ecp384!`
 - `left=%any`
 - `leftfirewall=yes`

- right=192.168.4.60
 - type=transport
 - auto=add
 - Defined pre-shared keys in /etc/ipsec.secrets:
 - %any : PSK "password"
 - Restarted the StrongSwan service:
 - sudo systemctl restart strongswan-starter
 - sudo ipsec statusall
-

5. Enabling IP Forwarding and Security Controls

- Modified /etc/sysctl.conf to enable routing and disable redirects:
 - \$ sudo su -
 - # echo "net.ipv4.ip_forward = 1" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.conf.all.accept_redirects = 0" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.conf.all.send_redirects = 0" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.conf.default.rp_filter = 0" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.conf.default.accept_source_route = 0" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.conf.default.send_redirects = 0" | tee -a /etc/sysctl.conf
 - # echo "net.ipv4.icmp_ignore_bogus_error_responses = 1" | tee -a /etc/sysctl.conf
 - # sysctl -p
 - # exit
 - Applied changes using:
-

6. Integrating StrongSwan with Splunk

Objective: Forward VPN logs to Splunk for real-time visibility.

- Modified the StrongSwan logging configuration file /etc/strongswan.d/charon-logging.conf:

```
charon {  
    filelog {  
        charon {  
            path = /var/log/charon.log  
            time_format = %b %e %T  
            ike_name = yes  
            append = no  
            default = 2  
            flush_line = yes  
        }  
    }  
}
```

```

•         stderr {
•             ike = 2
•             knl = 3
•         }
•     }

•     syslog {
•         identifier = charon-custom
•         daemon {
•         }
•         auth {
•             default = -1
•             ike = 0
•         }
•     }
• }
```

- Updated **AppArmor** permissions:
 - `/var/log/ r,`
 - `/var/log/** rwk,`

Then restarted AppArmor:

```
```bash
sudo service apparmor restart
```

## 7. Configuring Splunk Enterprise Receiver

- On the **Splunk-DMZ** machine (192.168.4.20):
  - **Settings → Forwarding and Receiving → New Receiving Port (9997)**
  - Created a new **index** named `strongswan` for VPN logs.




Figure 1/Splunk

## 8. Installing Splunk Forwarder on StrongSwan-DMZ

- Installed Splunk Universal Forwarder and enabled boot-start:

- sudo dpkg -i splunkforwarder.deb
  - sudo /opt/splunkforwarder/bin/splunk enable boot-start
  - sudo service SplunkForwarder start
  - **Added Splunk server and log path:**
  - sudo /opt/splunkforwarder/bin/splunk add forward-server 192.168.4.20:9997
  - sudo /opt/splunkforwarder/bin/splunk add monitor /var/log/charon.log - index strongswan
- 

## 9. Configuring the VPN Client (Client2-DMZ)

- Installed StrongSwan and configured /etc/ipsec.conf:
  - config setup
  - 
  - conn %default
  - ikelifetime=60m
  - keylife=20m
  - rekeymargin=3m
  - keyingtries=1
  - keyexchange=ikev2
  - authby=secret
  - mobike=no
  - 
  - conn host-host
  - keyexchange=ikev2
  - ike=aes256-sha384-ecp384-prfsha384!
  - esp=aes256gcm128-ecp384!
  - left=%any
  - leftfirewall=yes
  - right=192.168.4.60
  - auto=start
  - type=transport **Defined shared key in /etc/ipsec.secrets:**
  - 192.168.4.60 : PSK "password"
- **Restarted VPN service:**
- sudo systemctl restart strongswan-starter
- sudo ipsec statusall




Figure 2/Statusall

## 10. Testing and Verification

- Verified the tunnel by running:  
ping 192.168.4.60
- Captured traffic using **Wireshark** — confirmed encrypted ESP packets.
- Disconnected VPN and confirmed communication dropped as expected.
- Verified successful log forwarding in **Splunk** using queries:
  - index=strongswan
  - source="/var/log/charon.log"
- Logs showed successful IKE negotiations, rekey events, and connection teardowns.




Figure 3/Splunk