

# SCRUBBER 75

# **Robotic Floor Scrubber**

for Large-Scale Commercial and Industrial Environments













# Key Features

# **Industrial-Strength Cleaning Power**

#### 45kg Brush Pressure

Delivers exceptional scrubbing force for deep and effective cleaning.

#### পি Oil Cleaning Mode

Capable of removing stubborn oil stains with a detergent kit, ideal for heavily contaminated industrial environments and underground garages.

#### **Ultimate Productivity**

# **350mm Cleaning Width**

Delivers up to 3000m<sup>2</sup>/h scrubbing efficiency, expertly designed for heavy-duty cleaning tasks in large spaces.

#### (a) 270° Rotational Scrub Deck

Effortlessly accesses and cleans 90° corners, putting a stop to incomplete cleaning once and for all.

# **Advanced Sensing & Lighting Configuration**

#### (P) Best-in-Class Sensing

Features a market-leading sensor system, including 3D LiDAR and an optional millimeter-wave radar (75 P), ensuring unparalleled precision and reliability.

# **Enhanced Lighting**

Offers flashing lights, headlights, and other lighting elements to clearly communicate the machine's position.

# Sustainability

#### () Water Recycling

Features a built-in multi-stage filtration system that recycles and reuses water, reducing freshwater consumption by approximately 80%.

# **Effortless Maintenance**

#### Ergonomic Manual Operation

Equipped with stand-on pedal and steering wheel for users to effortlessly carry the machine around.

#### (a) Docking Stations

A standard workstation for self-docking power charging and water management.

# **Applicable Flooring Types**







Ceramic







Natural Stone Ar

**Artificial Stone** 

Concrete

PVC&Vinyl

Ероху



Dimension (L×W×H)		1,370×962×1,417 mm   54×38×56 in
Net Weight		400 kg   900 lb
Cleaning Width		750 mm   29.5 in
Brush Pressure		45 kg   99 lb
Clean/Waste Water Ta	nk	75L / 50 L   20 gal / 13 gal
Max. Cleaning Efficien	ncy (Theoretical)	3,000 m²/h   32,292 ft²/h
Practical Cleaning Effi	ciency	700-1,400 m²/h   7,535-15,069 ft²/h
Gradeability		8°
Min. Pass Width		General: 1,400 mm   55.1 in Underground garage: 1,800 mm   70.9 in
Min. U-turn Width		2,000 mm   78.7 in
Max. Cleaning Speed		1.1 m/s   2.5 mph
Runtime		≈ 4-6 h
Charging Time		≈ 6 h
Sensor System		D LiDAR, 3D Camera, Air Pressure Collision Sensor, Anti-Drop sensor Air Pressure Collision Sensor, Anti-Drop sensor, Millimeter-wave Radar
Optional Configuration	n (EU-Specific)	Roller Brush, Trash Tray, Headlights, Millimeter-wave Radar

Heavy-Duty Cleaning with Best-in-Class Sensing

