



CONSTRUCTION EQUIPMENT CATALOGUE

2025



BUILT FOR EVERY CHALLENGE



PLATE COMPACTOR DIESEL



DESCRIPTION	RBC- 90 _ 6.0 HP DIESEL	RBC- 120 _ 6.0 HP DIESEL
MODEL	RBC-90	RBC-120
PLATE SIZE L*W (MM)	550*420	550*670
MAX TRAVELLING SPEED (M/MIN)	15-20	15-20
LIMITED GRADE ABILITY	20	20
FREQUENCY (RPM)	5600	5600
IMPACT FORCE (KN)	13	13
ENGINE MODEL	RB173F	RB173F
STARTING SYSTEM	RECOIL STARTER	RECOIL STARTER
NET WEIGHT (KG)	100	110

PLATE COMPACTOR GASOLINE



DESCRIPTION	RBC- 60 5.0 HP GASOLIN	RBC- 90 5.0 HPGASOLIN	RBC- 120 5.0 HPGASOLIN
MODEL	RBC-60	RBC-90	RBC-120
PLATE SIZE L*W (MM)	510*350	550*420	550*670
MAX TRAVELLING SPEED (M/MIN)	20-25	15-20	15-20
LIMITED GRADE ABILITY	20	20	20
FREQUENCY (RPM)	5600	5600	5600
IMPACT FORCE (KN)	13	13	13
ENGINE MODEL	RB20-A	RB20-A	RB20-A
STARTING SYSTEM	RECOIL STARTER	RECOIL STARTER	RECOIL STARTER
NET WEIGHT (KG)	60	85	100

TAMPING RAMMER (DIESEL)

RBR-80-2



DESCRIPTION	DIESEL RB173F 6.0HP
MODEL	RBR-80-2
ENGINE MODEL	RB173F
DEVICED POWER	6.0HP
BOTTOM PLATE SIZE (MM)	300*280
IMPACT FREQUENCY	600~700/MIN
JUMP STORKE (MM)	40~65
IMPACT FORCE (KN)	12
FULE TANK CAPACITY (L)	3.5
STARTING SYSTEM	RECOIL STARTER
NET WEIGHT (KG)	105

TAMPING RAMMER (GASOLINE)

RBR-80



DESCRIPTION	GASOLINE RB20-A5.0HP
MODEL	RBR-80
ENGINE MODEL	RB20-A / HONDA GX160
DEVICED POWER	5.0HP
BOTTOM PLATE SIZE (MM)	300*280
IMPACT FREQUENCY	600~700/MIN
JUMP STORKE (MM)	40~65
IMPACT FORCE (KN)	12
FULE TANK CAPACITY (L)	2.8
STARTING SYSTEM	RECOIL STARTER
NET WEIGHT (KG)	95

ALPHA REBAR CUTTER MACHINE

GQ42 BAR CUTTER



TITLE	DESCRIPTION
MODEL	GQ42 BAR CUTTER
CUTTING RANGE	ROUND BAR:6-42MM DEFORMED BAR:6-32MM
BENDING SPEED	28T/MIN
MOTOR POWER	3KW
INPUT VOLTAGE	3PHASE 380V MOTOR SPEED:3400RPM
BLADE SIZE	83*83*26MM
NET WEIGHT	350KG
GROSS WEIGHT	380KG

OVERALL SIZE	1300*450*700MM
--------------	----------------

ALPHA REBAR CUTTER MACHINE

GQ46 BAR CUTTER



TITLE	DESCRIPTION
MODEL	GQ46 BAR CUTTER
CUTTING RANGE	ROUND BAR:6-46MM DEFORMED BAR:6-40MMA
BENDING SPEED	28T/MIN
MOTOR POWER	4KW-2P-3400RPM
INPUT VOLTAGE	3PHASE 380V
BLADE SIZE	83*83*26MM
NET WEIGHT	420KG
GROSS WEIGHT	450KG

OVERALL SIZE 1430*470*760MM

ALPHA REBAR CUTTER MACHINE

GQ50 BAR CUTTER



TITLE	DESCRIPTION
MODEL	GQ50 BAR CUTTER
CUTTING RANGE	ROUND BAR:6-50MM DEFORMED R:6-40MM
BENDING SPEED	28T/MIN
MOTOR POWER	4KW- 3400 RPM
INPUT VOLTAGE	3PHASE 380V
BLADE SIZE	90*90*26MM
NET WEIGHT	500KG
GROSS WEIGHT	530KG

OVERALL SIZE	1400*550*850MM
--------------	----------------

ALPHA REBAR BENDING MACHINE

GQ50 BAR CUTTER



TITLE	DESCRIPTION
MODEL	GW46 BAR BENDER
BENDING RANGE	ROUND BAR:6-46MM DEFORMED BAR:6-40MM
BENDING SPEED:	20-30PCS/MIN
MOTOR POWER	3KW -4P- (WITH BRAKE)
INPUT VOLTAGE	3PHASE 380V
DISK DIAMETER	350MM
WEIGHT	380 KGS
OVERALL SIZE	940X890X900MM

DRIVINGMODE	GEAR
-------------	------

ALPHA REBAR BENDING MACHINE

GW46 BAR BENDER



TITLE	DESCRIPTION
MODEL	GW46 BAR BENDER
BENDING RANGE	ROUND BAR:6-46MM DEFORMED BAR:6-40MM
BENDING SPEED:	20-30PCS/MIN
MOTOR POWER	3KW -4P- (WITH BRAKE)
INPUT VOLTAGE	3PHASE 380V
DISK DIAMETER	350MM
WEIGHT	380 KGS
OVERALL SIZE	940X890X900MM
DRIVINGMODE	GEAR

ALPHA REBAR BENDING MACHINE

GW50 BAR BENDER



TITLE	DESCRIPTION
MODEL	GW50 BAR BENDER
BENDING RANGE	ROUND BAR:6-50MM DEFORMED BAR:6-40MM
BENDING SPEED:	20-30PCS/MIN
MOTOR POWER	4KW (WITH BRAKE)
INPUT VOLTAGE	3PHASE 380V
DISK DIAMETER	400 MM
NET WEIGHT:	390 KG
GROSS WEIGHT:	530 KG
OVERALL SIZE:	1035*865*1005MM
DRIVING MODE	GEAR

ELECTRICAL CEMENT MIXER 200L

CM 200



TITLE	DESCRIPTION
MODEL	CM 200
POWER OUTPUT (W)	850
MOTOR	ELECTRIC MOTOR
VOLTAGE	220V
FREQUENCY	60HZ
MIXED BATCH OUTPUT (L)	150
DRUM VOLUME (L)	180
OPERATION MASS (KG)	40~65

CONCRETE CUTTER



DESCRIPTION	GASOLINE	DIESEL
MODEL	RBCT-3	RBCT-2
ENGINE MODEL	COPY GX390	RB186FA
POWER (HP)	13	10
MAX CUTTING DEPTH	17	18
BLADE SPEED RPM	UP TO 3600	UP TO 3601
MAXIMUM BLADE SIZE (IN)	20INCH	20INCH
BLADE HOLE DIAMETER (MM)	25.4	25.4
DEPTH ADJUSTMENT	HANDLE ROTATION	HANDLE ROTATION
DRIVING	MANUAL PUSH	MANUAL PUSH
WATER TANK CAPACITY	40L	40L
STARTING SYSTEM	RECOIL STARTER	RECOIL STARTER
FULE TANK CAPACITY (L)	5.5L	5.5L
NET WEIGHT (KG)	125	125

ROAD MARKING MACHINE (COLD PAINT)

HX-26



TITLE	DESCRIPTION
MODEL	HX-26
Power	6.5HP four-stroke gasoline engine
Main pump	Imported precision plunger pump
Maximum flow	12L/min
Maximum working pressure	21Mpa
Spray width	50-500mm (double gun) thickness: 0.2-0.4mm
Net weight	110kg
Dimension	1700*750*1100mm

ROAD MARKING MACHINE (HOT PAINT)

HX-36



TITLE	DESCRIPTION
MODEL	HX-36
COATING WIDTH	100-450MM
COATING SPEED	1.5KM/H
HEATING TEMPERATURE	180-210
HEATING METHOD	LIQUID GAS
STORAGE CAPACITY OF GLASS BEADS	25KG
STANDARD HOPPER CONFIGURATION	150MM
COATING VOLUME	100KG / BARREL
MARKING THICKNESS	1-3MM
WEIGHT	135KG
HEATING SPEED	20-30 MINUTES
GLASS BEAD DISPERSION	20-30G / 15CM

WALK BEHIND VIBRATING TANDEM ROLLERS



VR-650D



VR-600

MODEL	VR-650D	VR-600
WEIGHT	560/570KG	540KG
WATER TANK CAPACITY	30L	15L
FUEL TANK CAPACITY	12L	15L
TRAVEL SPEED	0-4KM/H	0-4KM/H
DRIVING METHOD	DUAL WHEEL DRIVE/HYDRAULIC DRIVE	DUAL DRIVE DUAL VIBRATION / HYDRAULIC DRIVE
WALKING METHOD	FORWARD OR BACKWARD	FORWARD OR BACKWARD
DRUM WHEEL SIZE	FRONTΦ426*650MM AFTER Φ426*650MM	FRONT Φ420*600MM AFTER Φ426*600MM
VIBRATION CLUTCH MODE	AUTOMATIC SEPARATION TYPE	AUTOMATIC SEPARATION TYPE
COMPACTING FORCE	25KN	25KN
COMPACTING FREQUENCY	70HZ	70HZ
CLIMBING ABILITY	30%	30%
OVERALL DIMENSIONS	L1180*W850*H1520MM	L1250*W800*H1520MM
POWER MODEL	CHANGCHAI 178FA / HONDA GX270	CHANGCHAI 178FA
STARTING METHOD	ELECTRIC START / MANUAL START	ELECTRIC START

TOWER LIGHT - 6 METRES HEIGHT



YANMAR POTABLE AIR-COOLED DIESEL GENERATORS

MODEL	YDG3700N-6EBYI2
MAX AC OUTPUT (KVA)	3.7
CONT. AC OUTPUT (KVA)	3.4
FREQUENCY (HZ)	60
START-UP TYPE	ELEECTRIC
OUTPUT VOLTAGE (VDC) 240	240
SOUND LEVEL (DB)	82
FUEL TANK VOLUME (L) 13	13
OPERATION CAPACITY (HR)	9.1
DRY WEIGHT (KG)	81

MOBILE LIGHT TOWER

HEIGHT	5.5M
LIFTING	MANUAL
LAMP	LED
FLOODLIGHT MODEL	KLB600LED*4
FLOODLIGHT MODEL	600-4
TOTAL POWER OF THE LAMPS.	2400
MAST	4 STAGES LIFTING MAST
LIFTING LIMIT OF THE MAST	2100-4900
DIMENSIONS (LXWXH)(AFTER RETREATING)	1180X790X2100
INCLINATION	≤10 DEGREES
WINDPROOF ABILITY	≤6 GRADE
DRY WEIGHT	140
LAMP BASE TYPE	LED

GASOLINE CONCRETE POWER TROWEL



DESCRIPTION	DIAMETER 1 (METER)	DIAMETER 60 (CM)
MODEL	RBT-36A	RB60
ENGINE MODEL	1000	600
TROWEL DIAMETER (MM)	4	4
NUMBER OF BLADES	50~130	50~130
DRIVING SPEED(RPM)	350*150	215*120
BLADE DIMENSION (MM)	RB20-A 5.0HP	RB20-A 5.0HP
STARTING SYSTEM	RECOIL START	RECOIL START
NET WEIGHT (KG)	75	65

CONCRETE VIBRATOR ELECTRICAL



TITLE	DESCRIPTION
MODEL	ZNA20
MOTOR POWER	2KW
VOLTAGE	220V
FREQUENCY	50/60HZ
SPEED R.P.M	2840/3450
ELECTRIC WIRE LENGTH	1.25 MTR.

VIBRATOR HOSE



TITLE		DESCRIPTION		
SIZE		SIZE 38MM×6 PIN	SIZE 45MM×6 PIN	SIZE 60MM×6 PIN
LENGTH		6M	6M	6M
COUPLING TYPE		PIN TYPE	PIN TYPE	PIN TYPE
DIAMETER		38MM	45MM	50MM
NET WEIGHT (KG)		13.2	14.5	20
GROS: WEIGHT		13.5	15	21

CONCRETE VIBRATOR



DESCRIPTION	GASOLINE 5.0HP	DIESEL 6.0 HP
MODEL	RBV	RBV
VIBRATION HEAD (MRN)	28*470 32*470	28*470 32*470
	38*470 45*470	38*470 45*470
	50*470 60*470	50*470 60*470
AMPLITUDE (M / MIN)	0.80 0.90	0.80 0.90
	1.20 1.30	1.20 1.30
	1.60 2.0	1.60 2.0
VIBRATION /MIN	9800 ~12000	9800 ~12000
SHAFT ROATE SPEED	3000	3000
ENGINE MODEL	RB20-A	RB173F
FULE TANK CAPACITY (L)	3.8L	3.6L
CONTINUOUS RUNNING TIME(H)	3.5H	3.5H
STARTING SYSTEM	RECOIL STARTER	RECOIL STARTER

VIBRATORY SCREED RULER



TITLE	DESCRIPTION
MODEL	ZPC-25
GASOLINE ENGINE	HONDA GX35
ENGINE POWER	1.0KW/6500R/MIN
FUEL TANK CAPACITY	0.65L
VIBRATION AMPLITUDE	<25MM
SUITABLE RULER LENGTH	1-4M
N.W.	11KG
G.W.	12.5KG
BODY MATERIAL	STAINLESS STEEL



CONTACT US

+351 5555 666 789
ASMITH@WOLTH.COM

WWW.WOLTH.COM

THANK YOU

