

Adobe Flash Player Exploit

Atum

About me

- Atum
 - @blue-lotus
 - @Tea Deliverers
 - @Peking University
- Keywords
 - Software Security, System Security
 - CTF PWNer, Weak Chicken
- lgcpku@gmail.com

Difficulties to exploit adobe flash

- No Symbol
- AVM abstraction
- IE Sandbox

Make symbol file

- Match symbol by AVMplus source code
- Match symbol by IDA FLIRT sig file
 - Identify compiler used by adobe flash
 - Use the same Compile Avmplus
 - Extract .sig file using IDA FLIRT
 - Load .sig file

Debug without symbol

- By Access Breakpoint
 - Malloc block 1000 times, set a access breakpoint on arbitrary bloc, then free all blocks
 - Malloc block and fill with 0xdeadc0de, search 0xdeadc0de in mem and set a access breakpoint on it
 - Other techniques..
- Set break point on JavaScript engine
 - ExternalCall

Exploit AVM

- Craft Arbitrary RW by Spray Vector/ByteArray
- Spray Vector (Vector is protected since 2016)
 - Vector memory layout (**length**, xxxx,data)
- Spray ByteArray

Exploit AVM

- Using Arbitrary to leak && Control flow hijack
- Control flow hijack
 - Change Vtable (Vtable is protected by CFG on Win10)
 - Change mmgc to bypass CFG on Win10
 - ROP+Vmprotect + shellcode

Bypass IE sandbox

- Launch a local server and exploit again(if EPM enable, this skill cannot be used)
- NBNS spoofing