ФЕДЕРАЛЬНОЕ АГЕНТСТВО СВЯЗИ ФЕДЕРАЛЬНОЕ ГОСУДАРСТВЕННОЕ БЮДЖЕТНОЕ ОБРАЗОВАТЕЛЬНОЕ УЧРЕЖДЕНИЕ ВЫСШЕГО ОБРАЗОВАНИЯ «САНКТ-ПЕТЕРБУРГСКИЙ ГОСУДАРСТВЕННЫЙ УНИВЕРСИТЕТ ТЕЛЕКОММУНИКАЦИЙ ИМ. ПРОФ. М.А. БОНЧ-БРУЕВИЧА» (СПбГУТ)

Факультет <u>Инфокоммуникационных сетей и систем</u> Кафедра Защищенных систем связи

Лабораторная работа №4

Управление операционной системой Cisco IOS и конфигурационными файлами на базе коммутаторов

Выполнили студенты группы ИКТЗ-83: Громов А.А., Миколаени М.С., Мазеин Д.С.	
Проверил:	(noonaes)
Скорых М.А.	
(VIII cmanaul VIII regulus († 14.0.)	(nodmici)

Санкт-Петербург

Установка обновления Cisco IOS

```
Router#sh version
Cisco IOS Software, C1900 Software (C1900-UNIVERSALK9-M), Version
15.1(4)M4, RELEASE SOFTWARE (fc2)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2007 by Cisco Systems, Inc.
Compiled Wed 23-Feb-11 14:19 by pt team
ROM: System Bootstrap, Version 15.1(4)M4, RELEASE SOFTWARE (fc1)
cisco1941 uptime is 17 seconds
System returned to ROM by power-on
System image file is "flash0:c1900-universalk9-mz.SPA.151-1.M4.bin"
Last reload type: Normal Reload
This product contains cryptographic features and is subject to United
States and local country laws governing import, export, transfer and
use. Delivery of Cisco cryptographic products does not imply
third-party authority to import, export, distribute or use
encryption.
Importers, exporters, distributors and users are responsible for
compliance with U.S. and local country laws. By using this product
you
agree to comply with applicable laws and regulations. If you are
to comply with U.S. and local laws, return this product immediately.
A summary of U.S. laws governing Cisco cryptographic products may be
found at:
http://www.cisco.com/wwl/export/crypto/tool/stqrg.html
```

```
copy tftp flash
10.0.0.2
3 c1900-universalk9-mz.SPA.155-3.M4a.bin
```

Physical Config Desktop Programming Attributes Terminal % Ambiguous command: "sh v" R1#sh v R1#sh ve R1#sh version Cisco IOS Software, C1900 Software (C1900-UNIVERSALK9-M), Version 15.5(3)M4a, RELEASE SOFTWARE (fc1) Technical Support: http://www.cisco.com/techsupport Copyright (c) 1986-2016 by Cisco Systems, Inc. Compiled Thu 06-Oct-16 13:56 by mnguyen ROM: System Bootstrap, Version 15.0(1r)M9, RELEASE SOFTWARE (fc1) R1 uptime is 30 seconds System returned to ROM by power-on System image file is "flash0:c1900-universalk9-mz.SPA.155-3.M4a.bin" Last reload type: Normal Reload Last reload reason: Reload Command This product contains cryptographic features and is subject to United States and local country laws governing import, export, transfer and use. Delivery of Cisco cryptographic products does not imply third-party authority to import, export, distribute or use encryption. Importers, exporters, distributors and users are responsible for compliance with U.S. and local country laws. By using this product agree to comply with applicable laws and regulations. If you are to comply with U.S. and local laws, return this product immediately. A summary of U.S. laws governing Cisco cryptographic products may be

Сброс пароля консольной линии

При загрузке нажать control+C, затем:

```
confreg 0x2142.
```

Система загрузится со стандартной конфигурацией. Далее, для того, чтобы восстановить предыдущую конфигурацию, нужно ввести команду:

```
copy startup-config running-config.
```

Теперь можно заменить забытый пароль, и сохранить новый пароль командой

```
copy running-config startup-config.
```