

Pylogeny

API Documentation

December 15, 2014

Contents

Contents	1
1 Package pylogeny	2
1.1 Modules	2
2 Module pylogeny.JSONWriter	3
2.1 Variables	3
2.2 Class JSONWriter	3
2.2.1 Methods	3
2.2.2 Properties	3
3 Module pylogeny.alignment	5
3.1 Variables	5
3.2 Class alignment	5
3.2.1 Methods	5
3.2.2 Properties	7
3.3 Class phylypFriendlyAlignment	7
3.3.1 Methods	8
3.3.2 Properties	9
4 Module pylogeny.base	10
4.1 Variables	10
4.2 Class treeStructure	10
4.2.1 Methods	10
4.2.2 Properties	11
4.2.3 Class Variables	11
4.3 Class treeNode	11
4.3.1 Methods	12
4.3.2 Properties	12
4.3.3 Class Variables	12
4.4 Class treeBranch	13
4.4.1 Methods	13
4.4.2 Properties	13
4.4.3 Class Variables	13
4.5 Class trieNode	14
4.5.1 Methods	14
4.5.2 Properties	15

4.5.3	Class Variables	15
4.6	Class trie	15
4.6.1	Methods	15
4.6.2	Properties	16
4.6.3	Class Variables	17
4.7	Class patriciaTree	17
4.7.1	Methods	17
4.7.2	Properties	18
4.7.3	Class Variables	18
5	Module pylogeny.database	19
5.1	Variables	19
5.2	Class DatabaseLandscape	19
5.2.1	Methods	19
5.2.2	Properties	20
5.2.3	Class Variables	20
5.3	Class SQLExhaustiveLandscape	21
5.3.1	Methods	21
5.3.2	Properties	23
5.3.3	Class Variables	23
5.4	Class SQLiteLandscape	23
5.4.1	Methods	24
5.4.2	Properties	25
5.4.3	Class Variables	25
5.5	Class database	25
5.5.1	Methods	25
5.5.2	Properties	26
5.5.3	Class Variables	26
5.6	Class SQLDatabase	27
5.6.1	Methods	27
5.6.2	Properties	28
5.6.3	Class Variables	28
5.7	Class SQLiteDatabase	28
5.7.1	Methods	28
5.7.2	Properties	29
5.7.3	Class Variables	29
6	Module pylogeny.executable	30
6.1	Functions	30
6.2	Variables	30
6.3	Class aTemporaryDirectory	30
6.3.1	Methods	30
6.3.2	Properties	31
6.4	Class executable	31
6.4.1	Methods	31
6.4.2	Properties	31
6.4.3	Class Variables	32
6.5	Class treepuzzle	32
6.5.1	Methods	32
6.5.2	Properties	32
6.5.3	Class Variables	33
6.6	Class consel	33

6.6.1	Methods	33
6.6.2	Properties	34
6.6.3	Class Variables	34
6.7	Class fasttree	34
6.7.1	Methods	34
6.7.2	Properties	35
6.7.3	Class Variables	35
6.8	Class raxml	35
6.8.1	Methods	35
6.8.2	Properties	36
6.8.3	Class Variables	36
7	Module pylogeny.heuristic	37
7.1	Variables	37
7.2	Class heuristic	37
7.2.1	Methods	37
7.2.2	Properties	38
7.3	Class phylogeneticLinearHeuristic	38
7.3.1	Methods	38
7.3.2	Properties	38
7.3.3	Class Variables	39
7.4	Class parsimonyGreedy	39
7.4.1	Methods	39
7.4.2	Properties	40
7.4.3	Class Variables	40
7.5	Class likelihoodGreedy	40
7.5.1	Methods	40
7.5.2	Properties	41
7.5.3	Class Variables	41
7.6	Class smoothGreedy	41
7.6.1	Methods	42
7.6.2	Properties	42
7.6.3	Class Variables	42
7.7	Class RAxMLIdentify	43
7.7.1	Methods	43
7.7.2	Properties	44
7.7.3	Class Variables	44
8	Module pylogeny.landscape	45
8.1	Variables	45
8.2	Class graph	45
8.2.1	Methods	45
8.2.2	Properties	48
8.3	Class landscape	48
8.3.1	Methods	48
8.3.2	Properties	53
8.3.3	Class Variables	53
8.4	Class vertex	53
8.4.1	Methods	53
8.4.2	Properties	55
9	Module pylogeny.landscapeWriter	56

9.1	Variables	56
9.2	Class landscapeWriter	56
9.2.1	Methods	56
9.2.2	Properties	56
9.3	Class landscapeParser	57
9.3.1	Methods	57
9.3.2	Properties	57
10	Module pylogeny.model	58
10.1	Variables	58
10.2	Class PhyloModelError	58
10.2.1	Methods	58
10.2.2	Properties	59
10.3	Class DiscreteStateModel	59
10.3.1	Methods	59
10.3.2	Properties	60
11	Module pylogeny.newick	61
11.1	Functions	61
11.2	Variables	62
11.3	Class ParsingError	62
11.3.1	Methods	62
11.3.2	Properties	63
11.4	Class node	63
11.4.1	Methods	63
11.4.2	Properties	64
11.4.3	Class Variables	64
11.5	Class branch	64
11.5.1	Methods	64
11.5.2	Properties	65
11.5.3	Class Variables	65
11.6	Class parser	65
11.6.1	Methods	65
12	Module pylogeny.parsimony	66
12.1	Functions	66
12.2	Variables	66
12.3	Class profile_set	66
12.3.1	Methods	66
12.4	Class site_profile	67
12.4.1	Methods	67
13	Module pylogeny.pll	68
13.1	Variables	68
13.2	Class dataModel	68
13.2.1	Methods	68
13.3	Class partitionModel	68
13.3.1	Methods	68
14	Module pylogeny.rearrangement	70
14.1	Functions	70
14.2	Variables	70

14.3 Class RearrangementError	70
14.3.1 Methods	70
14.3.2 Properties	71
14.4 Class rearrangement	71
14.4.1 Methods	71
14.5 Class topology	72
14.5.1 Methods	72
14.5.2 Properties	75
14.5.3 Class Variables	76
15 Module pylogeny.scoring	77
15.1 Functions	77
15.2 Variables	77
16 Module pylogeny.tree	79
16.1 Functions	79
16.2 Variables	79
16.3 Class tree	79
16.3.1 Methods	79
16.3.2 Properties	81
16.4 Class treeSet	81
16.4.1 Methods	81
16.4.2 Properties	82
16.4.3 Class Variables	82
16.5 Class bipartition	83
16.5.1 Methods	83
16.5.2 Properties	84

1 Package pylogeny

Pylogeny is a Python library and code framework for phylogenetic tree reconstruction and scoring.

Allows one to perform the following tasks: (1) Generate and manage phylogenetic tree landscapes. (2) Build and rearrange phylogenetic trees using preset operators such as NNI, SPR, and TBR. (3) Score phylogenetic trees by Log-likelihood and Parsimony.

Dependencies: Pandas, P4 Phylogenetic Library. Suggested: FastTree, RAxML, PytBEAGLEhon.

1.1 Modules

- **JSONWriter**: Serialize a phylogenetic landscape into a JSON object.
(Section 2, p. 3)
- **alignment**: Handle input biological sequence alignment files for the purposes of phylogenetic inference.
(Section 3, p. 5)
- **base**: Definitions for generalized containers and objects used by other structures in this framework.
(Section 4, p. 10)
- **database**: Connect, access, + manipulate external tree data from a remote SQL server or from a sqlite file.
(Section 5, p. 19)
- **executable**: Defines an interface to manage interfacing with the system for respective application calls and implements multiple of these for executables such as FastTree and RAxML.
(Section 6, p. 30)
- **heuristic**: Define the interface for a heuristic in order to implement any manner of heuristic for a combinatorial problem that can be abstracted into a state graph.
(Section 7, p. 37)
- **landscape**: Encapsulate a phylogenetic tree space.
(Section 8, p. 45)
- **landscapeWriter**: Serialize a phylogenetic landscape into an SQLite database file made up of three components: all tree IDs and respective scores, the alignment file as a set of sequences, and a representation of the graph as an edge list.
(Section 9, p. 56)
- **model**: Phylogenetic tree scoring models; intended to be coupled with the use of pytbeaglehon (BEAGLE) high-performance library.
(Section 10, p. 58)
- **newick**: Newick string parsing and object interaction.
(Section 11, p. 61)
- **parsimony**: Toolkit for performance of Parsimonious Criterion (Parsimony) methods of optimization of a phylogenetic topology with a particular set of data.
(Section 12, p. 66)
- **pll**: C Extension to wrap libpll library.
(Section 13, p. 68)
- **rearrangement**: Phylogenetic tree structure encapsulation; allow rearrangement of said structure.
(Section 14, p. 70)
- **scoring**: Phylogenetic tree scoring.
(Section 15, p. 77)
- **tree**: Container definition for (phylogenetic) bifurcating or multifurcating trees defined using Newick strings, collections of them, and for splits of these trees.
(Section 16, p. 79)


2 Module *pylogeny.JSONWriter*

Serialize a phylogenetic landscape into a JSON object.

2.1 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

2.2 Class *JSONWriter*



2.2.1 Methods

`__init__(self, ls, name)`

x.`__init__`(...) initializes x; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

`nodeToJSON(self, node)`

`getOnlyImprovements(self, groups=None)`

`getCompleteLandscape(self)`

`getJSON(self)`

Inherited from `pylogeny.landscapeWriter.landscapeWriter` (Section 9.2)

`writeFile()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

2.2.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

3 Module pylogeny.alignment

Handle input biological sequence alignment files for the purposes of phylogenetic inference. Will read all types of alignment files by utilizing the P4 python phylogenetic library.

3.1 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

3.2 Class alignment

object └─
 pylogeny.alignment.alignment

Known Subclasses: pylogeny.alignment.phylipFriendlyAlignment

Wrap a biological sequence alignment to enable functionality necessary for phylogenetic inference. Makes use of temporary files; requires to be closed once no longer needed.

3.2.1 Methods

<code>__init__</code> (<i>self</i> , <i>inal=None</i>) <hr/> Instantiate an object intended to wrap an alignment for the purposes of running phylogenetic inference. :param inal: An alignment file path (most formats are accepted). Overrides: object. <code>__init__</code>
<code>__getitem__</code> (<i>self</i> , <i>i</i>)
<code>__str__</code> (<i>self</i>) <hr/> <code>str(x)</code> Overrides: object. <code>__str__</code> extit(inherited documentation)
<code>__len__</code> (<i>self</i>)

__iter__ (<i>self</i>)
close (<i>self</i>) Delete all temporary files and clear data.
toStrList (<i>self</i>) Get all sequences as a list of strings.
getStateModel (<i>self</i>)
getSize (<i>self</i>) Return the size of the alignment, or how many characters there are in each respective item in the alignment.
getNumSeqs (<i>self</i>) Return the number of sequences that are present in the sequence alignment.
getDim (<i>self</i>) Return the dimensionality of the sequence alignment (how many different types of characters).
getSequence (<i>self</i> , <i>i</i>) Acquire the <i>i</i> th sequence.
getFASTA (<i>self</i>) Get (and create if not already) a path to a temporary FASTA file. This will be deleted upon closure of the alignment instance.
getApproxMLNewick (<i>self</i>) Get a tree in newick format via use of FastTree that serves as an approximation of the maximum likelihood tree for this data.
getApproxMLTree (<i>self</i>) Get a tree object for an approximation of the maximum likelihood tree for this data using FastTree.

getTaxa (<i>self</i>)

Return taxa names.

getAlignment (<i>self</i>)

Acquire the alignment data structure (P4 module).

bootstrap (<i>self</i>)

Perform bootstrapping on the alignment data.
--

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()
```

3.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

3.3 Class *phylipFriendlyAlignment*

object └

pylogeny.alignment.alignment └

pylogeny.alignment.phylipFriendlyAlignment

An alignment object that renames all comprising taxa in order to be able to be written as a Phylip file.

3.3.1 Methods

__init__(*self*, *inal*=None)

Instantiate an object intended to wrap an alignment for the purposes of running phylogenetic inference.

:param *inal*: An alignment file path (most formats are accepted).

Overrides: object.__init__ *exitit*(inherited documentation)

getPhylip(*self*)

Get a path to a temporary Phylip file. This will be deleted upon closure of the alignment instance.

writeProperNexus(*self*, *wri*)

Write a Nexus file with proper names.

reassignFromReinterpretedNewick(*self*, *tr*)

Replace all proper names with reassigned names in a Newick tree.

reinterpretNewick(*self*, *tr*)

Replaces all reassigned names to proper names in a Newick tree.

getProperName(*self*, *n*)

Return the actual name for an integer-based sequence name that was reassigned at initialization.

getTaxa(*self*)

Return current taxa names in the alignment.

Overrides: *pylogeny.alignment.alignment.getTaxa*

recreateObject(*self*)

Reintializes the object.

*Inherited from **pylogeny.alignment.alignment**(Section 3.2)*

__getitem__(), *__iter__*(), *__len__*(), *__str__*(), *bootstrap*(), *close*(), *getAlignment*(), *getApproxMLNewick*(), *getApproxMLTree*(), *getDim*(), *getFASTA*(), *getNumSeqs*(), *getSequence*(), *getSize*(), *getStateModel*(), *toStrList*()

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),  
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),  
__subclasshook__()
```

3.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

4 Module *pylogeny.base*

Definitions for generalized containers and objects used by other structures in this framework.

4.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'pylogeny'</code>

4.2 Class *treeStructure*



Known Subclasses: *pylogeny.base.trie*, *pylogeny.rearrangement.topology*

Defines a base collection of *treeNodes* and *treeBranches* in a hierarchical tree structure.

4.2.1 Methods

`__init__`(*self*, *root*=None)

x.**`__init__`**(...) initializes *x*; see `help(type(x))` for signature

Overrides: *object*.**`__init__`** *exitit*(inherited documentation)

`__contains__`(*self*, *x*)

Overrides: *_abcoll.Container*.**`__contains__`**

`getRoot`(*self*)

Return the top-level, root, node of the tree.

`leaves`(*root*)

`getAllLeaves`(*self*)

`nodes`(*root*)

<code>getAllNodes(<i>self</i>)</code>

<code>postOrderTraversal(<i>root</i>)</code>
--

<code>getPostOrderTraversal(<i>self</i>)</code>

<code>__str__(<i>self</i>)</code>

Returns a string representation of the tree.
--

Overrides: object.__str__

Inherited from *__abcoll.Container*

<code>__subclasshook__()</code>

Inherited from object

<code>__delattr__()</code> , <code>__format__()</code> , <code>__getattr__()</code> , <code>__hash__()</code> , <code>__new__()</code> , <code>__reduce__()</code> , <code>__reduce_ex__()</code> , <code>__repr__()</code> , <code>__setattr__()</code> , <code>__sizeof__()</code>

4.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

4.2.3 Class Variables

Name	Description
<code>root</code>	Value: None
<code>__abstractmethods__</code>	Value: frozenset([])

4.3 Class *treeNode*

```

object └─
          pylogeny.base.treeNode

```

Known Subclasses: *pylogeny.base.trieNode*, *pylogeny.newick.node*

A node in a tree.

4.3.1 Methods

__init__(*self*, *lbl*=None, *children*=None, *parent*=None)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

getLabel(*self*)

getParent(*self*)

addChild(*self*, *item*)

getChildByIndex(*self*, *i*)

getChildren(*self*)

isLeaf(*self*)

isInternalNode(*self*)

Inherited from object

`__delattr__`(), `__format__`(), `__getattr__`(), `__hash__`(), `__new__`(),
`__reduce__`(), `__reduce_ex__`(), `__repr__`(), `__setattr__`(), `__sizeof__`(),
`__str__`(), `__subclasshook__`()

4.3.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

4.3.3 Class Variables

Name	Description
<code>label</code>	Value: None
<code>parent</code>	Value: None
<code>children</code>	Value: None

4.4 Class *treeBranch*



Known Subclasses: *pylogeny.newick.branch*

A branch in a tree.

4.4.1 Methods

```
__init__(self, parent=None, child=None, label='')
```

`x.__init__(...)` initializes `x`; see `help(type(x))` for signature

Overrides: `object.__init__` `__init__` (inherited documentation)

```
getLabel(self)
```

```
getParent(self)
```

```
getChild(self)
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```


4.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

4.4.3 Class Variables

Name	Description
<code>label</code>	Value: <code>''</code>
<code>parent</code>	Value: <code>None</code>
<code>child</code>	Value: <code>None</code>

4.5 Class `trieNode`



A subclass of `treeNode` that allows for checking non-zero members amongst children branches and other conveniences.

4.5.1 Methods

<code>getParentNode(self)</code>

<code>setChildNode(self, child, newchild)</code>

<code>iterNonEmptyChildrenNodes(self)</code>

Iterate over all children that are not empty.

<code>getNonEmptyChildrenNodes(self)</code>
--

Acquire a list of all non-empty children.

<code>getNonEmptyChildrenBranches(self)</code>

Acquire a list of all non-empty children.

<code>getNonEmptyChildrenBranchLabels(self)</code>

<code>numEmptyChildrenNodes(self)</code>

Acquire the number of children nodes that are marked 0 or nonexistent.
--

Inherited from `pylogeny.base.treeNode` (Section 4.3)

`__init__()`, `addChild()`, `getChildByIndex()`, `getChildren()`, `getLabel()`, `getParent()`, `isInternalNode()`, `isLeaf()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`


4.5.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

4.5.3 Class Variables

Name	Description
<i>Inherited from pylogeny.base.treeNode (Section 4.3)</i> children, label, parent	

4.6 Class trie



Known Subclasses: `pylogeny.base.patriciaTree`

Defines a trie across a range of strings.

4.6.1 Methods

__init__(self) x.__init__(...) initializes x; see help(type(x)) for signature Overrides: object.__init__ extit(inherited documentation)
__contains__(self, x) Implementing for interface (Container). Overrides: _abcoll.Container.__contains__

<code>__len__(self)</code>
Implementing for interface (Sized).
Overrides: <code>__abcoll.Sized.__len__</code>

<code>getAlphabet(self)</code>

<code>getRoot(self)</code>
Return the top-level, root, node of the tree.
Overrides: <code>pylogeny.base.treeStructure.getRoot</code> <code>exitit</code> (inherited documentation)

<code>search(self, seq)</code>
Search for a sequence in the trie. Returns true if it exists.

<code>insert(self, seq)</code>
Dynamically insert a sequence into the trie.

<code>delete(self, seq)</code>
Remove a sequence from the trie. Will not remove added characters to alphabet.

Inherited from `__abcoll.Sized`

`__subclasshook__()`

Inherited from `pylogeny.base.treeStructure`(Section 4.2)

`__str__()`, `getAllLeaves()`, `getAllNodes()`, `getPostOrderTraversal()`, `leaves()`, `nodes()`, `postOrderTraversal()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`


4.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

4.6.3 Class Variables

Name	Description
alphabet	Value: None
root	Value: None
count	Value: 0
nextLabel	Value: 1
__abstractmethods__	Value: frozenset([])

4.7 Class *patriciaTree*



Defines a PATRICIA tree (condensed trie) across a range of strings.

4.7.1 Methods

__contains__(*self*, *x*)

Implementing for interface (Container).

Overrides: `_abcoll.Container.__contains__`

search(*self*, *seq*)

Search for a sequence in the PATRICIA tree. Returns its position in addition sequence if it exists. Else, returns 0.

Overrides: `pylogeny.base.trie.search`

insert (<i>self</i> , <i>seq</i>)
--

Dynamically insert a sequence into the PATRICIA tree. Returns the unique index in the tree for that string.

Overrides: <i>pylogeny.base.trie.insert</i>

delete (<i>self</i> , <i>seq</i>)
--

Remove a sequence from the PATRICIA tree. Will not remove added characters to alphabet.

Overrides: <i>pylogeny.base.trie.delete</i>

Inherited from *pylogeny.base.trie* (Section 4.6)

`__init__()`, `__len__()`, `getAlphabet()`, `getRoot()`

Inherited from *__abcoll.Sized*

`__subclasshook__()`

Inherited from *pylogeny.base.treeStructure* (Section 4.2)

`__str__()`, `getAllLeaves()`, `getAllNodes()`, `getPostOrderTraversal()`, `leaves()`, `nodes()`, `postOrderTraversal()`

Inherited from *object*

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`

4.7.2 Properties

Name	Description
<i>Inherited from <i>object</i></i>	
<code>__class__</code>	

4.7.3 Class Variables

Name	Description
<i>Inherited from <i>pylogeny.base.trie</i> (Section 4.6)</i>	
<code>__abstractmethods__</code> , <code>alphabet</code> , <code>count</code> , <code>nextLabel</code> , <code>root</code>	


5 Module pylogeny.database

Connect, access, + manipulate external tree data from a remote SQL server or from a sqlite file.

5.1 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

5.2 Class DatabaseLandscape



Known Subclasses: `pylogeny.database.SQLExhaustiveLandscape`

Abstract the landscape to one comprising a landscape.

5.2.1 Methods

getNode (<i>self</i> , <i>i</i>) Overrides: <code>pylogeny.landscape.graph.getNode</code>

Inherited from `pylogeny.landscape.landscape` (Section 8.3)

__getitem__(), __init__(), __iter__(), __str__(), addTree(), exploreRandomTree(), exploreTree(), findTree(), findTreeTopology(), findTreeTopologyByStructure(), getAlignment(), getAllPathsOfBestImprovement(), getBestImprovement(), getBipartitionFoundInTreeByIndex(), getGlobalOptimum(), getLocalOptima(), getLocks(), getNumberTaxa(), getPathOfBestImprovement(), getPossibleNumberRootedTrees(), getPossibleNumberUnrootedTrees(), getRootTree(), getTree(), getVertex(), indexOf(), isLocalOptimum(), isViolating(), iterAllPathsOfBestImprovement(), iterTrees(), lockBranchFoundInTree(), lockBranchFoundInTreeByIndex(), removeTree(), setAlignment(), toProperNewickTreeSet(), toTreeSet(), toggleLock()

Inherited from pylogeny.landscape.graph(Section 8.2)

__len__(), clearEdgeWeights(), getCenter(), getCliqueNumber(), getCliques(), getCliquesOfNode(), getComponentOfNode(), getComponents(), getDegreeFor(), getDiameter(), getEdge(), getEdges(), getEdgesFor(), getMST(), getNeighborsFor(), getNetworkXObject(), getNodeNames(), getNodes(), getNumCliques(), getNumComponents(), getShortestPath(), getShortestPathLength(), getSize(), hasPath(), iterNodes(), setDefaultWeight()

Inherited from pylogeny.tree.treeSet(Section 16.4)

addTreeByNewick(), toTreeFile()

Inherited from __abcoll.Sized

__subclasshook__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__()


5.2.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

5.2.3 Class Variables

Name	Description
__abstractmethods__	Value: frozenset(['_fetchRearrangementsFromDatabase', '_fetchTre...'])

5.3 Class *SQLExhaustiveLandscape*



5.3.1 Methods

__init__(*self*, *dbobj*, *aliname*)

Initialize the landscape.

:param ali: An :class:'alignment.alignment' object. :param starting__tree: An optional tree object to start the landscape with. :param root: Whether or not to acquire an approximate maximum likelihood tree (FastTree) or start the landscape with a given starting tree. :param operator: A string that describes what operator the landscape is mostly comprised of.

Overrides: *object.__init__* extit(inherited documentation)

exploreRandomTree(*self*, *i*)

Acquire a single neighbor to a tree in the landscape by performing a random rearrangement of type SPR (by default), NNI, or TBR. Rearrangement type is provided as a rearrangement module type definition of form, for example, TYPE_SPR, TYPE_NNI, etc.

Overrides: *pylogeny.landscape.landscape.exploreRandomTree* extit(inherited documentation)

getDatabaseNode (<i>self</i> , <i>i</i>)

exploreTree (<i>self</i> , <i>i</i>)

<p>Get all neighbors to a tree named <i>i</i> in the landscape using a respective rearrangement operator as defined in the rearrangement module.</p> <p>Rearrangement type is provided as a rearrangement module type definition of form, for example, TYPE_SPR, TYPE_NNI, etc. By default, this is TYPE_SPR.</p>

<p>Overrides: <i>pylogeny.landscape.landscape.exploreTree</i> extit(inherited documentation)</p>
--

Inherited from *pylogeny.database.DatabaseLandscape*(Section 5.2)

getNode()

Inherited from *pylogeny.landscape.landscape*(Section 8.3)

__getitem__(), *__iter__*(), *__str__*(), *addTree*(), *findTree*(), *findTreeTopology*(), *findTreeTopologyByStructure*(), *getAlignment*(), *getAllPathsOfBestImprovement*(), *getBestImprovement*(), *getBipartitionFoundInTreeByIndex*(), *getGlobalOptimum*(), *getLocalOptima*(), *getLocks*(), *getNumberTaxa*(), *getPathOfBestImprovement*(), *getPossibleNumberRootedTrees*(), *getPossibleNumberUnrootedTrees*(), *getRootTree*(), *getTree*(), *getVertex*(), *indexOf*(), *isLocalOptimum*(), *isViolating*(), *iterAllPathsOfBestImprovement*(), *iterTrees*(), *lockBranchFoundInTree*(), *lockBranchFoundInTreeByIndex*(), *removeTree*(), *setAlignment*(), *toProperNewickTreeSet*(), *toTreeSet*(), *toggleLock*()

Inherited from *pylogeny.landscape.graph*(Section 8.2)

__len__(), *clearEdgeWeights*(), *getCenter*(), *getCliqueNumber*(), *getCliques*(), *getCliquesOfNode*(), *getComponentOfNode*(), *getComponents*(), *getDegreeFor*(), *getDiameter*(), *getEdge*(), *getEdges*(), *getEdgesFor*(), *getMST*(), *getNeighborsFor*(), *getNetworkXObject*(), *getNodeNames*(), *getNodes*(), *getNumCliques*(), *getNumComponents*(), *getShortestPath*(), *getShortestPathLength*(), *getSize*(), *hasPath*(), *iterNodes*(), *setDefaultWeight*()

Inherited from *pylogeny.tree.treeSet*(Section 16.4)

addTreeByNewick(), *toTreeFile*()

Inherited from *__abcoll.Sized*

__subclasshook__()

Inherited from *object*

__delattr__(), *__format__*(), *__getattr__*(), *__hash__*(), *__new__*(),

`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`


5.3.2 Properties

Name	Description
<code>__class__</code>	<i>Inherited from object</i>

5.3.3 Class Variables

Name	Description
<code>__abstractmethods__</code>	Value: <code>frozenset([])</code>

5.4 Class *SQLiteLandscape*



Allow random access of all landscape data from an sqlite file found on the hard disk.

5.4.1 Methods

__init__(*self*, *dbobj*)

Initialize the landscape.

:param *ali*: An :class:'alignment.alignment' object. :param *starting_tree*: An optional tree object to start the landscape with. :param *root*: Whether or not to acquire an approximate maximum likelihood tree (FastTree) or start the landscape with a given starting tree. :param *operator*: A string that describes what operator the landscape is mostly comprised of.

Overrides: object.__init__ *exitit*(inherited documentation)

Inherited from pylogeny.landscape.landscape(Section 8.3)

__getitem__(), *__iter__*(), *__str__*(), *addTree*(), *exploreRandomTree*(), *exploreTree*(), *findTree*(), *findTreeTopology*(), *findTreeTopologyByStructure*(), *getAlignment*(), *getAllPathsOfBestImprovement*(), *getBestImprovement*(), *getBipartitionFoundInTreeByIndex*(), *getGlobalOptimum*(), *getLocalOptima*(), *getLocks*(), *getNumberTaxa*(), *getPathOfBestImprovement*(), *getPossibleNumberRootedTrees*(), *getPossibleNumberUnrootedTrees*(), *getRootTree*(), *getTree*(), *getVertex*(), *indexOf*(), *isLocalOptimum*(), *isViolating*(), *iterAllPathsOfBestImprovement*(), *iterTrees*(), *lockBranchFoundInTree*(), *lockBranchFoundInTreeByIndex*(), *removeTree*(), *setAlignment*(), *toProperNewickTreeSet*(), *toTreeSet*(), *toggleLock*()

Inherited from pylogeny.landscape.graph(Section 8.2)

__len__(), *clearEdgeWeights*(), *getCenter*(), *getCliqueNumber*(), *getCliques*(), *getCliquesOfNode*(), *getComponentOfNode*(), *getComponents*(), *getDegreeFor*(), *getDiameter*(), *getEdge*(), *getEdges*(), *getEdgesFor*(), *getMST*(), *getNeighborsFor*(), *getNetworkXObject*(), *getNode*(), *getNodeNames*(), *getNodes*(), *getNumCliques*(), *getNumComponents*(), *getShortestPath*(), *getShortestPathLength*(), *getSize*(), *hasPath*(), *iterNodes*(), *setDefaultWeight*()

Inherited from pylogeny.tree.treeSet(Section 16.4)

addTreeByNewick(), *toTreeFile*()

Inherited from __abcoll.Sized

__subclasshook__()

Inherited from object

__delattr__(), *__format__*(), *__getattr__*(), *__hash__*(), *__new__*(), *__reduce__*(), *__reduce_ex__*(), *__repr__*(), *__setattr__*(), *__sizeof__*()

5.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

5.4.3 Class Variables

Name	Description
<i>Inherited from pylogeny.tree.treeSet (Section 16.4)</i> __abstractmethods__	

5.5 Class database

object —
 pylogeny.database.database

Known Subclasses: *pylogeny.database.SQLDatabase*, *pylogeny.database.SQLiteDatabase*

Allow interfacing with a SQL/sqlite database.

5.5.1 Methods

isEmpty (<i>self</i>)
Determine if the database is empty.
getTables (<i>self</i>)
Get the list of tables from the database
getColumns (<i>self</i> , <i>table</i>)
Return column information for a given table.
getHeaders (<i>self</i> , <i>table</i>)
Get only header names for a given table's columns.
getRecordsColumn (<i>self</i> , <i>table</i> , <i>col</i>)
Get all data for a single colmun from records for a table.

getRecords (<i>self</i> , <i>table</i>)
--

Get all records from a given table in the database.

iterRecords (<i>self</i> , <i>table</i>)

Get a record, one at a time, from a table in the database.
--

filterRecords (<i>self</i> , <i>table</i> , <i>condn</i>)
--

Get all records from a given table following a condition.

getRecordsAsDict (<i>self</i> , <i>table</i>)
--

Acquires records using getRecords() and then leverages access using a dictionary data structure.
--

newTable (<i>self</i> , <i>tablename</i> , <i>**kwargs</i>)
--

insertRecords (<i>self</i> , <i>tablename</i> , <i>items</i>)
--

insertRecord (<i>self</i> , <i>tablename</i> , <i>record</i>)
--

query (<i>self</i> , <i>q</i>)

querymany (<i>self</i> , <i>q</i> , <i>i</i>)
--

close (<i>self</i>)

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __init__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()
--


5.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

5.5.3 Class Variables

Name	Description
<code>cursor</code>	Value: None
<code>__abstractmethods__</code>	Value: frozenset(['close', 'query', 'querymany'])

5.6 Class *SQLDatabase*



Database object to allow reading from a MySQL database.

5.6.1 Methods

__init__(*self*, *host*, *user*, *pw*, *db*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

connect(*self*)

query(*self*, *q*)

Overrides: `pylogeny.database.database.query`

querymany(*self*, *q*, *i*)

Overrides: `pylogeny.database.database.querymany`

close(*self*)

Overrides: `pylogeny.database.database.close`

Inherited from `pylogeny.database.database` (Section 5.5)

`filterRecords()`, `getColumnns()`, `getHeaders()`, `getRecords()`, `getRecordsAsDict()`,
`getRecordsColumn()`, `getTables()`, `insertRecord()`, `insertRecords()`, `isEmpty()`, `iter-`
`Records()`, `newTable()`

Inherited from `object`

```

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

```


5.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

5.6.3 Class Variables

Name	Description
<code>__abstractmethods__</code>	Value: <code>frozenset([])</code>
<i>Inherited from pylogeny.database.database (Section 5.5)</i>	
<code>cursor</code>	

5.7 Class `SQLiteDatabase`



5.7.1 Methods

<code>__init__(self, filepath)</code> x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exit</code> (inherited documentation)
<code>getColumns(self, table)</code> Return column information for a given table. Overrides: <code>pylogeny.database.database.getColumns</code>
<code>query(self, q)</code> Overrides: <code>pylogeny.database.database.query</code>

querymany (<i>self</i> , <i>q</i> , <i>i</i>)
--

Overrides: <i>pylogeny.database.database.querymany</i>
--

close (<i>self</i>)

Overrides: <i>pylogeny.database.database.close</i>
--

Inherited from *pylogeny.database.database* (Section 5.5)

filterRecords(), *getHeaders()*, *getRecords()*, *getRecordsAsDict()*, *getRecordsColumn()*, *getTables()*, *insertRecord()*, *insertRecords()*, *isEmpty()*, *iterRecords()*, *newTable()*

Inherited from object

__delattr__(), *__format__()*, *__getattr__()*, *__hash__()*, *__new__()*, *__reduce__()*, *__reduce_ex__()*, *__repr__()*, *__setattr__()*, *__sizeof__()*, *__str__()*, *__subclasshook__()*

5.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<i>__class__</i>	

5.7.3 Class Variables

Name	Description
<i>__abstractmethods__</i>	Value: <i>frozenset([])</i>
<i>Inherited from <i>pylogeny.database.database</i> (Section 5.5)</i>	
<i>cursor</i>	

6 Module *pylogeny.executable*

Defines an interface to manage interfacing with the system for respective application calls and implements multiple of these for executables such as FastTree and RAxML. Requires a UNIX environment.

6.1 Functions

exeExists (<i>cmd</i>)

Determines whether a function exists in a UNIX environment.

6.2 Variables

Name	Description
E_FASTTREE	Value: 'fasttree'
E_RAXML	Value: 'raxmlHPC'
E_TREPUZZ	Value: 'puzzle'
__package__	Value: 'pylogeny'

6.3 Class *aTemporaryDirectory*

object —
pylogeny.executable.aTemporaryDirectory

A class intended to be used as a context manager that allows Python to run in a temporary directory for a finite period of time.

6.3.1 Methods

__init__ (<i>self</i> , <i>dir</i> =None)

x. __init__ (...) initializes x; see help(type(x)) for signature

Overrides: object. __init__ exit (inherited documentation)
--

__enter__ (<i>self</i>)

__exit__ (<i>self</i> , * <i>args</i>)

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

6.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6.4 Class executable

```
object └─ pylogeny.executable.executable
```

Known Subclasses: pylogeny.executable.consel, pylogeny.executable.fasttree, pylogeny.executable.raxml, pylogeny.executable.treepuzzle

An interface for the instantiation and running of a single instance for a given application.

6.4.1 Methods

<code>getInstructionString(self)</code>
<code>run(self)</code>
Perform a run of this application.

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __init__(),
__new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(),
__sizeof__(), __str__(), __subclasshook__()
```

6.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6.4.3 Class Variables

Name	Description
exeName	Value: None
__abstractmethods__	Value: frozenset(['getInstructionString'])

6.5 Class treepuzzle

object └─

pylogeny.executable.executable └─
pylogeny.executable.treepuzzle

Wrap TREE-PUZZLE in order to create an intermediate file for CONSEL to read and assign confidence to a set of trees. Requires TREE-PUZZLE to be installed.

6.5.1 Methods

```
__init__(self, ali, treefile)
```

x.__init__(...) initializes x; see help(type(x)) for signature

Overrides: object.__init__ extit(inherited documentation)

```
getInstructionString(self)
```

Overrides: pylogeny.executable.executable.getInstructionString

```
getSiteLikelihoodFile(self)
```

Inherited from pylogeny.executable.executable(Section 6.4)

```
run()
```

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```


6.5.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6.5.3 Class Variables

Name	Description
<code>exeName</code>	Value: 'puzzle'
<code>__abstractmethods__</code>	Value: frozenset([])

6.6 Class *consel*



Denotes a single run of the CONSEL workflow in order to acquire a confidence interval and perform an AU test on a set of trees. Requires CONSEL to be installed.

6.6.1 Methods

<code>__init__(self, treeset, alignment, name)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature
Overrides: <code>object.__init__</code> <code>extit</code> (inherited documentation)

<code>getInstructionString(self)</code>
Overrides: <code>pylogeny.executable.executable.getInstructionString</code>

<code>getInterval(self)</code>
Compute the AU test. Return the interval of trees.

Inherited from `pylogeny.executable.executable` (Section 6.4)

`run()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,

`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

6.6.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6.6.3 Class Variables

Name	Description
<code>__abstractmethods__</code>	Value: <code>frozenset([])</code>
<i>Inherited from pylogeny.executable.executable (Section 6.4)</i>	
<code>exeName</code>	

6.7 Class *fasttree*

object └

pylogeny.executable.executable └
pylogeny.executable.fasttree

Denotes a single run of the FastTree executable in order to acquire an approximate maximum likelihood tree for the input alignment. See <http://www.microbesonline.org/fasttree/> for more information on FastTree. Requires FastTree to be installed.

6.7.1 Methods

<code>__init__(self, inp_align, out_file=None, isProtein=True)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature
Overrides: object. <code>__init__</code> <code>exitit</code> (inherited documentation)
 <code>getInstructionString(self)</code>
Overrides: <code>pylogeny.executable.executable.getInstructionString</code>

Inherited from pylogeny.executable.executable (Section 6.4)

`run()`

Inherited from object


```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

6.7.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6.7.3 Class Variables

Name	Description
<code>exeName</code>	Value: 'fasttree'
<code>__abstractmethods__</code>	Value: frozenset([])

6.8 Class raxml

Denotes a single run of the RAxML executable. See <http://sco.h-its.org/exelixis/software.html> for more information on RAxML. Requires RAxML to be installed.

6.8.1 Methods

<code>__init__</code> (<i>self</i> , <i>inp_align</i> , <i>out_file</i> , <i>model=None</i> , <i>is_Protein=True</i> , <i>interTrees=False</i> , <i>alg=None</i> , <i>startingTree=None</i> , <i>rapid=False</i> , <i>slow=False</i> , <i>optimizeBootstrap=False</i> , <i>numboot=100</i> , <i>log=None</i> , <i>wdir=None</i>) <i>x</i> . <code>__init__</code> (...) initializes <i>x</i> ; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)
<code>getInstructionString</code> (<i>self</i>) Overrides: <code>pylogeny.executable.executable.getInstructionString</code>

runFunction (<i>self</i> , <i>alg</i>)

Inherited from pylogeny.executable.executable(Section 6.4)

run()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
 __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
 __str__(), __subclasshook__()

6.8.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

6.8.3 Class Variables

Name	Description
exeName	Value: 'raxmlHPC'
__abstractmethods__	Value: frozenset([])

7 Module *pylogeny.heuristic*

Define the interface for a heuristic in order to implement any manner of heuristic for a combinatorial problem that can be abstracted into a state graph. In this case, a phylogenetic tree space.

7.1 Variables

Name	Description
SMGR_MIN_NUM_LIKELIHOOD	Value: 32
__package__	Value: 'pylogeny'

7.2 Class *heuristic*

object —
 pylogeny.heuristic.heuristic

Known Subclasses: *pylogeny.heuristic.phylogeneticLinearHeuristic*

A base interface for a heuristic that explores a state graph.

7.2.1 Methods

__init__(*self*, *G*=None, *start*=None)

x.**__init__**(...) initializes x; see help(type(x)) for signature

Overrides: object.**__init__** **exitit**(inherited documentation)

explore(*self*)

getStateGraph(*self*)

getStartState(*self*)


Inherited from object

__delattr__(), **__format__**(), **__getattr__**(), **__hash__**(), **__new__**(),
__reduce__(), **__reduce_ex__**(), **__repr__**(), **__setattr__**(), **__sizeof__**(),
__str__(), **__subclasshook__**()

7.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

7.3 Class *phylogeneticLinearHeuristic*



Known Subclasses: *pylogeny.heuristic.RAxMLIdentify*, *pylogeny.heuristic.likelihoodGreedy*, *pylogeny.heuristic.parsimonyGreedy*, *pylogeny.heuristic.smoothGreedy*

A base class for a heuristic that works on a phylogenetic landscape and only possesses a single path (of search).

7.3.1 Methods

`__init__(self, ls, startTree)`

`x.__init__(...)` initializes x; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

`getPath(self)`

`getBestTree(self)`

Inherited from `pylogeny.heuristic.heuristic` (Section 7.2)

`explore()`, `getStartState()`, `getStateGraph()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`


7.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

7.3.3 Class Variables

Name	Description
bestTree	Value: None
path	Value: []

7.4 Class *parsimonyGreedy*



Greedy (hill-climbing) landscape exploration by comparsion of parsimony.

7.4.1 Methods

__init__ (<i>self</i> , <i>ls</i> , <i>startTree</i>)
x. __init__ (...) initializes x; see help(type(x)) for signature
Overrides: object. __init__ extit(inherited documentation)

explore (<i>self</i>)
Perform greedy search of the landscape using a method of greed via parsimonious criterion.
Overrides: pylogeny.heuristic.heuristic.explore

Inherited from pylogeny.heuristic.phylogeneticLinearHeuristic(Section 7.3)

getBestTree(), getPath()

Inherited from pylogeny.heuristic.heuristic(Section 7.2)

getStartState(), getStateGraph()

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

7.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

7.4.3 Class Variables

Name	Description
<i>Inherited from <code>pylogeny.heuristic.phylogeneticLinearHeuristic</code> (Section 7.3)</i>	
<code>bestTree</code> , <code>path</code>	

7.5 Class `likelihoodGreedy`

```

object └─
pylogeny.heuristic.heuristic └─
pylogeny.heuristic.phylogeneticLinearHeuristic └─
                                                    pylogeny.heuristic.likelihoodGreedy
```

Greedy (hill-climbing) landscape exploration by comparsion of likelihood.

7.5.1 Methods

<code>__init__</code> (<i>self</i> , <i>ls</i> , <i>startTree</i>)
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature
Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>explore</code> (<i>self</i>)
Perform greedy search of the landscape using a method of greed via likelihood.
Overrides: <code>pylogeny.heuristic.heuristic.explore</code>

Inherited from pylogeny.heuristic.phylogeneticLinearHeuristic (Section 7.3)

getBestTree(), getPath()

Inherited from pylogeny.heuristic.heuristic (Section 7.2)

getStartState(), getStateGraph()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

7.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

7.5.3 Class Variables

Name	Description
<i>Inherited from pylogeny.heuristic.phylogeneticLinearHeuristic (Section 7.3)</i>	
bestTree, path	

7.6 Class smoothGreedy

object └

pylogeny.heuristic.heuristic └

pylogeny.heuristic.phylogeneticLinearHeuristic └
pylogeny.heuristic.smoothGreedy

Parsimony-driven greedy landscape exploration by comparsion of likelihoods.

7.6.1 Methods

__init__(*self*, *ls*, *startTree*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

explore(*self*)

Perform greedy search of the landscape using a method of greed via parsimonious criterion and then performing final smoothing via likelihood on top 10% of 1-SPR neighbors ranked on basis of parsimony.

Overrides: `pylogeny.heuristic.heuristic.explore`

Inherited from `pylogeny.heuristic.phylogeneticLinearHeuristic` (Section 7.3)

`getBestTree()`, `getPath()`

Inherited from `pylogeny.heuristic.heuristic` (Section 7.2)

`getStartState()`, `getStateGraph()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`


7.6.2 Properties

Name	Description
<i>Inherited from <code>object</code></i>	
<code>__class__</code>	

7.6.3 Class Variables

Name	Description
<i>Inherited from <code>pylogeny.heuristic.phylogeneticLinearHeuristic</code> (Section 7.3)</i>	
<code>bestTree</code> , <code>path</code>	

7.7 Class RAxMLIdentify



RAxML-driven landscape evaluation of intermediate checkpoint trees output from the RAxML executable.

7.7.1 Methods

```
__init__(self, ls, startNode, workdir='.rxml')
```

x.**__init__**(...) initializes x; see help(type(x)) for signature

Overrides: object.**__init__** extit(inherited documentation)

```
__setupWorkDir__(self)
```

```
__setupExecutable__(self)
```

```
__readLogFile__(self)
```

```
__readIterTrees__(self, iters)
```

```
explore(self)
```

Overrides: pylogeny.heuristic.heuristic.explore

Inherited from pylogeny.heuristic.phylogeneticLinearHeuristic (Section 7.3)

getBestTree(), getPath()

Inherited from pylogeny.heuristic.heuristic (Section 7.2)

getStartState(), getStateGraph()

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),  
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),  
__str__(), __subclasshook__()
```

7.7.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

7.7.3 Class Variables

Name	Description
<i>Inherited from pylogeny.heuristic.phylogeneticLinearHeuristic (Section 7.3)</i> bestTree, path	

8 Module *pylogeny.landscape*

Encapsulate a phylogenetic tree space. A phylogenetic landscape or tree space refers to the entire combinatorial space comprising all possible phylogenetic tree topologies for a set of n taxa. The landscape of n taxa can be defined as consisting of a finite set T of tree topologies. Tree topologies can be associated with a fitness function $f(t_i)$ describing their fit. This forms a discrete solution search space and finite graph $(T, E) = G$. $E(G)$ refers to the neighborhood relation on $T(G)$. Edges in this graph are bidirectional and represent transformation from one tree topology to another by a tree rearrangement operator. An edge between t_i and t_j would be notated as e_{ij} in $E(G)$.

8.1 Variables

Name	Description
LS_NOT_DEFINED	Value: -1
__package__	Value: 'pylogeny'

8.2 Class graph

object —
pylogeny.landscape.graph

Known Subclasses: *pylogeny.landscape.landscape*

Define an empty graph object.

8.2.1 Methods

__init__ (<i>self</i> , <i>gr</i> =None)
Instantiate a graph.
:param <i>gr</i> : A networkx graph object, if already exists.
Overrides: object.__init__
getNetworkXObject (<i>self</i>)
Return the internal networkx graph object.
__len__ (<i>self</i>)

<code>__iter__(self)</code>

<code>getSize(self)</code>

Return the number of nodes in the graph.
--

<code>getNodeNames(self)</code>

Return the names of nodes in the graph.

<code>iterNodes(self)</code>

Iterate over all nodes.

<code>getNodes(self)</code>

<code>getEdges(self)</code>

<code>getEdgesFor(self, i)</code>

<code>getNode(self, i)</code>

<code>getEdge(self, i, j)</code>

<code>getNeighborsFor(self, i)</code>

<code>getDegreeFor(self, i)</code>

Return in- and out-degree for node named i.

<code>setDefaultWeight(self, w)</code>
--

<code>clearEdgeWeights(self)</code>

<code>getNumComponents(self)</code>

Get the number of components of the graph.
--

<code>getComponents(self)</code>

Get the connected components in the graph.
--

getComponentOfNode (<i>self</i> , <i>i</i>)
--

Get the graph component of a given node.
--

getCliques (<i>self</i>)

Get the cliques present in the graph.

getCliqueNumber (<i>self</i>)
--

Get the clique number of the graph.

getNumCliques (<i>self</i>)

Get the number of cliques found in the graph.

getCliquesOfNode (<i>self</i> , <i>i</i>)
--

Get the clique that a node corresponds to.
--

getCenter (<i>self</i>)

Get the centre of the graph.

getDiameter (<i>self</i>)

Acquire the diameter of the graph.

getMST (<i>self</i>)

Acquire the minimum spanning tree for the graph.
--

hasPath (<i>self</i> , <i>nodA</i> , <i>nodB</i>)
--

See if a path exists between two nodes.

getShortestPath (<i>self</i> , <i>nodA</i> , <i>nodB</i>)
--

Get the shortest path between two nodes.
--

getShortestPathLength (<i>self</i> , <i>nodA</i> , <i>nodB</i>)
--

Get the shortest path length between two nodes.

Inherited from object


<code>__delattr__()</code> , <code>__format__()</code> , <code>__getattr__()</code> , <code>__hash__()</code> , <code>__new__()</code> , <code>__reduce__()</code> , <code>__reduce_ex__()</code> , <code>__repr__()</code> , <code>__setattr__()</code> , <code>__sizeof__()</code> ,

`__str__()`, `__subclasshook__()`

8.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8.3 Class *landscape*



Known Subclasses: `pylogeny.database.DatabaseLandscape`, `pylogeny.database.SQLiteLandscape`
 Defines an entire phylogenetic tree space.

8.3.1 Methods

<code>__init__</code> (<i>self</i> , <i>ali</i> , <i>starting_tree</i> =None, <i>root</i> =True, <i>operator</i> ='SPR')
Initialize the landscape.
:param ali: An :class:'alignment.alignment' object. :param starting_tree: An optional tree object to start the landscape with. :param root: Whether or not to acquire an approximate maximum likelihood tree (FastTree) or start the landscape with a given starting tree. :param operator: A string that describes what operator the landscape is mostly comprised of.
Overrides: <code>object.__init__</code>

getAlignment(*self*)

Acquire the alignment object associated with this space.

getNumberTaxa(*self*)

Return the number of different taxa present in any respective tree in the landscape.

getPossibleNumberRootedTrees(*self*)

Assuming all of the trees in the space are rooted, return the maximum possible number of unrooted trees that can possibly be generated for the number of taxa of trees in the landscape.

getPossibleNumberUnrootedTrees(*self*)

Assuming all of the trees in the space are unrooted, return the maximum possible number of unrooted trees that can possibly be generated for the number of taxa of trees in the landscape.

getRootTree(*self*)

Acquire the first tree that was placed in this space.

setAlignment(*self*, *ali*)

Set the alignment present in this landscape. WARNING; will not modify existing scores.

getTree(*self*, *i*)

Get the tree object for a tree by its ID or name *i*.

iterTrees(*self*)

Iterate over all trees found in this landscape.

__iter__(*self*)

Overrides: `_abcoll.Iterable.__iter__`

getVertex(*self*, *i*)

Acquire a vertex object from the landscape; this is a high-level representation of a tree in the landscape with additional functionality. Object created upon invocation of this function.

removeTree(*self*, *tree*)

Remove a tree from the landscape by object.

Overrides: `pylogeny.tree.treeSet.removeTree`

addTree(*self*, *tree*)

Add a tree to the landscape. Will return its index.

Overrides: `pylogeny.tree.treeSet.addTree`

exploreRandomTree(*self*, *i*, *type*=1)

Acquire a single neighbor to a tree in the landscape by performing a random rearrangement of type SPR (by default), NNI, or TBR. Rearrangement type is provided as a rearrangement module type definition of form, for example, `TYPE_SPR`, `TYPE_NNI`, etc.

exploreTree(*self*, *i*, *type*=1)

Get all neighbors to a tree named *i* in the landscape using a respective rearrangement operator as defined in the rearrangement module.

Rearrangement type is provided as a rearrangement module type definition of form, for example, `TYPE_SPR`, `TYPE_NNI`, etc. By default, this is `TYPE_SPR`.

getLocks(*self*)

toggleLock(*self*, *lock*)

Add a bipartition to the list of locked bipartitions if not present; otherwise, remove it. Return status of lock.

lockBranchFoundInTree(*self*, *tr*, *br*)

Given a tree node and a branch object, add a given bipartition to the bipartition lock list. Returns true if locked.

getBipartitionFoundInTreeByIndex(*self*, *tr*, *brind*, *topol*=None)

Given a tree node and a branch index, return the associated bipartition.

lockBranchFoundInTreeByIndex(*self*, *tr*, *brind*)

Given a tree node and a branch index, add a given bipartition to the bipartition lock list. Returns true if locked.

isViolating(*self*, *i*)

Determine if a tree is violating any locks intrinsic to the landscape.

__getitem__(*self*, *i*)

Overrides: `pylogeny.tree.treeSet.__getitem__`

indexOf(*self*, *tr*)

Acquire the index/name in this landscape of a tree object. Returns -1 if not found.

Overrides: `pylogeny.tree.treeSet.indexOf`

findTree(*self*, *newick*)

Find a tree by Newick string, taking into account branch lengths. Returns the name of this tree in the landscape.

findTreeTopology(*self*, *newick*)

Find a tree by topology, not taking into account branch lengths.

findTreeTopologyByStructure(*self*, *struct*)

Find a tree by topology, not taking into account branch lengths, given the topology.

getBestImprovement(*self*, *i*)

For a tree in the landscape, investigate neighbors to find a tree that leads to the best improvement of fitness function score on the basis of likelihood.

getPathOfBestImprovement(*self*, *i*)

For a tree in the landscape, investigate neighbors iteratively until a best path of score improvement is found on basis of likelihood.

getAllPathsOfBestImprovement(*self*)

Return all paths of best improvement as a dictionary.

iterAllPathsOfBestImprovement(*self*)

Return an iterator for all paths of best improvement.

isLocalOptimum (<i>self</i> , <i>i</i>)
--

Determine if a tree is, without any doubt, a local optimum.

getLocalOptima (<i>self</i>)

Get all trees in the landscape that can be labelled as a local optimum.

getGlobalOptimum (<i>self</i>)

Get the global optimum of the current space.
--

__str__ (<i>self</i>)

str(x)

Overrides: object.__str__ extit(inherited documentation)
--

toProperNewickTreeSet (<i>self</i>)
--

Convert this landscape into an unorganized set of trees where taxa names are transformed to their original form (i.e. not transformed to a state friendly for the Phylip format).
--

toTreeSet (<i>self</i>)

Convert this landscape into an unorganized set of trees.
--

Inherited from *pylogeny.landscape.graph*(Section 8.2)

`__len__()`, `clearEdgeWeights()`, `getCenter()`, `getCliqueNumber()`, `getCliques()`, `getCliquesOfNode()`, `GetComponentOfNode()`, `getComponents()`, `getDegreeFor()`, `getDiameter()`, `getEdge()`, `getEdges()`, `getEdgesFor()`, `getMST()`, `getNeighborsFor()`, `getNetworkXObject()`, `getNode()`, `getNodeNames()`, `getNodes()`, `getNumCliques()`, `getNumComponents()`, `getShortestPath()`, `getShortestPathLength()`, `getSize()`, `hasPath()`, `iterNodes()`, `setDefaultWeight()`

Inherited from *pylogeny.tree.treeSet*(Section 16.4)

`addTreeByNewick()`, `toTreeFile()`

Inherited from *__abcoll.Sized*

`__subclasshook__()`

Inherited from *object*

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`

8.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

8.3.3 Class Variables

Name	Description
<i>Inherited from pylogeny.tree.treeSet (Section 16.4)</i> __abstractmethods__	

8.4 Class vertex

object —
 pylogeny.landscape.vertex

Encapsulate a single vertex in the landscape and add convenient functionality to alias parent landscape functions.

8.4.1 Methods

__init__ (<i>self</i> , <i>i</i> , <i>obj</i> , <i>ls</i>) x. __init__ (...) initializes x; see help(type(x)) for signature Overrides: object. __init__ extit(inherited documentation)
getIndex (<i>self</i>)
getDict (<i>self</i>)
getObject (<i>self</i>)
getTree (<i>self</i>)
getNewick (<i>self</i>)
getScore (<i>self</i>)

getOrigin(*self*)**getNeighbors**(*self*)**getDegree**(*self*)**isLocalOptimum**(*self*)**isExplored**(*self*)**isFailed**(*self*)**approximatePossibleNumNeighbors**(*self*)

Approximate the possible number of neighbors to this vertex by considering the type of tree rearrangement operator.

scoreLikelihood(*self*)

Acquire the log-likelihood for this vertex.

getBestImprovement(*self*)

Alias function for function of same name in parent landscape.

getPathOfBestImprovement(*self*)

Alias function for function of same name in parent landscape.

isBestImprovement(*self*)

Check to see if this vertex is a best move for another node.

isViolating(*self*)

Alias function for function of same name in parent landscape.

getProperNewick(*self*)

Get the proper Newick string for a tree. :returns: A string.

getBipartitions(*self*)

Get all bipartitions for this vertex.

getBipartitionScores (<i>self</i>)
Get all corresponding bipartition vectors of SPR scores.

getNeighborsOfBipartition (<i>self</i> , <i>bi</i>)
Get corresponding neighbors of a bipartition in this vertex's tree.

getNeighborsOfBranch (<i>self</i> , <i>br</i>)
Get corresponding neighbors of a branch in this vertex's tree.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

8.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

9 Module `pylogeny.landscapeWriter`

Serialize a phylogenetic landscape into an SQLite database file made up of three components: all tree IDs and respective scores, the alignment file as a set of sequences, and a representation of the graph as an edge list.

9.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'pylogeny'</code>

9.2 Class `landscapeWriter`

object  `pylogeny.landscapeWriter.landscapeWriter`

Known Subclasses: `pylogeny.JSONWriter.JSONWriter`

Encapsulate the writing of a landscape to a file format.

9.2.1 Methods

<code>__init__(self, landscape, name)</code>
<code>x.__init__(...)</code> initializes <code>x</code> ; see <code>help(type(x))</code> for signature
Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>writeFile(self, path='.')</code>
Write the landscape serialized file to given path.

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

9.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

9.3 Class `landscapeParser`

object —
`pylogeny.landscapeWriter.landscapeParser`

Encapsulates the construction of a landscape object from a pickle file.

9.3.1 Methods

<code>__init__(self, path)</code>
<code>x.__init__(...)</code> initializes x; see <code>help(type(x))</code> for signature
Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)

<code>getName(self)</code>
Acquire the name of the parsed landscape.

<code>parse(self)</code>
Parse the file.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__new__()`,
`__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`,
`__str__()`, `__subclasshook__()`

9.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	


10 Module *pylogeny.model*

Phylogenetic tree scoring models; intended to be coupled with the use of *pytbeaglehon* (BEAGLE) high-performance library.

10.1 Variables

Name	Description
<code>pytbeaglehonEnabled</code>	Value: <code>True</code>
<code>__package__</code>	Value: <code>'pylogeny'</code>

10.2 Class *PhyloModelError*



10.2.1 Methods

```

__init__(self, v)

x.__init__(...) initializes x; see help(type(x)) for signature
Overrides: object.__init__ extit(inherited documentation)

```

```

__str__(self)

str(x)
Overrides: object.__str__ extit(inherited documentation)

```

Inherited from exceptions.Exception

```
__new__()
```

Inherited from exceptions.BaseException

```

__delattr__(), __getattr__(), __getitem__(), __getslice__(), __reduce__(),
__repr__(), __setattr__(), __setstate__(), __unicode__()

```

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

10.2.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
<code>args</code> , <code>message</code>	
<i>Inherited from object</i>	
<code>__class__</code>	

10.3 Class DiscreteStateModel

object —
pylogeny.model.DiscreteStateModel

Initialize a discrete state model for phylogenetic data. State frequencies and character time are determined from the given alignment object.

10.3.1 Methods

<code>__init__(self, alignment)</code>
x. <code>__init__</code> (...) initializes x; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)
<code>getAlignment(self)</code>
<code>getAlignmentAsStateList(self)</code>
<code>getSequenceMatrix(self)</code>
<code>getCharType(self)</code>
<code>getStateFreqs(self)</code>
<code>getRawStateFreqs(self)</code>

<code>getRawStateFreqsAsList(<i>self</i>)</code>
--

<code>getRawStateFreqsAsDict(<i>self</i>)</code>
--

<code>getFrequencyOfState(<i>self</i>, <i>i</i>)</code>

<code>getRawFrequencyOfState(<i>self</i>, <i>i</i>)</code>
--

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()
```

10.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

11 Module *pylogeny.newick*

Newick string parsing and object interaction. A Newick string can represent a phylogenetic tree.

11.1 Functions

assignParents (<i>top</i>)

Should be a one-time use function. Goes through and assigns parents to the parsed newick tree structure nodes and branches to allow for up-traversal.

removeBranchLengths (<i>top</i>)

Goes through and removes any stored branch lengths.

removeUnaryInternalNodes (<i>top</i>)
--

Goes through and ensures any degree-2 internal nodes are smoothed into a single degree-3 internal node.

invertAlongPathToNode (<i>target, top</i>)

DANGEROUS: Reverses all directionality to a given node from a top-level node. Intended as a low-level function for rerooting a tree.
--

shuffleLeaves (<i>top</i>)

DANGEROUS: Given a top-level node, shuffle all leaves in this tree.

getAllBranches (<i>br</i>)

Given a branch, traverse subtree and return comprising branches as a list.
--

isSibling (<i>br, other</i>)

Given a branch, determine if that branch is adjacent to another branch.

getBalancingBracket (<i>newick, i</i>)

Given a position of an opening bracket in a newick string, <i>i</i> , output the closing bracket's position that corresponds to this opening bracket.

getBranchLength(*newick*, *i*)

Given a position of a colon symbol (indicating a branch length), return the branch length.

getLeafName(*newick*, *i*)

Given the position of a leaf, find its complete name.


parseNewick(*newick*, *i*, *j*, *top*)

Parse a newick string into a topological newick structure given a top-level node.

11.2 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

11.3 Class *ParsingError*



11.3.1 Methods

__init__(*self*, *val*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.__init__` `extit`(inherited documentation)

__str__(*self*)

`str(x)`

Overrides: `object.__str__` `extit`(inherited documentation)

Inherited from exceptions.Exception

`__new__()`

Inherited from exceptions.BaseException

`__delattr__()`, `__getattr__()`, `__getitem__()`, `__getslice__()`, `__reduce__()`, `__repr__()`, `__setattr__()`, `__setstate__()`, `__unicode__()`

Inherited from object

`__format__()`, `__hash__()`, `__reduce_ex__()`, `__sizeof__()`, `__subclasshook__()`

11.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
<code>__class__</code>	

11.4 Class node

```

object ─┐
         │
pylogeny.base.treeNode ─┐
                        │
                        pylogeny.newick.node
  
```

Newick node.

11.4.1 Methods

`__init__(self, lbl='', children=None, parent=None)`
 x.`__init__`(...) initializes x; see `help(type(x))` for signature
 Overrides: `object.__init__` `extit`(inherited documentation)

`__str__(self)`
`str(x)`
 Overrides: `object.__str__` `extit`(inherited documentation)

Inherited from pylogeny.base.treeNode(Section 4.3)

addChild(), getChildByIndex(), getChildren(), getLabel(), getParent(), isInternalNode(), isLeaf()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()


11.4.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

11.4.3 Class Variables

Name	Description
<i>Inherited from pylogeny.base.treeNode (Section 4.3)</i> children, label, parent	

11.5 Class branch



Newick branch.

11.5.1 Methods

__init__(self, chi, l, parent=None, s=None)
x.__init__(...) initializes x; see help(type(x)) for signature
Overrides: object.__init__ extit(inherited documentation)

__str__ (<i>self</i>) str(<i>x</i>) Overrides: object.__str__ extit(inherited documentation)

Inherited from pylogeny.base.treeBranch(Section 4.4)

getChild(), getLabel(), getParent()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()

11.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

11.5.3 Class Variables

Name	Description
<i>Inherited from pylogeny.base.treeBranch (Section 4.4)</i>	
child, label, parent	

11.6 Class parser

Parsing object for Newick strings.

11.6.1 Methods

__init__ (<i>self</i> , <i>newick</i>)

parse (<i>self</i>)

Parse the stored newick string into a topological structure.
--

__str__ (<i>self</i>)

12 Module `pylogeny.parsimony`

Toolkit for performance of Parsimonious Criterion (Parsimony) methods of optimization of a phylogenetic topology with a particular set of data.

12.1 Functions

`fitch_cost`(*topology*, *profiles*)

Calculate the cost using Fitch algorithm on profile set and alignment.
 Deprecated: Python implementation of the Fitch algorithm; see `fitch C++` module for a C++ implementation that is roughly four times faster.

`fitch`(*topology*, *alignment*)

Perform the Fitch algorithm on a given tree topology and associated alignment. Deprecated: Python implementation of the Fitch algorithm; see `fitch C++` module for a C++ implementation that is roughly four times faster.

12.2 Variables

Name	Description
<code>__package__</code>	Value: <code>'pylogeny'</code>

12.3 Class `profile_set`

Hold a set of `site_profile` profiles for an entire alignment.

12.3.1 Methods

`__init__`(*self*, *alignment*)

`__len__`(*self*)

`weight`(*self*, *val*)

`get`(*self*, *val*)

```
getForTaxa(self, val, tax)
```

12.4 Class *site_profile*

Consolidate the single-column alignment at a region into a set of components on the basis of similarity alone.

12.4.1 Methods

```
__init__(self, alignment, site)
```

```
__eq__(self, o)
```

```
__ne__(self, o)
```

```
__str__(self)
```

13 Module *pylogeny.pll*

C Extension to wrap libpll library.

13.1 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

13.2 Class *dataModel*

Encapsulating a phylogenetic tree (as topology) + corresponding alignment into a libpll-associated data structure. Allows for log-likelihood scoring of this model. MUST BE CLOSED AFTER USE.

13.2.1 Methods

<code>__init__(self, topo, alignm, model=None)</code>
Initialize all structures.
<code>getLogLikelihood(self)</code>
Calculates log-likelihood using libpll.
<code>close(self)</code>
If done with this particular problem.

13.3 Class *partitionModel*

A partition model intended for libpll.

13.3.1 Methods

<code>__init__(self, ali)</code>
<code>getFileName(self)</code>
Get the file name of the model file.

createSimpleModel (<i>self</i> , <i>protein</i>)

Establish a simple model (e.g., one type).
--

createModel (<i>self</i> , <i>models</i> , <i>partnames</i> , <i>ranges</i>)

Establish a more complex model.

close (<i>self</i>)

Delete file.

14 Module *pylogeny.rearrangement*

Phylogenetic tree structure encapsulation; allow rearrangement of said structure. Tree rearrangements inducing other topologies include Nearest Neighbor Interchange (NNI), Subtree Pruning and Regrafting (SPR), and Tree Bisection and Reconstruction (TBR). Each of these describe a transfer of one node in phylogenetic trees from one parent of a tree to a new parent. Respectively, these operators describe transformations that are subsets of those possible by the successive operator. For example, an NNI operator can perform transformations that are a subset of the transformations possible by the SPR operator.

14.1 Functions

dup(*topo*, *where*=None)

14.2 Variables

Name	Description
TYPE_NNI	Value: 2
TYPE_SPR	Value: 1
TYPE_TBR	Value: 3
__package__	Value: 'pylogeny'

14.3 Class *RearrangementError*



14.3.1 Methods

__init__(*self*, *val*)

x.**__init__**(...) initializes *x*; see `help(type(x))` for signature

Overrides: `object.__init__` `exitit`(inherited documentation)

__str__ (<i>self</i>) str(<i>x</i>) Overrides: object.__str__ extit(inherited documentation)

Inherited from exceptions.Exception

__new__ ()

Inherited from exceptions.BaseException

__delattr__ (), __getattr__ (), __getitem__ (), __getslice__ (), __reduce__ (), __repr__ (), __setattr__ (), __setstate__ (), __unicode__ ()

Inherited from object

__format__ (), __hash__ (), __reduce_ex__ (), __sizeof__ (), __subclasshook__ ()

14.3.2 Properties

Name	Description
<i>Inherited from exceptions.BaseException</i>	
args, message	
<i>Inherited from object</i>	
__class__	

14.4 Class rearrangement

Encapsulates a single rearrangement move of type SPR, NNI, ...

14.4.1 Methods

__init__ (<i>self</i> , <i>struct</i> , <i>type</i> , <i>targ</i> , <i>dest</i>)
Initialize by providing a pointer to a base topology, a target branch to be moved, and its destination.

getType (<i>self</i>)
Get the type of movement.

isNNI (<i>self</i>)

isSPR (<i>self</i>)

isTBR (<i>self</i>)

toTopology (<i>self</i>)

Commit the actual move and return the topology.

toNewick (<i>self</i>)

Commit the move but do not create a new structure. Only retrieve resultant Newick string; will be more efficient.


toTree (<i>self</i>)

Commit the move and transform to tree object.

doMove (<i>self</i>)

__str__ (<i>self</i>)

14.5 Class topology



Encapsulate a tree topology, wrapping the newick tree structure. Is immutable.

14.5.1 Methods

__init__ (<i>self</i> , <i>t=None</i> , <i>rerootToLeaf=True</i> , <i>toLeaf=None</i>)

Initialize structure with a top-level internal node OR nothing.

Overrides: <code>object.__init__</code>

rerootToLeaf(*self*, *toleaf*=None)

PRIVATE: Reroots the given tree structure such that it is rooted nearest the lowest-order leaf.

getBranches(*self*)

getLeaves(*self*)

getBipartitions(*self*)

Get all bipartitions.

getStrBipartitionFromBranch(*self*, *br*)

Given a branch, return corresponding bipartition.

getBranchFromStrBipartition(*self*, *bip*)

Given a bipartition of taxa, return a branch that creates that partition of tree taxa.

getBranchFromBipartition(*self*, *bip*)

Given a bipartition object, return a branch that creates that partition of taxa.

lockBranch(*self*, *branch*)

Given a branch, lock it such that no transitions can ever occur across it.

move(*self*, *branch*, *destination*, *returnStruct*=True)

Move a branch and attach to a destination branch. Return new structure, or return merely the resultant Newick string.

SPR(*self*, *branch*, *destination*)

Perform an SPR move of a branch to a destination branch, creating a new node there. Returns a rearrangement structure (not the actual new structure) that can then be polled for the actual move; this is in order to save memory.

NNI(*self*, *branch*, *destination*)

Perform an NNI move of a branch to a destination, only if that destination branch is a parent's parent or a parent's sibling. Returns a rearrangement structure (not the actual new structure) that can then be polled for the actual move; this is in order to save memory.

iterSPRForBranch(*self*, *br*, *flip*=True)

Consider all valid SPR moves for a given branch in the topology and yield all possible rearrangements as a generator.

allSPRForBranch(*self*, *br*, *flip*=True)

Consider all valid SPR moves for a given branch in the topology and return all possible rearrangements.

allSPR(*self*)

Consider all valid SPR moves for a given topology and return all possible rearrangements.

iterNNIForBranch(*self*, *br*, *flip*=True)

Consider all valid NNI moves for a given branch in the topology and and yield all possible rearrangements as a generator.

allNNIForBranch(*self*, *br*, *flip*=True)

Consider all valid NNI moves for a given branch in the topology and return all possible rearrangements.

allNNI(*self*)

Consider all valid NNI moves for a given topology and return all possible rearrangements.

allType(*self*, *type*=1)

Consider all valid moves of a given rearrangement operator for a given topology. Uses a given rearrangement operator type defined in this module. For example, calling this function by providing TYPE_NNI as the type will iterate over all NNI operations. By default, the type is TYPE_SPR.

iterTypeForBranch(*self*, *br*, *type*=1, *flip*=True)

Iterate over all possible rearrangements for a branch using a given rearrangement operator type defined in this module. For example, calling this function by providing TYPE_NNI as the type will iterate over all NNI operations. By default, the type is TYPE_SPR.

fromNewick(*self*, *newickstr*)

Alias for parse().

parse (<i>self</i> , <i>newickstr</i>)

Parse a newick string and assign the tree to this object. Cannot already be initialized with a tree.
--

toNewick (<i>self</i>)

Return the newick string of the tree.

toUnrootedNewick (<i>self</i>)

Return the newick string of the tree as an unrooted topology with a multifurcating top-level node.
--

toTree (<i>self</i>)

Return the tree object for this topology.

toUnrootedTree (<i>self</i>)

Return the tree object of the unrooted version of this topology.
--

__str__ (<i>self</i>)

Return the newick string of the tree.

Overrides: object.__str__

Inherited from *pylogeny.base.treeStructure*(Section 4.2)

__contains__(), getAllLeaves(), getAllNodes(), getPostOrderTraversal(), getRoot(), leaves(), nodes(), postOrderTraversal()

Inherited from *__abcoll.Container*

__subclasshook__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__()

14.5.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

14.5.3 Class Variables

Name	Description
__abstractmethods__, root	<i>Inherited from pylogeny.base.treeStructure (Section 4.2)</i>

15 Module *pylogeny.scoring*

Phylogenetic tree scoring.

15.1 Functions

beaglegetLogLikelihood(*tree*, *alignment*)

Acquire log-likelihood via C++ library BEAGLE via use of pybeaglethon wrapper library. Parameters: newick.tree object and alignment object. Currently uses HKY85 model.

getLogLikelihoodForTopology(*topo*, *alignment*)

Acquire log-likelihood via C library libpll. Parameters: rearrangement.topology object and alignment object.

getLogLikelihood(*tree*, *alignment*)

Acquire log-likelihood via C library libpll. Parameters: newick.tree object and alignment object.

getParsimony(*newick*, *alignment*)

Acquire parsimony via a C++ implementation. Parameters: newick string and alignment object.

getParsimonyForTopology(*topology*, *alignment*)

Acquire parsimony via a C++ implementation. Parameters: rearrangement.topology and alignment object.

getParsimonyFromProfiles(*newick*, *profiles*)

Acquire parsimony via a C++ implementation. Parameters: newick string and parsimony.profile_set object.

getParsimonyFromProfilesForTopology(*topology*, *profiles*)

Acquire parsimony via a C++ implementation. Parameters: rearrangement.topology and parsimony.profile_set object.

15.2 Variables

Name	Description
<code>__package__</code>	Value: 'pylogeny'

16 Module `pylogeny.tree`

Container definition for (phylogenetic) bifurcating or multifurcating trees defined using Newick strings, collections of them, and for splits of these trees.

16.1 Functions

<code>numberRootedTrees(<i>t</i>)</code>
--

<code>numberUnrootedTrees(<i>t</i>)</code>
--

16.2 Variables

Name	Description
<code>__package__</code>	Value: <code>'pylogeny'</code>

16.3 Class tree

```

object └─
          pylogeny.tree.tree

```

Defines a single (phylogenetic) tree by newick string; can possess other metadata.

16.3.1 Methods

<code>__init__(<i>self</i>, <i>newi</i>='', <i>check</i>=False)</code>
--

If enabled, "check" will force the structure to reroot the given Newick string tree to a lowest-order leaf in order to ensure a consistent Newick string among any duplicate topologies.

Overrides: `object.__init__`

<code>getName(<i>self</i>)</code>

<code>setName(<i>self</i>, <i>n</i>)</code>

<code>getScore(<i>self</i>)</code>

setScore(*self*, *s*)

getOrigin(*self*)

setOrigin(*self*, *o*)

Set the "origin" or specification of where this tree was acquired or constructed from; a string.

getNewick(*self*)

toNewick(*self*)

setNewick(*self*, *n*)

Set Newick string to *n*; also reacquires corresponding "structure" or Newick string without branch lengths.

getStructure(*self*)

Returns "structure", a Newick string without branch lengths.

getRerootedNoBranchLengthNewick(*self*)

See `getStructure()`.

getSimpleNewick(*self*)

Return a Newick string with all taxa name replaced with successive integers.

toTopology(*self*)

Return a `rearrangement.topology` instance for this tree to allow for rearrangement of the actual structure of the tree.

__eq__(*self*, *o*)

__ne__(*self*, *o*)

__str__(*self*)

`str(x)`


Overrides: `object.__str__` extit(inherited documentation)

Inherited from object

```
__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__subclasshook__()
```

16.3.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

16.4 Class treeSet

Known Subclasses: pylogeny.landscape.landscape

Represents an ordered, unorganized collection of trees that do not necessarily comprise a combinatorial space.

16.4.1 Methods

<code>__init__(self)</code> x. <code>__init__</code> (...) initializes x; see help(type(x)) for signature Overrides: object. <code>__init__</code> extit(inherited documentation)
<code>addTree(self, tr)</code> Add a tree object to the collection.
<code>addTreeByNewick(self, newick)</code> Add a tree to the structure by Newick string.
<code>removeTree(self, tr)</code> Remove a tree object from the collection if present.

indexOf (<i>self</i> , <i>tr</i>)
--

Acquire the index in this collection of a tree object. Returns -1 if not found.

__getitem__ (<i>self</i> , <i>i</i>)

__len__ (<i>self</i>)

Overrides: <code>__abcoll.Sized.__len__</code>
--

toTreeFile (<i>self</i> , <i>fout</i>)

Output this landscape as a series of trees, separated by newlines, as a text file saved at the given path.
--

__str__ (<i>self</i>)

<code>str(x)</code>

Overrides: <code>object.__str__</code> <code>__extit__</code> (inherited documentation)

Inherited from `__abcoll.Sized`

<code>__subclasshook__</code> ()

Inherited from `object`

<code>__delattr__</code> ()
<code>__format__</code> ()
<code>__getattr__</code> ()
<code>__hash__</code> ()
<code>__new__</code> ()
<code>__reduce__</code> ()
<code>__reduce_ex__</code> ()
<code>__repr__</code> ()
<code>__setattr__</code> ()
<code>__sizeof__</code> ()

16.4.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

16.4.3 Class Variables

Name	Description
<code>__abstractmethods__</code>	Value: <code>frozenset([])</code>

16.5 Class bipartition

object └─
pylogeny.tree.bipartition

A tree bipartition. Requires a tree topology. Using the term borrowed from nomenclature of a bipartite graph, a bipartition for a phylogenetic tree coincides with the definition of two disjoint sets U and V . A branch in a phylogenetic tree defines a single bipartition that divides the tree into two disjoint sets U and V . The set U comprises all of the children leaf of the subtree associated with that branch. The set V contains the rest of the leaves or taxa in the tree.

16.5.1 Methods

__init__ (<i>self</i> , <i>topol</i> , <i>bra</i> =None) <hr/> Construct a bipartition from a branch in a topology. :param <i>topol</i> : A topology. :type <i>topol</i> : :class: 'rearrangement.topology' :param <i>bra</i> : An optional argument; can still acquire a bipartition from a string. :type <i>bra</i> : :class: 'newick.branch' Overrides: object.__init__
__hash__ (<i>self</i>) <hr/> hash(<i>x</i>) Overrides: object.__hash__ extit(inherited documentation)
__eq__ (<i>self</i> , <i>o</i>) <hr/>
__ne__ (<i>self</i> , <i>o</i>) <hr/>
fromStringRepresentation (<i>self</i> , <i>st</i>) <hr/> Acquire all component elements from a string representation of a bipartition. :param <i>st</i> : A string representation from a :class:'bipartition' object.
getBranch (<i>self</i>) <hr/> Get branch corresponding to this bipartition. :returns: :class:'newick.branch'

getBranchIndex(*self*)

Return an index of the branch with respect to a post order traversal of the topology.

getStringRepresentation(*self*)

Get the string representation corresponding to this bipartition.

getShortStringRepresentation(*self*)

Get the shorter string representation corresponding to this bipartition.

getShortStringMappings(*self*)

Get the mapping of symbols from taxa names for the shorter string representation.

getBranchListRepresentation(*self*)

Get the tuple of lists of branches that represent this bipartition.

getSPRRearrangements(*self*)

Return the set of all scores related to this bipartition.

getSPRScores(*self*, *ls*, *node=None*)

Given a landscape, return all possible scores, not actively performing scoring if not done.

getMedianSPRScore(*self*, *ls*, *node=None*)

Given a landscape, return the median SPR score.

getBestSPRScore(*self*, *ls*, *node=None*)

Given a landscape, return the best SPR score.

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__new__()`, `__reduce__()`,
`__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

16.5.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

Index

- pylogeny (*package*), 2
 - pylogeny.alignment (*module*), 5–9
 - pylogeny.alignment.alignment (*class*), 5–7
 - pylogeny.alignment.phylipFriendlyAlignment (*class*), 7–9
 - pylogeny.base (*module*), 10–18
 - pylogeny.base.patriciaTree (*class*), 17–18
 - pylogeny.base.treeBranch (*class*), 12–13
 - pylogeny.base.treeNode (*class*), 11–12
 - pylogeny.base.treeStructure (*class*), 10–11
 - pylogeny.base.trie (*class*), 15–17
 - pylogeny.base.trieNode (*class*), 13–15
 - pylogeny.database (*module*), 19–29
 - pylogeny.database.database (*class*), 25–27
 - pylogeny.database.DatabaseLandscape (*class*), 19–20
 - pylogeny.database.SQLDatabase (*class*), 27–28
 - pylogeny.database.SQLExhaustiveLandscape (*class*), 20–23
 - pylogeny.database.SQLiteDatabase (*class*), 28–29
 - pylogeny.database.SQLiteLandscape (*class*), 23–25
 - pylogeny.executable (*module*), 30–36
 - pylogeny.executable.aTemporaryDirectory (*class*), 30–31
 - pylogeny.executable.consel (*class*), 33–34
 - pylogeny.executable.executable (*class*), 31–32
 - pylogeny.executable.exeExists (*function*), 30
 - pylogeny.executable.fasttree (*class*), 34–35
 - pylogeny.executable.raxml (*class*), 35–36
 - pylogeny.executable.treepuzzle (*class*), 32–33
 - pylogeny.heuristic (*module*), 37–44
 - pylogeny.heuristic.heuristic (*class*), 37–38
 - pylogeny.heuristic.likelihoodGreedy (*class*), 40–41
 - pylogeny.heuristic.parsimonyGreedy (*class*), 39–40
 - pylogeny.heuristic.phylogeneticLinearHeuristic (*class*), 38–39
 - pylogeny.heuristic.RAxMLIdentify (*class*), 42–44
 - pylogeny.heuristic.smoothGreedy (*class*), 41–42
 - pylogeny.JSONWriter (*module*), 3–4
 - pylogeny.JSONWriter.JSONWriter (*class*), 3–4
 - pylogeny.landscape (*module*), 45–55
 - pylogeny.landscape.graph (*class*), 45–48
 - pylogeny.landscape.landscape (*class*), 48–53
 - pylogeny.landscape.vertex (*class*), 53–55
 - pylogeny.landscapeWriter (*module*), 56–57
 - pylogeny.landscapeWriter.landscapeParser (*class*), 57
 - pylogeny.landscapeWriter.landscapeWriter (*class*), 56–57
 - pylogeny.model (*module*), 58–60
 - pylogeny.model.DiscreteStateModel (*class*), 59–60
 - pylogeny.model.PhyloModelError (*class*), 58–59
 - pylogeny.newick (*module*), 61–65
 - pylogeny.newick.assignParents (*function*), 61
 - pylogeny.newick.branch (*class*), 64–65
 - pylogeny.newick.getAllBranches (*function*), 61
 - pylogeny.newick.getBalancingBracket (*function*), 61

- pylogeny.newick.getBranchLength (*function*), 61
- pylogeny.newick.getLeafName (*function*), 62
- pylogeny.newick.invertAlongPathToNode (*function*), 61
- pylogeny.newick.isSibling (*function*), 61
- pylogeny.newick.node (*class*), 63–64
- pylogeny.newick.parseNewick (*function*), 62
- pylogeny.newick.parser (*class*), 65
- pylogeny.newick.ParsingError (*class*), 62–63
- pylogeny.newick.removeBranchLengths (*function*), 61
- pylogeny.newick.removeUnaryInternalNodes (*function*), 61
- pylogeny.newick.shuffleLeaves (*function*), 61
- pylogeny.parsimony (*module*), 66–67
 - pylogeny.parsimony.fitch (*function*), 66
 - pylogeny.parsimony.fitch_cost (*function*), 66
 - pylogeny.parsimony.profile_set (*class*), 66–67
 - pylogeny.parsimony.site_profile (*class*), 67
- pylogeny.pll (*module*), 68–69
 - pylogeny.pll.dataModel (*class*), 68
 - pylogeny.pll.partitionModel (*class*), 68–69
- pylogeny.rearrangement (*module*), 70–76
 - pylogeny.rearrangement.dup (*function*), 70
 - pylogeny.rearrangement.rearrangement (*class*), 71–72
 - pylogeny.rearrangement.RearrangementError (*class*), 70–71
 - pylogeny.rearrangement.topology (*class*), 72–76
- pylogeny.scoring (*module*), 77–78
 - pylogeny.scoring.beaglegetLogLikelihood (*function*), 77
 - pylogeny.scoring.getLogLikelihood (*function*), 77
 - pylogeny.scoring.getLogLikelihoodForTopology (*function*), 77
 - pylogeny.scoring.getParsimony (*function*), 77
 - pylogeny.scoring.getParsimonyForTopology (*function*), 77
 - pylogeny.scoring.getParsimonyFromProfiles (*function*), 77
 - pylogeny.scoring.getParsimonyFromProfilesForTopology (*function*), 77
- pylogeny.tree (*module*), 79–85
 - pylogeny.tree.bipartition (*class*), 82–85
 - pylogeny.tree.numberRootedTrees (*function*), 79
 - pylogeny.tree.numberUnrootedTrees (*function*), 79
 - pylogeny.tree.tree (*class*), 79–81
 - pylogeny.tree.treeSet (*class*), 81–82