

Semantic Segmentation of Images

Using Deep Convolutional Neural
Networks



Fahimeh Fooladgar

Image Processing Lab (IPL)

Department of Computer Engineering

Sharif University of Technology



July 2019

Amirkabir Artificial Intelligence Summer Summit



Outline



- Introduction
 - Definition & Applications
- Approaches
 - Traditional Methods
 - Deep Learning Methods
- Available datasets and other directions

Introduction

Image Segmentation



Semantic Segmentation



Road	Sidewalk	Building	Fence
Pole	Vegetation	Vehicle	Unlabel

3




Introduction (cont.)



- Semantic segmentation classifying each and every pixel

Semantic Segmentation



GRASS, CAT,
TREE, SKY

No objects, just pixels


Classification &
Localization



CAT

Single Object

Object Detection



CAT, DOG, DUCK

Multiple Object

Instance Segmentation



DOG, DOG, CAT

This image 4/29 public domain



Applications: Self-Driving Car



self, etc.	dynamic	ground	road	sidewalk
parking	rail track	building	wall	fence
guard rail	bridge	tunnel	pole	polegroup
traffic light	traffic sign	vegetation	terrain	sky
person	rider	car	truck	bus
caravan	trailer	train	motorcycle	bicycle






Applications: Robotic









Applications: 3D Scene Understanding






Others ...










3/29





Traditional Methods








Early Deep Learning Methods






Early Deep Learning Methods (cont.)




R-CNN: *Regions with CNN features*




1. Input image



2. Extract region proposals (~2k)





3. Compute CNN features



4. Classify regions




Fully Convolutional Networks







Fully Convolutional Networks (cont.)







Fully Convolutional Networks (cont.)



optical flow Fischer et al. 2015




boundary prediction Xie & Tu 2015





Limitations of FCN







(a) Inconsistent labels due to large object size



(b) Missing labels due to small object size




DeconvNet





SegNet



Smaller model size
Efficient memory requirements



Atrous convolution



Small output feature
maps

Rough segmentation
results


Reduce accuracy

Removing all
down-sampling


Reduce
receptive field

Reduce context

Reduce
accuracy



Standard Convolution ($r=1$)




Dilated Convolution ^{19/29} ($r=2$)


Receptive
field
increased



DeepLab



(a) Going deeper without atrous convolution.




(b) Going deeper with atrous convolution. Atrous convolution with $rate > 1$ is applied after block3 when $output_stride = 16$.

Keep stride constant but larger
field-of-view




DeepLab






DeepLabv2



Atrous Spatial Pyramid Pooling (ASPP)




PSPNet: Pyramid Scene Parsing Network





PSPNet: Pyramid Scene Parsing Network



(a) Input Image

(b) Feature Map


(c) Pyramid Pooling Module

(d) Final Prediction

obtained global information of
the image



DeepLab v3+





Some Results



Datasets

- ✓ ADE2K
 - 20K/2K/3K + 150 classes
- ✓ PASCAL VOC 2012
 - 10582/1449/1456 + 20 classes
- ✓ Cityscapes
 - 2975/500/1525 +19 classes
- ✓ CamVid, SUN-RGBD, NYU-V2, Stanford-2D-3D-S, SceneNet, Matterport3D




Method	PascalVoc	Cityscape	ADE2K
Zoom-out	69.6	-	-
FCN	62.2	65.3	44.8
SegNet	-	57.0	40.8
DeconvNet	72.5		-
DeepLab	79.7	70.4	-
PSPNet	85.4	78.4	57.2
DeepLabv3+	89.0	82.1	-



Other directions



- RGB-D Semantic Segmentation






Other directions



- 3D Pointclouds Semantic Segmentation








Other directions





- Semi-supervised semantic segmentation using GAN



BW to Color



input output



29/29
output



References



- Girshick, Ross, et al. "Rich feature hierarchies for accurate object detection and semantic segmentation." Proceedings of the IEEE conference on computer vision and pattern recognition. 2014.
- Long, Jonathan, Evan Shelhamer, and Trevor Darrell. "Fully convolutional networks for semantic segmentation." Proceedings of the IEEE conference on computer vision and pattern recognition. 2015.
- Noh, Hyeonwoo, Seunghoon Hong, and Bohyung Han. "Learning deconvolution network for semantic segmentation." Proceedings of the IEEE international conference on computer vision. 2015.
- Mostajabi, Mohammadreza, Payman Yadollahpour, and Gregory Shakhnarovich. "Feedforward semantic segmentation with zoom-out features." Proceedings of the IEEE conference on computer vision and pattern recognition. 2015.
- Chen, Liang-Chieh, et al. "Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs." IEEE transactions on pattern analysis and machine intelligence 40.4 (2017): 834-848.
- Badrinarayanan, Vijay, Alex Kendall, and Roberto Cipolla. "Segnet: A deep convolutional encoder-decoder architecture for image segmentation." IEEE transactions on pattern analysis and machine intelligence 39.12 (2017): 2481-2495.
- Chen, Liang-Chieh, et al. "Encoder-decoder with atrous separable convolution for semantic image segmentation." Proceedings of the European conference on computer vision (ECCV). 2018.
- Zhao, Hengshuang, et al. "Pyramid scene parsing network." Proceedings of the IEEE conference on computer vision and pattern recognition. 2017.
- Isola, Phillip, et al. "Image-to-image translation with conditional adversarial networks." Proceedings of the IEEE conference on computer vision and pattern recognition. 2017.
- Hazirbas, Caner, et al. "Fusenet: Incorporating depth into semantic segmentation via fusion-based cnn architecture." Asian conference on computer vision. Springer, Cham, 2016.
- Li, Zhen, et al. "Lstm-cf: Unifying context modeling and fusion with lstms for rgb-d scene labeling." European conference on computer vision. Springer, Cham, 2016.

**THANKS FOR YOUR
ATTENTION!**

