



# BSM415M10-54HPH

**182** Bifacial Module With Transparent Backsheet  
10BB Half-cut Mono Perc

## Made In Thailand

**Long Beach, CA Stock**


**All Black, High Aesthetic**

**2M<sup>2</sup> Panel, Best Home Roof Fit**

- Dimensions: 1722\*1134\*30mm
- Weight: 21.5kg
- Max. System Voltage: 1000V/1500 V (IEC/UL)

### GREAT PERFORMANCE AND RELIABILITY

- ★ **10BB Half-cut Cell Technology**  
New circuit design, lower internal current, lower Rs loss  
Ga doped wafer, attenuation < 2% (1st year) / ≤ 0.55% (Linear)
- ★ **Industry Leading High Yield**  
Bifacial PERC cell technology,  
5%-25% more yield depends on different conditions
- ★ **Excellent Anti-PID Performance**  
2 times of industry standard Anti-PID test by TUV SUD
- ★ **Lower LCOE**  
2% more power generation, lower LCOE
- ★ **IP68 Junction Box**  
High waterproof level



### PERFORMANCE WARRANTY

**12** Years Enhanced Product Warranty on Materials and Workmanship\*

**25** Years Linear Power Performance Warranty\*  
\*According to the applicable Bluesun Solar Limited Warranty Statement.

### MANAGEMENT SYSTEM CERTIFICATES

- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems

### PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730



**US Solar Supplier**  
Add: 552 East , Suite 200, Louisville, KY 40205  
Tel: 502-956-0427  
Web: [www.ussolarsupplier.com](http://www.ussolarsupplier.com)



## ELECTRICAL CHARACTERISTICS


Testing Condition	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (P <sub>max</sub> /W)	400	298	405	302	410	306	415	309	420	313
Operating Voltage (V <sub>mpp</sub> /V)	31.05	29.0	31.24	29.2	31.43	29.3	31.63	29.5	31.82	29.7
Operating Current (I <sub>mp</sub> /A)	12.89	10.30	12.97	10.36	13.05	10.42	13.13	10.49	13.21	10.55
Open-Circuit Voltage (V <sub>oc</sub> /V)	37.00	34.8	37.25	35.1	37.50	35.3	37.75	35.6	38.00	35.8
Short-Circuit Current (I <sub>sc</sub> /A)	13.78	11.11	13.86	11.17	13.94	11.24	14.02	11.31	14.10	11.38
Module Efficiency (%)	20.50		20.70		21.00		21.25		21.51	

STC: Irradiance 1000W/m<sup>2</sup>, Spectra at AM1.5, Module Temperature 25°C. Power output tolerance: 0~+5W, Test uncertainty for P<sub>max</sub> : ±3%  
 NMOT: Irradiance 800W/m<sup>2</sup>, Spectra at AM1.5, Ambient Temperature 20 °C, Wind speed 1m/s

## MECHANICAL CHARACTERISTICS

Solar Cell	Monocrystalline 182*182mm
No. of Cells	108 (6*18)
Module Dimensions	1722*1134*30mm (67.80*44.65*1.18inches)
Weight	21.5kg (47.4lbs.)
Front Glass	3.2mm AR Coating Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, 3 Bypass Diodes
Output Cables	4mm <sup>2</sup> (IEC), 12AWG(UL) 300mm in Length or Customized Length
Connectors	T01/LJQ-3-CSY/MC4/MC4-EVO2


## I-V CURVE



## APPLICATION CONDITIONS

Maximun System Voltage	1000V/1500VDC/(IEC)
Operating Temperature	-40°C~+85°C
Maximun Series Fuse	25A
Safety Protection Class	Class II
Mechanical Load	Front side 5400Pa, Back side 2400Pa
Refer. Bifaciality Factor	70%(+5%~-10%)

## TECHNICAL DRAWINGS



## TEMPERATURE CHARACTERISTICS

Temperature Coefficient of P <sub>max</sub>	-0.35%/°C
Temperature Coefficient of V <sub>oc</sub>	-0.26%/°C
Temperature Coefficient of I <sub>sc</sub>	+0.048%/°C
Nominal Module Operating Temperature(NMOT)	43±2°C

## PACKING CONFIGURATION

Pieces Per Pallet	36	36(USA)
Pieces Per Container(40'HQ)	936	828

## US Solar Supplier

Add: 552 East , Suite 200, Louisville, KY 40205

Tel: 502-956-0427

Web: [www.ussolarsupplier.com](http://www.ussolarsupplier.com)

