Power Optimizer

P370 / P401 / P404 / P405 / P485 / P500 / P505

25 YEAR WARRANTY

PV power optimization at the module level

- Specifically designed to work with SolarEdge inverters

- Up to 25% more energy

- Next generation maintenance with module-level monitoring

- Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading

- Superior efficiency (99.5%)

- Flexible system design for maximum space utilization

- Module-level voltage shutdown for installer and firefighter safety

- Fast installation with a single bolt

solaredge.com

solaredge

/ Power Optimizer

P370 / P401 / P404 / P405 / P485 / P500 / P505

OPTIMIZER MODEL (typical module compatibilty)	P370 (60/72 Cell modules)	P401 (For high power 60/72-cell modules)	P404 (for 60/72-cell short strings)	P405 (for high-voltage modules)	P485 (for high-voltage modules)	P500 (for 96-cell modules)	P505 (for higher current modules)	UNIT
INPUT								
Rated Input DC Power[1]	370	400	405	405	485	500	505	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	60		80	125		80	83	Vdc
MPPT Operating Range	8 - 60		12.5 - 80	12.5 - 105		8 - 80	12.5-83	Vdc
Maximum Short Circuit Current (Isc)	11	11.75	11			10.1	14	Adc
Maximum Efficiency	99.5							%
Weighted Efficiency	98.8							%
Overvoltage Category	II							
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREDGE INVERTER)								
Maximum Output Current	15							Adc
Maximum Output Voltage	60		85			60	85	Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREDGE INVERTER OR SOLAREDGE INVERTER OFF)								
Safety Output Voltage per Power Optimizer	1 ± 0.1							Vdc
STANDARD COMPLIANCE								
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3							
Safety	IEC62109-1 (class II safety), UL1741							
RoHS	Yes							
Fire Safety	VDE-AR-E 2100-712:2013-05							
INSTALLATION SPECIFICATIONS								
Maximum Allowed System Voltage	1000							Vdc
Dimensions (W x L x H)	129 x 153 x 27.5 / 5.1 x 6 x 1.1	129 x 153 x29.5 / 5.08 x6.02 x 1.16	129 x 89 x 42.5 / 5.1 x 3.5 x 1.7	129 x 90 x 49.5 / 5.1 x 3.5 x 1.9		129 x 153 x 33.5 / 5.1 x 6 x 1.3	129 x 162 x 59 / 5.1 x 6.4 x 2.3	mm / in
Weight (including cables)	655 / 1.5		775 / 1.7	845 / 1.9		750 / 1.7	1064 / 2.3	gr / lb
Input Connector	MC4[2]				Single or Dual MC4[2][3]	MC4[2]		
Input Wire Length	0.16 / 0.52							m / ft
Output Connector	MC4							
Output Wire Length	1.2 / 3.9							m / ft
Operating Temperature Range	-40 - +85 / -40 - +185							˚C / ˚F
Protection Rating	IP68							
Relative Humidity	0 - 100							%

(1) Rated power of the module at STC will not exceed the optimizer "Rated Input DC Power". Modules with up to +5% power tolerance are allowed.
(2) For other connector types please contact SolarEdge.
(3) For dual version for parallel connection of two modules use the P485. In the case of an odd number of PV modules in one string, installing one P485 dual version power optimizer connected to one PV module is supported. When connecting a single module, seal the unused input connectors using the supplied pair of seals.

PV SYSTEM DESIGN USING A SOLAREDGE INVERTER[4][5]		SINGLE PHASE HD-WAVE	SINGLE PHASE	THREE PHASE	THREE PHASE FOR 277/480V GRID	
Minimum String Length (Power Optimizers)	P370, P401, P500[6]	8		16	18	
	P404, P405, P485, P505	6		14 (13 with SE3K[7])	14	
Maximum String Length (Power Optimizers)		25		50	50	
Maximum Power per String		5700	5250	11250[8]	12750[9]	W
Parallel Strings of Different Lengths or Orientations		Yes				

(4) It is not allowed to mix P404/P405/P485/P505 with P370/P401/P500/P600/P650/P730/P801/P800p/P850/P950 in one string.
(5) For SE15k and above, the minimum DC power should be 11KW.
(6) The P370/P401/P500 cannot be used with the SE3K three phase inverter (available in some countries; refer to the three phase inverter SE3K-SE10K datasheet).
(7) Exactly 10 when using SE3K-RW010BNN4
(8) For the 230/400V grid: it is allowed to install up to 13,500W per string when the maximum power diference between each string is 2,000W.
(9) For the 277/480V grid: it is allowed to install up to 15,000W per string when the maximum power diference between each string is 2,000W

CE