UCC28740 DESIGN CALCULATIONS

The Values Entered by the User on the DESIGN INPUT Page are Used in the Design Calculations

INPUT				
Input Voltage Type	AC or DC:	AC		**User Input Values From Design Input Page**
Minimum Input Voltage	$V_{INPUTmin}$ =	85	VAC	
Maximum Input Voltage	$V_{INPUTmax}$ =	265	VAC	
Nominal Input Voltage	$V_{INPUTnom}$ =	220	VAC	
Minimum Line Frequency	$f_{LINEmin}$ =	47	Hz	
Minimum Input Voltage for Start-Up	$V_{INPUTrun}$ =	80	VAC	
Minimum Peak Bulk Input Voltage	$V_{BULKmin}$ =	120.208	V	
Maximum Peak Bulk Input Voltage	$V_{BULKmax}$ =	374.767	V	
Nominal Peak Bulk Input Voltage	$V_{BULKnom}$ =	311.127	V	
Turn-On Peak Bulk Input Voltage	$V_{BULKstartup}$ =	113.137	V	
Line Cycle Period	t_{LINE} =	21.277	ms	
OUTPUT				
Regulated Output Voltage, Constant Voltage Mode	V_{OUT_CV} =	80	V	**User Input Values From Design Input Page**
Full Load Rated Output Current	I_{OUT} =	0.6	A	
Target Constant Current Mode Output Load Threshold	I_{OCC_target} =	0.65	A	
Target Minimum Output Voltage During Constant Current Regulation	V_{OUT_CC} =	79	V	
Allowable Output Voltage Drop During Load-Step Transient in Constant Voltage Mode	$V_{OUT\Delta}$ =	.0.5	V	
Maximum Peak to Peak Output Voltage Ripple	V_{RIPPLE} =	30	mV	
Required Positive Load Step Transient Current	I_{TRAN} =	0.65	A	
Maximum Allowable Response Time to Load Step Transient	t_{RESP} =	20	ms	
Output Over Voltage Protection	V_{OUT_OVP} =	82	V	
Maximum Stand By Power Dissipation	$P_{SBtarget}$ =	50	mW	
Estimated Efficiency	η =	0.850		
Output Power	P_{OUT} =	52.000	W	
Estimated Input Power	P_{IN} =	61.176	W	

COMPONENT PARAMETER CALCULATIONS

INPUT CAPACITOR, C_{BULK}				
Recommended Input Bulk Capacitance	$C_{BULKrecommended}$ =	237.73	µF	
Actual Input Bulk Capacitance	$C_{BULKactual}$ =	250.000	µF	**User Input**
Input Capacitor Value Used in Calculations	C_{BULK} =	250.000	µF	
Minimum Valley Voltage on Input Bulk Capacitors	$V_{BULKvalley}$ =	100.966	V	
Minimum Input Capacitor Ripple Current Rating	$I_{CINripple}$ =	1429.847	mA	
Minimum Input Capacitor Voltage Rating	V_{Cin} =	400	V	

INPUT FUSE				
Voltage Rating	V_{FUSE} =	265	VAC	
Peak Input Current	I_{INpeak} =	4.011	A	

BRIDGE RECTIFIER				
Voltage Rating	$V_{BRIDGE\_minrating}$ =	400.000	V	
Current Rating	$I_{BRIDGE\_minrating}$ =	1.212	A	
Forward Voltage Drop	V_{F_BRIDGE} =	1.100	V	**User Input**
Full Load Power Dissipation of Bridge Rectifier	P_{BRIDGE} =	3145.663	mW	

TRANSFORMER TURNS-RATIO, N_{PS}				
Demagnetizing Duty Cycle	D_{DEMAG_CC} =	0.425		Device Parameter
Amplitude Modulation Control Ratio	K_{AMnom} =	4		Device Parameter
Maximum Desired Switching Frequency	f_{max_target} =	100.000	kHz	**User Input**
Desired Switching Period	t_{SW_target} =	10.000	µs	
Resonant Frequency During DCM Dead Time	f_{RES} =	0.500	MHz	
Time to First Resonant Valley	t_{RES} =	1.000	µs	
Estimated Maximum Duty Cycle	D_{max_target} =	0.475		

Ideal Primary to Secondary Turns Ratio	$N_{PSideal}$ =	1.3889		Ideal N_{PS}
Actual Primary to Secondary Turns Ratio	$N_{PSactual}$ =	1.389		**User Input**
Primary to Secondary Turns Ratio Used in Calculations	N_{PS} =	1.389		
Actual Flyback Voltage	$V_{FLYBACK}$ =	112.856	V	
Allowable Leakage Inductance Voltage Spike	$V_{LEAKAGE}$ =	312.377	V	
Estimated Maximum On-Time	$t_{ONestimated}$ =	4.750	µs	
Estimated Transformer Efficiency	η_{XFMR} =	0.9		

CURRENT SENSE RESISTOR, R_{CS}, PEAK PRIMARY CURRENT, I_{PP}				
Constant Current Regulation Factor, Minimum	V_{CCR_min} =	318	mV	Device Parameter
Constant Current Regulation Factor, Nominal	V_{CCR_nom} =	330	mV	Device Parameter
Constant Current Regulation Factor, Minimum	V_{CCR_min} =	343	mV	Device Parameter
Initial estimate for L_P	$L_{P\_estimate}$ =	242.003	µH	
Recommended Current Sense Resistor Value	$R_{CSrecommended}$ =	0.329	Ω	
Actual Current Sense Resistor Used	$R_{CSactual}$ =	0.374	Ω	**User Input**
Current Sense Resistor Value Used in Calculation	R_{CS} =	0.374	Ω	
Power Dissipation of R_{CS}	P_{Rcs} =	252.991	mW	
Maximum Current Sense Threshold Voltage, Minimum	V_{CSTmax_min} =	738	mV	Device Parameter
Maximum Current Sense Threshold Voltage, Nominal	V_{CSTmax_nom} =	773	mV	Device Parameter
Maximum Current Sense Threshold Voltage, Maximum	V_{CSTmax_max} =	810	mV	Device Parameter
Peak Primary Current, Minimum, Full Load	I_{PPmin} =	1.973	A	
Peak Primary Current, Nominal, Full Load	**I_{PPnom} =**	**2.067**	**A**	
Peak Primary Current, Maximum, Full Load	I_{PPmax} =	2.166	A	
Actual Output Current During Constant Current Mode	**I_{OCC_actual} =**	**0.610**	**A**	
Peak Primary Current During Light Load, FM Mode	I_{PP_FM} =	0.517	A	
Worst Case Peak Primary Current	I_{PP_WC} =	2.188	A	Assumes -1%R_{CS} and V_{CSTmax_max}
Maximum Output Current During Constant Current Mode	I_{OCCmax} =	0.646	A	Worst Case Estimate

TRANSFORMER PRIMARY INDUCTANCE, L_P				
Calculated L_P to meet f_{max_target} with chosen R_{CS}	L_{Pcalc} =	257.848	µH	
Recommended Primary Inductance to meet t_{CSLEB} with chosen R_{CS}	$L_{Precommended}$ =	257.848	µH	Ideal L_P
Actual Primary Inductance	$L_{Pactual}$ =	257.848	µH	**User Input**
Primary Inductance Used in Calculations	L_P =	257.848	µH	
Actual Maximum Nominal Switching Frequency	**f_{max} =**	**90.000**	**kHz**	
Actual Switching Period	$t_{SWactual}$ =	11.111	µs	
Actual Maximum On-Time	t_{ONmax} =	5.278	µs	
Maximum Duty Cycle	D_{MAX} =	0.475		
Demagnetization Time	t_{DEMAG} =	4.722	µs	
Primary RMS Current	I_{PRI_RMS} =	0.822	A	
Secondary Peak Current	I_{SPmax} =	2.871	A	
Secondary RMS Current	I_{SEC_RMS} =	1.081	A	
VDD Under Voltage Lock Out (UVLO) Voltage, Maximum	VDD_{OFF_max} =	8.150	V	Device Parameter
VDD Under Voltage Lock Out (UVLO) Voltage, Minimum	VDD_{OFF_min} =	7.350	V	Device Parameter
Recommended Auxiliary to Secondary Turns Ratio	$N_{ASrecommended}$ =	0.117		
Recommended Primary to Auxilliary Turns Ratio	$N_{PArecommended}$ =	11.858		
Actual Primary to Auxiliary Turns Ratio	$N_{PAactual}$ =	9.000		**User Input**
Primary to Auxiliary Turns Ratio Used in Calculations	N_{PA} =	9.000		
Nominal VDD Voltage	**VDD =**	**11.290**	**V**	
Actual Auxiliary to Secondary Turns Ratio	N_{AS} =	0.154		
Minimum On-Time, t_{CSLEB}	$t_{ONmin(limit)}$ =	280.000	ns	
Actual Minimum On-Time	$t_{ONmin(actual)}$ =	355.509	ns	
Minimum Demagnetizing Time	$t_{DEMAGmin}$ =	1.181	µs	
Minimum Output Voltage During Constant Current Mode	**V_{OUT_CCmin} =**	**54.474**	**V**	

MOSFET, Q				
Required Drain to Soure Voltage Rating , $V_{DSrated}$ =	V_{DSmin_rating} =	633.910	V	
MOSFET Rated Drain to Source Voltage	V_{DS} =	800.000	V	**User Input Values From Design Input**
Output Capacitance of Selected MOSFET	C_{OSS} =	16	pF	
Drain to Source On-Resistance of Selected MOSFET	R_{DSon} =	0.360	Ω	

MOSFET Fall Time	t_f =	6.000	ns	**Page**
MOSFET Turn Off Delay Time	t_{Doff} =	40	ns	
MOSFET Total Gate Charge	Q_g =	30.000	nC	
Actual Resonant Frequency During DCM Dead Time	f_{RES_actual} =	1.752	MHz	
Actual Estimated Time to First Resonant Valley	t_{RES_actual} =	0.285	µs	
Valley Switching Achieved?	YES or NO	YES		
MOSFET V_{DS} Derating	$V_{DSderated}$ =	0.792		
MOSFET Continuous Current Rating	I_{DRAIN} =	8.705	A	
MOSFET Pulsed Current Rating	I_{PULSED} =	21.877	A	
Estimated MOSFET Conduction Losses	$P_{FETconduction}$ =	0.244	W	
Estimated MOSFET Switching Losses	$P_{FETswitching}$ =	0.322	W	
Total Estimated MOSFET Power Loss	P_{FET} =	0.565	W	
Recommended Clamping Voltage on Drain	$V_{DRAINclamp}$ =	272.377	V	

OUTPUT DIODE, D_{OUT}				
Forward Voltage Drop of Output Rectifier, V_F =	V_F =	1.250	V	**User Input**
Minimum Required Blocking Voltage Rating	$V_{DOUT\_blocking}$ =	547.906	V	
Required Minimum Average Rectified Output Current	I_{Dout} =	1.081	A	
Power Dissipation of D_{OUT}	P_{Dout} =	0.763	W	

AUXILIARY WINDING DIODE, D_{AUX}				
Auxiliary Rectifier Forward Voltage Drop	V_{FA} =	1.250	V	**User Input**
Minimum Required Blocking Voltage Rating	$V_{DBIAS\_blocking}$ =	65.277	V	

OUTPUT INDUCTOR, L_{OUT}				
DCR of Output Inductor	DCR_{Lout} =	0	mΩ	**User Input**

OUTPUT CAPACITOR, C_{OUT}				
Minimum Required C_{OUT} Without Opto-Coupled FeedBack	$C_{OUT\_no\_opto}$ =	#VALUE!	µF	The importance of using opto feedback should be noted here!
Recommended Minimum Required Output Capacitor With Opto-Coupled FeedBack	$C_{OUTrecommended}$ =	470.000	µF	
Actual Output Capacitance Used	$C_{OUTactual}$ =	540.000	µF	**User Input**
C_{OUT} Used in Calculations	C_{OUT} =	540.000	µF	
Required Minimum Ripple Current Rating	$I_{COUTrms}$ =	0.919	A	
Recommended Maximum ESR	$ESR_{Coutrecommended}$ =	10.450	mΩ	
Actual ESR of C_{OUT} Used	$ESR_{Coutactual}$ =	50.000	mΩ	**User Input**
ESR Used in Calculations	ESR_{Cout} =	50.000	mΩ	
Resultant Output Voltage Peak to Peak Ripple	**$V_{OUTripple}$ =**	**143.666**	**mV**	

VOLTAGE SENSE DIVIDER, R_{VS1}, R_{VS2}				
VS Line Sense Run Current, Minimum	I_{VSLrun_min} =	190	µA	Device Parameter
VS Line Sense Run Current, Nominal	I_{VSLrun_nom} =	225	µA	Device Parameter
VS Line Sense Run Current, Maximum	I_{VSLrun_max} =	275	µA	Device Parameter
VS Line Sense Stop Current, Minimum	$I_{VSLstop\_min}$ =	70	µA	Device Parameter
VS Line Sense Stop Current, Nominal	$I_{VSLstop\_nom}$ =	80	µA	Device Parameter
VS Line Sense Stop Current, Maximum	$I_{VSLstop\_max}$ =	100	µA	Device Parameter
Recommended Resistor Value for Minimum Start Up Line Voltage	$R_{VS1recommended}$ =	46.400	kΩ	
Actual Resistor Value Used for Minimum Start Up Line Voltage	$R_{VS1actual}$ =	46.4	kΩ	**User Input**
R_{VS1} Value Used in Calculations	R_{VS1} =	46.4	kΩ	
Resultant Turn On Voltage, Minimum	$V_{TURNONmin}$ =	56.105	VAC	
Resultant Turn On Voltage, Nominal	**$V_{TURNONnom}$ =**	**66.440**	**VAC**	
Resultant Turn On Voltage, Maximum	$V_{TURNONmax}$ =	81.204	VAC	
Resultant Input Brown Out Voltage, Minimum	$V_{BROWNOUTmin}$ =	34.276	VAC	
Resultant Input Brown Out Voltage, Nominal	**$V_{BROWNOUTnom}$ =**	**37.229**	**VAC**	
Resultant Input Brown Out Voltage, Maximum	$V_{BROWNOUTmax}$ =	43.135	VAC	
Internal VS Over Voltage Threshold, Minimum	V_{OVPmin} =	4.52	V	Device Parameter
Internal VS Over Voltage Threshold, Nominal	V_{OVPnom} =	4.600	V	Device Parameter
Internal VS Over Voltage Threshold, Maximum	V_{OVPmax} =	4.710	V	Device Parameter
Recommended Resistor Value for Desired Output Over Voltage Limit	$R_{VS2recommended}$ =	27.400	kΩ	
Actual Resistor Value Used for Desired Output Over Voltage Limit	$R_{VS2actual}$ =	27.400	kΩ	**User Input**
R_{VS2} Used in Calculations	R_{VS2} =	27.400	kΩ	
Resultant Output Over Voltage Threshold, Minimum	V_{OUT_OVPmin} =	80.133	V	
Resultant Output Over Voltage Threshold, Nominal	**V_{OUT_OVPnom} =**	**81.529**	**V**	**Actual Output Over Voltage**
Resultant Output Over Voltage Threshold, Maximum	V_{OUT_OVPmax} =	83.449	V	

LINE COMPENSATION, R_{LC}				
Line Compensation Current Ratio, Nominal	K_{LCnom} =	25	A/A	Device Parameter
Total Estimated Current Sense Delay	t_{DELAY} =	90	ns	
Recommended Resistor Value for Line Compensation	$R_{LCrecommended}$ =	1.330	kΩ	
Actual Resistor Value Used for Line Compensation	$R_{LCactual}$ =	1.330	kΩ	**User Input**
R_{LC} Used in Calculations	R_{LC} =	1.330	kΩ	
Result of R_{LC} selection	**Output Constant Current will have minimal deviation over input line voltage range.**			

VDD CAPACITOR, C_{VDD}				
Device Supply Current During Run Mode, Maximum	I_{RUNmax} =	2.65	mA	Device Parameter
VDD_{ON} Voltage, Maximum	VDD_{ONmax} =	23	V	Device Parameter
VDD_{OFF} Voltage, Maximum	VDD_{OFFmax} =	8.15	V	Device Parameter
Estimated Minimum Switching Frequency at No-Load	f_{SWmin} =	1.162	kHz	
Estimated Over Voltage Charge Duration	t_{OV} =	20.000	ms	
Minimum VDD Capacitor for Start UP	C_{VDD1} =	22.000	µF	
Minimum VDD Capacitor for Load Transient	C_{VDD2} =	15.000	µF	
Minimum VDD Capacitor for Target Ripple on VDD	C_{VDD3} =	2.200	µF	
Recommended Capacitor on VDD	$C_{VDDrecommended}$ =	22.000	µF	

OPTO-COUPLED FEEDBACK				
Reference Voltage of TL431 Shunt Regulator	$VREF_{431}$ =	80	V	**User Input**
Shunt Regulator Reference Input Current, Maximum	I_{REF431} =	10000	µA	**User Input**
Recommended Bottom Resistor Value for Output Voltage Set Point	$R_{FB2recommended}$ =	0.562	kΩ	
Actual Bottom Resistor Value Used for Output Voltage Set Point	$R_{FB2actual}$ =	0.55	kΩ	**User Input**
R_{FB2} Used in Calculations	R_{FB2} =	0.55	kΩ	
Recommended Top Resistor Value for Output Voltage Set Point	$R_{FB1recommended}$ =	Err:502	kΩ	
Actual Top Resistor Value Used for Output Voltage Set Point	$R_{FB1actual}$ =	170	kΩ	**User Input**
R_{FB1} Used in Calculations	R_{FB1} =	170.02	kΩ	
Noise Injection Resistor For Loop Analysis	R_{INJ} =	20	Ω	**May be changed by User here**
Resultant Nominal Constant Voltage Output Voltage	**V_{OUT_CV} =**	**24810.182**	**V**	
Minimum Current Transfer Ratio of Selected Opto-Coupler	CTR_{min} =	50	%	**User Input**
Response Fall Time of Opto-Coupler	t_{f_opto} =	3	µs	**User Input**
R_L of Specified Opto-Coupler Fall Time	R_{L_opto} =	100	Ω	**User Input**
Cut-Off Frequency of Opto-Coupler	f_{c_opto} =	80	kHz	**User Input**
Input Forward Voltage of Opto-Coupler	V_{F_opto} =	1.4	V	**User Input**
Equivalent Opto-Coupler Output Capacitance	C_{OPTO} =	4.775	nF	
Equivalent Internal UCC28740 Dynamic Reistance	R_{EQU} =	40	kΩ	
Recommended Value for External Capacitor on Opto-Coupler	$C_{EXTrecommended}$ =	0	µF	
Actual Value of External Capacitor on Opto-Coupler Used	$C_{EXTactual}$ =	0	µF	**User Input**
C_{EXT} Used in Calculations	C_{EXT} =	0	µF	
Recommended C_{FB}	$C_{FBrecommended}$ =	0.047	µF	
Actual C_{FB} Used	$C_{FBactual}$ =	0.047	µF	**User Input**
C_{FB} Used in Calculations	C_{FB} =	0.047		
Recommended Value For R_{FB4}	$R_{FB4recommended}$ =	22	kΩ	
Actual Value for R_{FB4} Used	$R_{FB4actual}$ =	22	kΩ	**User Input**
R_{FB4} Used in Calculations	R_{FB4} =	22	kΩ	
Opto-Coupler Emitter Current to FB Pin Current Gain	G_{FB1} =	0.355		
FB Pin Current to Control Law Voltage Gain, Full Load	G_{FB2} =	-192	kΩ	
Control Law Voltage to Power Stage Modulation Gain, FM Mode	K_{FM4} =	50.4	kHz/V	
Power Stage Modulation (FM) to Average Current Gain	G_{P4} =	7.222	µC	
Recommeded Value for Shunt Regulator Bias Resistor	$R_{TLrecommended}$ =	1.5	kΩ	
Actual Value of Shunt Regulator Bias Resistor Used	$R_{TLactual}$ =	1.5	kΩ	**User Input**
R_{TL} Used in Calculations	R_{TL} =	1.5	kΩ	
Recommended Value for Compensation Capacitor	$C_{Zrecommended}$ =	1500	pF	
Actual Value Used C_Z	$C_{Zactual}$ =	1500	pF	**User Input**
C_Z Used in Calculations	C_Z =	1500	pF	



RECOMMENDED BILL OF MATERIALS			
Reference Designator	**Description/Comments**		
BRIDGE RECTIFIER	Minimum DC Blocking Voltage:	400 V	
	Minimum Current Rating:	1.212 A	
	Power Dissipation:	3145.663 mW	
$C_{BULKtotal} = C_{BULK1} + C_{BULK2}$	Type:	Aluminum Electrolytic	
	Value:	250 µF	Total Capacitance
	Minimum Voltage Rating:	400 V	
	Minimum Ripple Current Rating:	1429.847 mA	
C_{EXT}	Type:	Ceramic	
	Value:	0 µF	±10%
	Minimum Voltage Rating:	50 V	
C_{FB}	Type:	Ceramic	
	Value:	0.047 µF	±10%
	Minimum Voltage Rating:	10 V	
$C_{OUTtotal} = C_{OUT1} + C_{OUT2}$	Type:	Aluminum Electrolytic	
	Minimum Value:	540 µF	Total Capacitance
	Minimum Voltage Rating:	80.000 V	
	Minimum Ripple Current Rating:	0.919 A	
	Maximum ESR Rating:	10.450 mΩ	
C_{SS431}	Type:	Ceramic	
	Value:	1 µF	±10%
	Minimum Voltage Rating:	10 V	
C_{VDD}	Type:	Ceramic	
	Minimum Value:	22 µF	±10%
	Voltage Rating:	50 V	
C_{Z}	Type:	Ceramic	
	Value:	1500 pF	±10%
	Voltage Rating:	10 V	
D_{AUX}	Type:	Switching	
	Minimum Required Blocking Voltage:	65.277 V	
	Minimum Rated Current:	250 mA	

D_{CLAMP}	Type:	Transient Voltage Suppressor	
	Voltage:	272.377 V	
	Power Rating:	600.000 W	
D_{OUT}	Type:	Schottky	
	Minimum Blocking Voltage Rating:	547.906 V	
	Minimum Average Current Rating:	1.081 A	
	Power Dissipation:	0.763 W	
D_1	Type:	Ultra Fast	
	Voltage Rating:	1000 V	
	Current Rating:	1 A	
FUSE	Type:	Slow Blow	
	Minimum Voltage Rating:	265 VAC	
	Minimum Peak Current Rating:	4.011 A	
OPTO-COUPLER	CTR_{min}:	50 %	
Q	Minimum V_{DS} Voltage Rating:	800 V	
	Minimum Continuous Current Rating:	8.705 A	
	Minimum Repetitive Peak Current Rating:	21.877 A	
	Power Dissipation:	0.565 W	
R_{CS}	Value:	0.374 Ω	±1%
	Power Dissipation:	252.991 mW	
	Type:	Low Inductance	
R_{FB1}	Value:	170 kΩ	±1%
	Power Rating:	1/10 W	
R_{FB2}	Value:	0.55 kΩ	±1%
	Power Rating:	1/10 W	
R_{FB3}	Value:	100 kΩ	±1%
	Power Rating:	1/10 W	
R_{FB4}	Value:	22 kΩ	±1%
	Power Rating:	1/10 W	
R_{INJ}	Value:	20 Ω	±1%
	Power Rating:	1/10 W	
R_{LC}	Value:	1.33 kΩ	±1%
	Power Rating:	1/10 W	
R_{OPT}	Value:	1 kΩ	±1%
	Power Rating:	1/10 W	
R_{TL}	Value:	1.5 kΩ	±1%
	Power Rating:	1/10 W	
R_{VDD}	Value:	2 to 50 Ω	As Needed for Voltage Spike Smoothing
	Power Rating:	1/10 to 1/2 W	
R_{VS1}	Value:	46.4 kΩ	±1%
	Power Rating:	1/10 W	
R_{VS2}	Value:	27.4 kΩ	±1%
	Power Rating:	1/10 W	
SHUNT REGULATOR	Voltage Reference:	80 V	
TRANSFORMER	Primary Inductance:	257.848 µH	
	Primary to Secondary Turns Ratio:	1.389	N_{PS}
	Primary to Auxiliary Turns Ratio:	9.000	N_{PA}
	Peak Primary Current:	2.067 A	
	Primary RMS Current:	0.822 A	
	Peak Secondary Current:	2.871 A	

Secondary RMS Current:	1.081	A
Maximum Switching Frequency:	90.000	kHz