

1	2	3	4	5	6	7	8	
Elément	NOMREPERE	NBRE	UNITES	SOUSQTE	FABRICANT	CATALOGUE	DESCCAT	REQUETE1
				*1	HOFFMAN	A36C30BLP	ELECTRICAL JUNCTION BOX	WALL-MOUNT ENCLOSURE
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	AB	199-DR1	ZINC/STEEL DIN RAIL EN 50022 (35mm x 7.5mm x 1m)	35mm x 7.5mm
				*1	AB	800H-PR16G	GREEN PILOT LIGHT - STANDARD, ROUND OILTIGHT	30.5mm
				*1	AB	800H-PR16G	GREEN PILOT LIGHT - STANDARD, ROUND OILTIGHT	30.5mm
				*1	AB	800H-PR16R	RED PILOT LIGHT - STANDARD, ROUND OILTIGHT	30.5mm
				*1	AB	800H-DR6A	PUSH BUTTON - MUSHROOM, NEMA 4/4X	30.5mm
				*1	AB	800H-BR6A	PUSH BUTTON - MOMENTARY, NEMA 4/4X	30.5mm EXTENDED
				*1	GE	CR115B1	LIMIT SWITCH - INDUSTRIAL	PRECISION SNAP-ACTING
				*1	GE	CR115B1	LIMIT SWITCH - INDUSTRIAL	PRECISION SNAP-ACTING
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	AB	700-P200A1	P TYPE ELECTRICALLY HELD RELAY, 4 POLE, AC COIL, CONVERTIBLE CONTACTS	TYPE P
				*1	SCHNEIDER ELECTRIC	MGN61522	MINIATURE CIRCUIT BREAKER, Multi9 C60H-DC SERIES, C CHARACTERISTIC, DIN RAIL MOUNTING	2-POLE CIRCUIT BREAKER
				*1	AB	199-DR1	ZINC/STEEL DIN RAIL EN 50022 (35mm x 7.5mm x 1m)	35mm x 7.5mm
				*1	AB	140UE-H2S3-D16	IEC MOLDED CASE SWITCH, 160A, H-FRAME, 20...29kA w/140U-H-RVM21R	3-POLE CIRCUIT BREAKER
				*1	AB	140U-H-RVM21R	ROTARY, VARIABLE-DEPTH OPERATING MECHANISM, NEMA 4X, RED/YELLOW HANDLE, 21 IN. (53.34 CM) OPERATING ROD	OPERATING MECHANISM
				*1	AB	199-DR1	ZINC/STEEL DIN RAIL EN 50022 (35mm x 7.5mm x 1m)	35mm x 7.5mm
	-Transfo			*1	SQD	1.5S1F	1PH TRANSFORMER, CLASS 7400	DRY TRANSFORMER

FOLIO 5: NOMENCLATURE