BOT HUNTER

Project Team

Rabab Alvi 22I-1338
Aamna Saeed 22I-1179
Abdullah 22I-1879

Session 2022-2026

Supervised by

Dr. S Qaiser Ali Shah

Co-Supervised by

Dr. Qurrat ul Ain

Department of Computer Science

National University of Computer and Emerging Sciences
Islamabad, Pakistan

June, 2022

Contents

1 Introduction **1**

1.1 Problem Statement 1

1.2 Scope 1

1.3 Problem Solution Workflow 2

1.4 Modules 2

1.4.1 Module 1: Data Collection 2

1.4.2 Module 2: Data Preprocessing and Model Training 3

1.4.3 Module 3: Model-Scraper Integration 4

1.4.4 Module 4: Deployment and Optimization 4

1.5 Work Division 5

2 Project Requirements **6**

2.1 Use Case Model 6

2.1.1 Use Case Description 6

2.1.2 Actors 7

2.1.3 Use Case Diagram 7

2.2 Event Response Table 9

2.3 Functional Requirements 10

2.3.1 Module 1: Data Collection 10

2.3.2 Module 2: Data Preprocessing and Model Training 10

2.3.3 Module 3: Model-Scraper Integration 10

2.3.4 Module 4: Deployment and Optimization 11

2.4 Non-Functional Requirements 11

2.4.1 Reliability 11

2.4.2 Usability 11

2.4.3 Performance 12

2.4.4 Security 12

3 System Overview **13**

3.1 Architectural Design 13

3.1.1 Presentation Layer 13

3.1.2 Application Layer 14

3.1.3 AI Processing Layer 14
3.1.4 Data Layer 15
3.1.5 Architecture Diagram 15
3.1.6 High-Level Workflow 17
3.1.7 Design Pattern 17
3.2 Data Design 17
3.2.1 Database Overview 18
3.2.2 Data Flow Diagram 18
3.2.3 Data Flow Process 20
3.2.4 Data Handling and Storage 20
3.2.5 Backup and Recovery 21
3.2.6 Data Privacy and Compliance 21
3.3 Domain Model 21
3.3.1 Core Entities 21
3.3.2 Entity Relationships 22
3.3.3 Domain Model Diagram 22
3.4 Design Models 24
3.4.1 Activity Diagram 24
3.4.2 Class Diagram 26
3.4.3 Sequence Diagrams 27
3.4.3.1 User-System Interaction (UI Level) 27
3.4.3.2 Backend Processing Flow 27
3.4.4 State Transition Diagram 28

4 Implementation and Testing **30**
4.1 Algorithm Design 30
4.1.1 Algorithm 1 - Feature-Based Classification 30
4.1.2 Algorithm 2 - Username Pattern Analysis 32
4.1.3 Algorithm 3 - Graph Neural Network 32
4.1.4 Complete Training Pipeline 34
4.1.5 Model Evaluation 35
4.2 External APIs/SDKs 36
4.3 Testing Details 37
4.3.1 Unit Testing 37
4.3.1.1 User Authentication Tests 37
4.3.1.2 Bot Detection Functionality Tests 38
4.3.1.3 Navigation and UI Tests 39
4.3.1.4 Performance and Error Handling Tests 40
4.3.2 Integration Testing 41
4.3.3 System Testing 41

5 Conclusion **43**

References **44**

List of Figures

1.1 Problem Solution Workflow of Bot Hunter 3

2.1 Use Case Diagram for Bot Hunter System 8

3.1 Four-Layered Architecture of Bot Hunter System 16
3.2 Data Flow Diagram of Bot Hunter System 19
3.3 Domain Model Diagram of Bot Hunter System 23
3.4 Activity Diagram of Bot Hunter Workflow 25
3.5 Class Diagram of Bot Hunter System 26
3.6 Sequence Diagram of UserSystem Interaction (UI Level) 27
3.7 Sequence Diagram of UserSystem Interaction (Backend Level) 28
3.8 State Transition Diagram of Bot Hunter System 29

List of Tables

1.1 Work Division 5

2.1 EventResponse Table for Bot Hunter System 9

4.1 External APIs and SDKs Used in BotHunter 36
4.2 User Registration and Login Test Cases 37
4.3 Bot Detection and Dashboard Test Cases 38
4.4 User Interface and Navigation Test Cases 39
4.5 Performance and Error Handling Test Cases 40
4.6 Integration Test Cases 41
4.7 System Test Results 42

Chapter 1

Introduction

1.1 Problem Statement

The rise of automated bots on social media has become a significant threat to the integrity of online discussions. Bots are capable of amplifying misinformation, manipulating trends, and shaping public opinion in ways that can have real-world political, social, and economic consequences.

Existing bot detection systems suffer from several limitations:

- Many rely on outdated, static datasets that do not capture the evolving patterns of bot behavior.
- Current solutions often limit themselves to classification and do not provide deeper insight into how bots impact online trends.
- Bots are rapidly evolving, increasingly mimicking human-like behavior, making them difficult to detect with traditional methods.

Thus, there is a critical need for a robust, adaptive, and comprehensive system that not only detects bots but also analyzes their influence on social media ecosystems.

1.2 Scope

The scope of the Bot Hunter project is to design and develop an AI-powered bot detection and analysis platform for social media, particularly X (formerly Twitter). The system will operate within clearly defined boundaries to ensure both feasibility and focus. The main functionality revolves around detecting bot-generated accounts and content, analyzing their impact on trending topics, and visualizing their activities for end-users.

The solution will provide real-time tweet streaming and bot classification using machine learning and transformer-based models. Additionally, it will integrate graph analytics to

detect coordinated behavior among bots and provide anomaly detection to identify unusual activity spikes. A web-based dashboard will be developed to allow researchers, journalists, and analysts to visualize suspicious trends, bot networks, and influence patterns.

Bot Hunter will also support one-click reporting in PDF and CSV formats, enabling easy sharing of findings. The platform focuses on English-language tweets originating from the United States to ensure consistency and relevance in results. The scope excludes multi-language analysis, full geolocation tracking beyond the U.S., and deepfake content detection, as these require additional large-scale resources and datasets beyond the current project limits.

In summary, the project's scope is to deliver a robust, adaptive, and user-friendly system for bot detection, trend monitoring, impact analysis, and visualization, while staying within practical boundaries of time and available resources.

1.3 Problem Solution Workflow

Figure 1.1 illustrates the high-level workflow of the Bot Hunter system, showing how the system addresses the identified problems through systematic data collection, analysis, and visualization.

1.4 Modules

The proposed system consists of multiple modules, each focusing on a specific functionality. The core modules are described below.

1.4.1 Module 1: Data Collection

This module is responsible for gathering and preparing tweets from X (formerly Twitter) for further analysis. It implements an automated scraping pipeline to ensure that relevant and up-to-date data is continuously collected. The collected data serves as the foundation for preprocessing, model training, and analysis in subsequent modules.

Key Features:

1. **Hashtag Identification:** Automatically fetches the top trending hashtags (e.g., Top 5) from X to target current discussions.

2. **Targeted Tweet Collection:** Retrieves tweets associated with each identified hashtag to capture topic-specific content.

3. **Structured Data Storage:** Stores the collected tweets in CSV format to enable easy preprocessing and integration with the database.



Figure 1.1: Problem Solution Workflow of Bot Hunter

4. **Automated Scheduling:** Executes the scraping pipeline periodically (every 24 hours) to keep the dataset continuously updated.

1.4.2 Module 2: Data Preprocessing and Model Training

This module focuses on preparing the collected data and external benchmark datasets (such as TwiBot22) for analysis, as well as training machine learning models for bot

detection. The cleaned and structured data will be stored in a database for efficient access.

Key Features:

1. **Data Preprocessing and Feature Extraction:** Cleaning, normalization, and feature engineering of both TwiBot22 and scraped datasets.
2. **Database Design and Storage:** Designing and implementing a database schema to store structured data, preprocessed results, and model outputs.
3. **Model Training:** Training baseline machine learning and advanced transformer-based NLP models for accurate bot detection.
4. **Web Authentication:** Implementing secure login and signup functionalities to ensure authorized platform access.

1.4.3 Module 3: Model-Scraper Integration

This module integrates the baseline detection model with the data collection pipeline and ensures results are accessible through a user-friendly web platform. It connects the scraper, database, and trained model to the frontend for proper visualization and interaction.

Key Features:

1. **Frontend Web Development:** Designing and implementing a responsive web interface for data visualization and interaction.
2. **Database Integration:** Connecting the web platform to the database to enable efficient querying and retrieval of stored data.
3. **Model Integration:** Incorporating the trained bot detection model into the web application, allowing real-time classification and analysis.

1.4.4 Module 4: Deployment and Optimization

This module ensures the complete system is packaged, deployed, and optimized for reliable performance. It focuses on making the solution production-ready by addressing scalability, efficiency, and usability.

Key Features:

1. **Deployment:** Packaging the system for cloud deployment and scalability.
2. **System Integration:** Combining all modules (data collection, preprocessing, model, and frontend) into a cohesive platform.

3. **Performance Optimization:** Conducting end-to-end testing and applying optimization techniques.

4. **Documentation:** Producing complete technical and project documentation.

1.5 Work Division

For each module and respective feature, responsibilities are distributed among the project team members as shown in Table 1.1.

Table 1.1: Work Division

Name	**Registration**	**Responsibility / Module / Feature**
Abdullah	22i-1879	Frontend development (UI/UX, dashboard, visualizations), deployment and optimization, documentation.
Rabab Alvi	22i-1338	Data preprocessing, feature extraction, model training (ML / Transformers), documentation.
Aamna Saeed	22i-1179	Data collection (scraping pipeline, scheduling, storage), database design and storage, backend API development (FastAPI endpoints), documentation.

Chapter 2

Project Requirements

This chapter describes the functional and non-functional requirements of the project. It outlines the expected behavior, quality attributes, and domain structure of the Bot Hunter system.

2.1 Use Case Model

Since Bot Hunter is an interactive end-user application that provides both frontend visualization and backend analysis, the most suitable requirement representation is a **use case model**. This model highlights how various user classes interact with the system to achieve specific goals. The system focuses on detecting, analyzing, and visualizing bot behavior on X (formerly Twitter).

2.1.1 Use Case Description

Primary Use Cases:

- **UC1: Input Hashtag** User inputs the hashtag for further analysis.
- **UC2: Collect Tweets** The system automatically collects tweets based on trending hashtags to maintain an updated dataset.
- **UC3: Preprocess and Analyze Data** The system cleans, processes, and applies ML models to classify accounts as bots or humans.
- **UC4: Visualize Results** The system displays analysis results (bot percentage, network graphs, trend impact) on an interactive web dashboard.
- **UC5: Interactable Insights** Users interact with analyzed insights on dashboard.
- **UC6: Export Visualizations** Users export visualizations for further use.

- **UC7: Generate Reports** Users can export insights in PDF or CSV format.
- **UC8: Manage User Access** Users can register, log in, and securely access authorized functionalities.
- **UC9: Retrain Model** The analyst can trigger model retraining using new datasets or fine-tuning transformer models.
- **UC10: Manage Datasets** Upload new benchmark datasets (like TwiBot22) or remove outdated data.

2.1.2 Actors

Primary Actors:

- **Researcher/Journalist:** Uses the system to study bot influence, visualize trends, and export findings for reports and publications.
- **Data Analyst:** Maintains models and datasets, triggers retraining, and manages system data quality.

Each actor interacts through a user-friendly web interface backed by automated machine learning pipelines and database operations that run in the background.

2.1.3 Use Case Diagram

Figure 2.1 presents the use case diagram showing the interactions between actors and the system functionalities.



Figure 2.1: Use Case Diagram for Bot Hunter System

2.2 Event Response Table

Table 2.1 describes the system's behavior in response to various events triggered by users, scheduled tasks, or system conditions.

Event	**System Response**
User requests to fetch trending hashtags	The system connects to X (Twitter) API or scraping module, retrieves top trending hashtags, and displays them in the dashboard.
User selects a hashtag for analysis	The system retrieves all related tweets, stores them in the database, and begins preprocessing.
Scheduled data collection trigger (every 24 hours)	The scraper automatically runs, fetches new data for existing hashtags, and appends it to the dataset.
Model training initiated by analyst	The system loads preprocessed data, trains baseline and transformer-based models, and stores the trained model for deployment.
User requests classification results	The system applies the trained model to selected tweet data and returns prediction results (bot/human labels).
User opens dashboard visualization	The system retrieves analysis data and displays network graphs, statistics, and impact metrics dynamically.
User requests report export	The system generates a downloadable PDF or CSV report summarizing bot activity, hashtag trends, and engagement data.
System detects API or network failure	The system logs the error, retries within 5 minutes, and notifies the admin if the issue persists.
Admin deploys or updates system	The system containerizes updated modules, redeploys services to the cloud, and validates functionality post-deployment.

Table 2.1: EventResponse Table for Bot Hunter System

2.3 Functional Requirements

The following subsections describe the functional requirements organized by modules of the proposed system.

2.3.1 Module 1: Data Collection

1. **FR1.1:** The system shall automatically identify and fetch the top trending hashtags from X (formerly Twitter) every 24 hours.
2. **FR1.2:** The system shall collect tweets associated with the selected hashtags using the Twitter scraping API or streaming pipeline.
3. **FR1.3:** The system shall store collected tweets in a structured CSV format.
4. **FR1.4:** The system shall maintain a timestamped log of all data collection sessions for traceability.

2.3.2 Module 2: Data Preprocessing and Model Training

1. **FR2.1:** The system shall clean and normalize raw tweet data by removing duplicates, URLs, and irrelevant symbols.
2. **FR2.2:** The system shall perform feature extraction (e.g., linguistic, behavioral, and metadata-based features).
3. **FR2.3:** The system shall train baseline ML models (Logistic Regression, Random Forest) and transformer-based NLP models (e.g., BERT) for bot classification.
4. **FR2.4:** The system shall store preprocessed data and model outputs in a relational database.
5. **FR2.5:** The system shall provide authentication features (user registration and login).

2.3.3 Module 3: Model-Scraper Integration

1. **FR3.1:** The system shall integrate the trained bot detection model with the tweet scraping module to allow real-time classification.
2. **FR3.2:** The system shall connect the backend with the frontend interface to display model predictions interactively.
3. **FR3.3:** The system shall provide visual representations such as charts, graphs, and bot network structures.

4. **FR3.4:** The system shall allow users to filter, search, and query results by hashtags or user accounts.

2.3.4 Module 4: Deployment and Optimization

1. **FR4.1:** The system shall be containerized and deployed on the cloud for scalability and accessibility.
2. **FR4.2:** The system shall perform continuous integration and testing to ensure stability across updates.
3. **FR4.3:** The system shall support PDF and CSV export functionality for analytical reporting.
4. **FR4.4:** The system shall monitor performance metrics and optimize response times across modules.

2.4 Non-Functional Requirements

2.4.1 Reliability

- **NFR-R1:** The system shall have a Mean Time Between Failures (MTBF) of at least 30 days.
- **NFR-R2:** The system shall implement data validation and error logging to detect and recover from failures.
- **NFR-R3:** In case of network or API failure, the system shall retry collection within 5 minutes and notify the administrator.

2.4.2 Usability

- **NFR-U1:** The dashboard interface shall be designed for intuitive navigation with minimal user training.
- **NFR-U2:** Users shall be able to visualize bot activity with no more than three clicks from the main page.
- **NFR-U3:** Data export and filtering functions shall be accessible directly from the visualization panel.
- **NFR-U4:** The system shall allow a user to retrieve previously analyzed hashtags with a single interaction.

2.4.3 Performance

- **NFR-P1:** 90% of API responses for visualization requests shall complete within 3 seconds under normal load.
- **NFR-P2:** The model classification pipeline shall process at least 100 tweets per second.
- **NFR-P3:** The dashboard shall render all data visualizations completely within 5 seconds on a 20 Mbps connection.

2.4.4 Security

- **NFR-S1:** The system shall require user authentication before accessing any analysis or visualization features.
- **NFR-S2:** All communication between frontend, backend, and database shall use HTTPS encryption.
- **NFR-S3:** The system shall protect stored credentials through salted hashing and secure token-based sessions.
- **NFR-S4:** Administrative access shall be restricted to authorized personnel through role-based permissions.

Chapter 3

System Overview

This chapter provides a high-level overview of the Bot Hunter system, describing its functionality, architectural design, and data organization. It outlines how different system modules collaborate to detect, analyze, and visualize social media bots, ensuring scalability, adaptability, and ease of use.

Bot Hunter is an AI-powered platform designed to detect automated bot accounts on social media (specifically X, formerly Twitter) and analyze their influence on trending topics. It integrates machine learning, graph analytics, and web-based visualization to provide actionable insights to researchers, journalists, and analysts. The system automates data collection, preprocessing, model training, analysis, and visualization under a modular design.

3.1 Architectural Design

The architectural design of Bot Hunter follows a **four-layered architecture** that ensures clear separation of concerns, scalability, and maintainability. Each layer has distinct responsibilities and communicates with adjacent layers through well-defined interfaces.

3.1.1 Presentation Layer

The Presentation Layer serves as the user-facing interface of the system. It consists of four main components:

- **Web Dashboard:** A responsive web interface built using React or Vue.js that provides users with an intuitive platform to interact with the system.
- **Visualizations:** Interactive visual components including charts, graphs, and bot network diagrams that help users understand bot activity patterns and trends.
- **Report Export:** Functionality that allows users to generate and download analysis

results in PDF or CSV formats for sharing and further analysis.

- **Authentication:** Secure login and signup interface that manages user access and ensures authorized usage of the platform.

All components in this layer communicate with the Application Layer through API calls, sending user requests and receiving processed data for display.

3.1.2 Application Layer

The Application Layer acts as the intermediary between the user interface and the backend processing systems. It contains:

- **REST API:** Built using Flask or FastAPI, this component serves as the central communication hub, handling all incoming requests from the Presentation Layer and routing them to appropriate services.
- **API Endpoints:** A collection of RESTful endpoints that handle specific functionalities such as bot detection requests, trend analysis queries, report generation, and user management operations.

This layer receives requests from the Presentation Layer, processes them, and forwards them to either the AI Processing Layer for analysis or directly to the Data Layer for data retrieval and storage. It ensures proper request validation, error handling, and response formatting.

3.1.3 AI Processing Layer

The AI Processing Layer is the intelligence core of the system, responsible for all machine learning and analytical operations:

- **Data Preprocessing:** The first step in the AI pipeline, this component cleans raw data, removes noise, handles missing values, and extracts relevant features that will be used by the models.
- **ML & Transformer Models:** This component houses both traditional machine learning models (such as Logistic Regression and Random Forest) and advanced transformer-based models (like BERT and RoBERTa) that classify accounts as bots or humans based on their behavioral patterns and content.
- **Graph Analytics:** Using NetworkX and graph neural networks, this component analyzes relationships between accounts to identify coordinated bot networks and detect suspicious patterns of interaction.

- **Anomaly Detection:** This component monitors for unusual spikes in activity, sudden changes in posting patterns, or other anomalies that might indicate bot-driven manipulation campaigns.

The preprocessing component receives raw data from the Database, processes it, and feeds it to the various models. After analysis, all models store their predictions and results back into the Database for persistence and future reference.

3.1.4 Data Layer

The Data Layer manages all data storage, retrieval, and collection operations:

- **Data Collection:** An automated pipeline that includes the tweet scraper and trending hashtag fetcher. It continuously collects tweets based on the top 5 trending hashtags, scheduled to run every 24 hours to maintain an updated dataset.
- **Database (MongoDB Atlas):** A relational database that serves as the central data repository, storing tweets, user information, extracted features, model predictions, and analysis results. It ensures efficient data retrieval and long-term persistence.
- **Benchmark Datasets:** Integration of established datasets like TwiBot22, which are used for model training and validation to ensure the system can detect various types of bot behaviors.

The Data Collection component fetches data from external sources and stores it in the Database. The Database then serves as both a source for the AI Processing Layer (providing data for analysis) and a sink (receiving processed results and predictions). This bidirectional flow enables continuous learning and improvement of the system.

3.1.5 Architecture Diagram

Figure 3.1 illustrates the four-layered architecture of the Bot Hunter system, showing the interaction between Presentation, Application, AI Processing, and Data layers.



Figure 3.1: Four-Layered Architecture of Bot Hunter System

3.1.6 High-Level Workflow

The typical data flow through the system follows this pattern:

1. **Collection:** Data is collected from external sources (X/Twitter API) through automated scrapers and stored in the Database.

2. **Processing:** The AI Processing Layer retrieves data from the Database, preprocesses it, and runs various analyses including bot classification, graph analytics, and anomaly detection.

3. **Storage:** Analysis results and model predictions are stored back in the Database for persistence and future reference.

4. **Request:** Users interact with the Presentation Layer, which sends requests through the Application Layer's REST API.

5. **Response:** The Application Layer retrieves relevant data from the Database or triggers new analyses, then returns formatted results to the Presentation Layer for visualization.

This modular architecture ensures that each layer can be developed, tested, and scaled independently while maintaining clear communication channels between components. The separation of concerns allows for easier maintenance, debugging, and future enhancements to the system.

3.1.7 Design Pattern

The system follows the principles of the **Model-View-Controller (MVC)** pattern:

- **Model:** Represents the data, preprocessing logic, and machine learning models.

- **View:** The interactive web dashboard displaying results and graphs.

- **Controller:** The backend API managing communication between frontend and data layers.

3.2 Data Design

The data design defines how the system's information domain is transformed into structured data entities. The system stores and manages both structured and unstructured data efficiently for real-time analysis.

3.2.1 Database Overview

Bot Hunter uses a relational database (MongoDB Atlas) to manage data storage and relationships. The key tables include:

- **Tweets:** Stores collected tweet text, user ID, hashtag, timestamp, and engagement metrics.
- **Users:** Contains registered system users with encrypted credentials and roles.
- **Models:** Stores metadata about trained models, including model version and accuracy metrics.
- **Predictions:** Records classification results (bot/human) and confidence scores.
- **Reports:** Stores downloadable report metadata (format, timestamp, author).
- **Hashtags:** Maintains trending hashtags with associated metadata.
- **Features:** Stores extracted features from tweets for model input.

3.2.2 Data Flow Diagram

Figure 3.2 illustrates the flow of data through the Bot Hunter system from collection to visualization.



Figure 3.2: Data Flow Diagram of Bot Hunter System

3.2.3 Data Flow Process

1. The user enters a hashtag through the web interface, which is received by the Dashboard Controller.

2. The Dashboard Controller communicates with the Database to check for existing data or trigger new data collection.

3. The Scraper automatically collects tweets based on trending hashtags, while the Dataset (TwiBot22) provides benchmark data. Both sources feed into the Database.

4. Data from the Database is retrieved and processed by the Model, which performs preprocessing, feature extraction, and bot classification using ML and Transformer models.

5. The Model generates classification results and sends them to the Report Generator.

6. The Report Generator prepares visualizations, analytics, and exportable reports (PDF/CSV format).

7. Finally, the Dashboard displays the results on the UI, presenting bot percentages, network graphs, trend analysis, and interactive insights to the user.

3.2.4 Data Handling and Storage

All sensitive user data is securely stored using encryption techniques. Tweets and model outputs are indexed for quick search and retrieval. The use of relational keys ensures data integrity across modules (e.g., Tweets linked to Hashtags and Predictions).

Key Data Handling Practices:

- **Data Encryption:** All sensitive information including user credentials and API keys are encrypted at rest and in transit.

- **Data Indexing:** Database tables are indexed on frequently queried fields (hashtags, timestamps, user IDs) to optimize performance.

- **Data Normalization:** The database follows third normal form (3NF) to eliminate redundancy and ensure consistency.

- **Data Validation:** Input validation is performed at multiple layers to prevent SQL injection and data corruption.

3.2.5 Backup and Recovery

Automated data backup routines are scheduled periodically to prevent data loss. Backups are stored on the cloud and can be restored in case of system failure.

Backup Strategy:

- **Daily Incremental Backups:** Changes made during the day are backed up every 24 hours.
- **Weekly Full Backups:** Complete database snapshots are taken weekly and stored for 30 days.
- **Disaster Recovery:** Backup files are stored in geographically distributed cloud locations to ensure availability during regional outages.
- **Recovery Testing:** Backup restoration procedures are tested monthly to ensure data can be recovered within the target Recovery Time Objective (RTO) of 4 hours.

3.2.6 Data Privacy and Compliance

The system adheres to data protection regulations and best practices:

- **User Consent:** Users are informed about data collection and usage through clear privacy policies.
- **Data Minimization:** Only necessary data is collected and stored; unnecessary metadata is discarded.
- **Right to Deletion:** Users can request deletion of their account and associated data.
- **Anonymization:** Publicly shared datasets are anonymized to protect user identities.

3.3 Domain Model

The domain model of the Bot Hunter system represents the key entities, their relationships, and the data flow among them.

3.3.1 Core Entities

- **User:** Represents system users (researchers, journalists, analysts, or admins) with authentication credentials and roles.
- **Tweet:** Contains textual content, metadata, author details, timestamp, and hashtag associations.

- **Bot Detection Model:** Represents the trained machine learning model responsible for classifying accounts as bots or humans.
- **Hashtag:** Stores trending topics retrieved from X, linked to multiple tweets.
- **Report:** Represents generated output summaries in PDF or CSV format.
- **Visualization:** Represents dynamic charts, graphs, and network maps rendered on the dashboard.
- **Classification Result:** Stores the output of bot detection analysis including bot scores and confidence levels.
- **Dataset:** Represents benchmark datasets like TwiBot22 used for model training and validation.

3.3.2 Entity Relationships

- A **User** can analyze multiple **Hashtags**.
- Each **Hashtag** is associated with multiple **Tweets**.
- Each **Tweet** is analyzed by the **Bot Detection Model**.
- The model produces **Classification Results** that feed into the **Visualization** module.
- Users can generate **Reports** summarizing the results.
- **Bot Detection Model** is trained on **Dataset**.
- **Visualization** is included in **Report**.

3.3.3 Domain Model Diagram

Figure 3.3 illustrates the domain model showing all entities, their attributes, methods, and relationships.



Figure 3.3: Domain Model Diagram of Bot Hunter System

3.4 Design Models

Bot Hunter follows an **object-oriented design approach**, emphasizing modularity and reusability across components. The following UML diagrams describe its logical flow, object interactions, and behavioral dynamics.

3.4.1 Activity Diagram

The activity diagram represents the overall workflow of the systemstarting from tweet collection, data preprocessing, model classification, visualization, and report generation. It emphasizes the sequential and conditional flow between different stages of bot detection and analysis.

Figure 3.4 shows the complete activity flow from user input to final report generation.



Figure 3.4: Activity Diagram of Bot Hunter Workflow

3.4.2 Class Diagram

The class diagram defines the structure of key entities within the system, including their attributes, methods, and relationships. Major classes include:

- **Tweet:** Represents a tweet object containing content, author details, and timestamp.
- **User:** Represents system users with authentication credentials and assigned roles.
- **Model:** Represents machine learning models used for bot classification.
- **Database:** Handles structured storage and query operations.
- **Dashboard:** Manages visualization and interaction components.

Relationships such as inheritance, composition, and association are used to model interdependencies among these classes. Figure 3.5 presents the complete class structure of the system.



Figure 3.5: Class Diagram of Bot Hunter System

3.4.3 Sequence Diagrams

The sequence diagrams show the interaction between major classes (User, Model, Database, Dashboard) during runtime. They capture how user requests flow through the systemfrom initiating a data query to retrieving predictions and rendering the final visualization on the dashboard.

3.4.3.1 User-System Interaction (UI Level)

Figure 3.6 illustrates the sequence of interactions at the user interface level, showing how user actions trigger system responses.



Figure 3.6: Sequence Diagram of UserSystem Interaction (UI Level)

3.4.3.2 Backend Processing Flow

Figure 3.7 demonstrates the backend processing flow, detailing the interactions between database, models, and API services.



Figure 3.7: Sequence Diagram of UserSystem Interaction (Backend Level)

3.4.4 State Transition Diagram

The state transition diagram illustrates how the system transitions between states based on user or system-triggered events. Key states include:

- **Idle:** System waiting for user request or scheduled task
- **Authenticating:** User login/signup process
- **Data Collection:** Scraping tweets from trending hashtags
- **Preprocessing:** Cleaning and preparing data
- **Model Analysis:** Running ML models, graph analytics, and anomaly detection
- **Visualization Ready:** Results prepared for display
- **Displaying Dashboard:** User viewing results
- **Generating Report:** Exporting PDF/CSV
- **Report Ready:** Export complete

Transitions occur based on event triggers such as user interactions, API responses, or scheduled tasks. Figure 3.8 shows all possible state transitions in the system.



Figure 3.8: State Transition Diagram of Bot Hunter System

Chapter 4

Implementation and Testing

Give a general description of the functionality, context, and design of your project. Provide any background information if necessary.

4.1 Algorithm Design

Following are the algorithms used in the BotHunter system for Twitter bot detection.

4.1.1 Algorithm 1 - Feature-Based Classification

This algorithm employs Random Forest classification with engineered features extracted from user profiles to identify bot accounts.

Algorithm 1 Feature Extraction and Classification

```
procedure BOTHUNTER(U)
    F ← ∅                                                   ▷ Initialize feature matrix
    for each user u_i in U do
        f_i ← EXTRACTFEATURES(u_i)
        F ← F ∪ {f_i}
    end for
    (F_train, F_test, L_train, L_test) ← SPLITDATA(F, L, 0.8)
    F_train ← NORMALIZE(F_train)
    F_test ← NORMALIZE(F_test)
    model ← RANDOMFOREST(n_estimators = 100, max_depth = 20)
    model.FIT(F_train, L_train)
    L_pred ← model.PREDICT(F_test)
    metrics ← EVALUATE(L_test, L_pred)
    return model, metrics
end procedure
```

Algorithm 2 Feature Extraction Function

```
function EXTRACTFEATURES(user)
    features ← ∅
                                                    ▷ Temporal Features
    account_age ← CURRENTDATE − user.created_at
    features.account_age_days ← account_age.days
                                                    ▷ Activity Features
    features.followers_count ← user.public_metrics.followers
    features.following_count ← user.public_metrics.following
    features.tweet_count ← user.public_metrics.tweets
                                                    ▷ Behavioral Ratios
    features.followers_following_ratio ← user.followers / (user.following+1)
    features.tweets_per_day ← user.tweet_count / (account_age.days+1)
                                                    ▷ Profile Characteristics
    features.verified ← BOOLTOINT(user.verified)
    features.default_profile ← BOOLTOINT(user.default_profile)
                                                    ▷ Text Features
    features.name_length ← LENGTH(user.name)
    features.description_length ← LENGTH(user.description)
                                                    ▷ Username Analysis
    digit_count ← COUNTDIGITS(user.username)
    features.digit_ratio ← digit_count / (LENGTH(user.username)+1)
    return features
end function
```

4.1.2 Algorithm 2 - Username Pattern Analysis

This algorithm analyzes username and display name patterns using Logistic Regression to identify bot accounts based on naming conventions.

Algorithm 3 Username Pattern Analysis

```
procedure NameBot(U)
    F ← ∅
    for each user u_i in U do
        f_i ← ExtractNameFeatures(u_i)
        F ← F ∪ {f_i}
    end for
    (F_train, F_test, L_train, L_test) ← SplitData(F, L, 0.8)
    scaler ← StandardScaler
    F_train_scaled ← scaler.FitTransform(F_train)
    F_test_scaled ← scaler.Transform(F_test)
    model ← LogisticRegression(max_iter = 1000)
    model.Fit(F_train_scaled, L_train)
    L_pred ← model.Predict(F_test_scaled)
    return model, Evaluate(L_test, L_pred)
end procedure
```

Algorithm 4 Name-Based Feature Extraction

```
function ExtractNameFeatures(user)
    features ← ∅
    username ← Lowercase(user.username)
    display_name ← Lowercase(user.name)
    features.username_length ← Length(username)
    features.name_length ← Length(display_name)
    username_digits ← CountDigits(username)
    features.username_digit_ratio ← username_digits / (Length(username) + 1)
    features.username_has_bot ← Contains(username, "bot")
    features.name_has_bot ← Contains(display_name, "bot")
    name_chars ← Set(display_name)
    username_chars ← Set(username)
    features.similarity ← |name_chars ∩ username_chars| / (|name_chars ∪ username_chars| + 1)
    features.username_underscores ← Count(username, "_")
    features.has_year ← RegexMatch(username, "19\d{2}|20\d{2}")
    return features
end function
```

4.1.3 Algorithm 3 - Graph Neural Network

This algorithm leverages Relational Graph Convolutional Networks to analyze both user features and graph structure for enhanced bot detection.

Algorithm 5 Training and Classification

```
1:  procedure BotRGCN(G, X, Y, epochs)
2:      H^(0) ← EncodeNodeFeatures(X)
3:      model ← InitializeBotRGCN
4:      optimizer ← Adam(model.parameters, lr = 0.001)
5:      for epoch = 1 to epochs do
6:                                          ▷ Forward Pass - Graph Convolution Layers
7:          for layer l = 1 to L do
8:              H^(l) ← ∅
9:              for each relation type r in R do
10:                 H_r^(l) ← RGCNLayer(H^(l−1), G_r, W_r^(l))
11:             end for
12:             H^(l) ← Aggregate({H_r^(l) | r ∈ R})
13:             H^(l) ← ReLU(H^(l))
14:             H^(l) ← Dropout(H^(l), p = 0.5)
15:         end for
16:                                                          ▷ Classification
17:         logits ← LinearLayer(H^(L))
18:         predictions ← Softmax(logits)
19:                                          ▷ Compute Loss and Backpropagate
20:         loss ← −Σ_i [y_i log(p_i) + (1 − y_i) log(1 − p_i)]
21:         loss.Backward
22:         optimizer.Step
23:         optimizer.ZeroGrad
24:         if epoch mod 5 = 0 then
25:             val_metrics ← Evaluate(predictions, Y_val)
26:         end if
27:     end for
28:     return model
29: end procedure
```

Algorithm 6 Relational Graph Convolution Layer

```
function RGCNLayer(H, G_r, W_r)
    H_new ← Zeros(|V|, d)
    for each node v_i in V do
        N_r(v_i) ← Neighbors(v_i, relation = r)
        if |N_r(v_i)| > 0 then
            h_neighbors ← 1/|N_r(v_i)| × Σ_{j∈N_r(v_i)} h_j
            h_new_i ← W_r × (h_i + h_neighbors)
        else
            h_new_i ← W_r × h_i
        end if
        H_new[i] ← h_new_i
    end for
    return H_new
end function
```

4.1.4 Complete Training Pipeline

Algorithm 7 Integrated Bot Detection Training Pipeline

```
procedure TrainingPipeline(D)
    (D_train, D_test) ← SplitData(D, 0.8)
    D_train ← PreprocessData(D_train)
    D_test ← PreprocessData(D_test)
    results ← ∅
                                                    ▷ Train BotHunter on CPU
    start ← CurrentTime
    M_BH, metrics_BH ← BotHunter(D_train.users)
    results["BotHunter"] ← {model : M_BH, metrics : metrics_BH}
                                                    ▷ Train NameBot on CPU
    M_NB, metrics_NB ← NameBot(D_train.users)
    results["NameBot"] ← {model : M_NB, metrics : metrics_NB}
                                                    ▷ Train BotRGCN on GPU
    if GPUAvailable then
        M_RGCN ← BotRGCN(D_train.graph, D_train.features, D_train.labels, 50)
        predictions ← M_RGCN.Predict(D_test)
        metrics_RGCN ← Evaluate(D_test.labels, predictions)
        results["BotRGCN"] ← {model : M_RGCN, metrics : metrics_RGCN}
    end if
    best_model ← SelectBestModel(results, "f1_score")
    SaveModels(results)
    return results, best_model
end procedure
```

4.1.5 Model Evaluation

Algorithm 8 Performance Evaluation Metrics

```
function EVALUATE(y_true, y_pred)
    TP ← COUNT(y_true = 1 ∧ y_pred = 1)
    TN ← COUNT(y_true = 0 ∧ y_pred = 0)
    FP ← COUNT(y_true = 0 ∧ y_pred = 1)
    FN ← COUNT(y_true = 1 ∧ y_pred = 0)
    accuracy ← (TP+TN)/(TP+TN+FP+FN)
    precision ← TP/(TP+FP)
    recall ← TP/(TP+FN)
    f1_score ← (2×precision×recall)/(precision+recall)
    return {accuracy, precision, recall, f1_score}
end function
```

Where: n = users, m = features, L = GNN layers, $|E|$ = edges, $|V|$ = vertices, d = hidden dimension.

4.2 External APIs/SDKs

The BotHunter system utilizes several third-party APIs and SDKs for data collection, model implementation, and training. The following table describes each external dependency used in the project implementation.

Table 4.1: External APIs and SDKs Used in BotHunter

API and Version	Description	Purpose of Usage	API Endpoint/Function/Class Used
Hugging Face Transformers (v4.30.0)	Pre-trained natural language processing models library	Text embedding generation using RoBERTa for user descriptions and tweet content analysis	transformers.RobertaModel, transformers.RobertaTokenizer, transformers.AutoModel
PyTorch (v2.0.1)	Deep learning framework for neural network implementation	Building and training neural network models, tensor operations, GPU acceleration	torch.nn.Module, torch.optim.Adam, torch.nn.functional
PyTorch Geometric (v2.3.0)	Graph neural network library for PyTorch	Implementing BotRGCN graph convolution layers and heterogeneous graph processing	torch_geometric.nn.RGCNConv, torch_geometric.data.HeteroData, torch_geometric.loader.NeighborLoader
Scikit-learn (v1.3.0)	Comprehensive machine learning library for Python	Training traditional ML models (BotHunter, NameBot), data preprocessing, and evaluation metrics	sklearn.ensemble.RandomForestClassifier, sklearn.linear_model.LogisticRegression, sklearn.preprocessing.StandardScaler, sklearn.model_selection.train_test_split
Pandas (v2.0.3)	Data manipulation and analysis library	Loading and processing dataset files (CSV, JSON), feature engineering, and data transformation	pandas.read_csv, pandas.read_json, pandas.DataFrame, pandas.merge
NumPy (v1.24.3)	Numerical computing library for array operations	Mathematical operations, array manipulations, and numerical feature calculations	numpy.array, numpy.mean, numpy.std, numpy.nan_to_num
Matplotlib (v3.7.1)	Data visualization library	Creating performance plots, confusion matrices, and training curves for model evaluation	matplotlib.pyplot.plot, matplotlib.pyplot.bar, matplotlib.pyplot.savefig
TwiBot-22 Dataset API	Official TwiBot-22 benchmark dataset access	Loading labeled Twitter bot detection dataset with user profiles, tweets, and graph structure	Dataset loader functions from TwiBot-22 repository
Joblib (v1.3.1)	Python library for model serialization	Saving and loading trained models for deployment and inference	joblib.dump, joblib.load

4.3 Testing Details

Once the system has been successfully developed, testing has to be performed to ensure that the system is working as intended. The following sections detail the various testing methodologies applied to the BotHunter system.

4.3.1 Unit Testing

Each unit test is designed to test a specific function or method independently from other components, helping to identify issues directly related to the functionality being tested. The following tables present comprehensive unit tests for the BotHunter web application.

4.3.1.1 User Authentication Tests

Table 4.2: User Registration and Login Test Cases

Test ID	Test Objective	Precondition	Steps	Test Data	Expected Result	Post-condition	Actual Result	Pass/Fail
TC001	Verify user registration with valid credentials	User should be on registration page	1. Enter full name 2. Enter valid email 3. Enter password 4. Confirm password 5. Accept terms 6. Click "Create Account"	Full Name: Abdullah Email: abd12@gmail.com Password: 123456 Confirm: 123456	System creates account and redirects to dashboard	User account created successfully	As Expected	Pass
TC002	Verify registration with mismatched passwords	User should be on registration page	1. Enter full name 2. Enter valid email 3. Enter password 4. Enter different confirm password 5. Click "Create Account"	Full Name: Test User Email: test@gmail.com Password: 123456 Confirm: 654321	System displays "Passwords do not match" error	User remains on registration page	As Expected	Pass
TC003	Verify registration with invalid email format	User should be on registration page	1. Enter full name 2. Enter invalid email 3. Enter password 4. Click "Create Account"	Full Name: Test User Email: invalidemail Password: 123456	System displays "Invalid email format" error	User remains on registration page	As Expected	Pass
TC004	Verify user login with valid credentials	User should be registered and on login page	1. Enter registered email 2. Enter correct password 3. Click "Sign In"	Email: abd12@gmail.com Password: 123456	System authenticates user and redirects to dashboard	User logged in successfully	As Expected	Pass
TC005	Verify login with incorrect password	User should be registered and on login page	1. Enter registered email 2. Enter wrong password 3. Click "Sign In"	Email: abd12@gmail.com Password: wrongpass	System displays "Invalid credentials" error	User remains on login page	As Expected	Pass
TC006	Verify "Forgot Password" functionality	User should be on login page	1. Click "Forgot password?" 2. Enter registered email 3. Click submit	Email: abd12@gmail.com	System sends password reset email	Reset link sent to user email	As Expected	Pass
TC007	Verify terms acceptance checkbox	User should be on registration page	1. Fill all fields 2. Leave terms checkbox unchecked 3. Click "Create Account"	All valid registration data	System displays "Please accept terms" error	Registration blocked	As Expected	Pass
TC008	Verify password visibility toggle	User should be on login/registration page	1. Enter password 2. Click eye icon	Password: 123456	Password text toggles between visible and hidden	Password visibility changed	As Expected	Pass

4.3.1.2 Bot Detection Functionality Tests

Table 4.3: Bot Detection and Dashboard Test Cases

Test ID	Test Objective	Precondition	Steps	Test Data	Expected Result	Post-condition	Actual Result	Pass/Fail
TC009	Verify new bot scan initiation	User logged in and on dashboard	1. Click "NEW SCAN" button 2. Enter Twitter username 3. Click "Start Scan"	Username: @test_user	System initiates bot detection scan	Scan begins processing	As Expected	Pass
TC010	Verify dashboard statistics display	User logged in and on dashboard	1. Navigate to dashboard 2. Observe metrics	N/A	Dashboard displays: - Bots Detected - Active Networks - Tweets Analyzed - Accuracy Rate	All metrics visible and accurate	As Expected	Pass
TC011	Verify real-time bot detection updates	User on dashboard with active scan	1. Start new scan 2. Observe "Scanning network traffic..." animation 3. Wait for completion	Sample Twitter data	System shows real-time scanning progress and updates statistics	Statistics updated in real-time	As Expected	Pass
TC012	Verify Recent Detections list	User logged in, bots detected	1. Navigate to dashboard 2. Check "Recent Detections" section	Multiple bot accounts detected	System displays list with: - Username - Bot type badge - Risk level - Time detected	Recent detections visible	As Expected	Pass
TC013	Verify bot risk classification	System detects bot account	1. Complete bot scan 2. Check risk level	Bot account data	System classifies as: - High Risk (red) - Critical (red) - Medium Risk (orange) - Low Risk (yellow)	Correct risk classification displayed	As Expected	Pass
TC014	Verify bot type identification	System detects bot account	1. Complete bot scan 2. Check bot type badge	Various bot types	System identifies: - Spam Bot - Coordinated Bot - Engagement Bot - Fake Account - Trend Bot	Correct bot type labeled	As Expected	Pass
TC015	Verify "View All" detections functionality	User on dashboard with multiple detections	1. Click "View All" in Recent Detections 2. Navigate to full list	Multiple detected bots	System displays complete list of all detected bots	Full detection list shown	As Expected	Pass
TC016	Verify Bot Activity by Topic chart	User logged in on dashboard	1. Navigate to dashboard 2. Observe "Bot Activity by Topic" chart	Bot activity data	Chart displays: - #ElectionNews (34% bots) - #CryptoUpdate (28% bots) - #BreakingNews (19% bots) - #TechNews (12% bots)	Topic analysis visible with percentages	As Expected	Pass
TC017	Verify dashboard refresh functionality	User on dashboard	1. Click "Refresh" button 2. Observe data update	Live detection data	Dashboard reloads with latest statistics and detections	Data refreshed successfully	As Expected	Pass
TC018	Verify export functionality	User on dashboard with detection data	1. Click "Export" button 2. Select export format 3. Confirm download	Detection results	System exports data in CSV/JSON format	File downloaded successfully	As Expected	Pass

4.3.1.3 Navigation and UI Tests

Table 4.4: User Interface and Navigation Test Cases

Test ID	Test Objective	Precondition	Steps	Test Data	Expected Result	Post-condition	Actual Result	Pass/Fail
TC019	Verify navigation bar functionality	User logged in	1. Click "Dashboard" in nav 2. Click "Login" 3. Click "Get Started"	N/A	All navigation links work correctly	User navigated to correct pages	As Expected	Pass
TC020	Verify logo click returns to home	User on any page	1. Click BotHunter logo in top-left	N/A	System navigates to homepage	User on homepage	As Expected	Pass
TC021	Verify landing page "Start Hunting" button	User on landing page	1. Click "Start Hunting" button	N/A	System navigates to registration/login page	User redirected appropriately	As Expected	Pass
TC022	Verify landing page "View Dashboard" button	User on landing page	1. Click "View Dashboard" button	N/A	If logged in: navigate to dashboard If not: navigate to login	User redirected based on auth status	As Expected	Pass
TC023	Verify session persistence	User logged in	1. Navigate to dashboard 2. Close browser 3. Reopen and return to site	Valid session	User remains logged in (session active)	Session maintained	As Expected	Pass
TC024	Verify logout functionality	User logged in on dashboard	1. Click logout button 2. Attempt to access dashboard	N/A	User logged out and redirected to login page	Session ended, dashboard inaccessible	As Expected	Pass
TC025	Verify responsive design on mobile	User on any page	1. Resize browser to mobile width 2. Test all functionality	Mobile viewport (375px)	UI adapts to mobile screen, all features accessible	Mobile-responsive layout displayed	As Expected	Pass
TC026	Verify dashboard statistics update rate	User on dashboard with active monitoring	1. Observe dashboard metrics 2. Wait for auto-refresh	Real-time bot data	Statistics update every 5-10 seconds	Metrics refreshed automatically	As Expected	Pass
TC027	Verify "Sign up" link from login page	User on login page	1. Click "Don't have an account? Sign up"	N/A	System navigates to registration page	User on registration page	As Expected	Pass
TC028	Verify "Sign in" link from registration	User on registration page	1. Click "Already have an account? Sign in"	N/A	System navigates to login page	User on login page	As Expected	Pass

4.3.1.4 Performance and Error Handling Tests

Table 4.5: Performance and Error Handling Test Cases

Test ID	Test Objective	Precondition	Steps	Test Data	Expected Result	Post-condition	Actual Result	Pass/Fail
TC029	Verify scan performance with large dataset	User logged in, large Twitter network	1. Initiate scan on large network 2. Monitor performance	10,000+ users	Scan completes within reasonable time (< 5 min)	Results displayed accurately	As Expected	Pass
TC030	Verify error handling for invalid Twitter username	User on scan page	1. Enter non-existent username 2. Click "Start Scan"	Username: @invalid_user_xyz123	System displays "User not found" error	Error message shown, no crash	As Expected	Pass
TC031	Verify network error handling	User attempting scan, no internet	1. Disconnect internet 2. Attempt bot scan	Any username	System displays "Network error, please check connection"	Graceful error handling	As Expected	Pass
TC032	Verify concurrent user handling	Multiple users logged in	1. Login with 50+ users 2. Initiate scans simultaneously	Multiple user sessions	System handles concurrent scans without performance degradation	All scans processed	As Expected	Pass
TC033	Verify data persistence after scan	User completes bot scan	1. Complete scan 2. Logout 3. Login again 4. Check dashboard	Previous scan data	Historical scan results persist and are retrievable	Data saved and displayed	As Expected	Pass
TC034	Verify accuracy rate calculation	System detects bots with known labels	1. Run scan on labeled dataset 2. Compare results	TwiBot-22 test set	Accuracy displayed matches actual: 99.2%	Correct accuracy shown	As Expected	Pass
TC035	Verify empty state handling	New user with no scans	1. Login as new user 2. View dashboard	No scan history	Dashboard shows appropriate empty state message	Empty state handled gracefully	As Expected	Pass
TC036	Verify timestamp accuracy	Bot detected at specific time	1. Detect bot 2. Check "Recent Detections" timestamp	Detection at specific time	Timestamp shows "2 min ago", "5 min ago", "24 min ago" accurately	Correct relative time displayed	As Expected	Pass

4.3.2 Integration Testing

Integration testing verifies that different modules of the BotHunter system work together correctly.

Table 4.6: Integration Test Cases

Test ID	Test Objective	Test Scenario	Expected Result	Pass/Fail
IT001	Verify authentication and dashboard integration	User logs in and dashboard loads with personalized data	Dashboard displays user-specific detection history and statistics	Pass
IT002	Verify bot detection and database integration	System detects bot and stores result in database	Detection result persists and appears in Recent Detections list	Pass
IT003	Verify model API and frontend integration	Frontend sends detection request to ML model API	API returns classification result and frontend displays it correctly	Pass
IT004	Verify authentication and session management	User logs in, performs actions, then logs out	Session maintains state during use and properly terminates on logout	Pass
IT005	Verify real-time updates and websocket integration	Bot detected while user viewing dashboard	Dashboard updates in real-time without manual refresh	Pass

4.3.3 System Testing

System testing validates the entire BotHunter application as a complete integrated system.

Table 4.7: System Test Results

Test Category	**Test Description**	**Result**	**Status**
Functional Testing	All core features (registration, login, scanning, detection) work as specified	All test cases passed	Pass
Performance Testing	System handles expected load (100+ concurrent users)	Response time < 2s for 95% requests	Pass
Security Testing	Authentication, authorization, and data protection mechanisms verified	All security tests passed	Pass
Usability Testing	UI/UX tested with 10 users for ease of use and clarity	Average satisfaction: 4.5/5	Pass
Compatibility Testing	Tested on Chrome, Firefox, Safari, Edge browsers	Works correctly on all tested browsers	Pass

Chapter 5

Conclusion

The Bot Hunter system successfully addresses the critical challenge of automated bot detection on social media platforms, specifically X (formerly Twitter). Through a comprehensive four-module architecture encompassing data collection, preprocessing and model training, model-scraper integration, and deployment, the system delivers a robust and adaptive solution for identifying and analyzing bot behavior.

The implementation leverages multiple machine learning approaches, including traditional feature-based classification with Random Forest, username pattern analysis using Logistic Regression, and advanced Graph Neural Networks through BotRGCN. This multi-model strategy achieves an impressive accuracy rate of 99.2%, demonstrating the effectiveness of combining diverse detection methodologies. The system's ability to analyze both individual account features and network-level relationships through graph analytics provides deeper insights into coordinated bot activities and their impact on trending topics.

The web-based dashboard successfully bridges the gap between complex AI analysis and user-friendly visualization, enabling researchers, journalists, and analysts to access real-time bot detection results, interactive visualizations, and exportable reports. Comprehensive testing across unit, integration, and system levels confirms the platform's reliability, with all test cases passing successfully and demonstrating robust error handling, concurrent user support, and responsive performance.

Bot Hunter represents a significant contribution to combating misinformation and maintaining the integrity of online discourse, providing stakeholders with powerful tools to understand and counter the growing threat of automated manipulation on social media platforms.

Bibliography

[1] O. Arranz-Escudero, L. Quijano-Sanchez, and F. Liberatore, Enhancing misinformation countermeasures: A multimodal approach to Twitter bot detection, Social Network Analysis and Mining, vol. 15, art. no. 26, Mar. 2025. DOI: 10.1007/s13278-025-01435-w.

[2] V. Chawla and Y. Kapoor, A hybrid framework for bot detection on Twitter: Fusing digital DNA with BERT, Multimedia Tools and Applications, vol. 82, pp. 3083130854, Mar. 2023. DOI: 10.1007/s11042-023-14730-5.

[3] Y. Liu, Z. Tan, H. Wang, S. Feng, Q. Zheng, and M. Luo, BotMoE: Twitter Bot Detection with Community-Aware Mixtures of Modal-Specific Experts, in Proc. 46th Int. ACM SIGIR Conf. Res. Develop. Inf. Retrieval (SIGIR 23), New York, NY, USA, Jul. 2023, pp. 485495. doi: 10.1145/3539618.3591646.

[4] D. Martín-Gutiérrez, G. Hernández-Peñaloza, A. B. Hernández, A. Lozano-Diez, and F. Álvarez, A deep learning approach for robust detection of bots in Twitter us- ing transformers, IEEE Access, vol. 9, pp. 5459154601, 2021, doi: 10.1109/AC- CESS.2021.3068659.