

# CYBERSECURITY INTERNSHIP TRAINING REPORT

## Cybersecurity Fundamentals



Submitted By : **ABHI DHRUVE**



Course : **BCA**



Internship : **ApexPlanet Software Pvt. Ltd.**



Domain : **CYBER SECURITY AND  
ETHICAL HACKING**



Year : **2026**



Date : **22 SEPTEMBER 2026**

# INDEX



| Sr. No.  | Contents                                      | Page No. |
|----------|-----------------------------------------------|----------|
| <b>1</b> | <b>Capstone Project Selection</b>             | ---      |
| 1.1      | Web Application Pentest Report (DVWA / bWAPP) | ---      |
| 1.2      | Vulnerability Assessment of Test Network      | ---      |
| 1.3      | Mini SIEM with ELK Stack                      | ---      |
| 1.4      | Security Awareness Phishing Simulation        | ---      |
| <b>2</b> | <b>Project Planning</b>                       | ---      |
| 2.1      | Objectives of the Project                     | ---      |
| 2.2      | Project Scope                                 | ---      |
| 2.3      | Tools and Technologies Used                   | ---      |
| 2.4      | Project Timeline                              | ---      |
| 2.5      | ER Diagram / Network Diagram                  | ---      |
| <b>3</b> | <b>Implementation</b>                         | ---      |
| 3.1      | Reconnaissance                                | ---      |
| 3.2      | Scanning                                      | ---      |
| 3.3      | Controlled Exploitation                       | ---      |
| 3.4      | Documentation of Findings and Evidence        | ---      |
| 3.5      | Mitigation Strategies                         | ---      |
| <b>4</b> | <b>Testing and Analysis</b>                   | ---      |
| 4.1      | Security Testing                              | ---      |
| 4.2      | Vulnerability Analysis                        | ---      |
| 4.3      | Results and Findings                          | ---      |
| <b>5</b> | <b>Final Documentation</b>                    | ---      |
| 5.1      | Executive Summary                             | ---      |
| 5.2      | Methodology                                   | ---      |
| 5.3      | Findings                                      | ---      |
| 5.4      | Mitigation / Recommendations                  | ---      |
| 5.5      | ER Diagrams / Network Diagrams                | ---      |
| 5.6      | Screenshots and Tool Outputs                  | ---      |
| <b>6</b> | <b>Conclusion</b>                             | ---      |
| <b>7</b> | <b>References</b>                             | ---      |
| <b>8</b> | <b>Appendix</b>                               | ---      |



## Suggested Final Report Order

Title Page → Certificate → Declaration → Acknowledgement → Abstract → Index → Introduction → Project Planning → Implementation → Testing & Analysis → Findings → Mitigation → Final Documentation → Conclusion → References → Appendix

# 1 CAPSTONE PROJECT SELECTION

- Vulnerability Assessment of test network

**Vulnerability Assessment of Test Network** is a cybersecurity project in which we examine an **authorized test network** to find security weaknesses, understand their possible impact, and recommend ways to fix them.

For your project, you can use **Kali Linux as the testing machine** and **Metasploitable 2 as the intentionally vulnerable target** inside an isolated virtual network.

## **1. Objective**

The main objectives are:

- Identify devices in the test network.
- Discover open ports and running services.
- Identify outdated or insecure services.
- Find potential vulnerabilities.
- Collect evidence using security tools.

- Analyze the risk of each finding.
- Suggest mitigation/remediation.
- Perform a retest after mitigation where possible.

| Tool              | Purpose                       |
|-------------------|-------------------------------|
| Kali Linux        | Security testing platform     |
| Metasploitable 2  | Vulnerable test machine       |
| Nmap              | Network/port/service scanning |
| Nikto             | Web-server assessment         |
| OpenVAS/Greenbone | Vulnerability assessment      |
| Wireshark         | Network traffic analysis      |
| SearchSploit      | Vulnerability research        |

## STEP BY STEP METHODOLOGY

### 1 Find the Target Machine

If you don't know the Metasploitable IP:

```
sudo nmap -sn 192.168.29.77/24
```

Example:

Nmap scan report for 192.168.29.77/24

Nmap scan report for 192.168.29.11

Here:

192.168.29.11 = Kali

192.168.29.77/24 = Target

Set a variable:

```
export TARGET=192.168.29.11
```

Check:

```
echo 192.168.29.11
```

### **Test Connectivity**

```
ping -c 4 192.168.29.11
```

## 2 PROJECT PLANNING:

- Define objectives

### **Objectives of Vulnerability Assessment of Test Network**

The main objective of this project is to **identify security weaknesses in an authorized test network and recommend suitable security improvements.**

#### **1. Identify Network Devices**

Find the active systems available in the authorized test network.

##### **Example:**

Identify Kali Linux and the vulnerable test machine.

#### **2. Discover Open Ports**

Scan the target machine to find open TCP/UDP ports.

##### **Example:**

21 → FTP

22 → SSH

80 → HTTP

3306 → MySQL

### **3. Identify Running Services**

Determine which services and software versions are running on the discovered ports.

**Tool:** Nmap

```
nmap -sV <TARGET-IP>
```

### **4. Find Security Vulnerabilities**

Identify known weaknesses in the services, applications, and configurations discovered during the assessment.

## **Tools:**

- Nmap NSE
- Nikto
- OpenVAS/Greenbone

## **5. Collect Evidence**

Document the assessment results using **command output, screenshots, scan reports, and network information.**

## **6. Analyze Security Risks**

Analyze each identified vulnerability based on its potential **likelihood and impact.**

## **7. Recommend Mitigation**

Suggest appropriate solutions to reduce or remove the identified security weaknesses.

## **Examples:**

- Update outdated software.
- Disable unnecessary services.
- Restrict unnecessary ports.
- Improve insecure configurations.

## **8. Perform Retesting**

After applying a mitigation, perform another scan to determine whether the identified issue has been addressed.

## **Short Objectives for Your Project Report**

You can directly use these:

### **Objectives:**

- 1.To identify active devices in the authorized test network.
- 2.To discover open ports and running services.
- 3.To identify security vulnerabilities in the test environment.

4. To collect and document evidence of identified vulnerabilities.
5. To analyze the potential risks associated with the findings.
6. To recommend appropriate mitigation strategies.
7. To perform retesting and verify security improvements.

• **Define tools**

| No. | Tool                       | Purpose                                                 |
|-----|----------------------------|---------------------------------------------------------|
| 1   | <b>Kali Linux</b>          | Main cybersecurity testing platform                     |
| 2   | <b>Metasploitable 2</b>    | Intentionally vulnerable test machine                   |
| 3   | <b>Nmap</b>                | Network discovery, port scanning, and service detection |
| 4   | <b>Nikto</b>               | Web-server vulnerability assessment                     |
| 5   | <b>OpenVAS / Greenbone</b> | Automated vulnerability scanning                        |
| 6   | <b>Wireshark</b>           | Capture and analyze network traffic                     |
| 7   | <b>SearchSploit</b>        | Research publicly documented vulnerabilities            |

| No. | Tool                | Purpose                                  |
|-----|---------------------|------------------------------------------|
| 8   | VirtualBox / VMware | Create the isolated virtual test network |

## 1. Kali Linux

Used as the **attacker/tester machine**. It contains many security-testing tools.

## 2. Metasploitable 2

Used as the **target machine**. It is intentionally designed with vulnerable services for security training.

## 3. Nmap

Used for:

- Finding active hosts
- Finding open ports
- Identifying services
- Detecting service versions
- Running selected vulnerability-detection scripts

Example:

```
nmap -sV <TARGET-IP>
```

## 4. Nikto

Used to assess web servers for common security issues.

```
nikto -h http://<TARGET-IP>
```

## 5. OpenVAS / Greenbone

Used for **automated vulnerability assessment** and generating vulnerability reports.

## 6. Wireshark

Used to capture and analyze network packets during the authorized assessment.

## 7. SearchSploit

Used to research known vulnerabilities associated with identified software versions.

```
searchsploit <software> <version>
```

## 8. VirtualBox / VMware

Used to create the **isolated laboratory environment** containing Kali Linux and Metasploitable 2.

### 3 Define Scope

#### **Scope of Vulnerability Assessment of Test Network**

**Scope** defines **what systems, services, and activities are included in the vulnerability assessment and what is excluded.**

For your project, the scope is limited to an **authorized and isolated test network.**

#### **Scope of the Project**

##### **1. Test Network Assessment**

Assess only the virtual test network created for the project.

##### **2. Target Machine**

Use **Metasploitable 2** as the intentionally vulnerable target.

##### **3. Network Discovery**

Identify active devices and network information within the test network.

##### **4. Port Scanning**

Identify open ports on the authorized target.

## 5. **Service Enumeration**

Identify running services and their versions.

## 6. **Vulnerability Identification**

Use tools such as **Nmap**, **Nikto**, and **OpenVAS/Greenbone** to identify potential vulnerabilities.

## 7. **Evidence Collection**

Record scan results, screenshots, logs, and other relevant evidence.

## 8. **Risk Analysis**

Analyze the potential impact of identified vulnerabilities.

## 9. **Mitigation Recommendations**

Suggest appropriate security measures to reduce the identified risks.

## 10. **Retesting**

Where possible, scan the target again after mitigation to verify the improvement.

## **Out of Scope**

The project does **not** include:

- Real-world/public websites
- Unauthorized computer systems

- Third-party networks
- Destructive attacks
- Data theft
- Credential theft
- Persistent access
- Attacking production systems
- Incident Response Simulation

## 3 IMPLEMENTATION:

### FULL PORT SCAN

#### Scan all TCP port:

Sudo nmap -p- 192.168.29.11 -oN

#### Service and version detection:

Sudo nmap -sV 192.168.29.11 -oN

Sudo nmap -sC 192.168.29.11 -oN

#### Operating system detection:

Nmap -O 192.168.29.11 -oN

Nmap -A 192.168.29.11 -oN

#### Scan specific services

nmap -p80 -Sv 192.168.29.11

nmap -p21 -Sv 192.168.29.11

```
nmap -p22 -Sv 192.168.29.11
```

```
nmap -p3306 -Sv 192.168.29.11
```

```

[ Kali@kali:~ ]$ sudo nmap -p- 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 08:48 +0530
Nmap scan report for 192.168.29.11
Host is up (0.0025s latency).
Not shown: 65505 closed tcp ports (reset)
PORT      STATE SERVICE
21/tcp    open  ftp
22/tcp    open  ssh
23/tcp    open  telnet
25/tcp    open  smtp
53/tcp    open  domain
80/tcp    open  http
111/tcp   open  rpcbind
139/tcp   open  netbios-ssn
445/tcp   open  microsoft-ds
512/tcp   open  exec
513/tcp   open  login
514/tcp   open  shell
1049/tcp  open  rmiregistry
1524/tcp  open  ingreslock
2849/tcp  open  nfs
2121/tcp  open  ccproxy-ftp
3306/tcp  open  mysql
3632/tcp  open  distccd
5432/tcp  open  postgresql
5900/tcp  open  vnc
6080/tcp  open  x11
6667/tcp  open  irc
6697/tcp  open  ircs-u
8089/tcp  open  ajp13
8180/tcp  open  unknown
8787/tcp  open  msgrsrv
424347/tcp open  unknown
58270/tcp open  unknown
53675/tcp open  unknown
58435/tcp open  unknown
MAC Address: 00:0C:29:37:AS:4E (VMware)

Nmap done: 1 IP address (1 host up) scanned in 6.70 seconds

[ Kali@kali:~ ]$ sudo nmap -v 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 08:49 +0530
Nmap scan report for 192.168.29.11
Host is up (0.0025s latency).
Not shown: 977 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
21/tcp    open  ftp          OpenSSH 4.7p1 Debian Bubuntu1 (protocol 2.0)
22/tcp    open  ssh          Linux telnetd
23/tcp    open  telnet       Postfix smtpd
25/tcp    open  smtp         ISC BIND 9.4.2
53/tcp    open  http         Apache/2.2.8 ((Ubuntu) DAV/2)
80/tcp    open  rpcbind      2 (RPC #100000)
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)

```

```

kali@kali:~$ sudo nmap -p80 -sV 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:11 +0530
Nmap scan report for 192.168.29.11
Host is up (0.00030s latency).

PORT      STATE SERVICE VERSION
80/tcp    open  http    Apache httpd 2.2.8 ((Ubuntu) DAV/2)
MAC Address: 00:0C:29:37:A5:4E (VMware)

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 7.07 seconds

kali@kali:~$ sudo nmap -p21 -sV 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530
Nmap scan report for 192.168.29.11
Host is up (0.00034s latency).

PORT      STATE SERVICE VERSION
21/tcp    open  ftp     vsftpd 2.3.4
MAC Address: 00:0C:29:37:A5:4E (VMware)
Service Info: OS: Unix

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.93 seconds

kali@kali:~$ sudo nmap -p22 -sV 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530
Nmap scan report for 192.168.29.11
Host is up (0.00028s latency).

PORT      STATE SERVICE VERSION
22/tcp    open  ssh     OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)
MAC Address: 00:0C:29:37:A5:4E (VMware)
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 0.95 seconds

kali@kali:~$ sudo nmap -p3306 -sV 192.168.29.11
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530
Nmap scan report for 192.168.29.11
Host is up (0.00036s latency).

PORT      STATE SERVICE VERSION

```

```
kali@kali: ~  
Session Actions Edit View Help  
80/tcp open  http    Apache httpd 2.2.8 ((Ubuntu) DAV/2)  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 7.07 seconds  
  
kali@kali:~$ sudo nmap -p21 -sv 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00034s latency).  
  
PORT      STATE SERVICE VERSION  
21/tcp open  ftp      vsftpd 2.3.4  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
Service Info: OS: Unix  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.93 seconds  
  
kali@kali:~$ sudo nmap -p22 -sv 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00028s latency).  
  
PORT      STATE SERVICE VERSION  
22/tcp open  ssh      OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.95 seconds  
  
kali@kali:~$ sudo nmap -p3306 -sv 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00036s latency).  
  
PORT      STATE SERVICE VERSION  
3306/tcp open  mysql    MySQL 5.0.51a-3ubuntu5  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.93 seconds  
  
kali@kali:~$
```

```
kali@kali: ~$ sudo nmap -p- -sv 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 09:12 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00036s latency).  
  
5432/tcp open  postgresql PostgreSQL DB 8.3.0 - 8.3.7  
|_ssl-date: 2026-09-17T07:18:20+00:00; -3d20h09m15s from scanner time.  
|_ssl-cert: Subject: commonName=ubuntu004-base.localdomain/organizationName=OCOSA/stateOrProvinceName=There is no such thing outside US/countryName=XX  
|_Not valid before: 2010-03-17T14:07:45  
|_Not valid after: 2010-04-16T14:07:45  
5900/tcp open  vnc      VNC (protocol 3.3)  
|_vnc-info:  
|_ Protocol version: 3.3  
|_ Security types:  
|_ VNC Authentication (2)  
6000/tcp open  x11      (access denied)  
6667/tcp open  irc      UnrealIRCd  
|_irc-info:  
|_ users: 1  
|_ servers: 1  
|_ lusers: 1  
|_ lservers: 0  
|_ server: irc.Metasploitable.LAN  
|_ version: Unreal3.2.8.1. irc.Metasploitable.LAN  
|_ uptime: 0 days, 0:58:50  
|_ source ident: nmap  
|_ source host: 68A2C2D8.E5C4C5A1.FFFA6D49.IP  
|_ error: Closing link: ngfeyoeon[192.168.29.77] (Quit: ngfeyoeon)  
8009/tcp open  ajp13?   Apache Tomcat/Coyote JSP engine 1.1  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
Device type: general purpose  
Running: Linux 2.6.X  
OS CPE: cpe:/o:linux:linux_kernel:2.6  
OS details: Linux 2.6.9 - 2.6.33  
Network Distance: 1 hop  
Service Info: Hosts: metasploitable.localdomain, irc.Metasploitable.LAN; OSs: Unix, Linux; CPE: cpe:/o:linux:linux_kernel  
  
Host script results:  
|_ smb-os-discovery:  
|_ OS: Unix (Samba 3.0.20-Debian)  
|_ Computer name: metasploitable  
|_ NetBIOS computer name:  
|_ Domain name: localdomain  
|_ FQDN: metasploitable.localdomain  
|_ System time: 2026-09-17T03:17:03-04:00  
|_ smb-security-mode:  
|_ account_used: <blank>  
|_ authentication_level: user  
|_ challenge_response: supported  
|_ message_signing: disabled (dangerous, but default)  
|_ smb2-time: Protocol negotiation failed (SMB2)  
|_ clock-skew: mean: -3d19h09m14s, deviation: 2h00m00s, median: -3d20h09m15s  
|_ nbstat: NetBIOS name: METASPLOITABLE, NetBIOS user: <unknown>, NetBIOS MAC: <unknown> (unknown)  
  
TRACEROUTE  
HOP RTT ADDRESS  
1 0.36 ms 192.168.29.11  
  
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 182.87 seconds
```



```
Session Actions Edit View Help
|
| State: VULNERABLE
| Ids: CVE:CVE-2014-3566 BID:70574
| The SSL protocol 3.0, as used in OpenSSL through 1.0.1i and other
| products, uses nondeterministic CBC padding, which makes it easier
| for man-in-the-middle attackers to obtain cleartext data via a
| padding-oracle attack, aka the "POODLE" issue.
| Disclosure date: 2014-10-14
| Check results:
| TLS_RSA_WITH_AES_128_CBC_SHA
| References:
| https://www.imperialviolet.org/2014/10/14/poodle.html
| https://www.openssl.org/~bodo/ssl-poodle.pdf
| https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3566
| https://www.securityfocus.com/bid/70574
|
| ssl-dh-params:
| VULNERABLE:
| Anonymous Diffie-Hellman Key Exchange MitM Vulnerability
| State: VULNERABLE
| Transport Layer Security (TLS) services that use anonymous
| Diffie-Hellman key exchange only provide protection against passive
| eavesdropping, and are vulnerable to active man-in-the-middle attacks
| which could completely compromise the confidentiality and integrity
| of any data exchanged over the resulting session.
| Check results:
| ANONYMOUS DH GROUP 1
| Cipher Suite: TLS_DH_anon_WITH_3DES_EDE_CBC_SHA
| Modulus Type: Safe prime
| Modulus Source: postfix builtin
| Modulus Length: 1024
| Generator Length: 8
| Public Key Length: 1024
| References:
| https://www.ietf.org/rfc/rfc2246.txt
|
| Transport Layer Security (TLS) Protocol DHE_EXPORT Ciphers Downgrade MitM (Logjam)
| State: VULNERABLE
| Ids: CVE:CVE-2015-4000 BID:74733
| The Transport Layer Security (TLS) protocol contains a flaw that is
| triggered when handling Diffie-Hellman key exchanges defined with
| the DHE_EXPORT cipher. This may allow a man-in-the-middle attacker
| to downgrade the security of a TLS session to 512-bit export-grade
| cryptography, which is significantly weaker, allowing the attacker
| to more easily break the encryption and monitor or tamper with
| the encrypted stream.
| Disclosure date: 2015-5-19
| Check results:
| EXPORT-GRADE DH GROUP 1
| Cipher Suite: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
| Modulus Type: Safe prime
| Modulus Source: Unknown/Custom-generated
| Modulus Length: 512
| Generator Length: 8
| Public Key Length: 512
| References:
| https://www.securityfocus.com/bid/74733
| https://weakdh.org
| https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-4000
```

```
Session Actions Edit View Help
|
| State: VULNERABLE
| Ids: CVE:CVE-2014-3566 BID:70574
| The SSL protocol 3.0, as used in OpenSSL through 1.0.1i and other
| products, uses nondeterministic CBC padding, which makes it easier
| for man-in-the-middle attackers to obtain cleartext data via a
| padding-oracle attack, aka the "POODLE" issue.
| Disclosure date: 2014-10-14
| Check results:
| TLS_RSA_WITH_AES_128_CBC_SHA
| References:
| https://www.imperialviolet.org/2014/10/14/poodle.html
| https://www.openssl.org/~bodo/ssl-poodle.pdf
| https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3566
| https://www.securityfocus.com/bid/70574
|
| ssl-dh-params:
| VULNERABLE:
| Anonymous Diffie-Hellman Key Exchange MitM Vulnerability
| State: VULNERABLE
| Transport Layer Security (TLS) services that use anonymous
| Diffie-Hellman key exchange only provide protection against passive
| eavesdropping, and are vulnerable to active man-in-the-middle attacks
| which could completely compromise the confidentiality and integrity
| of any data exchanged over the resulting session.
| Check results:
| ANONYMOUS DH GROUP 1
| Cipher Suite: TLS_DH_anon_WITH_3DES_EDE_CBC_SHA
| Modulus Type: Safe prime
| Modulus Source: postfix builtin
| Modulus Length: 1024
| Generator Length: 8
| Public Key Length: 1024
| References:
| https://www.ietf.org/rfc/rfc2246.txt
|
| Transport Layer Security (TLS) Protocol DHE_EXPORT Ciphers Downgrade MitM (Logjam)
| State: VULNERABLE
| Ids: CVE:CVE-2015-4000 BID:74733
| The Transport Layer Security (TLS) protocol contains a flaw that is
| triggered when handling Diffie-Hellman key exchanges defined with
| the DHE_EXPORT cipher. This may allow a man-in-the-middle attacker
| to downgrade the security of a TLS session to 512-bit export-grade
| cryptography, which is significantly weaker, allowing the attacker
| to more easily break the encryption and monitor or tamper with
| the encrypted stream.
| Disclosure date: 2015-5-19
| Check results:
| EXPORT-GRADE DH GROUP 1
| Cipher Suite: TLS_DHE_RSA_EXPORT_WITH_DES40_CBC_SHA
| Modulus Type: Safe prime
| Modulus Source: Unknown/Custom-generated
| Modulus Length: 512
| Generator Length: 8
| Public Key Length: 512
| References:
| https://www.securityfocus.com/bid/74733
| https://weakdh.org
| https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2015-4000
```

```
Session Actions Edit View Help
|
| Diffie-Hellman Key Exchange Insufficient Group Strength
| State: VULNERABLE
| Transport Layer Security (TLS) services that use Diffie-Hellman groups
| of insufficient strength, especially those using one of a few commonly
| shared groups, may be susceptible to passive eavesdropping attacks.
| Check results:
|   WEAK DH GROUP 1
|     Cipher Suite: TLS_DHE_RSA_WITH_AES_256_CBC_SHA
|     Modulus Type: Safe prime
|     Modulus Source: postfix builtin
|     Modulus Length: 1024
|     Generator Length: 8
|     Public Key Length: 1024
| References:
|   https://www.kh.org
| S3/tcp open domain
| 80/tcp open http
| _http-stored-xss: Couldn't find any stored XSS vulnerabilities.
| http-slowloris-check:
|   VULNERABLE:
|     Slowloris DOS attack
|     State: LIKELY VULNERABLE
|     ID: CVE-2007-6750
|     Slowloris tries to keep many connections to the target web server open and hold
|     them open as long as possible. It accomplishes this by opening connections to
|     the target web server and sending a partial request. By doing so, it starves
|     the http server's resources causing Denial of Service.
| Disclosure date: 2009-09-17
| References:
|   http://ha.ckers.org/slowloris/
|   https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2007-6750
| _http-trace: TRACE is enabled
| _http-vuln-cve2017-1801900: ERROR: Script execution failed (use -d to debug)
| _http-dombased-xss: Couldn't find any DOM based XSS.
| http-enum:
|   /ikiwiki/: Tikiwiki
|   /test/: Test page
|   /phpinfo.php: Possible information file
|   /phpMyAdmin/: phpMyAdmin
|   /doc/: Potentially interesting directory w/ listing on 'apache/2.2.8 (ubuntu) dav/2'
|   /icons/: Potentially interesting folder w/ directory listing
|   /index/: Potentially interesting folder
| http-csrf:
| Spidering limited to: maxdepth=3; maxpagecount=20; withinhost=192.168.29.11
| Found the following possible CSRF vulnerabilities:
|
|   Path: http://192.168.29.11:80/dwaa/
|   Form id:
|   Form action: login.php
|
|   Path: http://192.168.29.11:80/dwaa/login.php
|   Form id:
|   Form action: login.php
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
```

```
Session Actions Edit View Help
|
|   Form action: login.php
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
|   Form action: http://TWiki.org/cgi-bin/passwd/TWiki/WebHome
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
|   Form action: http://TWiki.org/cgi-bin/passwd/Main/WebHome
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
|   Form action: http://TWiki.org/cgi-bin/edit/TWiki/
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
|   Form action: http://TWiki.org/cgi-bin/view/TWiki/TWikiSkins
|
|   Path: http://192.168.29.11:80/twiki/TWikiDocumentation.html
|   Form id:
|   Form action: http://TWiki.org/cgi-bin/manage/TWiki/ManagingWebs
| _http-sql-injection: ERROR: Script execution failed (use -d to debug)
| http-fileupload-exploiter:
|
|   Couldn't find a file-type field.
| 111/tcp open rpcbind
| 139/tcp open netbios-ssn
| 445/tcp open microsoft-ds
| 512/tcp open exec
| 513/tcp open login
| 514/tcp open shell
| 1899/tcp open rmtregistry
| rmi-vuln-classloader:
|   VULNERABLE:
|     RMI registry default configuration remote code execution vulnerability
|     State: VULNERABLE
|     Default configuration of RMI registry allows loading classes from remote URLs which can lead to remote code execution.
| References:
|   https://github.com/rapid7/metasploit-framework/blob/master/modules/exploits/multi/misc/java_rmi_server.rb
| 1524/tcp open ingreslock
| 2049/tcp open nfs
| 2121/tcp open cproxy-ftp
| 3306/tcp open mysql
| _sql-ccs-injection: No reply from server (TIMEOUT)
| 5432/tcp open postgresql
| ssl-dh-params:
|   VULNERABLE:
|     Diffie-Hellman Key Exchange Insufficient Group Strength
|     State: VULNERABLE
|     Transport Layer Security (TLS) services that use Diffie-Hellman groups
|     of insufficient strength, especially those using one of a few commonly
|     shared groups, may be susceptible to passive eavesdropping attacks.
| Check results:
|   WEAK DH GROUP 1
|     Cipher Suite: TLS_DHE_RSA_WITH_AES_256_CBC_SHA
|     Modulus Type: Safe prime
|     Modulus Source: Unknown/Custom-generated
```

```
Session Actions Edit View Help
Modulus Source: Unknown/Custom-generated
Modulus Length: 1024
Generator Length: 8
Public Key Length: 1024

References:
  https://weakdh.org
ssl-ccs-injection:
VULNERABLE!
SSL/TLS MITM vulnerability (CCS Injection)
State: VULNERABLE
Risk factor: High
  OpenSSL before 0.9.8za, 1.0.0 before 1.0.0a, and 1.0.1 before 1.0.1h
  does not properly restrict processing of ChangeCipherSpec messages,
  which allows man-in-the-middle attackers to trigger use of a zero
  length master key in certain OpenSSL-to-OpenSSL communications, and
  consequently hijack sessions or obtain sensitive information, via
  a crafted TLS handshake, aka the "CCS Injection" vulnerability.

References:
  http://www.cvedetails.com/cve/2014-0224
  https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-0224
  http://www.openssl.org/news/secadv_20140605.txt
ssl-poodle:
VULNERABLE!
SSL POODLE information leak
State: VULNERABLE
IDs: CVE: CVE-2014-3566 BID: 70574
  The SSL protocol 3.0, as used in OpenSSL through 1.0.1i and other
  products, uses nondeterministic CBC padding, which makes it easier
  for man-in-the-middle attackers to obtain cleartext data via a
  padding-oracle attack, aka the "POODLE" issue.
Disclosure date: 2014-10-14
Check results:
  TLS_RSA_WITH_AES_128_CBC_SHA
References:
  https://www.imperialviolet.org/2014/10/14/poodle.html
  https://www.openssl.org/~bodo/ssl-poodle.pdf
  https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2014-3566
  https://www.securityfocus.com/bid/70574
5900/tcp open  vnc
6000/tcp open  X11
6667/tcp open  irc
|_irc-unrealircd-backdoor: Looks like trojaned version of unrealircd. See http://seclists.org/fulldisclosure/2010/Jun/277
8009/tcp open  ajp13
8180/tcp open  unknown
|_http-axonet-debug: ERROR: Script execution failed (use -d to debug)
|_http-vuln-cve2014-3704: ERROR: Script execution failed (use -d to debug)
MAC Address: 00:0C:29:37:A5:4E (VMware)

Host script results:
|_smb-vuln-regsvc-dos: ERROR: Script execution failed (use -d to debug)
|_smb-vuln-ms10-054: false
|_smb-vuln-ms10-061: false

Nmap done: 1 IP address (1 host up) scanned in 347.49 seconds

kali@kali:~$
```

```
kali@kali: ~  
Session Actions Edit View Help  
|  
| ssh-rsa  
| ssh-dss  
| encryption_algorithms: (13)  
| aes128-cbc  
| 3des-cbc  
| blowfish-cbc  
| cast128-cbc  
| arcfour128  
| arcfour256  
| arcfour  
| aes192-cbc  
| aes256-cbc  
| rijndael-cbc@lysator.liu.se  
| aes128-ctr  
| aes192-ctr  
| aes256-ctr  
| mac_algorithms: (7)  
| hmac-md5  
| hmac-sha1  
| umac-64@openssh.com  
| hmac-ripemd160  
| hmac-ripemd160@openssh.com  
| hmac-sha1-96  
| hmac-md5-96  
| compression_algorithms: (2)  
| none  
| zlib@openssh.com  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.98 seconds
```


```
kali@kali: ~  
Session Actions Edit View Help  
$(kali@kali)-[~]  
$ sudo nmap -p139,445 -sV 192.168.29.11  
[sudo] password for kali:  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 11:32 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00044s latency).  
  
PORT      STATE SERVICE      VERSION  
139/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)  
445/tcp   open  netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 12.24 seconds  
  
$(kali@kali)-[~]  
$ nmap -p22 -sV --script ssh2-enum-algos 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 11:33 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00069s latency).  
  
PORT      STATE SERVICE      VERSION  
22/tcp    open  ssh          OpenSSH 4.7p1 Debian 8ubuntu1 (protocol 2.0)  
| ssh2-enum-algos:  
|   kex_algorithms: (4)  
|     diffie-hellman-group-exchange-sha256  
|     diffie-hellman-group-exchange-sha1  
|     diffie-hellman-group14-sha1  
|     diffie-hellman-group1-sha1  
|   server_host_key_algorithms: (2)  
|     ssh-rsa  
|     ssh-dss  
| encryption_algorithms: (13)
```

```
kali@kali: ~  
Session Actions Edit View Help  
aes256-ctr  
mac_algorithms: (7)  
  hmac-md5  
  hmac-sha1  
  umac-64@openssh.com  
  hmac-ripemd160  
  hmac-ripemd160@openssh.com  
  hmac-sha1-96  
  hmac-md5-96  
compression_algorithms: (2)  
  none  
  zlib@openssh.com  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.98 seconds  
  
(kali@kali)-[~]  
$ sudo nmap -p3306 -sV 192.168.29.11  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-21 11:33 +0530  
Nmap scan report for 192.168.29.11  
Host is up (0.00031s latency).  
  
PORT      STATE SERVICE VERSION  
3306/tcp  open  mysql    MySQL 5.0.51a-3ubuntu5  
MAC Address: 00:0C:29:37:A5:4E (VMware)  
  
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .  
Nmap done: 1 IP address (1 host up) scanned in 0.98 seconds  
  
(kali@kali)-[~]  
$
```

```
kali@kali: ~  
Session Actions Edit View Help  
  
(kali@kali)-[~]  
$ nikto -h http://192.168.29.11  
- Nikto v2.6.0  
  
+ Target IP: 192.168.29.11  
+ Target Hostname: 192.168.29.11  
+ Target Port: 80  
+ Platform: Unknown  
+ Start Time: 2026-09-21 09:21:00 (GMT+5)  
  
+ Server: Apache/2.2.8 (Ubuntu) DAV/2  
+ ERROR: Failed to check for updates: 403  
+ [999986] /: Retrieved x-powered-by header: PHP/5.2.4-2ubuntu5.10.  
+ [758500] /icons/: Directory indexing found.  
+ No CGI Directories found (use '-C all' to force check all possible dirs). CGI tests skipped.  
+ [608625] PHP/5.2.4-2ubuntu5.10 appears to be outdated (current is at least 8.5.1).  
+ [600050] Apache/2.2.8 appears to be outdated (current is at least 2.4.66).  
+ [013587] /: Suggested security header missing: strict-transport-security. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-Security  
+ [013587] /: Suggested security header missing: permissions-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Permissions-Policy  
+ [013587] /: Suggested security header missing: x-content-type-options. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options  
+ [013587] /: Suggested security header missing: referrer-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy  
+ [013587] /: Suggested security header missing: content-security-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP  
+ [999100] /index: Uncommon header(s) 'Cn' found, with contents: list.  
+ [999965] /index: Apache mod_negotiation is enabled with MultiViews, which allows attackers to easily brute force file names. The following alternatives for 'index' were found: index.php. See: http://www.wisec.it/sectou.php?id=4698ebdc59d15,https://exchange.force.ibmcloud.com/vulnerabilities/8275  
+ [999967] /: Web Server returns a valid response with junk HTTP methods which may cause false positives.  
+ [000434] /: HTTP TRACE method is active and replies which suggests the host is vulnerable to XST. See: https://owasp.org/www-community/attacks/Cross_Site_Tracing  
+ [758510] /phpinfo.php: Output from the phpinfo() function was found.  
+ [758500] /doc/: Directory indexing found.  
+ [001213] /doc/: The /doc/ directory is browsable. This may be /usr/doc. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-1999-0678  
+ [001384] /~/PHPBB5F2A0-3C92-11d3-A3A9-4C7808C10000: PHP Easter Eggs reveals potentially sensitive information via HTTP requests that contain specific QUERY strings. See: https://labs.detectify.com/writups/do-you-dare-to-show-your-php-easter-egg/  
+ [001386] /~/PHPPE568F34-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requests that contain specific QUERY strings. See: https://labs.detectify.com/writups/do-you-dare-to-show-your-php-easter-egg/  
+ [001387] /~/PHPPE568F34-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requests that contain specific QUERY strings. See: https://labs.detectify.com/writups/do-you-dare-to-show-your-php-easter-egg/  
+ [001397] /~/PHPPE568F35-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requests that contain specific QUERY strings. See: https://labs.detectify.com/writups/do-you-dare-to-show-your-php-easter-egg/  
+ [001795] /phpMyAdmin/changeLog.php: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorized hosts.  
+ [999984] /phpMyAdmin/changeLog: Server may leak inodes via ETags, header found with file /phpMyAdmin/ChangeLog, inode: 92462, size: 40540, mtime: Tue Dec 9 22:54:00 2008. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1418  
+ [001796] /phpMyAdmin/ChangeLog: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorized hosts.  
+ [758500] /test/: Directory indexing found.  
+ [001894] /test/: This might be interesting.  
+ [002989] /phpinfo.php: PHP is installed, and a test script which runs phpinfo() was found. This gives a lot of system information. See: CVE-552  
+ [003584] /icons/README: Apache default file found. See: https://www.vntweb.co.uk/apache-restricting-access-to-iconsreadme/  
  
+ [007107] /phpMyAdmin/README: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorized hosts. See: https://typo3.org/  
+ [007342] /: X-Frame-Options header is deprecated and was replaced with the Content-Security-Policy HTTP header with the frame-ancestors directive. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options  
+ [007352] /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerability-scanner/vulnerabilities/missing-content-type-header/  
+ 8242 requests: 16 errors and 30 items reported on the remote host  
+ End Time: 2026-09-21 09:26:45 (GMT+5) (345 seconds)  
  
+ 1 host(s) tested  
  
(kali@kali)-[~]  
$
```


# ER DIAGRAM

ER Diagram – Vulnerability Assessment of Test Network



# NETWORK DIAGRAM:

## Network Diagram (Vulnerability Assessment of Test Network)



### Network Details

|                     |                            |
|---------------------|----------------------------|
| Network Range       | : 192.168.29.0/24          |
| Kali Linux IP       | : 192.168.29.77            |
| Metasploitable 2 IP | : 192.168.29.11            |
| Gateway             | : Not Required (Host-Only) |
| Adapter             | : Host-Only                |

### Tools Used

|  |                     |
|--|---------------------|
|  | Kali Linux          |
|  | Metasploitable 2    |
|  | Nmap                |
|  | Nikto               |
|  | OpenVAS / Greenbone |
|  | Wireshark           |

### Legend

|  |                    |
|--|--------------------|
|  | Network Connection |
|  | No Internet Access |
|  | Isolated Network   |

# Nikto

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help
-evasion+      Encoding technique:
               1 Random URI encoding (non-UTF8)
               2 Directory self-reference (../)
               3 Premature URL ending
               4 Prepend long random string
               5 Fake parameter
               6 TAB as request spacer
               7 Change the case of the URL
               8 Use Windows directory separator (\)
               A Use a carriage return (0x0d) as a request spacer
               B Use binary value 0x0b as a request spacer

-followredirects Follow 3xx redirects to new location
-Format+        Save file (-o) format:
               csv Comma-separated-value
               json JSON Format
               htm HTML Format
               sql Generic SQL (see docs for schema)
               txt Plain text
               xml XML Format
               (if not specified the format will be taken from the file extension passed to -output)

-Help           This help information
-host+         Target host/URL
-id+           Host authentication to use, format is id:pass or id:pass:realm
-ipv4          IPv4 Only
-ipv6          IPv6 Only
-key+          Client certificate key file
-list-plugins   List all available plugins, perform no testing
-maxtime+      Maximum testing time per host (e.g., 1h, 60m, 3600s)
-mutate+       Guess additional file names:
               1 Test all files with all root directories
               2 Guess for password file names
               3 Enumerate user names via Apache (/~user type requests)
               4 Enumerate user names via cgiwrap (/cgi-bin/cgiwrap/~user type requests)
               6 Attempt to guess directory names from the supplied dictionary file
```

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help
(kali@kali)-[~]
$ ls
CREATE Documents engineering lab Music Pictures Public Templates Vulnerability
Desktop Downloads index.html linux_practical passwords.txt Projects social Videos

(kali@kali)-[~]
$ cd Vulnerability

(kali@kali)-[~/Vulnerability]
$ ls
nmap.txt

(kali@kali)-[~/Vulnerability]
$ nikto -version
Unknown option: version

Options:
-Add-header      Add HTTP headers (can be used multiple times, one per header pair)
-ask+           Whether to ask about submitting updates
               yes Ask about each (default)
               no Don't ask, don't send
               auto Don't ask, just send
-check6         Check if IPv6 is working (connects to ipv6.google.com or value set in nikto.conf)
-Cgidirs+       Scan these CGI dirs: "none", "all", or values like "/cgi/ /cgi-a/"
-config+        Use this config file
-Display+       Turn on/off display outputs:
               1 Show redirects
               2 Show cookies received
               3 Show all 200/OK responses
               4 Show URLs which require authentication
               D Debug output
               E Display all HTTP errors
               P Print progress to STDOUT
               S Scrub output of IPs and hostnames
```

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help

(kali@kali)-[~/Vulnerability]
$ nikto -h http://127.0.0.1
- Nikto v2.6.0

+ Target IP: 127.0.0.1
+ Target Hostname: 127.0.0.1
+ Target Port: 80
+ Platform: Linux/Unix
+ Start Time: 2026-09-22 10:28:13 (GMT+5.5)

+ Server: Apache/2.4.68 (Debian)
+ ERROR: Failed to check for updates: 403
+ No CGI Directories found (use '-C all' to force check all possible dirs). CGI tests skipped.
+ [999984] /: Server may leak inodes via ETags, header found with file /, inode: 29cf, size: 658e6a8d5b33b, mtime: gzip. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1418
+ [013587] /: Suggested security header missing: content-security-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/CSP
+ [013587] /: Suggested security header missing: x-content-type-options. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Content-Type-Options
+ [013587] /: Suggested security header missing: strict-transport-security. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-Security
+ [013587] /: Suggested security header missing: referrer-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Referrer-Policy
+ [013587] /: Suggested security header missing: permissions-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Permissions-Policy
+ [999990] OPTIONS: Allowed HTTP Methods: GET, POST, OPTIONS, HEAD .
+ [001406] /server-status: The mod_status module reveals Apache information. See: https://httpd.apache.org/docs/2.4/mod/mod_status.html
^C
```

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help

(kali@kali)-[~/Vulnerability]
$ sudo systemctl start apache2
[sudo] password for kali:

(kali@kali)-[~/Vulnerability]
$ sudo systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; disabled; preset: disabled)
   Active: active (running) since Tue 2026-09-22 10:26:43 IST; 8s ago
 Invocation: 89e05db86b2e4e6fab0907c54bef12c3
    Docs: https://httpd.apache.org/docs/2.4/
 Main PID: 3451 (apache2)
   Status: "Processing requests ..."
    Tasks: 6 (limit: 9406)
  Memory: 21.3M (peak: 21.7M)
     CPU: 131ms
   CGroup: /system.slice/apache2.service
           └─3451 /usr/sbin/apache2 -k start -DFOREGROUND
             └─3467 /usr/sbin/apache2 -k start -DFOREGROUND
               └─3468 /usr/sbin/apache2 -k start -DFOREGROUND
                 └─3469 /usr/sbin/apache2 -k start -DFOREGROUND
                   └─3470 /usr/sbin/apache2 -k start -DFOREGROUND
                     └─3472 /usr/sbin/apache2 -k start -DFOREGROUND

Sep 22 10:26:43 kali systemd[1]: Starting apache2.service - The Apache HTTP Server...
Sep 22 10:26:43 kali apachectl[3451]: AH00558: apache2: Could not reliably determine the server's fully qualified domain name
Sep 22 10:26:43 kali systemd[1]: Started apache2.service - The Apache HTTP Server.

(kali@kali)-[~/Vulnerability]
$ nikto -h http://127.0.0.1
- Nikto v2.6.0

+ Target IP: 127.0.0.1
```

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help
+ [999965] /index: Apache mod_negotiation is enabled with MultiViews, which allows attackers to easily brute force file names
. The following alternatives for 'index' were found: index.php. See: http://www.wisec.it/sectou.php?id=4698ebdc59d15,https://
exchange.xforce.ibmcloud.com/vulnerabilities/8275
+ [999967] /: Web Server returns a valid response with junk HTTP methods which may cause false positives.
+ [000434] /: HTTP TRACE method is active and replies which suggests the host is vulnerable to XST. See: https://owasp.org/ww
w-community/attacks/Cross_Site_Tracing
+ [750510] /phpinfo.php: Output from the phpinfo() function was found.
+ [750500] /doc/: Directory indexing found.
+ [001213] /doc/: The /doc/ directory is browsable. This may be /usr/doc. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name
=CVE-1999-0678
+ [001384] /?PHPB8B5F2A0-3C92-11d3-A3A9-4C7B08C10000: PHP Easter Eggs reveals potentially sensitive information via HTTP req
uests that contain specific QUERY strings. See: https://labs.detectify.com/writeups/do-you-dare-to-show-your-php-easter-egg/
+ [001385] /?PHPE9568F36-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requ
ests that contain specific QUERY strings. See: https://labs.detectify.com/writeups/do-you-dare-to-show-your-php-easter-egg/
+ [001386] /?PHPE9568F34-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requ
ests that contain specific QUERY strings. See: https://labs.detectify.com/writeups/do-you-dare-to-show-your-php-easter-egg/
+ [001387] /?PHPE9568F35-D428-11d2-A769-00AA001ACF42: PHP Easter Egg reveals potentially sensitive information via HTTP requ
ests that contain specific QUERY strings. See: https://labs.detectify.com/writeups/do-you-dare-to-show-your-php-easter-egg/
+ [001795] /phpMyAdmin/changelog.php: phpMyAdmin is for managing MySQL databases, and should be protected or limited to autho
rized hosts.
+ [999984] /phpMyAdmin/ChangeLog: Server may leak inodes via ETags, header found with file /phpMyAdmin/ChangeLog, inode: 9246
2, size: 40540, mtime: Tue Dec 9 22:54:00 2008. See: https://cve.mitre.org/cgi-bin/cvename.cgi?name=CVE-2003-1418
+ [001796] /phpMyAdmin/ChangeLog: phpMyAdmin is for managing MySQL databases, and should be protected or limited to authorize
d hosts.
+ [750500] /test/: Directory indexing found.
+ [001894] /test/: This might be interesting.
+ [002989] /phpinfo.php: PHP is installed, and a test script which runs phpinfo() was found. This gives a lot of system infor
mation. See: CWE-552
+ [003584] /icons/README: Apache default file found. See: https://www.vntweb.co.uk/apache-restricting-access-to-iconsreadme/
^C
(kali@kali)-[~/Vulnerability]
$
```

```
kali@kali: ~/Vulnerability
Session Actions Edit View Help
^C
(kali@kali)-[~/Vulnerability]
$ nikto -h 192.168.29.11 -p 80
- Nikto v2.6.0

Apache2 Debian Default Page

+ Target IP: 192.168.29.11
+ Target Hostname: 192.168.29.11
+ Target Port: 80
+ Platform: Unknown
+ Start Time: 2026-09-22 10:29:25 (GMT5.5)

+ Server: Apache/2.2.8 (Ubuntu) DAV/2
+ ERROR: Failed to check for updates: 403
+ [999986] /: Retrieved x-powered-by header: PHP/5.2.4-2ubuntu5.10.
+ [750500] /icons/: Directory indexing found.
+ No CGI Directories found (use '-C all' to force check all possible dirs). CGI tests skipped.
+ [600050] Apache/2.2.8 appears to be outdated (current is at least 2.4.66).
+ [600625] PHP/5.2.4-2ubuntu5.10 appears to be outdated (current is at least 8.5.1).
+ [013587] /: Suggested security header missing: referrer-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Head
ers/Referrer-Policy
+ [013587] /: Suggested security header missing: permissions-policy. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/H
eaders/Permissions-Policy
+ [013587] /: Suggested security header missing: strict-transport-security. See: https://developer.mozilla.org/en-US/docs/Web
/HTTP/Headers/Strict-Transport-Security
+ [013587] /: Suggested security header missing: x-content-type-options. See: https://developer.mozilla.org/en-US/docs/Web/HT
TP/Headers/X-Content-Type-Options
+ [013587] /: Suggested security header missing: content-security-policy. See: https://developer.mozilla.org/en-US/docs/Web/H
TTP/CSP
+ [999100] /index: Uncommon header(s) 'tcn' found, with contents: list.
+ [999965] /index: Apache mod_negotiation is enabled with MultiViews, which allows attackers to easily brute force file names
. The following alternatives for 'index' were found: index.php. See: http://www.wisec.it/sectou.php?id=4698ebdc59d15,https://
exchange.xforce.ibmcloud.com/vulnerabilities/8275
+ [999967] /: Web Server returns a valid response with junk HTTP methods which may cause false positives.
```