

Git Commands from git init to get code of another repo in your local system for command for windows

git commands from initialize repo to push

- go your path where you want to initialize empty repository or Code you want to push
 - git init [Initialized empty Git repository in]
E:/Giri's-Tech-Full-Stack-Java/Core-Java/Oct-Revision-Plan/.git/
- git status;
- git add .
- git commit -m "revision code of Java-HTML-SQL";
- git remote add origin
<https://github.com/ABHI7pute0205/Giri-s-TechHub-Task.git>
- git branch -M main
- git push -u origin main
- git remote -v
origin https://github.com/ABHI7pute0205/Giri-s-TechHub-Task.git (fetch)
origin https://github.com/ABHI7pute0205/Giri-s-TechHub-Task.git (push)
- (after successfully push code file on git you will see like this |)

Ya main branch var ti ch code push kara y cha asla tar same path (Local repo) chya location var tun hya 3 command follow kara y chya varchya step's complete zalya var in future if we want to add some code on this same location

- git add .
- git commit -m "Updated something"
- git push

Git commands to create new file and make change in it and push

- Make a new directory (folder) → **mkdir MyProject**
- Check it's created: → **dir**
- Go inside the folder → **cd MyProject**
- Create a new file → **echo.> MyFile.java**
- Open the file in CMD (using Notepad) → **notepad MyFile.java**
- Check Git status (if repo initialized) → **git status**
- Add file to Git staging area → **git add MyFile.java**
- Commit the changes → **git commit -m "Added MyFile.java"**

Steps to Create and Merge a Branch in Git :

→ git branch **(we see the branch in which we are currently)**

→git branch new-feature **(here we create new Branch)**

→git checkout new-feature **(Switch to that new branch)**

make Some changes

→ git add . (add those files)

→ git commit -m "message" **(add commit)**

→ git checkout main **(Go back to the main branch)**

→ git merge new-feature **(Merge the new branch into main)**

→ git branch -d new-feature **((Optional) Delete the merged branch)**

→ git push **(Push the updated main branch to GitHub)**

this command is used to **check the number files present on your current gitHub repo** → **git ls-files**

clone a GitHub repository to your local system in Windows terminal :

→ Open Terminal

- You can open:
- Git Bash (recommended) OR
- Command Prompt (cmd)

→ Go to the location where you want to clone the repo

- cd "E:\Giri's-Tech-Full-Stack-Java\Core-Java"

→ Copy the repository URL from GitHub

→ On GitHub:

- Go to your repository page
- Click on the green "Code" button
- Copy the HTTPS URL
- e.g /https://github.com/your-username/your-repo-name.git

→ Clone the repository

- Now in your terminal, run:
- **git clone /https://github.com/your-username/your-repo-name.git**

This command downloads all the code and creates a local copy of the repository.

→ Go inside the cloned folder

- cd your-repo-name

→ Verify

- dir (for Command Prompt) OR
- ls (for Git Bash)

How to Add remote repository

1 Go to your local repository

```
cd "E:\Giri's-Tech-Full-Stack-Java\Core-Java\MyProject"
```

2 Initialize Git (if not already done)

```
git init
```

3 Check current remotes

```
git remote -v
```

4 Add remote repository

```
git remote add origin https://github.com/YourUsername/YourRepoName.git
```

Note: **origin** is just a conventional name for the remote. You can use any name.

5 Verify remote is added

```
git remote -v
```

Output should look like:

```
origin https://github.com/YourUsername/YourRepoName.git (fetch)
origin https://github.com/YourUsername/YourRepoName.git (push)
```

6 Push your local code to GitHub

If your branch is **main**:

```
git push -u origin main
```

- **-u** → sets upstream so next time you can just do **git push**

- `origin` → remote name
- `main` → branch name

For older repos, the default branch might be `master`. Adjust accordingly

To change remote URL later:

```
git remote set-url origin https://github.com/YourUsername/NewRepoName.git
```

To remove remote:

```
git remote remove origin
```

Other commands of the git are same on all OS Just change the File create open commands based on OS

Git Commands for Ubuntu/Linux OS

Git commands to create a new file and push

Make a new directory:

```
mkdir MyProject
```

Check it's created:

```
ls
```

Go inside the folder:

```
cd MyProject
```

Create a new file:

```
touch MyFile.java
```

Open the file using nano editor:

```
nano MyFile.java
```

Other ways to open a File in Ubuntu/Linux OS

1 Using `vim` editor (usually pre-installed)

```
vim MyFile.java
```

Press **i** to enter **Insert mode** and start typing.

Press **Esc** → type **:wq** → press **Enter** to **save and exit**.

To exit without saving: **:q!**

2 Using **gedit (GUI text editor)**

```
gedit MyFile.java &
```

Opens a graphical window.

Use **&** to keep the terminal free.

Useful if you're on Ubuntu Desktop.

3 Using **cat (view only, not for editing)**

```
cat MyFile.java
```

Displays file content in the terminal.

Not editable, just for checking.

4 Using **less (view only, scrollable)**

```
less MyFile.java
```

Scroll with arrow keys.

Press **q** to quit.

5 Using **touch + redirect operators (quick edit in terminal)**

```
echo "public class MyFile {}" > MyFile.java
```

Creates or overwrites files with content.

Not interactive editing, but fast for small edits.

Check Git status:

```
git status
```

Add file to staging:

```
git add MyFile.java
```

Commit changes:

```
git commit -m "Added MyFile.java"
```