

Mysql

`<!-- https://mvnrepository.com/artifact/mysql/mysql-connector-java -->`

```
<dependency>
  <groupId>mysql</groupId>
  <artifactId>mysql-connector-java</artifactId>
  <version>8.0.33</version>
</dependency>
```

LomBok

```
<dependency>
  <groupId>org.projectlombok</groupId>
  <artifactId>lombok</artifactId>
  <version>1.18.32</version>
  <scope>provided</scope>
</dependency>
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-web</artifactId>
  <version>3.3.0</version>
</dependency>
```

JUnit

```
<dependency>
  <groupId>org.junit.jupiter</groupId>
  <artifactId>junit-jupiter-api</artifactId>
  <version>5.10.0</version> <!-- Or the latest stable version -->
  <scope>test</scope>
</dependency>
<dependency>
  <groupId>org.junit.platform</groupId>
  <artifactId>junit-platform-suite</artifactId>
  <version>1.10.2</version> <!-- or latest -->
  <scope>test</scope>
</dependency>
```

Build jar file he dependency always dependencies tag chya baher lihaychi

```
<build>
  <plugins>
```

```

<!-- Compiler Plugin -->
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-compiler-plugin</artifactId>
  <version>3.11.0</version>
  <configuration>
    <source>17</source> <!-- your Java version -->
    <target>17</target>
  </configuration>
</plugin>
<!-- Jar Plugin (optional, but useful) -->
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-jar-plugin</artifactId>
  <version>3.3.0</version>
  <configuration>
    <archive>
      <manifest>
        <addClasspath>true</addClasspath>
        <mainClass>com.example.Main</mainClass> <!-- Change to your
main class -->
      </manifest>
    </archive>
  </configuration>
</plugin>
</plugins>
</build>

```

Example of test Case

src/main/java

```

package Demo;
public class Cal {
    public int add(int a,int b)
    {
        return a+b;
    }
    public int sub(int a,int b)

```

```

    {
        return a-b;
    }
}

```

```

src/test/java
package mavenDemo;

import org.junit.jupiter.api.Assertions;
import org.junit.jupiter.api.Test;

import Junit_Code.Calculator;

public class TestCal {
    @Test
    public void testPositiveNumber()
    {
        Calculator c=new Calculator();
        int r=c.add(2, 2);
        Assertions.assertEquals(4, r,"result =>");
    }
    @Test
    public void testNeg()
    {
        Calculator c=new Calculator();
        int r=c.add(-1, 10);
        Assertions.assertEquals(9,r);
    }
}

```

Example of lombok
package praticePrg;

```

import lombok.AllArgsConstructor;
import lombok.Data;
import lombok.Getter;
import lombok.NoArgsConstructor;
import lombok.Setter;
import lombok.ToString;

```

```
@Getter
@Setter
@ToString
@Data
@NoArgsConstructor
@AllArgsConstructor
class Emp {
    private int id;
    private String name;
}

public class DemoPrg {

    public static void main(String[] args) {
        Emp e = new Emp();
        e.setId(1);
        e.setName("Om");

        System.out.println(e.getId() + "\t" + e.getName());
        System.out.println(e);

        Emp e1 = new Emp(1, "sai");
        System.out.println(e1);

    }

}
```