Dell EMC OpenManage Ansible Modules

Version 2.0.9 User's Guide



Notes, cautions, and warnings

i NOTE: A NOTE indicates important information that helps you make better use of your product.

CAUTION: A CAUTION indicates either potential damage to hardware or loss of data and tells you how to avoid the problem.

MARNING: A WARNING indicates a potential for property damage, personal injury, or death.

Dell EMC OpenManage Ansible Modules

Version 2.0.9

© Copyright 2019 - 2020 Dell Inc.

GNU General Public License v3.0+ (see COPYING or https://www.gnu.org/licenses/gpl-3.0.txt)

All rights reserved. Dell, EMC, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

Contents

1 Overview	5
Key Features	5
What's new?	5
2 Getting Started	7
How OpenManage Ansible Modules works	7
Running your first Playbook	7
3 Modules for iDRAC	8
How OpenManage Ansible Modules work with iDRAC	8
Running your first iDRAC Playbook	
Updating Firmware	9
View firmware inventory	9
Install firmware	10
Configuring PowerEdge Servers	15
View LC status	15
Server Configuration Profile	15
Configuring iDRAC	23
Configure BIOS	31
Configure RAID	35
Configure Collect System Inventory on Restart	40
Configure syslog	41
Deploying operating system	42
Boot to a network ISO image	42
Server Inventory	44
View the system inventory	44
Server administration tasks	45
Configure the power state on the PowerEdge servers	
Reset iDRAC	46
View LC job status	46
Export LC logs	47
Delete LC job	48
Delete LC job queue	49
Configure System Lockdown Mode	49
Storage controller	50
Configure storage controller settings	50
4 Modules for OpenManage Enterprise (OME)	55
How OpenManage Ansible Modules work with OME	
Running your first OME Playbook	
View device information	56
View device inventory	58
Manage device configuration templates	61
View templates	61

Template operations	63
Attach or detach an identity pool	71
Set tagged and untagged vLANs in a template	73
Manage the device firmware	75
Update device firmware	75
Create a firmware catalog	79
Create a firmware baseline	82
Retrieve firmware baseline compliance details	84
Manage jobs	88
View job details	88
Manage power state operations	89
Manage users	91
View user account details	91
Configure user accounts	94
Manage identity pool	96
Manage Identity pool settings	96
5 Modules for Redfish APIs	99
How OpenManage Ansible Modules work with Redfish APIs	99
Firmware update using standard Redfish URI	99
Manage storage volume configuration	101
6 Accessing documents from the Dell EMC support site	106

Overview

Dell EMC OpenManage Ansible Modules allows data center and IT administrators to use RedHat Ansible to automate and orchestrate the configuration, deployment, and update of Dell EMC PowerEdge Servers (12th generation of PowerEdge servers and later) and modular infrastructure by leveraging the management automation capabilities in-built into the Integrated Dell Remote Access Controller (iDRAC) and OpenManage Enterprise (OME) respectively.

With the latest release of Dell EMC OpenManage Ansible Modules, the capabilities have improved with support for OpenManage Enterprise. OpenManage Ansible Modules simplifies and automates provisioning, deployment, and updates of PowerEdge servers and modular infrastructure. It allows system administrators and software developers to introduce the physical infrastructure provisioning into their software provisioning stack, integrate with existing DevOps pipelines and manage their infrastructure using version-controlled playbooks, server configuration profiles, and templates in line with the **Infrastructure-as-Code** (IaC) principles.

This user guide provides information about using **Dell EMC OpenManage Ansible Modules** and its different use cases.

The latest stable version of OpenManage Ansible Modules is available at dell.com/support. In addition to dell.com/support, you can download Ansible modules from https://github.com/dell/dellemc-openmanage-ansible-modules. Dell EMC supports modules that are downloaded from this GitHub location only.

Topics:

- Key Features
- · What's new?

Key Features

The key features in OpenManage Ansible Modules are:

- · Support for creating, modifying or deleting a user account.
- · Perform the supported power state management operations on devices managed by OME.
- \cdot $\;$ Support for creating, modifying or deploying a template.
- · Get the list and details of all user accounts or of a specific account.
- · Get the list and details of templates or of a specific template.
- · Support for firmware update of PowerEdge devices and all its components.
- · Support for retrieving job details for a given job ID or the entire job queue.
- · Support for retrieving the list of all devices with the exhaustive inventory of each device.
- Export a server configuration profile (SCP) containing either the entire server configuration or component level configuration (iDRAC, BIOS, RAID, NIC) to a local file path on Ansible controller or a remote network share.
- · Import an SCP from a local file path on Ansible controller or a remote network share.
- Support for configuration of BIOS, Integrated Dell Remote Access Controller (iDRAC), NIC, and RAID.
- \cdot $\;$ Support for firmware update using a Firmware Repository hosted on a remote network share.
- · Support for viewing firmware inventory details.
- · Support for Windows, Linux, and ESXi operating system deployments.
- Support for configuring power controls, resetting iDRAC, viewing Lifecycle Controller (LC) job status, deleting LC job, deleting LC job queue, exporting LC logs, and configuring system lockdown mode.
- · Retrieve the system inventory details.



What's new?

- The module ome_identity_pool is updated to delete an identity pool.
- · The new OpenManage Enterprise module(ome_template_identity_pool) allows to-
 - · Attach an identity pool to a template.
 - · Detach an identity pool from a template.

- The new ome_template_network_vlan module lets you select tagged and untagged VLANs to be used in the OpenManage Enterprise template.
- The option group_names in the ome_firmware_baseline and ome_firmware_baseline_compliance_info module is replaced with device_group_names.
- The ome_firmware module allows firmware updates using a single DUP path and a baseline name
- · The installation and uninstallation scripts have been updated to display the path where the modules have been installed.
- · Success and failure messages in the scripts now appear in green and red.

Getting Started

How OpenManage Ansible Modules works

- How OpenManage Ansible Modules work with iDRAC
- · How OpenManage Ansible Modules work with OME
- How OpenManage Ansible Modules work with Redfish APIs

Running your first Playbook

Playbooks are essentially sets of instructions (plays) that you send to run on a single target or groups of targets (hosts).

To see how to run your first iDRAC and OME playbooks, see the following:

- · Running your first iDRAC Playbook
- · Running your first OME Playbook

Modules for iDRAC

How OpenManage Ansible Modules work with iDRAC

OpenManage Ansible modules uses iDRAC REST APIs based on Redfish standards and Server Configuration Profiles (SCP) for automated configuration, deployment and update of PowerEdge servers. An SCP contains all BIOS, iDRAC, Network and Storage settings of a PowerEdge server. You can apply them to multiple servers, enabling rapid, reliable, and reproducible configuration.

You can perform an SCP operation using any of the following methods:

- Export to or import from a remote network share via CIFS, NFS. Ensure that the remote network share is mounted on the Ansible controller with read-write privileges for user running the Ansible playbooks.
- Export or import via local file streaming (for iDRAC firmware 2.60.60.60 and above).

Setting up a local mount point for a remote network share

Mount the remote network share (CIFS or NFS) locally on the Ansible controller where you want to run the playbook or modules. Local mount point should have read-write privileges in order for OpenManage Ansible modules to write an SCP file to remote network share that will be imported by iDRAC.

i) NOTE: Refer to Linux man pages for mounting an NFS or CIFS network share on Ansible control machine.

Running your first iDRAC Playbook

Before you run a playbook to manage your iDRACs, you need to have a valid inventory of target PowerEdge servers. For more information on inventory, see Ansible documentation.

- 1. Install OpenManage Ansible Modules either from the dell.com/support or the https://github.com/dell/dellemc-openmanage-ansible-modules.git repository. For more details, see *Dell EM C OpenManage Ansible Modules Installation Guide*.
- 2. Create an inventory file containing a list of the iDRACs. In the following inventory example, we are using the inventory variables to store the iDRAC IP addresses and the user credentials. For more information on variables, see Ansible documentation.

```
inventory:

[PowerEdge]
R740.example.com
idrac_ip='192.168.10.10'
idrac_user='root'
idrac_password='idrac_password'
```

3. Define a playbook to fetch the hardware inventory of the servers. Create the playbook in the same directory where you created the inventory. Following is a playbook example:

```
playbook.yml
---
- hosts: PowerEdge
  connection: local
  gather_facts: False

tasks:
- name: Get hardware inventory
  dellemc_get_system_inventory:
    idrac_ip: "{{ idrac_ip }}"
    idrac_user: "{{ idrac_user }}"
    idrac_password: "{{ idrac_password }}"
```

4. Now run the playbook. Run the following command from the directory where you created the inventory and the playbook:

ansible-playbook playbook.yml -i inventory

5. Press Enter.

With OpenManage Ansible Modules, you can construct a playbook with a set of modules resulting in an automation workflow for configuration, deployments, and updates of PowerEdge servers.

To view the list of all available iDRAC modules:

1. Run the following command on the Ansible control machine:

```
ansible-doc -l | grep "idrac"
```

2. Press Enter.

List of the available iDRAC modules is displayed.

To view the documentation of a module:

1. Run the following command on the Ansible control machine:

```
ansible-doc <module name>
```

2. Press Enter.

Updating Firmware

You can maintain up-to-date firmware versions of Dell EMC server components to get better efficiency, security protection and enhanced features. Create update sources to do the firmware update.

Following are the tasks for the firmware update activities:

- View firmware inventory
- · Install firmware

View firmware inventory

Command: dellemc_get_firmware_inventory

Synopsis

You can view the firmware inventory of a server using this module. This module displays components of a server and the corresponding firmware versions.

Check_mode support: No

Options

Table 1. dellemc_get_firmware_inventory

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_username	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port

Table 2. Return Values

Name	Description	Returned	Туре	Sample
Firmware Inventory	 Components of a server and their firmware versions. 	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_get_firmware_inventory.md

Name	Description	Returned	Туре	Sample
	List of dictionaries, 1 dictionary per firmware.			

Examples

```
-name: Get Installed Firmware Inventory
dellemc_get_firmware_inventory:
   idrac_ip: "xx.xx.xx.xx"
   idrac_user: "xxxx"
   idrac_password: "xxxxxxxx"
```

Install firmware

Module: idrac_firmware

Synopsis: The firmware can be installed from a repository on a network share (CIFS, NFS, HTTP, HTTPS, FTP) to keep the system updated. To install the firmware, connect to a network share that contains a valid repository of Dell Update Packages (DUPs), and a catalog file describing the DUPs.

Check_mode support: No

Options

Table 3. idrac_firmware

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_wait	Yes	True	NA	Provides the option to wait for job completion.
catalog_file_name	No	Catalog.xml	NA	Catalog file name relative to the I (share_name).
reboot	No	False	NA	Provides the option to reboot after the updates have been applied.
share_name	Yes	NA	NA	Network share path of update repository. CIFS, NFS, HTP, HTTPS and FTS share types are supported.
share_user	No	NA	NA	User name required to access the network share must be provided as either 'user@domain' or 'domain\user'. This option is mandatory for CIFS network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	Yes	NA	NA	Local mount path of the network share with read/write permission for the Ansible user.

Parameter/aliases	Required	Default	Choices	Comments
ignore_cert_warning	No	True	NA	Specifies if certificate warnings are ignored when HTTPS share is used. If C(True) option is set, then the certificate warnings are ignored.
apply_update	No	True	NA	If I(apply_update) is set to C(True), then packages are applied. If set to C(False), packages are not applied.

Return Values

```
type: str
    description: Overall firmware update status.
    returned: always
    sample: "Successfully updated the firmware."

update_status:
    type: dict
    description: Firmware Update job and progress details from the iDRAC.
    returned: success
    sample: {
        'InstanceID': 'JID_XXXXXXXXXXXX',
        'JobState': 'Completed',
        'Message': 'Job completed successfully.',
        'MessageId': 'REDXXX',
        'Name': 'Repository Update',
        'JobStartTime': 'NA',
        'Status': 'Success',
     }
}
```

Example

```
- name: Update firmware from a repository on a NFS Share.
  idrac_firmware:
        idrac_ip: "192.168.0.1"
idrac_user: "user_name"
idrac_password: "user_password"
        share name: "192.168.0.0:/share"
        reboot: True
        job wait: True
        apply_update: True
catalog_file_name: "Catalog.xml"
- name: Update firmware from a repository on a CIFS Share.
  idrac firmware:
        idrac ip: "192.168.0.1"
        idrac user: "user name"
        idrac_password: "user_password" share_name: "\\\192.168.0.0\\cifs" share_user: "share_user"
        share_password: "share_password" share_mnt: "/mnt_path"
        reboot: True
        job wait: True
        apply update: True
        catalog_file_name: "Catalog.xml"
- name: Update firmware from a repository on a HTTP share.
  idrac_firmware:
    idrac_ip: "192.168.0.1"
        idrac_user: "user_name"
        idrac password: "user password"
        share name: "http://downloads.dell.com"
        reboot: True
        job wait: True
```

```
apply_update: True
- name: Update firmware from a repository on a HTTPS share.
  idrac firmware:
       idrac_ip: "192.168.0.1"
idrac_user: "user_name"
       idrac_password: "user_password"
       share_name: "https://downloads.dell.com"
       reboot: True
       job_wait: True
       apply_update: True
- name: Update firmware from a repository on a FTP share.
  idrac firmware:
       idrac_ip: "192.168.0.1" idrac_user: "user_name"
       idrac_password: "user_password"
       share_name: "ftp://ftp.dell.com"
       reboot: True
       job wait: True
       apply update: True
```

Module: dellemc_idrac_firmware

Synopsis: You can install the firmware from a repository on a network share (CIFS, NFS) to keep the system updated.

To install the firmware:

- Ensure that the network share contains a valid repository of Dell Update Packages (DUPs) and a catalog file that consists the latest DUPs.
- \cdot All applicable updates that are contained in the repository are applied to the system.

Check_mode support: No

i NOTE: This module is deprecated and replaced with idrac_firmware.

Table 4. dellemc_idrac_firmware

Parameter	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_wait	Yes	True	NA	Whether to wait for job completion or not.
catalog_file_name	No	Catalog.xml	NA	Catalog file name relative to the I (share_name).
reboot	No	False	NA	Whether to reboot after applying the updates or not.
share_name	Yes	NA	NA	CIFS or NFS Network share
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain \\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.

Parameter	Required	Default	Choices	Comments
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	Yes	NA	NA	Local mount path of the network share with read/write permission for ansible user This option is mandatory for Network share.

Return Values

```
msg:
           type: str
           description: Over all firmware update status.
           returned: always
           sample: "Successfully updated the firmware."
update status:
           type: dict
           description: Firmware Update job and progress details from the iDRAC.
           returned: success
           sample:
                  'InstanceID': 'JID XXXXXXXXXXX',
                  'JobState': 'Completed',
                   'Message': 'Job completed successfully.',
                  'MessageId': 'REDXXX',
                  'Name': 'Repository Update',
                   'JobStartTime': 'NA',
                   'Status': 'Success',
```

Example

```
- name: Update firmware from repository on a Network Share
    dellemc_idrac_firmware:
     idrac ip:
                         "192.168.0.1"
      idrac_user:
                         "user_name"
                      "user_pwd"
"192.168.0.0:/share"
      idrac pwd:
     share name:
                         "share_user_name"
      share_user:
      share_pwd:
                         "share_user_pwd"
"/mnt/share"
      share mnt:
      reboot:
                          True
      job wait:
                           True
      catalog_file_name: "Catalog.xml"
```

Module: dellemc_install_firmware

Synopsis

You can install the firmware from a repository on a network share (CIFS, NFS) to keep the system updated.

- For 12th and 13th generation of PowerEdge servers, firmware update from a network repository is performed using WS-Man APIs.
- For 14th generation of PowerEdge servers, firmware update from a network repository is performed using the SCP.

To install the firmware:

- Ensure that the network share contains a valid repository of Dell Update Packages (DUPs) and a catalog file that consists the latest DUPs.
- · All applicable updates that are contained in the repository are applied to the system.

Check_mode support: No

i NOTE: This module is deprecated and replaced with idrac_firmware.

Table 5. dellemc_install_firmware

Parameter	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_wait	Yes	True	NA	Whether to wait for job completion or not.
catalog_file_name	No	Catalog.xml	NA	Catalog file name relative to the I (share_name).
reboot	No	False	NA	Whether to reboot after applying the updates or not.
share_name	Yes	NA	NA	CIFS or NFS Network share
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain \user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	Yes	NA	NA	Local mount path of the network share with read/write permission for ansible user. This option is mandatory for Network share.

Table 6. Return Values

Name	Description	Returned	Туре	Sample
Firmware	Updates firmware from a repository on a network share (CIFS, NFS).	Success		https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_install_firmware.md

Example

Configuring PowerEdge Servers

Integrated Dell Remote Access Controller (iDRAC) with LC provide the ability to generate a human-readable representation of server configuration using Server Configuration Profile (SCP) feature. This file contains BIOS, iDRAC, LC, network, and RAID configuration settings. You can modify this file as per your need and apply to other servers.

The SCP feature is used in the Ansible module to automate the configuration activity of PowerEdge servers and their components.

Following are the tasks:

- View LC status
- Server Configuration Profile
- Configuring iDRAC
- · Configure BIOS
- Configure RAID
- · Configure Collect System Inventory on Restart
- Configure syslog

View LC status

Module: dellemc_get_lcstatus

Synopsis

You can view the LC status on a PowerEdge server using this module. You must check the readiness of the LC before carrying out any configuration or update. This module returns the LC readiness as True or False and its status.

Check_mode support: No

Options

Table 7. dellemc_get_lcstatus

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port

Table 8. Return Values

Name	Description	Returned	Туре	Sample
LC status	Displays the LC status on a PowerEdge server	Success	String	https://github.com/dell/Dell-EMC- Ansible-Modules-for-iDRAC/blob/ master/samples/ dellemc_get_lcstatus.md

Example

```
-name: Get LC Status
dellemc_get_lcstatus:
   idrac_ip: "xx.xx.xx."
   idrac_user: "xxxx"
   idrac_password: "xxxxxxxx"
```

Server Configuration Profile

Export or Import Server Configuration Profile

Module: idrac_server_config_profile

Synopsis

This module exports the Server Configuration Profile (SCP) from iDRAC. It can also import from a network share or from a local file.

Table 9. idrac_server_config_profile

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
command	No	export	· import · export	If C(import), will perform SCP import operations. If C(export), will perform SCP export operations.
job_wait	Yes	NA	NA	Whether to wait for job completion or not.
share_name	Yes	NA	NA	CIFS or NFS Network Share or a local path.
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\\user' if user is a part of a domain, else 'user'. This option is mandatory for CIFS Network Share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network Share.
scp_file	No	NA	NA	SCP file name. This option is mandatory for C(import) state.
scp_components	No	ALL	· ALL · IDRAC · BIOS · NIC · RAID	 If C(ALL), the module imports all components configurations from SCP file. If C(iDRAC), the module imports iDRAC configuration from SCP file. If C(BIOS), the module imports BIOS configuration from SCP file. If C(NIC), the module imports NIC configuration from SCP file. If C(RAID), the module imports RAID configuration from SCP file.
shutdown_type	No	Graceful	GracefulForcedNoReboot	 This option is applicable for C(import) state. If C(Graceful), it gracefully shuts down the server If C(Forced), it forcefully shuts down the system If C(NoReboot), it does not reboot the server
end_host_power_state	No	On	· On · Off	This option is applicable for C(import) state. If C(On), End host power state is on If C(Off), End host power state is off
export_format	No	XML	· JSON · XML	Specify the output file format. This option is applicable for C(export) state.
export_use	No	Default	· Default	Specify the type of SCP to be exported. This option is applicable for C(export) state.

Parameter/aliases	Required	Default	Choices	Comments
			CloneReplace	

Return Values

```
msq:
  type: str
  description: status of the import or export SCP job.
  returned: always
  sample: "Successfully imported the Server Configuration Profile"
scp status:
  type: dict
  description: SCP operation job and progress details from the iDRAC.
  returned: success
  sample:
    {
      "Id": "JID XXXXXXXXX",
      "JobState": "Completed",
      "JobType": "ImportConfiguration",
      "Message": "Successfully imported and applied Server Configuration Profile.",
      "MessageArgs": [],
      "MessageId": "XXX123",
      "Name": "Import Configuration",
      "PercentComplete": 100,
      "StartTime": "TIME_NOW",
      "Status": "Success"
      "TargetSettingsURI": null,
      "retval": true
```

Examples

```
- name: Import SCP from a network share and wait for this job to get completed.
  dellemc idrac server config profile:
                    "192.168.0.1
    idrac_ip:
    idrac_ip: "192.168.0. idrac_user: "user_name"
    idrac password: "user_password"
                     "import"
    command:
                    "192.168.0.2:/share"
    share name:
                   "share_user_name"
    share user:
    share password: "share user password"
    scp_file: "scp_filename.xml"
scp_components:"ALL"
    scp_file:
    job wait:
- name: Import SCP from a local path and wait for this job to get completed.
  dellemc_idrac_server_config_profile:
   idrac_ip: "192.168.0.1"
   idrac_user: "user_name"
    idrac password:"user password"
    command:
                     "import"
                    "/scp_folder"
    share_name:
    share user: "share_user_name"
    job wait:
- name: Export SCP to a network share
  dellemc_idrac_server_config_profile:
   idrac_ip: "192.168.0.1"
   idrac_user: "user_name"
                     "user_name"
    idrac user:
    idrac_password: "user_password"
                      "192.168.0.2:/share"
    share name:
    share user:
                     "share_user_name"
    share_password: "share_user_password"
    job wait:
                  False
```

```
- name: Export SCP to a local path
dellemc_idrac_server_config_profile:
    idrac_ip: "192.168.0.1"
    idrac_user: "user_name"
    idrac_password:"user_password"
    share_name: "/scp_folder"
    share_user: "share_user_name"
    share_password:"share_user_password"
    job_wait: False
```

Module: dellemc_idrac_server_config_profile

Synopsis

This module exports Server Configuration profile (SCP) to a given network share or imports SCP from a network share or a local file.

i NOTE: This module is deprecated and replaced with idrac_server_config_profile.

Table 10. dellemc_idrac_server_config_profile

Parameter	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
command	No	export	· import · export	 If C(import), will perform SCP import operations. If C(export), will perform SCP export operations.
job_wait	Yes	NA	NA	Whether to wait for job completion or not.
share_name	Yes	NA	NA	CIFS or NFS Network Share or a local path.
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\\user' if user is a part of a domain, else 'user'. This option is mandatory for CIFS Network Share.
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network Share.
scp_file	No	NA	NA	Server Configuration Profile file name. This option is mandatory for C(import) state.
scp_components	No	ALL	· ALL · IDRAC · BIOS · NIC · RAID	 If C(ALL), the module imports all components configurations from SCP file. If C(iDRAC), the module imports iDRAC configuration from SCP file. If C(BIOS), the module imports BIOS configuration from SCP file. If C(NIC), the module imports NIC configuration from SCP file. If C(RAID), the module imports RAID configuration from SCP file.
shutdown_type	No	Graceful	GracefulForcedNoReboot	This option is applicable for C(import) state. If C(Graceful), it gracefully shuts down the server

Parameter	Required	Default	Choices	Comments
				 If C(Forced), it forcefully shuts down the system If C(NoReboot), it does not reboot the server
end_host_power_state	No	On	· On · Off	This option is applicable for C(import) state. If C(On), End host power state is on If C(Off), End host power state is off
export_format	No	XML	· JSON · XML	Specify the output file format. This option is applicable for C(export) state.
export_use	No	Default	DefaultCloneReplace	Specify the type of Sever Configuration Profile (SCP) to be exported. This option is applicable for C(export) state.

Return Values

```
msa:
  description: status of the import or export SCP job.
  returned: always
  sample: "Successfully imported the Server Configuration Profile"
scp status:
  type: dict
  description: SCP operation job and progress details from the iDRAC.
  returned: success
  sample:
      "Id": "JID_XXXXXXXXX",
      "JobState": "Completed",
"JobType": "ImportConfiguration",
      "Message": "Successfully imported and applied Server Configuration Profile.",
      "MessageArgs": [],
      "MessageId": "XXX123",
      "Name": "Import Configuration",
      "PercentComplete": 100,
      "StartTime": "TIME NOW",
      "Status": "Success\overline{}",
      "TargetSettingsURI": null,
      "retval": true
    }
```

Examples

```
- name: Import Server Configuration Profile from a network share

dellemc_idrac_server_config_profile:
    idrac_ip: "192.168.0.1"
    idrac_user: "user_name"
    idrac_pwd: "user_pwd"
    command: "import"
    share name: "192.168.0.2:/share"
    share_user: "share_user_name"
    share_user: "share_user_pwd"
    scp_file: "scp_filename.xml"
    scp_components: "ALL"
    job_wait: True

- name: Import Server Configuration Profile from a local path
    dellemc_idrac_server_config_profile:
    idrac_ip: "192.168.0.1"
    idrac_user: "user_name"
    idrac_pwd: "user_pwd"
    command: "import"
    share name: "/scp folder"
```

```
share user: "share user name"
    share_pwd: "share_user_pwd"
scp_file: "scp_filename.xml"
scp_components: "ALL"
    job wait: True
- name: Export Server Configuration Profile to a network share
  dellemc idrac server config profile:
    idrac_ip: "192.168.0.1"
    idrac_user: "user_name"
    idrac_pwd: "user_pwd"
share_name: "192.168.0.2:/share"
    share user: "share user name"
    share_pwd: "share_user_pwd"
    job_wait: False
- name: Export Server Configuration Profile to a local path
  dellemc idrac_server_config_profile:
    idrac_ip: "192.168.0.1"
    idrac_user: "user_name"
    idrac_password: "user_password"
    share name: "/scp folder"
    share_user: "share_user_name" share_pwd: "share_user_pwd"
    job wait: False
```

Module: dellemc_import_server_config_profile

Synopsis

You can import an SCP file (in an XML or JSON format) exported from a golden PowerEdge server configuration to one or more servers, thus achieving an effortless, consistent, and automated deployment. Importing an SCP file is useful in restoring the configuration of the server to the state stored in the profile.

You can import SCP from a local or a remote share to iDRAC. For a remote share, make sure that a network share path and the file name are available. If there are component configurations (such as BIOS, RAID, NIC, iDRAC, and so on) present in the SCP file that require a server restart, you can use the **I(shutdown_type)** argument to specify whether a **Graceful** or **Forced** shutdown of the server is required.

Check_mode support: No

i NOTE: This module is deprecated and replaced with idrac_server_config_profile.

Table 11. dellemc_import_server_config_profile

Parameter	Required	Default	Choices	Comments
end_host_power_state	No	On	· On · Off	If On, End host power is on If Off, End host power is off
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_wait	Yes	NA	· True · False	If the value is True, it waits for the SCP import job to finish and returns the job completion status If the value is False, it returns immediately with a JOB ID after queuing the SCP import job in LC job queue
scp_components	No	ALL	· ALL	If ALL, the module imports all components configurations from SCP file

Parameter	Required	Default	Choices	Comments
			IDRAC BIOS RIC RAID	 If iDRAC, the module imports iDRAC configuration from SCP file If BIOS, the module imports BIOS configuration from SCP file If NIC, the module imports NIC configuration from SCP file If RAID, the module imports RAID configuration from SCP file
scp_file	Yes	NA	NA	Server Configuration Profile file name
share_name	Yes	NA	NA	Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
shutdown_type	No	Graceful	GracefulForcedNoReboot	 If Graceful, it gracefully shuts down the server If Forced, it forcefully shuts down the system If NoReboot, it does not reboot the server

Table 12. Return Values

Name	Description	Returned	Туре	Sample
Import SCP	Imports SCP from a network share or from a local file	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_import_server_config_profile.md

Example

```
-name: Import Server Configuration Profile

dellemc_import_server_config_profile

idrac_ip: "xx.xx.xx.xx"

idrac_user: "xxxx"

idrac_pwd: "xxxxxxxxx"

share_name: "xx.xx.xx.xx:/share"

share_user: "xxxx"

share_pwd: "xxxxxxxxx"

scp_file: "scp_file.xml"

scp_components: "ALL"

job_wait: "True"
```

Module: dellemc_export_server_config_profile

Synopsis

You can export **Server Configuration Profile (SCP)** with various components such as iDRAC, BIOS, NIC, RAID together or with one of these components. You can export SCP from iDRAC to a local or a network shared location. For shared location, make sure that a network share path is established.

Check_mode support: No

i NOTE: This module is deprecated and replaced with idrac_server_config_profile.

Table 13. dellemc_export_server_config_profile

Parameter	Required	Default	Choices	Comments
export_format	No	XML	· JSON · XML	The output file format
export_use	No	Default	Default Clone Replace	 If C(Default), will export the SCP using the Default method If C(Clone), will export the SCP using the Clone method If C(Replace), will export the SCP using the Replace method
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_wait	Yes	NA	True False	If the value is True, it waits for the SCP export job to finish and returns the job completion status If the value is False, it returns immediately with a JOB ID after queuing the SCP export job in LC job queue
share_name	Yes	NA	NA	CIFS or NFS network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
scp_components	No	ALL	· ALL · IDRAC · BIOS · NIC · RAID	Specify the hardware components configuration to be exported If ALL, the module exports all components configurations in SCP file If IDRAC, the module exports iDRAC configuration in SCP file If BIOS, the module exports BIOS configuration in SCP file If NIC, the module exports NIC configuration in SCP file If RAID, the module exports RAID configuration in SCP file

Table 14. Return Values

Name	Description	Returned	Туре	Sample
Export SCP	Exports the SCP to the provided network share or to the local path	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_export_server_config_profile.md

Example

-name: Export Server Configuration Profile (SCP)
dellemc_export_server_config_profile:
 idrac_ip: "xx.xx.xx.xx"
 idrac_user: "xxxx"

idrac_pwd: "xxxxxxxx"
share_name: "xx.xx.xx.xx:/share"
share_user: "xxxx"
share_pwd: "xxxxxxxxx" export_format: "XML"
export_use: "Default"
job_wait: "True"

Configuring iDRAC

Following are the modules responsible for configuring specific iDRAC attributes.

- Configure iDRAC users
- · Configure iDRAC timezone
- · Configure iDRAC eventing
- Configure iDRAC services
- Configure iDRAC network

Configure iDRAC users

Module: dellemc_configure_idrac_users

Synopsis

This module creates, modifies or deletes an iDRAC local user.

Check_mode support: Yes

Options

Table 15. dellemc_configure_idrac_users

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
action	No	create	createdeletemodify	This value decides whether to create or delete or modify iDRAC user
user_name	No	NA	NA	Provide the username to be created or deleted or modified
user_password	No	NA	NA	Provide the password for the user to be created or modified
privilege_users	No	NA	· NoAccess	Privilege user access is configurable

Parameter/aliases	Required	Default	Choices	Comments
			ReadonlyOperatorAdministrator	
ipmilanprivilege_users	No	NA	No_AccessAdministratorOperatorUser	IPMI Lan Privilege user access is configurable
ipmiserialprivilege_users	No	NA	No_AccessAdministratorOperatorUser	IPMI Serial Privilege user access is configurable NOTE: This parameter is not supported by PowerEdge Modular servers.
enable_users	No	NA	EnabledDisabled	Enabling or Disabling the new iDRAC user
solenable_users	No	NA	EnabledDisabled	Enabling or Disabling SOL for iDRAC user
protocolenable_users	No	NA	Enabled Disabled	Enabling or Disabling protocol for iDRAC user
authenticationprotocol_u sers	No	NA	T_None SHA MD5	Configuring authentication protocol for iDRAC user
privacyprotocol_users	No	NA	T_None DES AES	Configuring privacy protocol for iDRAC user

Table 16. Return Values

Name	Description	Returned	Туре	Sample
iDRAC users	Configures the iDRAC users attributes	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_configure_idrac_users.md

Example

```
-name: Configure the iDRAC users attributes
   dellemc_configure_idrac_users:
      idrac_ip:
idrac_user:
                                               "xx.xx.xx"
                                               "xxxx"
     idrac_password:
share_name:
share_password:
                                               "xxxxxxxx"
                                             "xx.xx.xx.xx:/share"
"xxxxxxxxx"
                                               "xxxx"
      share_user:
      share_mnt:
                                               "/mnt/share"
                                              "create"
      action:
                                             "username"
      user_name:
                                               "xxxxxxxx"
      user_password:
      user_password: "xxxxxxxx"
privilege_users: "Administrator"
ipmilanprivilege_users: "Administrator"
ipmilanprivilege_users: "Administrator"
      enable_users:
solenable_users:
                                               "Enabled"
                                               "Enabled"
      protocolenable_users:
                                               "Enabled"
      authenticationprotocol_users: "SHA" privacyprotocol_users: "AES"
```

Configure iDRAC timezone

Module: dellemc_configure_idrac_timezone

Synopsis

This module configures the iDRAC timezone related attributes.

Check_mode support: Yes

Options

Table 17. dellemc_configure_idrac_timezone

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
setup_idrac_timezone	No	NA	NA	Configuring the timezone for iDRAC
enable_ntp	No	NA	NA	Whether to Enable or Disable NTP for iDRAC
ntp_server_1	No	NA	NA	NTP configuration for iDRAC
ntp_server_2	No	NA	NA	NTP configuration for iDRAC
ntp_server_3	No	NA	NA	NTP configuration for iDRAC

Table 18. Return Values

Name	Description	Returned	Туре	Sample
iDRAC Timezone	Configures the iDRAC timezone attributes	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_configure_idrac_timezone.md

Example

Configure iDRAC eventing

Module: dellemc_configure_idrac_eventing

Synopsis

This module configures iDRAC eventing related attributes.

Check_mode support: Yes

Options

Table 19. dellemc_configure_idrac_eventing

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
destination_number	No	None	NA	Destination number for SNMP Trap
destination	No	None	NA	Destination for SNMP Trap
snmp_v3_username	No	NA	NA	SNMP v3 username for SNMP Trap
snmp_trap_state	No	NA	EnabledDisabled	Whether to Enable or Disable SNMP alert
email_alert_state	No	NA	EnabledDisabled	Whether to Enable or Disable Email alert
alert_number	No	None	NA	Alert number for Email configuration
address	No	NA	NA	Email address for SNMP Trap
custom_message	No	NA	NA	Custom message for SNMP Trap reference
enable_alerts	No	NA	EnabledDisabled	Whether to Enable or Disable iDRAC alerts
authentication	No	NA	EnabledDisabled	Simple Mail Transfer Protocol Authentication

Parameter/aliases	Required	Default	Choices	Comments
smtp_ip_address	No	NA	NA	SMTP IP address for communication
smtp_port	No	None	NA	SMTP Port number for access
username	No	None	NA	Username for SMTP authentication
password	No	None	NA	Password for SMTP authentication

Table 20. Return Values

Name	Description	Returned	Туре	Sample
_	Configures the iDRAC eventing attributes	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_configure_idrac_eventing.md

Example

Configure iDRAC services

Module: dellemc_configure_idrac_services

Synopsis

This module configures the iDRAC services related attributes.

Check_mode support: Yes

Options

Table 21. dellemc_configure_idrac_services

Parameter	Required	Default	Choices	Comments
idrac_ip	True	NA	NA	iDRAC IP Address
idrac_user	True	NA	NA	iDRAC username
idrac_password/ idrac_pwd	True	NA	NA	iDRAC user password
idrac_port	False	443	NA	iDRAC port
share_name	True	NA	NA	CIFS or NFS Network share or a local path

Parameter	Required	Default	Choices	Comments
share_user	False	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	False	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	False	NA	NA	Local mount path of the network share with read/write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
enable_web_server	False	NA	EnabledDisabled	Whether to Enable or Disable web server configuration for iDRAC
ssl_encryption	False	NA	Auto_NegotiateT_128_Bit_or_higherT_168_Bit_or_higherT_256_Bit_or_higher	Secure Socket Layer encryption for web server
tls_protocol	False	NA	TLS_1_0_and_HigherTLS_1_1_and_HigherTLS_1_2_Only	Transport Layer Security for web server
https_port	False	NA	NA	HTTPS access port
http_port	False	NA	NA	HTTP access port
timeout	False	NA	NA	Timeout value
snmp_enable	False	NA	Enabled Disabled	Whether to Enable or Disable SNMP protocol for iDRAC
snmp_protocol	False	NA	· All · SNMPv3	Type of the SNMP protocol
community_name	False	test	NA	SNMP community name for iDRAC
alert_port	False	None	NA	SNMP alert port for iDRAC
discovery_port	False	162	NA	SNMP discovery port for iDRAC
trap_format	False	None	SNMPv1, SNMPv2 or SNMPv3	SNMP trap format for iDRAC

Table 22. Return Values

Name	Description	Returned	Туре	Sample
iDRAC services	Configures the iDRAC services attributes	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_configure_idrac_services.md

Example

share_mnt: "/mnt/share"

share_mnt:
enable_web_server: "Enabled"
http_port: "80"
https_port: "443"
ssl_encryption: "Auto_Negotiate"
tls_protocol: "TLS_1_2_Only"
timeout: "1800"
snmp_enable: "Enabled"
snmp_protocol: "SNMPv3"
community_name: "test"
alert_port: "None"
discovery_port: "162"
trap_format: "None"

Configure iDRAC network

Module: dellemc_configure_idrac_network

Synopsis

This module configures the iDRAC networking attributes.

Check_mode support: Yes

Options

Table 23. dellemc_configure_idrac_network

Required	Default	Choices	Comments
Yes	NA	NA	iDRAC IP Address
Yes	NA	NA	iDRAC username
Yes	NA	NA	iDRAC user password
No	443	NA	iDRAC port
Yes	NA	NA	CIFS or NFS Network share or a local path
No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
No	NA	NA	Configuring the VLAN-related setting for iDRAC
No	NA	EnabledDisabled	Registering Domain Name System for iDRAC
No	NA	NA	DNS Name for iDRAC
No	NA	EnabledDisabled	Automatically creates the records for DNS
No	NA	NA	Static configuration for DNS
No	None	NA	Configuring the VLAN ID for iDRAC
No	None	NA	Configuring the VLAN priority for iDRAC
	Yes Yes Yes No Yes No	Yes NA Yes NA Yes NA No 443 Yes NA No No No No No No	Yes NA NA Yes NA NA Yes NA NA No 443 NA Yes NA NA No NA NA

Parameter/aliases	Required	Default	Choices	Comments
enable_nic	No	NA	Enabled Disabled	Whether to Enable or Disable Network Interface Controller for iDRAC
nic_selection	No	NA	DedicatedLOM1LOM2LOM3LOM4	Selecting Network Interface Controller types for iDRAC
failover_network	No	NA	· ALL · LOM1 · LOM2 · LOM3 · LOM4 · T_None	Failover Network Interface Controller types for iDRAC
auto_detect	No	NA	Enabled Disabled	Auto detect Network Interface Controller types for iDRAC
auto_negotiation	No	NA	Enabled Disabled	Auto negotiation of Network Interface Controller for iDRAC
network_speed	No	NA	T_10T_100T_1000	Network speed for Network Interface Controller types for iDRAC
duplex_mode	No	NA	· Full · Half	Transmission of data Network Interface Controller types for iDRAC
nic_mtu	No	None	NA	NIC Maximum Transmission Unit
ip_address	No	NA	NA	IP Address needs to be defined
enable_dhcp	No	NA	NA	Whether to Enable or Disable DHCP Protocol for iDRAC
dns_from_dhcp	No	NA	Enabled Disabled	Specifying Domain Name System from Dynamic Host Configuration Protocol
enable_ipv4	No	NA	Enabled Disabled	Whether to Enable or Disable IPv4 configuration
static_dns_1	No	NA	NA	Specify Domain Name System Configuration
static_dns_2	No	NA	NA	Specify Domain Name System Configuration
static_gateway	No	None	NA	Interfacing the network with another protocol
static_net_mask	No	None	NA	Determine whether IP address belongs to host

Table 24. Return Values

Name	Description	Returned	Туре	Sample
iDRAC network	Configures the iDRAC network attributes	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_configure_idrac_network.md

Example

-name: Configure the iDRAC network attributes
 dellemc_configure_idrac_network:

Configure BIOS

Module: dellemc_configure_bios

Synopsis

This module configures the BIOS attributes for PowerEdge servers.

Check_mode support: Yes

Table 25. dellemc_configure_bios

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	No	NA	NA	CIFS or NFS network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.

Parameter/aliases	Required	Default	Choices	Comments
boot_mode	No	NA	BiosUefi	(deprecated) Configures the boot mode to BIOS or UEFI. NOTE: This option has been deprecated, and will be removed in the later version. Please use the I(attributes) for BIOS attributes configuration instead. NOTE: I(boot_mode) is mutually exclusive with I(boot_sources).
boot_sequence	No	NA	NA	(deprecated) Boot devices' FQDDs in the sequential order for BIOS or UEFI Boot Sequence. Provide the I (boot_mode) option to determine the appropriate boot sequence to be applied. NOTE: This option has been deprecated, and will be removed in the later version. Please use the I(attributes) or I(boot_sources) for Boot Sequence modification instead. NOTE: I(boot_sequence) is mutually exclusive with I(boot_sources).
nvme_mode	No	NA	· NonRaid · Raid	(deprecated) Configures the NVME mode in the 14 th generation of PowerEdge servers. NOTE: This option has been deprecated, and will be removed in the later version. Please use the I(attributes) for BIOS attributes configuration instead. NOTE: I(nvme_mode) is mutually exclusive with I(boot_sources).
secure_boot_mode	No	NA	AuditMode,DeployedModeSetupModeUserMode	(deprecated) Configures how the BIOS uses the Secure Boot Policy Objects in the 14 th generation of PowerEdge servers. NOTE: This option has been deprecated, and will be removed in the later version. Please use the I(attributes) for BIOS attributes configuration instead. NOTE: I(secure_boot_mode) is mutually exclusive with I(boot_sources).
onetime_boot_mode	No	NA	 Disabled OneTimeBootSeq OneTimeCustomBootSeqSt r OneTimeCustomHddSeqStr 	(deprecated) Configures the one time boot mode setting. NOTE: This option has been deprecated, and will be removed in the later version. Please use the

Parameter/aliases	Required	Default	Choices	Comments
			 OneTimeCustomUefiBootS eqStr OneTimeHddSeq OneTimeUefiBootSeq 	I(attributes) for BIOS attributes configuration instead. NOTE: I(onetime_boot_mode) is mutually exclusive with I(boot_sources).
attributes	No	NA	NA	Dictionary of BIOS attributes and value pair. Attributes should be part of the Redfish Dell BIOS Attribute Registry. Redfish URI to view BIOS attributes: (https://l(idrac_ip)/redfish/v1/Systems/System.Embedded.1/Bios). If deprecated options are given and the same are repeated in I(attributes) then values in I(attributes) will take precedence.
				NOTE: I(attributes) is mutually exclusive with I(boot_sources).
				List of boot devices to set the boot sources settings. Boot devices are dictionary. While applying boot sequence, Index of at least one boot device should be 0. NOTE: I(boot_sources) is mutually exclusive with I(attributes), I(boot_sequence), I(onetime_boot_mode), I(secure_boot_mode), I(nvme_mode), and I(boot_mode).
boot_sources	No	NA	NA	NOTE: When user does not provide Index or Enabled value in boot_sources option, dellemc_configure_bios module uses the current Index or Enabled value from the target server for the specified boot source while applying boot sources. NOTE: In case the selected Index
				or Enabled value from the target server conflicts with any of the boot_sources option values to be applied, dellemc_configure_bios module may fail to apply with appropriate error message.

Table 26. Return Values

Name	Description	Returned	Туре	Sample
BIOS	Configures the BIOS configuration attributes	Success	String	https://github.com/dell/Dell-EMC- Ansible-Modules-for-iDRAC/blob/master/ samples/dellemc_configure_bios.md

Examples

-name: Configure BIOS Generic attributes
 dellemc_configure_bios:

```
attributes:
                  "Bios"
      BootMode :
      OneTimeBootMode: "Enabled"
      BootSeqRetry: "Enabled"
- name: Configure PXE Generic Attributes
   idrac_user:
                         "xxxx"
     idrac_password:
                         "xxxxxxxx"
     attributes:
      PxeDev1EnDis:
                         "Enabled"
       PxeDev1Protocol:
                         "IPV4"
                        "Enabled"
       PxeDev1VlanEnDis:
                         Х
       PxeDev1VlanId:
       PxeDev1Interface: "NIC.Embedded.x-x-x"
       PxeDev1VlanPriority: x
- name: Configure Boot Sources
   dellemc configure bios:
     idrac_ip: ":
idrac_user: ":
idrac_password: "xxxxxxxx"
                             "xx.xx.xx"
                             "xxxx"
     boot_sources:
       - Name : "NIC.Integrated.x-x-x"
         Enabled : True
         Index : 0
- name: Configure Boot Sources
  dellemc configure bios:
    idrac_password: "xxxxxxxx"
    boot sources:
      - Name : "NIC.Integrated.x-x-x"
       Enabled : True
        Index : 0
      - Name : "NIC.Integrated.x-x-x"
       Enabled : true
        Index : 1
      - Name : "NIC.Integrated.x-x-x"
       Enabled : true
        Index: 2
- name: Configure Boot Sources - Enabled
   dellemc_configure_bios:
     idrac_ip:
idrac_user:
                                    "xx.xx.xx"
                                    "xxxx"
     idrac_password: "xxxxxxxx"
     boot sources:
       - Name : "NIC.Integrated.x-x-x"
         Enabled : True
- name: Configure Boot Sources - Index
   dellemc_configure_bios:
     idrac_ip:
idrac_user:
                                   "xx.xx.xx"
                                  "xxxx"
     idrac_password: "xxxxxxxx"
     boot sources:
       - Name : "NIC.Integrated.x-x-x"
         Index : 0
```

Configure RAID

Module: dellemc_configure_raid

Synopsis

This module hosts the RAID configuration related attributes.

i NOTE: This module is deprecated and replaced with dellemc_idrac_storage_volume.

Options

Table 27. dellemc_configure_raid

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for Network share.
vd_name	No	NA	NA	Virtual disk name Optional, if we perform create operations Mandatory, if we perform remove operations
span_depth	No	1	NA	Span Depth
span_length	No	2	NA	Span Length
number_dedicated_hot_spare	No	0	NA	Number of Dedicated Hot Spare
number_global_hot_spare	No	0	NA	Number of Global Hot Spare
raid_level	No	RAID 0	 RAID 0 RAID 1 RAID 5 RAID 6 RAID 10 RAID 50 RAID 60 	Provide the required RAID level
disk_cache_policy	No	Default	DefaultEnabledDisabled	Disk Cache Policy

Parameter/aliases	Required	Default	Choices	Comments
write_cache_policy	No	WriteThrough	WriteThroughWriteBackWriteBackForce	Write cache policy
read_cache_policy	No	NoReadAhead	NoReadAheadReadAheadAdaptive	Read cache policy
stripe_size	No	65536	NA	Provide stripe size value in multiples of 64 * 1024
controller_fqdd	Yes	NA	NA	Fully Qualified Device Descriptor (FQDD) of the storage controller, for e.g. RAID. Integrated. 1-1
media_type	No	HDD	· HDD · SSD	Media type
bus_protocol	No	SATA	· SAS · SATA	Bus protocol
state	Yes	NA	presentabsent	If the value is 'present', the module will perform 'create' operations If the value is 'absent', the module will perform 'remove' operations

Table 28. Return Values

Name	Description	Returned	Туре	Sample
RAID configuration	Configures the RAID configuration attributes	Success		https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_configure_raid.md

Example

Configure storage volume

Module: dellemc_idrac_storage_volume

Synopsis

This module hosts the RAID configuration related attributes.

Check_mode support: Yes

Table 29. dellemc_idrac_storage_volume

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
span_depth	No	1	NA	Span Depth
span_length	No	1	NA	Span Length
number_dedicated_hot_ spare	No	0	NA	Number of Dedicated Hot Spare
volume_type	No	RAID 0	 RAID 0 RAID 1 RAID 5 RAID 6 RAID 10 RAID 50 RAID 60 	Provide the required RAID level
disk_cache_policy	No	Default	DefaultEnabledDisabled	Disk Cache Policy
write_cache_policy	No	WriteThrough	WriteThroughWriteBackWriteBackForce	Write Cache Policy
read_cache_policy	No	NoReadAhead	NoReadAheadReadAheadAdaptiveReadAhead	Read Cache Policy
stripe_size	No	65536	NA	Provide stripe size value in multiples of 64 * 1024
controller_id	No	NA	NA	Fully Qualified Device Descriptor (FQDD) of the storage controller, for example: RAID.Integrated.1-1 i NOTE: Controller FQDD is required for C(create) RAID configuration.
volume_id	No	NA	NA	Fully Qualified Device Descriptor (FQDD) of the virtual disk, for example: Disk.virtual.0:RAID.Slot.1-1 NOTE: This option is used to get the virtual disk information.
media_type	No	None	· HDD · SDD	Media type
protocol	No	None	· SAS · SATA	Bus protocol
state	Yes	view	createdeleteview	C(create) performs create volume operations.

Parameter/aliases	Required	Default	Choices	Comments
				 C(delete) performs remove volume operations. C(view) returns the storage view.
volumes	No	NA	NA	A list of virtual disk-specific iDRAC attributes. This is applicable for C(create) and C(delete) operations.
				 For C(create) operation, name and drives are applicable options, other volume options can also be specified. NOTE: The drives is a required option for C(create) operation and accepts either location (list of drive slot) or id (list of drive fqdd). For C(delete) operation, only name option is applicable.
capacity	No	NA	NA	Virtual disk size in GB
raid_reset_config	No	NA	NA	This option represents whether a Reset Config operation needs to be performed on the RAID controller. Reset Config operation deletes all the virtual disks present on the RAID controller.
raid_init_operation	No	None	None Fast	This option represents Initialization Configuration operation to be performed on the virtual disk.

```
msg:
  type: str
  description: Overall status of the storage configuration operation.
  returned: always
  sample: "Successfully completed the view storage volume operation"
storage_status:
  type: dict
  description: Storage configuration job and progress details from the iDRAC.
  returned: success
  sample:
    {
      "Id": "JID_XXXXXXXXX",
      "JobState": "Completed",
"JobType": "ImportConfiguration",
"Message": "Successfully imported and applied Server Configuration Profile.",
       "MessageId": "XXX123",
       "Name": "Import Configuration",
       "PercentComplete": 100,
      "StartTime": "TIME NOW",
       "Status": "Success",
       "TargetSettingsURI": null,
       "retval": true
```

```
-name: Create single volume

dellemc_idrac_storage_volume:
   idrac_ip: "192.168.0.1"
   idrac_user: "username"
   idrac_password: "password"
   controller_id: "RAID.Slot.1-1"
   state: "create"
```

```
volumes:
        - drives:
           location:
                         [5]
-name: Create multiple volume
   dellemc idrac storage volume:
                                     "192.168.0.1"
     idrac ip:
                                    "username"
     idrac_user:
     idrac_password:
raid_reset_config:
                                    "password"
                                    "True"
                                    "create"
     state:
     controller_id:
                                     "RAID.Slot.1-1"
     volume_type:
                                      "RAID 1"
     span depth:
     span_length:
number_dedicated_hot_spare: 1
"Enabled"
     span_length:
     disk_cache_policy:
write_cache_policy:
read_cache_policy:
                                      "WriteBackForce"
     read cache policy:
                                     "ReadAhead"
                                      65536
     stripe_size:
     capacity:
                                       100
     raid_init_operation:
                                      "Fast"
     volumes:
        - name:
                                      "volume 1"
         drives:
              id:
                                      ["Disk.Bay.1:Enclosure.Internal.0-1:RAID.Slot.1-1",
                                       "Disk.Bay.2:Enclosure.Internal.0-1:RAID.Slot.1-1"]
                                      "volume_2"
       - name:
          volume_type:
                                      "RAID 5"
          span_length:
                                      3
          span depth:
                                      1
         drives:
         location: [7,3,5]
disk_cache_policy: "Disabled"
write_cache_policy: "WriteBack"
read_cache_policy: "NoReadAhead"
          read_cache_policy:
          stripe size:
                                      131072
                                       200
          capacity:
                                      "None"
          raid_init_operation:
-name: View all volume details
   dellemc_idrac_storage_volume:
                                           "192.168.0.1"
     idrac_ip:
     idrac_user:
                                           "username"
     idrac_password: "password"
                                           "view"
     state:
-name: View specific volume details
   dellemc_idrac_storage_volume:
     idrac_ip: "192.168.0.1" idrac_user: "username"
     idrac_password: "password"
state: "view"
     state:
controller_id: "RAID.Slot.1-1"
wolume id: "Disk.Virtual.0:RAID.Slot.1-1"
-name: Delete single volume
   dellemc_idrac_storage_volume:
                                   "192.168.0.1"
     idrac_ip:
     idrac_user: ""
idrac_password: "password"
                                   "username"
                                   "delete"
     state:
     volumes:
                 "volume_1"
       - name:
-name: Delete multiple volume
   dellemc_idrac_storage_volume:
                                   "192.168.0.1"
     idrac ip:
```

```
idrac_user: "username"
idrac_password: "password"
state: "delete"
volumes:
    - name: "volume_1"
    - name: "volume_2"
```

Configure Collect System Inventory on Restart

Module: dellemc_idrac_lc_attributes

Synopsis

This module is responsible for enabling or disabling of **Collect System Inventory on Restart (CSIOR)** property for all iDRAC or LC jobs. When you enable the **CSIOR** property, hardware inventory and part configuration information are discovered and compared with previous system inventory information on every system restart.

Check_mode support: Yes

Options

Table 30. dellemc_idrac_lc_attributes

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA Local mount path of the network shar read-write permission for Ansible user option is mandatory for CIFS or NFS ishare.	
csior	Yes	NA	 Enabled Disabled Whether to Enable or Disable Collect System Inventory on Restart (CSIOR) property to iDRAC or LC jobs 	

Table 31. Return Values

Name	Description	Returned	Туре	Sample
iDRAC CSIOR	Configures CSIOR property for all iDRAC or LC jobs	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_idrac_lc_attributes.md

```
-name: Set up iDRAC LC Attributes

dellemc_idrac_lc_attributes:
    idrac_ip: "xx.xx.xx.xx"
    idrac_user: "xxxx"
    idrac_password: "xxxxxxxx"
    share_name: "xx.xx.xx.xx:/share"
    share_user: "xxxxx"
    share_password: "xxxxxxxxx"
```

Configure syslog

Module: dellemc_setup_idrac_syslog

Synopsis

This module enables or disables syslog parameters for iDRAC.

Check_mode support: Yes

Options

Table 32. dellemc_setup_idrac_syslog

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
share_mnt	No	NA	NA	Local mount path of the network share with read-write permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
syslog	Yes	NA	EnabledDisabled	Whether to Enable or Disable iDRAC syslog

Table 33. Return Values

Nam	Description	Returned	Туре	Sample
iDRAC Syslog	Configures iDRAC Syslog parameters	Success		https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_setup_idrac_syslog.md

Deploying operating system

To provision a bare metal server, it is essential to deploy the required operating system in the device before you start using it. This section describes the process of deploying the operating system on the PowerEdge servers using Ansible.

To automate the process of operating system deployment in an unattended manner using Ansible, the iDRAC's capability is utilized to transfer the customized ISO to iDRAC for boot.

To perform OS deployment, ensure:

- · Operating system image is injected with required Dell drivers, and unattended response file.
- · iDRAC is enabled, configured, and reachable.
- · RAID is configured.

Boot to a network ISO image

Module: idrac_os_deployment

Synopsis

This module facilitates the operating system deployment. You can run this module to boot the target system to a bootable ISO image on a CIFS or NFS share. This module looks for the customized ISO in the configured share location and transfers the image to iDRAC to load it. On the system reboot, the operating system deployment begins.

Check_mode support: No

Options

Table 34. idrac_os_deployment

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC password
idrac_port	No	443	NA	iDRAC port
iso_image	Yes	NA	NA	Network ISO name
share_name	Yes	NA	NA	CIFS or NFS Network share
share_user	No	NA	NA	User name required to access the network share must be provided as either 'user@domain' or 'domain\user'. This option is mandatory for CIFS network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network shares.
expose_duration	No	1080	NA	It is the time taken in minutes for the ISO image file to be exposed as a local CD-ROM device to the host server. When the specified time expires, the ISO image gets automatically detached.

Table 35. Return Values

Name	Description	Returned	Туре	Sample
Boot to Network ISO	Boots to a network ISO Image	Success	l Strina	https://github.com/dell/Dell-EMC- Ansible-Modules-for-iDRAC/blob/

Name	Description	Returned	Туре	Sample
				master/samples/ dellemc_boot_to_network_iso.md

```
-name: Boot to Network ISO

idrac_os_deployment:
idrac_ip: "192.168.0.1"
idrac_user: "user_name"
idrac_password: "user_password"
share_name: "192.168.0.0:/nfsfileshare"
share_user: "share_user_name"
share_password: "share_user_pwd"
iso_image: "unattended_os_image.iso"
expose_duration: 180
```

Return

```
description: Details of the boot to network ISO image operation.
returned: always
type: dict
sample: {
    "DeleteOnCompletion": "false",
    "InstanceID": "DCIM_OSDConcreteJob:1",
    "JobName": "BootToNetworkISO",
    "JobStatus": "Success",
    "Message": "The command was successful.",
    "MessageID": "OSD1",
    "Name": "BootToNetworkISO",
    "Status": "Success",
    "file": "192.168.0.0:/nfsfileshare/unattended_os_image.iso",
    "retval": true
}
```

Module: dellemc_boot_to_network_iso

Synopsis

This module facilitates the operating system deployment. You can run this module to boot the target system to a bootable ISO image on a CIFS or NFS share. This module looks for the customized ISO in the configured share location and transfers the image to iDRAC to load it. On the system reboot, the OS deployment begins.

Check_mode support: No

i NOTE: This module is deprecated and replaced with idrac_os_deployment.

Table 36. dellemc_boot_to_network_iso

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC password
idrac_port	No	443	NA	iDRAC port
iso_image	Yes	NA	NA	Network ISO name
share_name	Yes	NA	NA	CIFS or NFS Network share
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part

Parameter/aliases	Required	Default	Choices	Comments
				of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.

Table 37. Return Values

Name	Description	Returned	Туре	Sample
Boot to Network ISO	Boots to a network ISO Image	Success	String	https://github.com/dell/Dell-EMC- Ansible-Modules-for-iDRAC/blob/ master/samples/ dellemc_boot_to_network_iso.md

Example

Server Inventory

This section describes the process of retrieving the server inventory of the PowerEdge Servers using Ansible Modules.

View the system inventory

Module: dellemc_get_system_inventory

Synopsis

System inventory provides basic and component level detailed inventory information. You can run this module when you want to verify the asset, configured state, inventory, and health-related information for the system and its component.

Check_mode support: No

Options

Table 38. dellemc_get_system_inventory

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port

Table 39. Return Values

Name	Description	Returned	Туре	Sample
System Inventory	Displays the PowerEdge Server System Inventory	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_get_system_inventory.md

```
-name: Get System Inventory
dellemc_get_system_inventory:
   idrac_ip: "xx.xx.xx.xx"
   idrac_user: "xxxxx"
   idrac_password:"xxxxxxxxx"
```

Server administration tasks

This section describes the tasks that you can run using OpenManage Ansible Modules. Following are the tasks:

- · Configure the power state on the PowerEdge servers
- Reset iDRAC
- · View LC job status
- Export LC logs
- · Delete LC job
- · Delete LC job queue
- Configure System Lockdown Mode

Configure the power state on the PowerEdge servers

Module: dellemc_change_power_state

Synopsis

This module configures the power control options on a PowerEdge server. You can run this module:

- To turn on the server.
- · To turn off the server.
- · To reboot the server.
- · For hard reset of the server.

Check_mode support: Yes

Options

Table 40. dellemc_change_power_state

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
change_power	Yes	NA	On ForceOff GracefulRestart GracefulShutdown PushPowerButton Nmi	Desired power state

Table 41. Return Values

Name	Description	Returned	Туре	Sample
Power state of a server	Configures the power control options on a PowerEdge server	Success	String	https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_change_power_state.md

Reset iDRAC

Module: dellemc_idrac_reset

Synopsis

You can reset the iDRAC using this module.

Check_mode support: Yes

Options

Table 42. dellemc_idrac_reset

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port

Table 43. Return Values

Name	Description	Returned	Туре	Sample
Reset iDRAC	Resets the iDRAC	Success		https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_idrac_reset.md

Example

View LC job status

Module: dellemc_get_lc_job_status

Synopsis

You can view the iDRAC or LC job status using this module. To view information about a job status, a job id is required. After a job is initiated, the system stages the job request information and sends a job id back to the system. You can query the progress and status of the job by using the job id.

Check_mode support: No

Options

Table 44. dellemc_get_lc_job_status

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address

Parameter/aliases	Required	Default	Choices	Comments
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_id	Yes	NA	NA	JOB ID in the format "JID_123456789012"

Table 45. Return Values

Name	Description	Returned	Туре	Sample
LC Job Status	Displays the status of an LC job	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_get_lc_job_status.md

Example

```
-name: Get LC Job Status
dellemc_get_lc_job_status
idrac_ip: "xx.xx.xx.xx"
idrac_user: "xxxx"
idrac_password: "xxxxxxxxx"
job_id: "JID_1234567890"
```

Export LC logs

Module: dellemc_export_lc_logs

Synopsis

LC logs provide records of past activities on a managed system. These log files are useful for the server administrators since they provide detailed information about recommended actions and some other technical information that is useful for troubleshooting purposes.

The various types of information available in LC logs are alerts-related, configuration changes on the system hardware components, firmware changes due to an upgrade or downgrade, replaced parts, temperature warnings, detailed timestamps of when the activity has started, severity of the activity, and so on.

Check_mode support: No

Options

Table 46. dellemc_export_lc_logs

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS Network share
share_user	No	NA	NA	Network share user in the format 'user@domain' or 'domain\user' if user is part of a domain else 'user'. This option is mandatory for CIFS Network share.
share_password/ share_pwd	No	NA	NA	Network share user password. This option is mandatory for CIFS Network share.
job_wait	Yes	NA	True False	If the value is True, it waits for the job to complete and returns the job completion status

Parameter/aliases	Required	Default	Choices	Comments
				If the value is False, it returns immediately with a JOB ID after queuing the job in LC job queue

Table 47. Return Values

Name	Description	Returned	Туре	Sample
LC logs	Exports the LC logs to the given network share	Success		https://github.com/dell/Dell-EMC-Ansible- Modules-for-iDRAC/blob/master/samples/ dellemc_export_lc_logs.md

Example

Delete LC job

Module: dellemc_delete_lc_job

Synopsis

This module deletes an LC job for a given valid JOB ID from the job queue.

You can delete an LC job:

- · after the job is completed.
- · if you do not want to perform the job or if it is taking long to execute.

Check_mode support: Yes

Options

Table 48. dellemc_delete_lc_job

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
job_id	Yes	NA	NA	JOB ID in the format "JID_XXXXXXXXX"

Table 49. Return Values

Name	Description	Returned	Туре	Sample
Delete LC job	Deletes an LC job for a given a JOB ID	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_delete_lc_job.md

Delete LC job queue

Module: dellemc_delete_lc_job_queue

Synopsis

You can delete all the jobs in the LC job queue using this module. All the jobs in the job queue are terminated when you delete a job queue. Check_mode support: No

Options

Table 50. dellemc_delete_lc_job_queue

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port

Table 51. Return Values

Name	Description	Returned	Туре	Sample
LC Job Queue	Deletes the LC job queue	Success	I String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_delete_lc_job_queue.md

Example

Configure System Lockdown Mode

Module: dellemc_system_lockdown_mode

Synopsis

System Lockdown Mode provides a mechanism to protect configuration from any unintentional or accidental changes after the system is provisioned to a certain level.

This module is responsible for enabling or disabling the lockdown mode of a system. When System Lockdown Mode is enabled, the system's configuration is locked and system cannot be configured or updated until the lockdown mode is disabled.

Check_mode support: No

Table 52. dellemc_system_lockdown_mode

Parameter/aliases	Required	Default	Choices	Comments
idrac_ip	Yes	NA	NA	iDRAC IP Address
idrac_user	Yes	NA	NA	iDRAC username
idrac_password/ idrac_pwd	Yes	NA	NA	iDRAC user password
idrac_port	No	443	NA	iDRAC port
share_name	Yes	NA	NA	CIFS or NFS network share or a local path
share_user	No	NA	NA	Network share user in the format 'user@domain' or user\domain if user is part of a domain else 'user'. This field is mandatory for CIFS Network Share.
share_password/ share_pwd	No	NA	NA	Network share user password. This field is mandatory for CIFS Network Share.
share_mnt	No	NA	NA	Local mount path of the network share with readwrite permission for Ansible user. This option is mandatory for CIFS or NFS Network share.
lockdown_mode	Yes	NA	EnabledDisabled	Whether to Enable or Disable system lockdown mode

Table 53. Return Values

Name	Description	Returned	Туре	Sample
System Lockdown Mode	Configures lockdown mode of the system	Success	String	https://github.com/dell/Dell-EMC-Ansible-Modules-for-iDRAC/blob/master/samples/dellemc_system_lockdown_mode.md

Example

Storage controller

This section describes the process of configuring the storage controller settings of the PowerEdge servers using Ansible modules.

Configure storage controller settings

Module: idrac_redfish_storage_controller

Synopsis

This module configures the storage controller settings using Redfish APIs.

Table 54. idrac_redfish-storage-controller

Parameter	Required	Default	Choices	Comments
baseuri	True	NA	NA	IP address of the target iDRAC. For example- <ipaddress>:<port></port></ipaddress>
username	True	NA	NA	Username of the target iDRAC.
password	True	NA	NA	Password of the target iDRAC.
command	False	AssignSpare	ResetConfig, AssignSpare, SetControllerKey, RemoveControllerKey,or ReKey.	Set of actions to configure the storage controller settings. C(ResetConfig) - Deletes all the virtual disks and unassigns all hot spares on physical disks. C(AssignSpare) - Assigns a physical disk as a dedicated or global hot spare for a virtual disk. C(SetControllerKey) - Sets the key on controllers, which is used to encrypt the drives in Local key Management(LKM). C(RemoveControllerKey) - Erases the encryption key on the controller. C(ReKey) - Resets the key on the controller.
target	False	NA	NA	 Fully Qualified Device Descriptor (FQDD) of the target physical drive that is assigned as a spare. This [option] is mandatory when I(command) is C(AssignSpare) If I(volume_id) is not specified or empty, this physical drive will be assigned as a global hot spare.
volume_id	False	NA	NA	 FQDD of the volumes to which a hot spare is assigned. [This option is] Applicable if I(command) is C(AssignSpare). To know the number of volumes to which a hot spare can be assigned, refer iDRAC Redfish API guide.
controller_id	False	NA	NA	FQDD of the storage controller. For example- 'RAID.Slot.1-1'. This option is mandatory when I(command) is C(ResetConfig), C(SetControllerKey), C(RemoveControllerKey) and C(ReKey).
key	False	NA	NA	A new security key passphrase that the encryption-capable controller uses to create the encryption key. The controller uses the encryption key to lock

Parameter	Required	Default	Choices	Comments
				or unlock access to the Self Encryption Disk(SED). Only one encryption key can be created for each controller. This option is mandatory when I(command) is C(SetControllerKey) or C(ReKey), and when I(mode) is C(LKM).
key_id	False	NA	NA	 This is a user supplied text label associated with the passphrase. This option is mandatory when I(command) is C(SetControllerKey) or C(ReKey), and when I(mode) is C(LKM).
old_key	False	NA	NA	 Security key passphrase used by the encryption-capable controller. This option is mandatory when I(command) is C(ReKey) and I(mode) is C(LKM).
mode	False	NA	LKM or SEKM	Encryption mode of the encryption-capable controller: 1 Local Key Management (LKM), 2 - Security Enterprise Key Manager(SEKM). This option is applicable only when I(command) is C(ReKey). C(SEKM) requires secure enterprise key manager license on the iDRAC.

```
msg:
  type: str
  description: Overall status of the storage controller configuration operation.
 returned: always
 sample: "Successfully submitted the job that performs AssignSpare operation"
task:
  type: dict
  description: ID and URI resource of the created job.
  returned: success
 sample: {
  "id": "JID_XXXXXXXXXXXXX",
    error info:
  type: dict
  description: Details of a http error.
 returned: on http error
  sample: {
    "error": {
      "@Message.ExtendedInfo": [
         "Message": "Cannot run the method because the requested HTTP method is not
allowed.",

"MessageArgs": [],
         "MessageArgs@odata.count": 0,
"MessageId": "iDRAC.1.6.SYS402",
```

```
- name: Assign [a] dedicated hot spare.
  idrac redfish storage controller:
    baseuri: "192.168.0.1:443"
    username: "user_name"
    password: "user_password"
    volume_id: "Disk.Virtual.0:RAID.Slot.1-1"
    target: "Disk.Bay.0:Enclosure.Internal.0-1:RAID.Slot.1-1"
    - assign dedicated hot spare
- name: Assign [a] global hot spare.
  idrac redfish storage controller:
    baseuri: "192.168.0.1:443"
    username: "user_name"
password: "user_password"
    target: "Disk.Bay.0:Enclosure.Internal.0-1:RAID.Slot.1-1"
  tags:
    - assign global hot spare
- name: Set [a] controller encryption key.
  idrac_redfish_storage_controller:
    baseuri: "192.168.0.1:443"
    username: "user_name"
password: "user_password"
    command: "SetControllerKey"
    controller id: "RAID.Slot.1-1"
    key: "PassPhrase@123"
    key_id: "mykeyid123"
  tags:
    - set controller key
- name: Rekey in LKM mode.
  idrac_redfish_storage_controller:
    baseuri: "192.168.0.1:443"
    username: "user_name"
    password: "user_password"
command: "ReKey"
    controller id: "RAID.Slot.1-1"
    key: "PassPhrase@123"
    key_id: "mykeyid123"
    old key: "OldPassPhrase@123"
  tags:
    - rekey_lkm
- name: Rekey in SEKM mode.
  idrac_redfish_storage_controller:
    baseuri: "192.168.0.1:443"
    username: "user_name"
    password: "user_password"
    command: "ReKey"
    controller id: "RAID.Slot.1-1"
    mode: "SEKM"
  tags:
    - rekey_sekm
- name: Remove [the] controller key.
  idrac redfish storage controller:
   baseuri: "192.168.0.1:443"
```

Modules for OpenManage Enterprise (OME)

How OpenManage Ansible Modules work with OME

OpenManage Enterprise (OME) is a system management and monitoring application that provides rich sets of features to manage the Dell EMC servers, chassis, storage, and network switches in an enterprise data center or IT environment. Using the comprehensive set of REST APIs provided by OME, system administrators and software developers can discover, configure, provision, update, and manage their entire Dell EMC infrastructure.

OpenManage Ansible modules for OME simplifies and automates the PowerEdge server and modular infrastructure provisioning, deployment, and updates supported by OME. Leveraging the repeatable template configuration and deployment feature provided by OME, administrators can automatically deploy the changes, ensure consistency and thereby significantly improve productivity by reducing manual interactions and errors.

For information on which user roles in OME have the required privileges to run modules, refer roles and associated privileges for OME.

Running your first OME Playbook

Before you run a playbook to manage your iDRACs using OME, you need to have an inventory file that contains the target OME server details. For more information on inventory, see Ansible documentation

- 1. Install OpenManage Ansible Modules either from the dell.com/support or the https://github.com/dell/dellemc-openmanage-ansible-modules.git repository. For more details, see Dell EM C OpenManage Ansible Modules Installation Guide.
- 2. Create an inventory file containing a list of the OMEs. In the following inventory example, we are using the inventory variables to store the OME IP addresses and the user credentials. For more information on variables, see Ansible documentation.

```
inventory:

[PowerEdge]
ome.example.com
ome_ipaddress= '192.168.1.1'
ome_username='ome_user'
ome_password='ome_password'
```

3. Define a playbook to fetch the server inventory managed by the OME. Create the playbook in the same directory where you created the inventory. Following is a playbook example:

```
playbook.yml
---
- hosts: PowerEdge
  connection: local
  gather_facts: False

tasks:
- name: Get server inventory
  dellemc_ome_device_facts:
    hostname: "{{ ome_ipaddress }}"
    username: "{{ ome_username }}"
    password: "{{ ome_password }}"
    system_query_options:
       filter: "Type eq 1000"
```

4. Now run the playbook. Run the following command from the directory where you created the inventory and the playbook:

```
ansible-playbook playbook.yml -i inventory
```

5. Press Enter.

With OpenManage Ansible Modules, you can construct a playbook with a set of modules resulting in an automation workflow for configuration, deployments, and updates of PowerEdge and modular servers.

To view the list of all available OME modules:

1. Run the following command on the Ansible control machine:

```
ansible-doc -1 | grep "ome"
```

2. Press Enter.

List of the available OME modules is displayed.

To view the documentation of a module:

1. Run the following command on the Ansible control machine:

```
ansible-doc <module name>
```

2. Press Enter.

View device information

Module: ome_device_info

Synopsis

This module retrieves the list of devices in the inventory of OpenManage Enterprise along with the details of each device.

Options

Table 55. ome_device_info

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
fact_subset	No	basic_inventory	basic_inventorydetailed_inventorysubsystem_health	 C(basic_inventory) returns the list of the devices. C(detailed_inventory) returns the inventory details of specified devices. C(subsystem_health) returns the health status of specified devices.
system_query_options	No	NA	 device_id: A list of unique identifier is applicable for C(detailed_inventory) and C(subsystem_health). device_service_tag: A list of service tags is applicable for C(detailed_inventory) and C(subsystem_health). inventory_type: For C(detailed_inventory), it returns details of the specified inventory type. filter: For C(basic_inventory), it filters the collection of devices. I(filter) query format should be aligned with OData standards. 	Il(system_query_options) is applicable for the choices of the fact_subset. Either I(device_id) or I(device_service_tag) is mandatory for C(detailed_inventory) and C(subsystem_health). Il(device_id) or I(device_service_tag)

Parameter	Required	Default	Choices	Comments
				can be used individually or together.

```
msq:
  type: str
  description: Overall device information status.
  returned: on error
  sample: "Failed to fetch the device information"
device_info:
  type: dict
  description: Returns the information collected from the device.
  returned: success
  sample: {
         "value": [
             {
                  "Actions": null,
"AssetTag": null,
                  "ChassisServiceTag": null,
                  "ConnectionState": true,
"DeviceManagement": [
                       {
                           "DnsName": "dnsname.host.com",
                           "InstrumentationName": "MX-12345"
                           "MacAddress": "11:10:11:10:11:10"
                           "ManagementId": 12345,
                           "ManagementProfile": [
                                {
                                     "HasCreds": 0,
                                    "ManagementId": 12345,
                                     "ManagementProfileId": 12345,
                                    "ManagementURL": "https://192.168.0.1:443",
                                    "Status": 1000,
                                    "StatusDateTime": "2019-01-21 06:30:08.501"
                                }
                          "ManagementType": 2,
"NetworkAddress": "192.168.0.1"
                  ],
"DeviceName": "MX-0003I"
"MXL-0003I"
                  "DeviceServiceTag": "MXL1234",
                  "DeviceSubscription": null,
"LastInventoryTime": "2019-01-21 06:30:08.501",
                  "LastStatusTime": "2019-01-21 06:30:02.492",
                  "ManagedState": 3000,
                  "Model": "PowerEdge MX7000",
                  "PowerState": 17,
                  "SlotConfiguration": {},
                  "Status": 4000,
                  "SystemId": 2031,
                  "Type": 2000
             }
         ]
    }
```

```
    name: Retrieve basic inventory of all devices.
    ome_device_info:
        hostname: "192.168.0.1"
        username: "username"
        password: "password"
    name: Retrieve basic inventory for devices identified by IDs 33333 or 11111 using filtering.
        ome_device_info:
        hostname: "192.168.0.1"
```

```
username: "username"
    password: "password"
    fact subset: "basic inventory"
    system query options:
      filter: "Id eq 33333 or Id eq 11111"
- name: Retrieve inventory details of specified devices identified by IDs 11111 and 22222.
  ome device info:
     hostname: "192.168.0.1"
     username: "username"
     password: "password"
     fact subset: "detailed inventory"
     system_query_options:
       device_id:
        - 11111
        - 22222
- name: Retrieve inventory details of specified devices identified by service tags MXL1234
and MXL4567.
  ome device info:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    fact subset: "detailed inventory"
    system_query_options:
      device_service_tag:
         - MX\overline{L}1234
        - MXL4567
- name: Retrieve details of specified inventory type of specified devices identified by ID
and service tags.
  ome_device_info:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    fact subset: "detailed inventory"
    system_query_options:
     device id:
         -11\overline{1}11
      device service tag:
        - MXL1234
        - MXL4567
      inventory_type: "serverDeviceCards"
- name: Retrieve subsystem health of specified devices identified by service tags.
  ome device info:
    hostname: "192.168.0.1" username: "username"
    username: "username"
password: "password"
    fact subset: "subsystem health"
    system_query_options:
      device_service_tag:
        - MXL1234
        - MXL4567
```

View device inventory

Module: dellemc_ome_device_facts

Synopsis

This module retrieves the list of all devices with the exhaustive inventory of each device discovered using OpenManage Enterprise.

i NOTE: This module is deprecated and replaced with ome_device_info

Table 56. dellemc_ome_device_facts

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
fact_subset	No	basic_inventory	basic_inventorydetailed_inventorysubsystem_health	 C(basic_inventory) returns the list of the devices. C(detailed_inventory) returns the inventory details of specified devices. C(subsystem_health) returns the health status of specified devices.
system_query_options	No	NA	 device_id: A list of unique identifier is applicable for C(detailed_inventory) and C(subsystem_health). device_service_tag: A list of service tags is applicable for C(detailed_inventory) and C(subsystem_health). inventory_type: For C(detailed_inventory), it returns details of the specified inventory type. filter: For C(basic_inventory), it filters the collection of devices. I(filter) query format should be aligned with OData standards. 	I(system_query_options) is applicable for the choices of the fact_subset. Either I(device_id) or I(device_service_tag) is mandatory for C(detailed_inventory) and C(subsystem_health) or both can be applicable.

```
msg:
 type: str
  description: Over all device facts status.
 returned: on error sample: "Failed to fetch the device facts"
ansible_facts:
  type: dict
  description: Device inventory details.
  returned: success
  sample: {
         "value": [
                 "Actions": null,
                 "AssetTag": null,
                 "ChassisServiceTag": null,
                 "ConnectionState": true,
                 "DeviceManagement": [
                          "DnsName": "dnsname.host.com",
                          "InstrumentationName": "MX-12345",
                          "MacAddress": "11:10:11:10:11:10"
"ManagementId": 12345,
                          "ManagementProfile": [
                                   "HasCreds": 0,
                                   "ManagementId": 12345,
                                   "ManagementProfileId": 12345,
                                   "ManagementURL": "https://192.168.0.1:443",
                                   "Status": 1000,
```

```
"StatusDateTime": "2019-01-21 06:30:08.501"
                          }
                     "ManagementType": 2,
                     "NetworkAddress": "192.168.0.1"
             "DeviceName": "MX-00031",
             "DeviceServiceTag": "MXL1234",
             "DeviceSubscription": null,
"LastInventoryTime": "2019-01-21 06:30:08.501",
             "LastStatusTime": "2019-01-21 06:30:02.492",
             "ManagedState": 3000,
             "Model": "PowerEdge MX7000",
             "PowerState": 17,
             "SlotConfiguration": {},
             "Status": 4000,
             "SystemId": 2031,
             "Type": 2000
        }
   ]
}
```

```
- name: Retrieve basic inventory of all devices.
  dellemc ome device facts:
    hostname: "192.168.0 username: "username"
                "192.1<del>6</del>8.0.1"
    password: "password"
- name: Retrieve basic inventory for devices identified by IDs 33333 or 11111 using filtering.
  dellemc ome device facts:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    fact_subset: "basic_inventory"
    system_query_options:
      filter: "Id eq 33333 or Id eq 11111"
- name: Retrieve inventory details of specified devices identified by IDs 11111 and 22222.
  dellemc_ome_device_facts:
     hostname: "192.168.0.1" username: "username"
     password: "password"
     fact subset: "detailed inventory"
     system_query_options:
       device id:
         -111\overline{1}1
         - 22222
- name: Retrieve inventory details of specified devices identified by service tags MXL1234
and MXL4567.
  dellemc ome device facts:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    fact_subset: "detailed_inventory"
    system_query_options:
  device_service_tag:
         - MXL1234
         - MXL4567
- name: Retrieve details of specified inventory type of specified devices identified by ID
and service tags.
  dellemc ome device facts:
    hostname: "192.168.0.1" username: "username"
    password: "password"
```

```
fact subset: "detailed inventory"
    system_query_options:
      device id:
        -11\overline{1}11
      device_service_tag:
        - MXL1234
        - MXL4567
      inventory_type: "serverDeviceCards"
- name: Retrieve subsystem health of specified devices identified by service tags.
  dellemc_ome_device_facts:
   hostname: "192.168.0.1"
   username: "username" password: "password"
    fact_subset: "subsystem_health"
    system_query_options:
      device_service_tag:
        - MXL1234
         - MXL4567
```

Manage device configuration templates

This section describes the specifications for template operations on devices managed by OME for hardware configuration and deployment operations.

Following are the tasks for managing device configuration templates:

- 1. View templates
- 2. Template operations
- 3. Attach or detach an identity pool
- 4. Set tagged and untagged vLANs

View templates

Module: ome_template_info

Synopsis

This module retrieves the list and details of all templates or details of a specific template.

Options

Table 57. ome_template_info

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
template_id	No	NA	NA	ID of the template.
system_query_options	No	NA	filter: Filter records by the supported values.	Provides the option to filter the output for the supported values. I(filter) query format must be aligned with OData standards.

Return Values

```
msg:
type: str
```

```
description: Overall template facts status.
  returned: on error
  sample: "Failed to fetch the template facts"
ansible facts:
  type: dict
  description: Details of the templates.
 returned: success
 sample: {
    "192.168.0.1": {
        "3564 ed By":
            "CreatedBy": "system",
            "CreationTime": "1970-01-31 00:00:56.372144",
            "Description": "Tune workload for Performance Optimized Virtualization",
            "HasIdentityAttributes": false,
            "Id": 1,
            "IdentityPoolId": 0,
            "IsBuiltIn": true,
            "IsPersistencePolicyValid": false,
            "IsStatelessAvailable": false,
            "LastUpdatedBy": null,
            "LastUpdatedTime": "1970-01-31 00:00:56.372144",
            "Name": "iDRAC 14G Enable Performance Profile for Virtualization",
            "SourceDeviceId": 0,
            "Status": 0,
            "TaskId": 0,
            "TypeId": 2
            "ViewTypeId": 4
        }
    }
```

```
- name: Retrieve basic details of all templates.
   ome template info:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
- name: Retrieve details of a specific template identified by its template ID.
    ome template info
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    template_id: 1
- name: Get filtered template info based on name.
   ome_template_info:
   hostname: "192.168.0.1"
   username: "username"
password: "password"
    system_query_options:
     filter: "Name eq 'new template'"
```

Module: dellemc_ome_template_facts

Synopsis

This module retrieves the list and details of all templates or details of a specific template.

i NOTE: This module is deprecated and replaced with ome_template_info.

Table 58. dellemc_ome_template_facts

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password

Parameter	Required	Default	Choices	Comments
port	No	443	NA	Target device HTTPS port
template_id	No	Na	Na	Unique ID of the template

```
msa:
  type: str
  description: Over all template facts status.
  returned: on error sample: "Failed to fetch the template facts"
ansible_facts:
  type: dict
  description: Details of the templates.
  returned: success
  sample: {
        "192.168.0.1": {
            "CreatedBy": "system",
            "CreationTime": "1970-01-31 00:00:56.372144",
            "Description": "Tune workload for Performance Optimized Virtualization",
            "HasIdentityAttributes": false,
            "Id": 1,
            "IdentityPoolId": 0,
            "IsBuiltIn": true,
            "IsPersistencePolicyValid": false,
            "IsStatelessAvailable": false,
            "LastUpdatedBy": null,
            "LastUpdatedTime": "1970-01-31 00:00:56.372144",
            "Name": "iDRAC 14G Enable Performance Profile for Virtualization",
            "SourceDeviceId": 0,
            "Status": 0,
            "TaskId": 0,
            "TypeId": 2,
            "ViewTypeId": 4
```

Examples

```
- name: Retrieve basic details of all templates.
  dellemc_ome_template_facts:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"

- name: Retrieve details of a specific template identified by its template ID.
  dellemc_ome_template_facts:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    template_id: 1
```

Template operations

Module: ome_template

Synopsis

This module creates, modifies, deploys, deletes, exports, imports, or clones a template.

Options

Table 59. ome_template

Parameter	Required	Default	Choices Comments	
hostname	True	NA	NA	Target IP Address or hostname

Parameter	Required	Default	Choices	Comments
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target device HTTPS port
command	False	create	create, modify, deploy, delete, export, import or clone.	 C(create) creates a new template. C(modify) modifies an existing template. C(deploy) creates a template-deployment job. C(delete) deletes an existing template. C(export) exports an existing template. C(import) creates a template from a specified configuration text in SCP XML format. C(clone) creates a clone of an existing template.
template_id	False	NA	NA	 ID of the existing template. This option is applicable when I(command) is C(modify), C(deploy), C(delete) and C(export). It is mutually exclusive with I(template_name).
template_name	False	NA	NA	 Name of the existing template. This option is applicable when I(command) is C(modify), C(deploy), C(delete). It is mutually exclusive with I(template_name).
device_id	False	[]	NA	Specify the list of targeted device IDs when I(command) is C(deploy). When I (Command) is C(create), specify a single device ID. Either I(device_id), or I(device_service_tag) can be used individually or together.
device_service_tag	False	[]	NA	Specify the list of targeted device service tags when I (command) is C(deploy). When I(Command) is C(create), specify the service tag of a single device. Either I(device_id), or I(device_service_tag) can be used individually or together.
template_view_type	False	Deployment	Deployment, Compliance, Inventory, Sample, or None	 Select the type of view of the OME template. This is applicable when I(command) is C(create), C(clone), or C(import).
attributes	No	{}	NA	Payload data for the template operations. All the variables in this option are added as payload for C(create), C(modify), C(deploy), C(import), and C(clone) operations. It takes the following attributes. Name: Name of the template. This is mandatory when I(command) is C(create), C(import), C(clone), and optional when I(command) is C(modify). Description for the template. This is applicable when I(command) is C(deploy) or C(modify). Fqdds: This allows to create [Creates] a template using components from a specified reference server. One or more, of the following values must be specified in a comma-separated string: iDRAC, System, BIOS, NIC, LifeCycleController, RAID, EventFilters, and All. If none of the values are specified, the default value 'All' is selected. This is applicable when I (command) is C(create).

Parameter	Required	Default	Choices	Comments
				 Options: Allows to control device shutdown or end power state during template deployment. This is applicable when I(command) is C(deploy). Schedule: Provides options to schedule the deployment task immediately, or at a specified time. This is applicable when I (command) is C(deploy). NetworkBootIsoModel: Payload to specify the ISO deployment details. This is applicable when I(command) is C(deploy). Attributes: List of dictionaries of attributes (if any) to be modified in the deployment template. This is applicable for when I(command) is C(deploy) and C(modify). Content: The XML content of template. This is applicable when I(command) is C(import). Type: Template type ID, indicating the type of device for which configuration is supported, such as chassis and servers. This is applicable when I(command) is C(import). Typeld: Template type ID, indicating the type of device for which configuration is supported, such as chassis and servers. This is applicable when I(command) is C(import). Typeld: Template type ID, indicating the type of device for which configuration is supported, such as chassis and servers. This is applicable when I(command) is C(create). NOTE: See OpenManage Enterprise API Reference Guide for more details.

```
msa:
      description: Overall status of the template operation.
      returned: always
      type: str
      sample: "Successfully created a template with ID 123"
return id:
      description: ID of the template used for C(create), C(modify), C(import), and C(clone) or
task created in case of C(deploy).
     returned: on success
      type: int
      sample: 12
TemplateId:
      description: ID of the template for C(export).
      returned: success, when I(command) is C(export)
      sample: 13
Content:
      description: XML content of the exported template.
      returned: success, when I (command) is C (export)
      type: str
      sample: "<SystemConfiguration Model=\"PowerEdge R940\" ServiceTag=\"DG22TR2\" TimeStamp=</pre>
\"Tue Sep 24 09:20:57.872551
               2019\">\n<Component FQDD=\"AHCI.Slot.6-1\">\n<Attribute Name=\"RAIDresetConfig\">True</
Attribute>\n<Attribute
               Name=\"RAIDforeignConfig\">Clear</Attribute>\n</Component>\n<Component FQDD=
\"Disk.Direct.0-0:AHCI.Slot.6-1\">\n
               <attribute Name=\"RAIDPDState\">Ready</attribute>\n<attribute Name=\"RAIDHotSpareStatus
\">No</Attribute>\n
              </ \texttt{Component} \\ \texttt{Name=1:AHCI.Slot.6-1}'' \\ \texttt{Name=1:AHCI.Slot.6-1}' \\ \texttt{Na
\"RAIDPDState\">Ready
               </Attribute>\n<Attribute Name=\"RAIDHotSpareStatus\">No</Attribute>\n</Component>\n</
SystemConfiguration>\n"
error info:
      description: Details of the HTTP Error.
      returned: on HTTP error
      type: dict
      sample: {
```

```
- name: Create a template from a reference device.
  ome_template:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device id: 25123
    attributes:
      Name: "New Template"
      Description: "New Template description"
- name: Modify template name, description, and attribute value.
  ome_template:
  hostname: "192.168.0.1"
    username: "username"
    password: "password"
    command: "modify"
    template_id: 12
    attributes:
      Name: "New Custom Template"
      Description: "Custom Template Description"
      # Attributes to be modified in the template.
      # For information on any attribute ID, use API /TemplateService/Templates(Id)/Views(Id)/
AttributeViewDetails
      # This section is optional
      Attributes:
         - Id: 1234
          Value: "Test Attribute"
          IsIgnored: false
- name: Deploy template on multiple devices.
  ome template:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    command: "deploy"
    template id: 12
    device id:
      -12765
      - 10173
    device service_tag:
      - 'SVTG123'
      - 'SVTG456'
- name: Deploy template on multiple devices along with the attribute values to be modified on
the target devices.
  ome template:
               "192.168.0.1"
    hostname:
    username: "username"
    password: "password" command: "deploy"
    template id: 12
    device id:
      - 12765
      - 10173
```

```
device_service_tag:
      - 'SVTG123'
    attributes:
      # Device specific attributes to be modified during deployment.
      # For information on any attribute id, use API /TemplateService/Templates(Id)/Views(Id)/
AttributeViewDetails
      # This section is optional
      Attributes:
        # The device where attribute to be modified during deployment runtime.
        # The Device ID should be mentioned above in the 'device_id' section.
        # Service tags not allowed.
          DeviceId: 12765
          Attributes:
             - Id : 15645
               Value : "0.0.0.0"
               IsIgnored : false
        - DeviceId: 10173
          Attributes:
              - Id : 18968,
               Value : "hostname-1"
               IsIgnored : false
- name: Deploy template and Operating System (OS) on multiple devices.
  ome template:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    command: "deploy"
    template id: 12
    device i\overline{d}:
      -12\overline{7}65
    device_service_tag:
      - 'SVTG123'
    attributes:
      # Include this to install OS on the devices.
      # This section is optional
      NetworkBootIsoModel:
        BootToNetwork: false
        ShareType: "NFS"
IsoPath: "/home/iso_path/filename.iso"
        ShareDetail:
          IpAddress: "192.168.0.2"
           ShareName: "sharename"
           User: "share user"
           Password: "share_password"
      Options:
        EndHostPowerState: 1
        ShutdownType: 0
        TimeToWaitBeforeShutdown: 300
      Schedule:
        RunLater: true
        RunNow: false
- name: Deploy template on multiple devices and change the device-level attributes. After the
template is deployed, install OS using its image.
  ome_template:
  hostname: "192.168.0.1"
    username: "username" password: "password"
    command: "deploy"
    template id: 12
    device i\overline{d}:
      -12\overline{7}65
      - 10173
    device_service_tag:
      - 'SVTG123'
      - 'SVTG456'
    attributes:
      Attributes:
        - DeviceId: 12765
          Attributes:
            - Id : 15645
               Value : "0.0.0.0"
```

```
IsIgnored : false
         - DeviceId: 10173
           Attributes:
              - Id : 18968,
               Value : "hostname-1"
               IsIgnored : false
      NetworkBootIsoModel:
         BootToNetwork: false
         ShareType: "NFS"
IsoPath: "/home/iso_path/filename.iso"
         ShareDetail:
           IpAddress: "192.168.0.2"
           ShareName: "sharename"
           User: "share user"
           Password: "share_password"
      Options:
         EndHostPowerState: 1
         ShutdownType: 0
         TimeToWaitBeforeShutdown: 300
      Schedule:
         RunLater: true
         RunNow: false
- name: Delete a template.
  ome_template:
  hostname: "192.168.0.1"
    username: "username"
    password: "password" command: "delete"
    template_id: 12
- name: Export a template.
  ome_template:
    hostname: "192.168.0.1"
    username: "username"
password: "password"
command: "export"
    template id: 12
- name: Export template to local xml file
  ome template:
    hostname: "{{hostname}}"
    username: "{{username}}"
    password: "{{password}}"
    command: "export"
    template name: "my template"
  register: result
  tags:
    - export_xml_to_file
- copy:
    content: "{{ result.Content}}"
    dest: "/path/to/exported template.xml"
  tags:
    - export_xml_to file
- name: Clone a template.
  ome template:
    hostname: "192.168.0.1" username: "username" password: "password"
    command: "clone"
    template_id: 12
    attributes:
      Name: "New Cloned Template Name"
- name: Import template from XML content.
  ome template:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    command: "import"
    attributes:
      Name: "Imported Template Name"
```

```
# Template Type from TemplateService/TemplateTypes
      Type: 2
      # xml string content
      Content: "<SystemConfiguration Model=\"PowerEdge R940\" ServiceTag=\"SVCTAG1\"
      TimeStamp=\"Tue Sep 24 09:20:57.872551 2019\">\n<Component FQDD=\"AHCI.Slot.6-1\">
\n<Attribute
      Name=\"RAIDresetConfig\">True</Attribute>\n<Attribute Name=\"RAIDforeignConfig\">Clear</
Attribute>\n
      </Component>\n<Component FQDD=\"Disk.Direct.0-0:AHCI.Slot.6-1\">\n<Attribute Name=</pre>
\"RAIDPDState\">Ready
      </Attribute>\n<Attribute Name=\"RAIDHotSpareStatus\">No</Attribute>\n</Component>\n
      <Component FQDD=\"Disk.Direct.1-1:AHCI.Slot.6-1\">\n<Attribute Name=\"RAIDPDState</pre>
\">Ready</Attribute>\n
      <Attribute Name=\"RAIDHotSpareStatus\">No</Attribute>\n</Component>\n
SystemConfiguration>\n"
      Description: "Imported Template description"
- name: Import template from local XML file.
  ome template:
   hostname: "192.168.0.1"
    username: "username"
    password: "password" command: "import"
    attributes:
      name: "Imported Template Name"
      Type: 2
      Content: "{{ lookup('file', '/path/to/xmlfile') }}"
```

Module: dellemc_ome_template

Synopsis

This module creates, modifies or deploys a template.

i NOTE: This module is deprecated and replaced with ome_template.

Table 60. dellemc_ome_template

Parameter	Require d	Default	Choices	Comments		
hostname	Yes	NA	NA	Target IP Address or hostname		
username	Yes	NA	NA	Target username		
password	Yes	NA	NA	Target user password		
port	No	443	NA	Target device HTTPS port		
state	No	create	createmodifydeploy	 C(create) creates a new template. C(modify) modifies an existing template. C(deploy) deploys an existing template. 		
template_id	No	NA	NA	Unique ID of the template to be modified or deployed. This option is mandatory for C(modify) and C(deploy) operations.		
device_id	No	[]	NA	List of targeted device id(s) for C(deploy) or a single id for C(create) operation. Either I(device_id) or I(device_service_tag) is mandatory or both can be applicable.		
device_service_ta	No	[]	NA	List of targeted device service tag(s) for C(deploy) or a single service tag for C(create) operation. Either I(device_id) or I(device_service_tag) is mandatory or both can be applicable.		
template_view_ty pe	No	Deployment	Deployment,ComplianceInventorySample	The features that support template operations. This is applicable only for C(create) operation.		

Parameter	Require d	Default	Choices	Comments
			· None	
attributes	No	{}	NA	 Name: Name of the template. This is mandatory for C(create) and C(modify) operations. Description: Description of the template. This is applicable for C(create) and C(modify) operations. Fqdds: This provides functionality to copy only certain areas of system configuration from the specified reference server. One or more of the following values may be specified in a commaseparated string: iDRAC, System, BIOS, NIC, LifeCycleController, RAID, EventFilters, All. Default value is 'All'. This is applicable for C(create) operation. Options: Options to control device shutdown or end power state during template deployment. This is applicable for C(deploy) operation. Schedule: Options to schedule the deployment task immediately or at a specified time. This is applicable for C(deploy) operation. NetworkBootIsoModel: Payload to specify the ISO deployment details. This is applicable for C(deploy) operation. Attributes: list of dictionaries of attribute values (if any) to be modified in the template to be deployed. This is applicable for C(deploy) operation. NOTE: See OpenManage Enterprise API Reference Guide for more details.

```
description: Overall status of the template operation.
  returned: always
  type: str
  sample: "Successfully created a Template with id 123"
return_id:
  description: id of the template for C(create) and C(modify) or task created in case of
C(deploy)
 returned: success
  type: int
  sample: 124
template status:
  description: Details of the HTTP Error.
  returned: on HTTP error
  type: dict
  sample: {
    "error": {
   "code": "Base.1.0.GeneralError",
      "message": "A general error has occurred. See ExtendedInfo for more information.",
      "@Message.ExtendedInfo": [
           "MessageId": "GEN1234",
           "RelatedProperties": [],
"Message": "Unable to process the request because an error occurred.",
           "MessageArgs": [],
"Severity": "Critical",
           "Resolution": "Retry the operation. If the issue persists, contact your system
administrator."
      ]
    }
```

```
- name: create template.
  dellemc_ome_template:
   hostname: "192.168.0.1"
    username: "username"
    password: "password" device_id: 25123
    attributes:
      Name: "New Template"
      Description: "New Template description"
- name: modify template
  dellemc_ome_template:
  hostname: "192.168.0.1"
    username: "username"
password: "password"
    state: "modify"
    template_id: 1234
    attributes:
      Name: "New Custom Template"
      Description: "Custom Template Description"
- name: deploy template.
  dellemc_ome_template:
  hostname: "192.168.0.1"
    username: "username"
    password: "password"
    state: "deploy"
    template id: 1234
    device id:
      -12\overline{3}45
-45678
    device service tag: ['SVTG123', 'SVTG456']
    attributes:
      NetworkBootIsoModel:
        BootToNetwork: false
         ShareType: "NFS" IsoPath: "bootToIsoPath.iso"
         ShareDetail:
           IpAddress: "192.168.0.2"
           ShareName: "/nfsshare"
           User: null
           Password: null
      Attributes:
          - Id: 1234
           Value: "Test Attribute"
           IsIgnored: false
      Options:
         EndHostPowerState: 1
         ShutdownType: 0
         TimeToWaitBeforeShutdown: 300
      Schedule:
         RunLater: true
         RunNow: false
```

Attach or detach an identity pool

ome_template_identity_pool

Synopisis

This module allows to-

- · Attach an identity pool to a requested template.
- · Detach an identity pool from a requested template.

Table 61. ome_template_identity_pool

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target IP Address or hostname
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target HTTPS port
template_name	True	NA	NA	Name of the template to which an identity pool is attached to or detached from.
identity_pool_name	False	NA	NA	Name of the identity pool. To attach an identity pool to a template, provide the name of the identity pool. This option is not applicable when detaching an identity pool from a template.

```
msq:
  type: str
  description: Overall identity pool status of the attach or detach operation.
  returned: always
 sample: Successfully attached identity pool to template.
error info:
 description: Details of the HTTP Error.
  returned: on HTTP error
  type: dict
  sample: {
    "error": {
      "code": "Base.1.0.GeneralError",
      "message": "A general error has occurred. See ExtendedInfo for more information.",
      "@Message.ExtendedInfo": [
        {
          "MessageId": "GEN1234",
          "RelatedProperties": [],
          "Message": "Unable to process the request because an error occurred.",
          "MessageArgs": [],
          "Severity": "Critical",
          "Resolution": "Retry the operation. If the issue persists, contact your system
administrator."
      ]
   }
  }
```

```
- name: Attach an identity pool to a template.
ome_template_identity_pool:
  hostname: "192.168.0.1"
  username: "username"
  password: "password"
  template_name: template_name
  identity_pool_name: identity_pool_name
- name: Detach an identity pool from a template.
ome_template_identity_pool:
```

hostname: "192.168.0.1" username: "username" password: "password"

template_name: template_name

Set tagged and untagged vLANs in a template

ome_template_network_vlan

Synopsis

This module lets you select tagged and untagged vLANs to be used in the OpenManage Enterprise template.

Options

Table 62. ome_template_network_vlan

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target IP Address or hostname.
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target HTTPS port
template_name	False	NA	NA	Name of the template It is mutually exclusive with I(template_id).
template_id	False	NA	NA	ID of the template It is mutually exclusive with I(template_name).
nic_identifier	True	NA	NA	Display name of the NIC port in the template for vLAN configuration.
untagged_networks	False	NA	NA	List of untagged networks and their corresponding NIC ports. Suboptions- • port- NIC port number of the untagged vLAN • untagged_network_id- • ID of the untagged vLAN • Enter 0 to clear the untagged vLAN from the port. • This option is mutually exclusive with I(untagged_network_name). • To get the vLAN network ID use the API U(https://I(hostname)/api/ NetworkConfigurationService/ Networks) • untagged_network_name- • Name of the untagged vLAN • Enter 0 to clear the untagged vLAN from the port. • This option is mutually exclusive with I(untagged_network_id).
tagged_networks	False	NA	NA	List of tagged vLANs and their corresponding NIC ports. Suboptions-

Parameter	Required	Default	Choices	Comments
				port- NIC port number of the tagged vLANtagged_network_ids-
				 List of IDs of the tagged vLANs Enter [] to remove the tagged VLAN from a port. List of I(tagged_network_ids) is combined with list of I(tagged_network_names) when adding tagged vLANs to a port. To get the vLAN network ID use the API U(https://I(hostname)/api/NetworkConfigurationService/Networks) tagged_network_names-
				 List of names of tagged vLANs Enter [] to remove the tagged VLAN from a port. List of I(tagged_network_names) is combined with list of I(tagged_network_ids) when adding tagged vLANs to a port.

```
msq:
  type: str
  description: Overall status of the template vlan operation.
  returned: always sample: "Successfully applied the network settings to template"
error info:
  description: Details of the HTTP Error.
  returned: on HTTP error
  type: dict
  sample: {
       "error": {
                 "@Message.ExtendedInfo": [{
                 "Message": "Unable to process the request because an error occurred:",
                 "MessageArgs": "",
"MessageId": "CGEN6001",
                "RelatedProperties": [],
"Resolution": "Retry the operation. If the issue persists, contact your system
administrator."
                ',
"Severity": "Critical"
       "code": "Base.1.0.GeneralError",
       "message": "A general error has occurred. See ExtendedInfo for more information."
       } }
1 1 1
```

```
- name: Add tagged or untagged vLANs to a template using vLAN ID and name.
ome_template_network_vlan:
  hostname: "192.168.0.1"
  username: "username"
  password: "password"
  template_id: 78
  nic_identifier: NIC Slot 4
  untagged_networks:
   - port: 1
     untagged_network_id: 127656
   - port: 2
     untagged_network_name: vlan2
  tagged_networks:
```

```
- port: 1
        tagged network ids:
           - 12767
          - 12768
      - port: 4
        tagged network ids:
          <del>-</del> 12<del>7</del>67
          - 12768
        tagged network names:
          - vlan3
      - port: 2
        tagged network names:
          - vlan4
          - vlan1
- name: Clear the tagged and untagged vLANs from a template.
  ome template network vlan:
   hostname: "192.168.0.1"
   username: "username"
password: "password"
    template id: 78
    nic identifier: NIC Slot 4
    untagged_networks:
      - port: 1
       untagged_network_id: 0
      - port: 2
        untagged network name: 0
    tagged networks:
       port: 1
        tagged network ids: []
      - port: \overline{4}
        tagged_network_ids: []
        tagged_network_names: []
      - port: 2
        tagged network names: []
```

Manage the device firmware

This section describes the following firmware processes that can be carried out on the devices managed by OME, using OpenManage Ansible Modules-

- · Update device firmware.
- · Create a firmware catalog.
- Create a firmware baseline.
- · Retrieve baseline compliance details.

Update device firmware

Module: ome_firmware

Synopsis

This module updates the firmware of PowerEdge devices and all its components.

Options

Table 63. ome_firmware

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target IP Address or hostname
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target HTTPS port
device_service_tag	False	NA	NA	· List of targeted device service tags.

Parameter	Required	Default	Choices	Comments
				 Either I(device_id) or I(device_service_tag) can be used individually or together. I(device_service_tag) is mutually exclusive with I(device_group_names).
device_id	False	NA	NA	 List of targeted device ids. Either I(device_id), or I(device_service_tag) can be used individually or together. I(device_id) is mutually exclusive with I(device_group_names).
device_group_names	False	NA	NA	 Enter the name of the group to update the firmware of all the devices within the group. I(device_group_names) is mutually exclusive with I(device_id) and I(device_service_tag).
basline_name	False	NA	NA	 Enter the baseline name to update the firmware of all the devices or groups of devices against the available compliance report. The firmware update can also be done by providing the baseline name and the path to the single DUP file. To update multiple baselines at once, provide the baseline names separated by commas. I(baseline_names) is mutually exclusive with I(device_group_names), I(device_id) and I(device_service_tag).
dup_file	False	NA	NA	Executable file to apply on the targets.

```
msg:
  description: Overall firmware update status.
  returned: always
  sample: "Successfully submitted the firmware update job."
update_status:
  type: dict
  description: Firmware Update job and progress details from the OME.
  returned: success
  sample: {
     'LastRun': None,
     'CreatedBy': 'user',
'Schedule': 'startnow',
     'LastRunStatus': {
       'Id': 1111,
        'Name': 'NotRun'
     'Builtin': False,
'Editable': True,
     'NextRun': None,
     'JobStatus': {
        'Id': 1111,
       'Name': 'New'
     },
     'JobName': 'Firmware Update Task',
'Visible': True,
'State': 'Enabled',
     'JobDescription': 'dup test',
     'Params': [{
 'Value': 'true',
 'Key': 'signVerify',
 'JobId': 11111}, {
 'Value': 'false',
        'Key': 'stagingValue',
```

```
'JobId': 11112}, {
       'Value': 'false',
'Key': 'complianceUpdate',
       'JobId': 11113}, {
       'Value': 'INSTALL_FIRMWARE', 'Key': 'operationName',
       'JobId': 11114}],
     'Targets': [{
       'TargetType': {
       'Id': 1000,
       'Name': 'DEVICE'},
       'Data': 'DCIM:INSTALLED#701 NIC.Mezzanine.1A-1-1=111111111111111',
       'Id': 11115,
       'JobId': 11116}],
     'StartTime': None,
     'UpdatedBy': None, 'EndTime': None,
     'Id': 11117,
     'JobType':
       'Internal': False,
       'Id': 5,
       'Name': 'Update Task'}
  description: Details of the HTTP Error.
  returned: on HTTP error
  type: dict
  sample: {
     "error": {
       "code": "Base.1.0.GeneralError",
       "message": "A general error has occurred. See ExtendedInfo for more information.",
       "@Message.ExtendedInfo": [
        "MessageId": "GEN1234",
        "RelatedProperties": [],
"Message": "Unable to process the request because an error occurred.",
        "MessageArgs": [],
"Severity": "Critical",
        "Resolution": "Retry the operation. If the issue persists, contact your system
administrator."
]
```

```
- name: Update firmware from a DUP file using device ids.
  dellemc_ome_firmware:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    device_id:
      -11\overline{1}11
-22222
    dup file: "/path/Chassis-System-Management Firmware 6N9WN WN64 1.00.01 A00.EXE"
- name: Update firmware from a DUP file using device service tags.
  dellemc ome firmware:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    device_service_tag:
      - KLBR111
      - KLBR222
   dup file: "/path/Network Firmware NTRWO WN64 14.07.07 A00-00 01.EXE"
-name: Update firmware from a DUP file using a device group name.
  ome firmware:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device group names:
      - servers
    dup_file: "/path/BIOS_87V69_WN64_2.4.7.EXE"
```

```
-name: Update firmware using a baseline name.
ome_firmware:
hostname: "192.168.0.1"
username: "username"
password: "password"
baseline_name: baseline_devices
```

Update device firmware

Module: dellemc_ome_firmware

Synopsis

This module updates the device firmware and all its components.

i NOTE: This module is deprecated and replaced with ome_firmware.

Options

Table 64. dellemc_ome_firmware

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target HTTPS port
device_service_tag	No	NA	NA	List of targeted device service tags.
device_id	No	NA	NA	List of targeted device ids.
dup_file	Yes	NA	NA	Executable file to apply on the targets.

```
msg:
  type: str
  description: "Overall firmware update status."
 returned: always
  sample: "Successfully updated the firmware."
update status:
  type: dict
  description: "Firmware Update job and progress details from the OME."
  returned: success
  sample: {
     'LastRun': None,
    'CreatedBy': 'user',
'Schedule': 'startnow',
    'LastRunStatus': {
       'Id': 1111,
       'Name': 'NotRun'
     'Builtin': False,
     'Editable': True,
     'NextRun': None,
     'JobStatus': {
       'Id': 1111,
       'Name': 'New'
    'JobName': 'Firmware Update Task',
'Visible': True,
'State': 'Enabled',
```

```
'JobDescription': 'dup test',
     'Params': [{
       'Value': 'true',
'Key': 'signVerify',
       'JobId': 11111}, {
'Value': 'false',
'Key': 'stagingValue',
       'JobId': 11112}, {
       'Value': 'false',
'Key': 'complianceUpdate',
       'JobId': 11113}, {
       'Value': 'INSTALL_FIRMWARE',
'Key': 'operationName',
       'JobId': 11114}],
     'Targets': [{
       'TargetType':
       'Id': 1000,
       'Name': 'DEVICE'},
'Data': 'DCIM:INSTALLED#701__NIC.Mezzanine.1A-1-1=111111111111111',
       'Id': 11115,
       'JobId': 11116}],
     'StartTime': None,
     'UpdatedBy': None,
     'EndTime': None,
     'Id': 11117,
     'JobType':
       'Internal': False,
       'Id': 5,
       'Name': 'Update Task'}
}
```

```
- name: "Update firmware from DUP file using device ids."
  dellemc_ome_firmware:
   hostname: "192.168.0.1"
   username: "username"
    password: "password"
    device id:
     -11\overline{1}11
      - 22222
    dup file: "/path/Chassis-System-Management Firmware 6N9WN WN64 1.00.01 A00.EXE"
- name: "Update firmware from DUP file using device service tags."
  dellemc_ome_firmware:
   hostname: "192.168.0.1"
   username: "username"
    password: "password"
   device service tag:
      - KLBR111
   dup_file: "/path/Network_Firmware_NTRW0_WN64_14.07.07_A00-00_01.EXE"
```

Create a firmware catalog

Module: ome_firmware_catalog

Synopsis

This module triggers the job to create a catalog.

Options

Table 65. ome_firmware_catalog

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target IP Address or
				hostname

Parameter	Required	Default	Choices	Comments
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target HTTPS port
catalog_name	True	NA	NA	Name of the firmware catalog being created.
catalog_description	False	NA	NA	Description of the catalog being created.
source	False	NA	NA	The share address of the system where the firmware catalog is stored on the network.
source_path	False	NA	NA	Full path of the catalog file location excluding the file name.
file_name	False	NA	NA	Catalog file name relative to the I (source_path).
repository_type	False	HTTPS	HTTP, NFS, CIFS, HTTPS	The type of supported repositories are: HTTP, NFS, CIFS, HTTPS.
repository_username	False	NA	NA	User name of the repository where the catalog is stored. This option is mandatory when I(repository_type) is CIFS.
repository_password	False	NA	NA	Password to access the repository. This option is mandatory when I(repository_type) is CIFS.
repository_domain	False	NA	NA	Domain name of the repository.
check_certificate	False	False	NA	Specifies if certificate warnings are ignored when I(repository_type) is HTTPS. If C(True) option is set, then the certificate warnings are ignored otherwise certificate warnings are not ignored.

```
msg:
          description: Overall status of the firmware catalog creation
          returned: always
          type: str
          sample: "Successfully triggered the job to create a catalog with Task Id : 10094"
        catalog_status:
          description: Details of the catalog creation.
          returned: on success
          type: dict
          sample: {
                "AssociatedBaselines": [],
                "BaseLocation": null, "BundlesCount": 0,
                "Filename": "catalog.gz",
                "Id": 0,
                "LastUpdated": null,
                "ManifestIdentifier": null,
                 "ManifestVersion": null,
```

```
"NextUpdate": null,
                "PredecessorIdentifier": null,
                "ReleaseIdentifier": null,
                "Repository": {
                    "CheckCertificate": true,
                   "Description": "HTTPS Desc",
                   "DomainName": null,
                   "Id": null,
                   "Name": "catalog4",
                   "Password": null,
                   "RepositoryType": "HTTPS",
                   "Source": "company.com",
                   "Username": null
                "Schedule": null,
                "SourcePath": "catalog",
                "Status": null,
                "TaskId": 10094
error info:
  type: dict
  description: Details of http error.
  returned: on http error
  sample: {
        "error": {
            "@Message.ExtendedInfo": [
                    "Message": "Unable to create or update the catalog because a
                    repository with the same name already exists.",
                    "Resolution": "Enter a different name and retry the operation.",
                    "Severity": "Critical"
                }
             "code": "Base.1.0.GeneralError",
             "message": "A general error has occurred. See ExtendedInfo for more information."
         }
```

```
- name: create catalog from a repository on a HTTPS.
  ome_firmware_catalog:
  hostname: "192.168.0.1"
    username: "username"
    catalog_name: "catalog_name"
catalog_description: "catalog_description"
    repository type: "HTTPS"
    source: "downloads.dell.com"
    source_path: "catalog"
file_name: "catalog.gz"
    check_certificate: True
- name: create catalog from a repository on a HTTP.
  ome_firmware_catalog:
  hostname: "192.168.0.1"
    username: "username"
    catalog name: "catalog name"
    catalog_description: "catalog_description"
    repository_type: "HTTP"
    source: "downloads.dell.com"
    source_path: "catalog"
    file name: "catalog.gz"
- name: create catalog from a CIFS network share.
  ome_firmware_catalog:
  hostname: "192.168.0.1"
    username: "username"
    catalog_name: "catalog_name"
catalog_description: "catalog_description"
    repository_type: "CIFS"
    source: "192.167.0.1"
     source path: "cifs/R940"
    file_name: "catalog.gz"
```

```
repository_username: "repository_username"
repository_password: "repository_password"
repository_domain: "repository_domain"

- name: create catalog from a NFS network share.
ome_firmware_catalog:
   hostname: "192.168.0.1"
   username: "username"
   catalog_name: "catalog_name"
   catalog_description: "catalog_description"
   repository_type: "NFS"
   source: "192.166.0.2"
   source_path: "/nfs/R940"
   file_name: "catalog.xml"
```

Create a firmware baseline

Module: ome_firmware_baseline

Synopsis

This module allows to create a baseline.

Options

Table 66. ome_firmware_baseline

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target share address or hostname.
username	True	NA	NA	Target username.
password	True	NA	NA	Target user password.
port	False	443	NA	Target HTTPS port.
baseline_name	True	NA	NA	Name of the baseline being created.
baseline_description	False	NA	NA	Description of the baseline being created.
catalog_name	False	NA	NA	Name of the catalog associated with the baseline.
downgrade_enabled	False	True	NA	Indicates if a downgrade is allowed or not.
is_64_bit	False	True	NA	Indicates if 64 bit is supported.
device_ids	False	NA	NA	List olf device ids. I(device_ids) is mutually exclusive with I(device_service_tags) and I(device_group_names).
device_service_tags	False	NA	NA	List of service tags I(device_service_tags) is mutually exclusive with I(device_ids) and I(device_group_names).
device_group_names	False	NA	NA	List of group names. I(device_group_names) is mutually exclusive with I(device_ids) and I(device_service_tags).

```
msg:
  description: Overall status of the firmware baseline creation
  returned: always
  type: str
  sample: "Successfully created task for creating Baseline"
baseline status:
  description:
  returned: success
  type: dict
  sample: {
    "CatalogId": 123,
    "Description": "BASELINE DESCRIPTION",
    "DeviceComplianceReports": [],
    "DowngradeEnabled": true,
    "Id": 0,
    "Is64Bit": true,
    "Name": "my_baseline",
    "RepositoryId": 123,
"RepositoryName": "catalog123",
    "RepositoryType": "HTTP",
    "Targets": [
        {
            "Id": 10083,
            "Type": {
                "Id": 1000,
                 "Name": "DEVICE"
        },
            "Id": 10076,
            "Type": {
                "Id": 1000,
                "Name": "DEVICE"
        }
    "TaskId": 11235,
    "TaskStatusId": 0
error info:
  type: dict
  description: Details of http error.
  returned: on http error
  sample: {
        "error": {
             "@Message.ExtendedInfo": [
                     "Message": "Unable to retrieve baseline list either because the device
ID(s) entered are invalid",
                     "Resolution": "Make sure the entered device ID(s) are valid and retry the
operation.",
                     "Severity": "Critical"
                }
            "code": "Base.1.0.GeneralError",
            "message": "A general error has occurred. See ExtendedInfo for more information."
    }
```

```
- name: create baseline from device Ids.
ome_firmware_baseline:
hostname: "192.168.0.1"
username: "username"
password: "password"
baseline_name: "baseline_name"
baseline_description: "baseline_description"
catalog_name: "catalog_name"
device_ids:
```

```
- 1010
       - 2020
- name: create baseline from device service tags.
  ome_firmware_baseline:
  hostname: "192.168.0.1"
  username: "username"
    password: "password"
    baseline name: "baseline name"
    baseline_description: "baseline_description"
    catalog_name: "catalog_name"
    device_service_tags:
      - "SVCTAG1"
       - "SVCTAG2"
- name: create baseline from device group names.
  ome firmware baseline:
    hostname: "192.168.0.1" username: "username" password: "password"
    baseline name: "baseline name"
    baseline_description: "baseline_description"
    catalog_name: "catalog_name"
    device_group_names:
       - "Group1"
       - "Group2"
```

Retrieve firmware baseline compliance details

Module: ome_firmware_baseline_compliance_info

Synopsis

This module allows to retrieve firmware compliance for a list of devices, or against a specified baseline.

Options

Table 67. ome_firmware_baseline_compliance_info

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target share address or hostname.
username	True	NA	NA	Target username.
password	True	NA	NA	Target user password.
port	False	443	NA	Target HTTPS port.
baseline_name	False	NA	NA	 Name of the baseline for which the device based compliance report is generated. This option is mandatory for generating baseline based device compliance report. I(baseline_name) is mutually exclusive with I(device_ids), I(device_service_tags), and I(device_group_names).
device_ids	False	NA	NA	 A list of unique identifiers for which the device based compliance report is generated. Either I(device_ids), I(device_service_tags), or

Parameter	Required	Default	Choices	Comments
				I(device_group_names) is required to generate device based compliance report. I(device_ids) is mutually exclusive with I (device_service_tags),I(device_group_names), and I(baseline_name). Devices without reports are ignored.
device_service_tags	False	NA	NA	A list of service tags for which the device based compliance report is generated. Either I(device_ids), I(device_service_tags), or I(device_group_names) is required to generate device based compliance report. I(device_service_tags) is mutually exclusive with I(device_ids), I(device_group_names), and I(baseline_name). Devices without reports are ignored.
device_group_names	False	NA	NA	A list of group names for which the device based compliance report is generated. Either I(device_ids), I(device_service_tags), or I(device_group_names) is required to generate device based compliance report. I(device_group_names) is mutually exclusive with I(device_ids), I(device_service_tags), and I(baseline_name). Devices without reports are ignored.

```
"NumberOfNormal": 0,
                    "NumberOfWarning": 0
                "Description": "",
                "DeviceComplianceReports": [
                        "ComplianceStatus": "CRITICAL",
                        "ComponentComplianceReports": [
                                "ComplianceDependencies": [],
                                "ComplianceStatus": "DOWNGRADE",
                                "Criticality": "Ok",
                                "CurrentVersion": "OSC 1.1",
                                "Id": 1258,
                                "ImpactAssessment": ""
                                "Name": "OS COLLECTOR 2.1"
                                "Path": "FOLDER04118304M/2/
Diagnostics_Application_JCCH7_WN64_4.0_A00_01.EXE",
                                "PrerequisiteInfo": ""
                                "RebootRequired": false,
                                "SourceName": "DCIM:INSTALLED#802_OSCollector.Embedded.1",
                                "TargetIdentifier": "101734",
                                "UpdateAction": "DOWNGRADE",
                                "Uri": "http://www.dell.com/support/home/us/en/19/Drivers/
DriversDetails?driverId=XXXXX",
                                "Version": "4.0"
                                "ComplianceDependencies": [],
                                "ComplianceStatus": "CRITICAL",
                                "Criticality": "Recommended",
                                "CurrentVersion": "DN02",
                                "Id": 1259,
                                "ImpactAssessment": "",
                                "Name": "TOSHIBA AL14SE 1.8 TB 2.5 12Gb 10K 512n SAS HDD
Drive",
                                "Path": "FOLDER04086111M/1/SAS-
Drive Firmware VDGFM WN64 DN03 A00.EXE",
                                "PrerequisiteInfo": "",
                                "RebootRequired": true,
                                "SourceName":
"DCIM:INSTALLED#304_C_Disk.Bay.1:Enclosure.Internal.0-1:RAID.Integrated.1-1", "TargetIdentifier": "103730",
                                "UpdateAction": "UPGRADE",
                                "Uri": "http://www.dell.com/support/home/us/en/19/Drivers/
DriversDetails?driverId=XXXXX",
                               "Version": "DN03"
                        "DeviceId": 11603,
                        "DeviceModel": "PowerEdge R630",
                        "DeviceName": null,
                        "DeviceTypeId": 1000,
                        "DeviceTypeName": "CPGCGS",
"FirmwareStatus": "Non-Compliant",
                        "Id": 194,
                        "RebootRequired": true,
                        "ServiceTag": "MXL1234"
                    }
                "DowngradeEnabled": true,
                "Id": 53,
                "Is64Bit": false,
                "LastRun": "2019-09-27 05:08:16.301",
                "Name": "baseline1",
                "RepositoryId": 43,
"RepositoryName": "catalog2",
                "RepositoryType": "CIFS",
                "Targets": [
                    {
                        "Id": 11603,
```

```
"Type": {
                           "Id": 1000,
                           "Name": "DEVICE"
                   }
               "TaskId": 11710,
               "TaskStatusId": 0
           }
       1
error info:
  type: dict
  description: Details of http error.
  returned: on http error
  sample: {
       "error": {
           "@Message.ExtendedInfo": [
                   "Message": "Unable to retrieve baseline list either because the device
ID(s) entered are invalid",
                   "Resolution": "Make sure the entered device ID(s) are valid and retry the
operation.",
                   "Severity": "Critical"
               }
           "message": "A general error has occurred. See ExtendedInfo for more information."
       }
    }
```

```
- name: Retrieves baseline based compliance report for specific device IDs.
  ome_firmware_baseline_compliance_info:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device ids:
        - <del>1</del>1111
        - 22222
- name: Retrieves device based compliance report for specific device service Tags.
  ome_firmware_baseline_compliance_info:
hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device service tags:
        - MXL1234
        - MXL4567
- name: Retrieves device based compliance report for specific group names.
  ome firmware baseline compliance info:
    hostname: "192.168.0.1" username: "username"
    password: "password"
    device_group_names:
    - "group1"
         - "group2"
- name: Retrieves device compliance report for a specific baseline.
  ome_firmware_baseline_compliance_info:
    hostname: "192.168.0.1"
    username: "username" password: "password"
    baseline name: "baseline name"
```

Manage jobs

This section describes the modules using which you can manage job operations.

Following are the tasks for managing jobs:

- View job details
- · Manage power state operations

View job details

Module: dellemc_ome_job_facts

Synopsis

This module retrieves job details for a given job ID or the entire job queue.

Options

Table 68. dellemc_ome_job_facts

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target HTTPS port
job_id	No	NA	NA	Unique ID of the job
system_query_options	No	NA	 top: Number of records to return. Default value is 100. skip: Number of records to skip. Default value is 0. filter: Filter records by the values supported. 	Options for pagination of the output

```
msq:
  description: Overall status of the job facts operation.
 returned: always
  type: str
job_facts:
  description: Details of the OpenManage Enterprise jobs.
  returned: success
  type: dict
  sample: {
    "value": [
      "Builtin": false,
      "CreatedBy": "system",
"Editable": true,
      "EndTime": null,
      "Id": 12345,
      "JobDescription": "Refresh Inventory for Device",
      "JobName": "Refresh Inventory for Device",
"JobStatus": {
         "Id": 2080,
         "Name": "New"
      "JobType": {
         "Id": 8,
         "Internal": false,
        "Name": "Inventory Task"
      "LastRun": "2000-01-29 10:51:34.776",
```

```
"LastRunStatus": {
       "Id": 2060,
       "Name": "Completed"
    "NextRun": null,
"Params": [],
"Schedule": "",
     "StartTime": null,
     "State": "Enabled",
"Targets": [
         "Data": "''",
         "Id": 123123,
         "JobId": 12345,
         "TargetType": {
           "Id": 1000,
            "Name": "DEVICE"
         }
     "UpdatedBy": null,
     "Visible": true
] }
```

```
- name: Get all jobs details.
  dellemc_ome_job_facts:
  hostname: "192.168.0.1"
     username: "username"
password: "password"
- name: Get job details for id.
  dellemc_ome_job_facts:
    hostname: "192.168.0.1"
     username: "username"
password: "password"
     job id: 12345
- name: Get filtered job details.
  dellemc_ome_job_facts:
    hostname: "192.168.0 username: "username" password: "password"
                   "1\overline{9}2.168.0.1"
     system_query_options:
       top: 2
       skip: 1
        filter: "JobType/Id eq 8"
```

Manage power state operations

Module: ome_power_state

Synopsis

This module performs the supported power state management operations.

Options

Table 69. ome_power_state

Parameter	Require d	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username

Parameter	Require d	Default	Choices	Comments
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
power_state	Yes	NA	onoffcoldbootwarmbootshutdown	Desired end power state
device_id	No	NA	NA	Targeted device id. i NOTE: I(device_id) is mutually exclusive with I(device_service_tag).
device_service_ta	No	NA	NA	Targeted device service tag. i NOTE: I(device_service_tag) is mutually exclusive with I(device_id).

```
msg:
  type: str
  description: "Overall power state operation job status."
  returned: always
  sample: "Power State operation job submitted successfully."
job status:
  type: dict
  description: "Power state operation job and progress details from the OME."
  returned: success
  sample: {
    "Builtin": false,
    "CreatedBy": "user",
"Editable": true,
"EndTime": null,
    "Id": 11111,
     "JobDescription": "DeviceAction Task",
     "JobName": "DeviceAction_Task_PowerState",
     "JobStatus": {
       "Id": 1111,
"Name": "New"
    "JobType": {
    "Id": 1,
       "Internal": false,
       "Name": "DeviceAction_Task"
     "LastRun": "2019-04-01 06:39:02.69",
     "LastRunStatus": {
       "Id": 1112,
       "Name": "Running"
    "NextRun": null,
"Params": [
         "JobId": 11111,
"Key": "powerState",
"Value": "2"
       },
         "JobId": 11111,
"Key": "operationName",
         "Value": "POWER_CONTROL"
    !,
"Schedule": "",
"inc": nu
     "StartTime": null,
     "State": "Enabled",
```

```
- name: Power state operation based on device id.
  ome powerstate:
   hostname: "192.168.0.1"
    username: "username"
    password: "password" device_id: 11111
    power state: "off"
- name: Power state operation based on device service tag.
  ome_powerstate:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device service tag: "KLBR111"
    power_state: "on"
- name: Power state operation based on list of device ids.
  ome powerstate:
   hostname: "192.168.0.1" username: "username"
    password: "password"
device_id: "{{ item.device_id }}"
    power state: "{{ item.state }}"
  with_items:
    - { "device_id": 11111, "state": "on" }
- { "device_id": 22222, "state": "off" }
- name: Power state operation based on list of device service tags.
  ome powerstate:
   hostname: "192.168.0.1"
    username: "username"
    password: "password"
    device_service_tag: "{{ item.service_tag }}"
    power_state: "{{ item.state }}"
  with items:
    - { "service_tag": "KLBR111", "state": "on" }
- { "service_tag": "KLBR222", "state": "off" }
```

Manage users

The following tasks are responsible for managing user accounts:

- · View user account details
- · Configure user accounts

View user account details

Module: ome_user_info

Synopsis

This module retrieves the list and basic details of all user accounts or details of a specific user account.

Options

Table 70. ome_user_info

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
account_id	No	NA	NA	Unique ID of the account
system_query_options	No	NA	filter: Filter records for the supported values	Provides the option to filter the output for the supported values. I(filter) query format must be aligned with OData standards.

Return Values

```
type: str
  description: Over all status of fetching user facts.
  returned: on error
  sample: "Failed to fetch the user facts"
user info:
  type: dict
  description: Details of the users.
  returned: success
  sample: {
    "192.168.0.1": {
        "-3". "1814"
              "Id": "1814",
"UserTypeId": 1,
              "DirectoryServiceId": 0,
              "Description": "user name description",
              "Name": "user name",
              "Password": null,
              "UserName": "user_name",
              "RoleId": "10",
"Locked": false,
              "IsBuiltin": true,
              "Enabled": true
```

```
- name: Retrieve basic details of all accounts.
  ome_user_info:
    hostname: "192.168.0.1"
    username "username"
    password: "password"

- name: Retrieve details of a specific account identified by its account ID.
    ome_user_info:
    hostname: "192.168.0.1"
    username: "username"
    password: "password"
    account_id: 1

- name: Get filtered user info based on user name
```

```
ome_user_info:
hostname: "192.168.0.1"
username: "username"
password: "password"
system query options:
  filter: "Username eq 'test'"
```

Module: dellemc_ome_user_facts

Synopsis

This module retrieves the list and basic details of all user accounts or details of a specific user account.

i NOTE: This module is deprecated and replaced with ome_user_info.

Options

Table 71. dellemc_ome_user_facts

Parameter	Required	Default	Choices	Comments
hostname	Yes	NA	NA	Target IP Address or hostname
username	Yes	NA	NA	Target username
password	Yes	NA	NA	Target user password
port	No	443	NA	Target device HTTPS port
account_id	No	NA	NA	Unique ID of the account

Return Values

```
msq:
  type: str
  description: Over all status of fetching user facts.
  returned: on error
 sample: "Failed to fetch the user facts"
ansible_facts:
  type: dict
  description: Details of the users.
  returned: success
  sample: {
        "192.168.0.1": {
            "Id": "1814",
            "UserTypeId": 1,
            "DirectoryServiceId": 0,
            "Description": "user name description",
            "Name": "user name",
            "Password": null,
            "UserName": "user name",
            "RoleId": "10",
            "Locked": false,
            "IsBuiltin": true,
            "Enabled": true
        }
    }
```

```
- name: Retrieve basic details of all accounts.
dellemc_ome_user_facts:
   hostname: "192.168.0.1"
   username: "username"
   password: "password"

- name: Retrieve details of a specific account identified by its account ID.
   dellemc_ome_user_facts:
   hostname: "192.168.0.1"
   username: "username"
```

Configure user accounts

Module: ome_user

Synopsis

This module:

· creates a new user account.

· modifies or deletes an existing user account.

Options

Table 72. ome_user

Parameter	Required	Default	Choices	Comments	
hostname	Yes	NA	NA	Target IP Address or hostname	
username	Yes	NA	NA	Target username	
password	Yes	NA	NA	Target user password	
port	No	443	NA	Target device HTTPS port	
state	No	present	presentabsent	 C(present) creates a user in case the I(UserName) provided inside I(attributes) does not exist . C(present) modifies a user in case the I(UserName) provided inside I(attributes) exists . C(absent) deletes an existing user. 	
user_id	No	NA	NA	 ID of the user to be deleted. Either I (user_id) or I (name) is mandatory for C (absent) operation. 	
name	No	NA	NA	 Name of the user to be deleted Either I (user_id) or I (name) is mandatory for C (absent) operation. 	
attributes	No	{}	NA	Payload data for the user operations. It can take the following attributes for C(present): UserTypeld DirectoryServiceld Description Name Password UserName Roleld Locked Enabled NOTE: OME will throw an error message if required parameter is not provided for the operation. NOTE: See OpenManage Enterprise API Reference Guide for more details.	

```
msg:
   description: Overall status of the user operation.
   returned: always
```

```
type: str
  sample: "Successfully created a User"
user status:
  description: Details of the user operation when I(state) is C(present).
  returned: When I(state) is C(present).
  type: dict
  sample:
    {
        "Description": "Test user creation",
        "DirectoryServiceId": 0,
        "Enabled": true,
        "Id": "61546",
        "IsBuiltin": false,
        "Locked": false,
        "Name": "test",
        "ObjectGuid": null,
        "Oem": null,
        "Password": null,
        "PlainTextPassword": null,
        "RoleId": "10",
        "UserName": "test",
        "UserTypeId": 1
```

```
- name: Create user with required parameters.
  ome user:
   hostname: "192.168.0.1"
    username: "username"
    password: "password"
    attributes:
      UserName: "user1"
      Password: "UserPassword"
      RoleId: "10",
      Enabled: True
- name: Create user with all parameters
  ome user:
   hostname: "192.168.0.1"
   username: "username" password: "password"
    attributes:
      UserName: "user2"
      Description: "user2 description"
      Password: "UserPassword"
      RoleId: "10"
      Enabled: True
      DirectoryServiceId: 0
      UserTypeId: 1
      Locked: False
      Name: "user2"
- name: Modify existing user
  ome user:
   hostname: "192.168.0.1"
    username: "username"
    password: "password"
    state: "present"
    attributes:
      UserName: "user3"
      RoleId: "10"
      Enabled: True
      Description: "Modify user Description"
- name: Delete existing user using id.
  ome user:
    hostname: "192.168.0.1"
    username: "username"
   password: "password"
    state: "absent"
    user id: "1234"
```

```
- name: Delete existing user using name.
ome_user:
hostname: "192.168.0.1"
username: "username"
password: "password"
state: "absent"
name: "name"
```

Manage identity pool

Identity pools are used in template-based deployment of servers. They facilitate the virtualization of network identities required for accessing systems using Ethernet, iSCSI, FCoE, or Fibre Channel (FC). This section describes how to manage the settings of an identity pool.

Manage Identity pool settings

Module: ome_identity_pool

Synopsis

This module allows to create, modify or delete a single identity pool.

Options

Table 73. ome_identity_pool

Parameter	Required	Default	Choices	Comments
hostname	True	NA	NA	Target IP Address or hostname
username	True	NA	NA	Target username
password	True	NA	NA	Target user password
port	False	443	NA	Target HTTPS port
state	False	Present	Present	 C(present) modifies an existing identity pool. If the provided I (pool_name) does not exist, it creates a new identity pool. C(absent) deletes an existing identity pool.
pool_name	True	NA	NA	This option is mandatory if I(command) is C(present) when creating, modifying and deleting an identity pool.
new_pool_name	False	NA	NA	 After creating an identity pool, I(pool_name) can be changed to I(new_pool_name). This option is ignored when creating an identity pool.
pool_description	False	NA	NA	Description of the identity pool.
ethernet_settings	False	NA	NA	Applicable for creating and modifying an identity

Parameter	Required	Default	Choices	Comments
				pool using Ethernet settings.
				Sub-options-
				 starting_mac_addres s-Starting MAC address. identity_count- Number of MAC addresses.
fcoe_settings	False	NA	NA	Applicable for creating and modifying an identity pool using FCoE settings.
				Sub-options-
				 starting_mac_addres s-Starting MAC address. identity_count- Number of MAC addresses.

```
msq:
  type: str
  description: "Overall status of the identity pool operation"
  returned: always
  sample: "Successfully created an identity pool."
pool status:
  type: dict
  description: Details of the user operation when I(state) is C(present).
 returned: success
  sample: {
            "Id":29,
            "IsSuccessful":True,
            "Issues":[]
error info:
  description: Details of the HTTP Error.
  returned: on HTTP error
  type: dict
  sample: {
  "error": {
         "@Message.ExtendedInfo": [{
         "Message": "Unable to process the request because an error occurred:
         Ethernet-MAC Range overlap found (in this Identity Pool or in a different one) .",
         "MessageArgs": [Ethernet-MAC Range overlap found (in this Identity Pool or in a
different one)"],
         "MessageId": "CGEN6001",
         "RelatedProperties": [],
         "Resolution": "Retry the operation. If the issue persists, contact your system
administrator.",
         "Severity": "Critical"
         }],
  "code": "Base.1.0.GeneralError",
  "message": "A general error has occurred. See ExtendedInfo for more information."
  } }
```

```
- name: Create an identity pool with ethernet_settings and fcoe_settings.
ome_identity_pool:
   hostname: "192.168.0.1"
   username: "username"
```

```
password: "password"
    state: present
    pool name: "pool1"
    pool description: "create identity pool with ethernet and fcoe settings"
    ethernet_settings:
        starting_mac_address: "50:50:50:50:50:00"
        identity count: 60
    fcoe_settings:
        starting mac address: "70:70:70:70:70:00"
        identity_count: 75
- name: Create an identity pool with only ethernet_settings.
  ome_identity_pool:
  hostname: "192.168.0.1"
    username: "username"
    password: "password" pool_name: "pool2"
    pool_description: "create identity pool with ethernet"
    ethernet settings:
        starting mac address: "aa-bb-cc-dd-ee-aa"
        identity count: 80
- name: Modify an identity pool.
 ome_identity_pool:
hostname: "192.168.0.1"
username: "username"
    password: "password"
    pool name: "pool2"
    new_pool_name: "pool3"
    pool_description: "modifying identity pool with ethernet and fcoe settings"
    ethernet_settings:
        starting_mac_address: "90-90-90-90-90"
        identity_count: 61
    fcoe settings:
        starting_mac_address: "aabb.ccdd.5050"
        identity count: 77
- name: Delete an identity pool.
  ome_identity_pool:
  hostname: "192.168.0.1"
    username: "username"
    password: "password"
    state: "absent"
    pool name: "pool2"
```

Modules for Redfish APIs

How OpenManage Ansible Modules work with Redfish APIs

The Redfish Scalable Platforms Management API is a standard defined by the Distributed Management Task Force (DMTF). Redfish is a next-generation systems management interface standard which enables scalable, secure, and open server management. It is an interface that uses RESTful interface semantics to access data that is defined in model format to perform out-of-band systems management.

OpenManage Anisble modules use standard redfish URIs supported by iDRAC, to perform firmware updates or manage storage volume configurations on PowerEgde servers.

Firmware update using standard Redfish URI

Module: redfish_firmware

Synoposis

- This module allows the firmware update of only one component at a time. If the module is run for more than one component, an error message is returned.
- · Depending on the component, the firmware update is applied after an automatic or manual reboot.

Options

Table 74. redfish_firmware

Parameter	Required	Default	Choices	Comments
baseuri	True	NA	NA	IP Address of the target out-of-band controller. For example- <ipaddress>:<port></port></ipaddress>
username	True	NA	NA	Username of the target out-of-band controller .
password	True	NA	NA	Password of the target out-of-band controller .
image_uri	True	NA	NA	 Firmware image location URI or local path. For example-U(http:// web_address>/components.exe) or /home/firmware_repo/component.exe
transfer_protocol	False	HTTP	HTTP, HTTPS, FTP, NSF, CIFS, FTP, OEM, SCP, SFTP, or TFTP	 Protocol used to transfer the firmware image file. Applicable for URI-based update. NOTE: Dell PowerEdge servers

Parameter	Required	Default	Choices	Comments
				support transfer protocols only through HTTP- based shares.

```
msa:
  description: Overall status of the firmware update task.
  returned: always
  type: str
  sample: Successfully submitted the firmware update task.
  description: Returns ID and URI of the created task.
  returned: success
  type: dict
  sample: {
       "id": "JID XXXXXXXXXXXXX",
       error_info:
  type: dict
  description: Details of a http error.
  returned: on http error
  sample: {
        "error": {
            "@Message.ExtendedInfo": [
                   "Message": "Unable to complete the operation because the JSON data format
entered is invalid."
                   "Resolution": "Do the following and the retry the operation:
                       1) Enter the correct JSON data format and retry the operation.
                       2) Make sure that no syntax error is present in JSON data format.
                       3) Make sure that a duplicate key is not present in JSON data
format.",
                   "Severity": "Critical"
               },
                   "Message": "The request body submitted was malformed JSON and
                       could not be parsed by the receiving service.",
                   "Resolution": "Ensure that the request body is valid JSON and resubmit
the request.",
                   "Severity": "Critical"
               }
           "code": "Base.1.2.GeneralError",
           "message": "A general error has occurred. See ExtendedInfo for more information."
       }
    }
```

```
- name: Update the firmware from a single executable file available in a HTTP protocol
redfish_firmware:
   baseuri: "192.168.0.1"
   username: "user_name"
   password: "user_password"
   image_uri: "http://192.168.0.2/firmware_repo/component.exe"
   transfer_protocol: "HTTP"

- name: Update the firmware from a single executable file available in a local path
redfish_firmware:
   baseuri: "192.168.0.1"
   username: "user_name"
   password: "user_password"
   image_uri: "/home/firmware_repo/component.exe"
```

Manage storage volume configuration

Module: redfish_storage_volume

Synopsis

This module allows to create, modify, initialize, or delete a single storage volume.

Options

Table 75. redfish_storage_volume

Parameter	Required	Default	Choices	Comments
baseuri	True	NA	NA	IP address of the target out-of-band controller. For example- <ipaddress>:<port></port></ipaddress>
username	True	NA	NA	Username of the target out-of-band controller.
password	True	NA	NA	Password of the target out- of-band controller.
controller_id	False	NA	NA	 Fully Qualified Device Descriptor (FQDD) of the storage controller. For example- RAID.Slot.1-1. This option is mandatory when I(state) is C(present) when creating a volume.
volume_id	False	NA	NA	FQDD of existing volume. For example-Disk.Virtual.4:RAID.Slot.1-1. This option is mandatory in the following scenarios-: I(state) is C(present), when updating a volume. I(state) is C(absent), when deleting a volume. I(command) is C(initialize), when initializing a volume.
state	False	NA	Present, or absent.	C(present) creates a storage volume for a specified I (controller_id), or modifies the storage volume for a specified I (volume_id). NOTE: Modification of an existing volume depends on drive

Parameter	Required	Default	Choices	Comments
				and controller capabilities. C(absent) deletes the volume for a specified I(volume_id).
command	False	NA	Initialize	C(initialize) initializes an existing storage volume for a specified I (volume_id).
volume_type	False	NA	NonRedundant, Mirrored,StripedWithParity, SpannedMirrors, or SpannedStripesWithParity.	One of the following volume types must be selected to create a volume- C(Mirrored) The volume is a mirrored device. C(NonRedundant) The volume is a nonredundant storage device. C(SpannedMirrors) The volume is a spanned set of mirrored devices. C(SpannedStripesWithParity) The volume is a spanned set of devices which uses parity to retain redundant information. C(StripedWithParity) The volume is a device which uses parity to retain redundant information.
name	False	NA	NA	Name of the volume to be created.Only applicable when I(state) is C(present).
drives	False	NA	NA	FQDD of the Physical disks. For example-Disk.Bay.0:Enclosure.Internal.0-1:RAID.Slot.1-1. Only applicable when I(state) is C(present) when creating a new volume.
block_size_bytes	False	NA	NA	Block size in bytes.Only applicable when I(state) is C(present).
capacity_bytes	False	NA	NA	Virtual disk size in bytes.Only applicable when I(state) is C(present).
optimum_io_size_bytes	False	NA	NA	Stripe size value must be in multiples of 64 * 1024.

Parameter	Required	Default	Choices	Comments
				Only applicable when I(state) is C(present).
encryption_types	False	NA	NativeDriveEncryption, ControllerAssisted, or SoftwareAssisted.	The following encryption types can be selected. C(ControllerAssisted) The volume is encrypted by the storage controller entity. C(NativeDriveEncryption) The volume utilizes the native drive encryption capabilities of the drive hardware. C(SoftwareAssisted) The volume is encrypted by the software running on the system or the operating system. Only applicable when I(state) is C(present).
encrypted	False	NA	NA	 Indicates whether volume is currently utilizing encryption or not. Only applicable when I(state) is C(present).
oem	False	NA	NA	Includes OEM extended payloads.Only applicable when I(state) is I(present).
initialize_type	False	NA	Fast, or slow.	 Initialization type of existing volume. Only applicable when I(command) is C(initialize).

```
msg:
 description: Overall status of the storage configuration operation.
 returned: always
 type: str
 sample: "Successfully submitted create volume task."
task:
 type: dict
 description: Returns ID and URI of the created task.
 returned: success
 sample: {
  "id": "JID_XXXXXXXXXXXXXXX",
   error_info:
 type: dict
 description: Details of a http error.
 returned: on http error
 sample: {
   "error": {
       "@Message.ExtendedInfo": [
```

```
- name: Create a volume with supported options.
  redfish storage volume:
    baseuri: "192.168.0.1"
    username: "username"
    password: "password"
    state: "present"
    volume type: "Mirrored"
    name: "VD0"
    controller id: "RAID.Slot.1-1"
    drives:
      - Disk.Bay.5:Enclosure.Internal.0-1:RAID.Slot.1-1
      - Disk.Bay.6:Enclosure.Internal.0-1:RAID.Slot.1-1
    block size bytes: 512
    capacity_bytes: 299439751168
    optimum_io_size_bytes: 65536
    encryption_types: NativeDriveEncryption
    encrypted: true
- name: Create a volume with minimum options.
  redfish storage volume:
   baseuri: "192.168.0.1"
   username: "username"
password: "password"
    state: "present"
    controller_id: "RAID.Slot.1-1"
    volume_type: "NonRedundant"
       - Disk.Bay.1:Enclosure.Internal.0-1:RAID.Slot.1-1
- name: Modify a volume's encryption type settings.
  redfish_storage_volume:
    baseuri: "192.168.0.1"
    username: "username"
    password: "password"
    state: "present"
    volume id: "Disk.Virtual.5:RAID.Slot.1-1"
    encryption types: "ControllerAssisted"
    encrypted: true
- name: Delete an existing volume.
  redfish_storage_volume:
    baseuri: "192.168.0.1"
    username: "username"
    password: "password"
    state: "absent"
    volume_id: "Disk.Virtual.5:RAID.Slot.1-1"
- name: Initialize an existing volume.
  redfish storage volume:
    baseuri: "192.168.0.1"
   username: "username" password: "password"
    command: "initialize"
```

volume_id: "Disk.Virtual.6:RAID.Slot.1-1"
initialize_type: "Slow"

Accessing documents from the Dell EMC support site

You can access the required documents using the following links:

- · For Dell EMC Enterprise Systems Management documents —
- · For Dell EMC OpenManage documents —
- For Dell EMC Remote Enterprise Systems Management documents —
- · For iDRAC and Dell Lifecycle Controller documents —
- For Dell EMC OpenManage Connections Enterprise Systems Management documents —
- · For Dell EMC Serviceability Tools documents —
- · 1. Go to .
 - 2. Click Browse all products.
 - 3. From **All products** page, click **Software**, and then click the required link from the following:
 - Analytics
 - · Client Systems Management
 - · Enterprise Applications
 - · Enterprise Systems Management
 - Public Sector Solutions
 - Utilities
 - · Mainframe
 - Serviceability Tools
 - · Virtualization Solutions
 - Operating Systems
 - Support
 - **4.** To view a document, click the required product and then click the required version.
- · Using search engines:
 - · Type the name and version of the document in the search box.