

Package ‘DatabaseConnector’

April 24, 2018

Type Package

Title A Package for Connecting to Various DBMSs

Version 2.1.0

Date 2018-04-19

Author Martijn J. Schuemie and Marc A. Suchard

Maintainer Martijn Schuemie <schuemie@ohdsi.org>

Description Package for connecting to various DBMSs. Also includes support for fetching data as ffd objects. Implements the DBI interface.

Imports rJava,
bit,
ff,
ffbase (>= 0.12.1),
SqlRender,
methods,
utils,
DBI,
urltools

Suggests aws.s3,
uuid,
R.utils,
testthat,
DBItest,
knitr,
rmarkdown,

License Apache License

VignetteBuilder knitr

URL <https://github.com/OHDSI/DatabaseConnector>

BugReports <https://github.com/OHDSI/DatabaseConnector/issues>

Copyright See file COPYRIGHTS

RoxygenNote 6.0.1.9000

R topics documented:

connect 2

createConnectionDetails	6
DatabaseConnector	9
DatabaseConnectorDriver	9
dbClearResult,DatabaseConnectorResult-method	9
dbColumnInfo,DatabaseConnectorResult-method	10
dbConnect,DatabaseConnectorDriver-method	11
dbDisconnect,DatabaseConnectorConnection-method	11
dbExecute,DatabaseConnectorConnection,character-method	12
dbExistsTable,DatabaseConnectorConnection,character-method	13
dbFetch,DatabaseConnectorResult-method	14
dbGetQuery,DatabaseConnectorConnection,character-method	15
dbGetRowCount,DatabaseConnectorResult-method	16
dbGetRowsAffected,DatabaseConnectorResult-method	16
dbGetStatement,DatabaseConnectorResult-method	17
dbHasCompleted,DatabaseConnectorResult-method	18
dbIsValid,DatabaseConnectorConnection-method	18
dbListFields,DatabaseConnectorConnection,character-method	19
dbListTables,DatabaseConnectorConnection-method	20
dbQuoteIdentifier,DatabaseConnectorConnection,character-method	21
dbQuoteString,DatabaseConnectorConnection,character-method	22
dbReadTable,DatabaseConnectorConnection,character-method	23
dbRemoveTable,DatabaseConnectorConnection,character-method	24
dbSendQuery,DatabaseConnectorConnection,character-method	25
dbSendStatement,DatabaseConnectorConnection,character-method	26
dbUnloadDriver,DatabaseConnectorDriver-method	27
dbWriteTable,DatabaseConnectorConnection,character,data.frame-method	28
disconnect	29
executeSql	29
getTableNames	30
insertTable	31
jdbcDrivers	32
lowLevelExecuteSql	33
lowLevelQuerySql	33
lowLevelQuerySql.ffdf	34
querySql	35
querySql.ffdf	35
show,DatabaseConnectorConnection-method	36
show,DatabaseConnectorDriver-method	38

Index 40

connect	<i>connect</i>
---------	----------------

Description

connect creates a connection to a database server .There are four ways to call this function:

- connect(dbms, user, password, server, port, schema, extraSettings, oracleDriver, pathToDriver)
- connect(connectionDetails)
- connect(dbms, connectionString, pathToDriver))
- connect(dbms, connectionString, user, password, pathToDriver)

Arguments

connectionDetails	An object of class connectionDetails as created by the createConnectionDetails function.
dbms	The type of DBMS running on the server. Valid values are <ul style="list-style-type: none"> • "oracle" for Oracle • "postgresql" for PostgreSQL • "redshift" for Amazon Redshift • "sql server" for Microsoft SQL Server • "pdw" for Microsoft Parallel Data Warehouse (PDW) • "netezza" for IBM Netezza • "bigquery" for Google BigQuery
user	The user name used to access the server.
password	The password for that user.
server	The name of the server.
port	(optional) The port on the server to connect to.
schema	(optional) The name of the schema to connect to.
extraSettings	(optional) Additional configuration settings specific to the database provider to configure things as security for SSL. These must follow the format for the JDBC connection for the RDBMS specified in dbms.
oracleDriver	Specify which Oracle drive you want to use. Choose between "thin" or "oci".
connectionString	The JDBC connection string. If specified, the server, port, extraSettings, and oracleDriver fields are ignored. If user and password are not specified, they are assumed to already be included in the connection string.
pathToDriver	Path to the JDBC driver JAR files. Currently only needed for Impala and Netezza. See jdbcDrivers for details on how to get the drivers.

Details

This function creates a connection to a database.

Value

An object that extends DBIConnection in a database-specific manner. This object is used to direct commands to the database engine.

DBMS parameter details

Depending on the DBMS, the function arguments have slightly different interpretations: Oracle:

- user. The user name used to access the server
- password. The password for that user
- server. This field contains the SID, or host and servicename, SID, or TNSName: '`<sid>`', '`<host>/<sid>`', '`<host>/<service name>`', or '`<tnsname>`'
- port. Specifies the port on the server (default = 1521)
- schema. This field contains the schema (i.e. 'user' in Oracle terms) containing the tables

- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as "(PROTOCOL=tcp)")
- `oracleDriver` The driver to be used. Choose between "thin" or "oci".

Microsoft SQL Server:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `schema`. The database containing the tables. If both database and schema are specified (e.g. 'my_database.dbo', then only the database part is used, the schema is ignored.
- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as "encrypt=true; trustServerCertificate=false;")

Microsoft PDW:

- `user`. The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server
- `port`. Not used for SQL Server
- `schema`. The database containing the tables
- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as "encrypt=true; trustServerCertificate=false;")

PostgreSQL:

- `user`. The user used to log in to the server
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server and the database holding the relevant schemas: <host>/<database>
- `port`. Specifies the port on the server (default = 5432)
- `schema`. The schema containing the tables.
- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")

Redshift:

- `user`. The user used to log in to the server
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server and the database holding the relevant schemas: <host>/<database>
- `port`. Specifies the port on the server (default = 5439)
- `schema`. The schema containing the tables.

- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as `"ssl=true&sslfactory=com.amazon.redshift.ssl.NonValidatingFactory"`)

Netezza:

- `user`. The user used to log in to the server
- `password`. The password used to log on to the server
- `server`. This field contains the host name of the server and the database holding the relevant schemas: `<host>/<database>`
- `port`. Specifies the port on the server (default = 5480)
- `schema`. The schema containing the tables.
- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as `"ssl=true"`)
- `pathToDriver` The path to the folder containing the Netezza JDBC driver JAR file (`nzjdbc.jar`).

Impala:

- `user`. The user name used to access the server
- `password`. The password for that user
- `server`. The host name of the server
- `port`. Specifies the port on the server (default = 21050)
- `schema`. The database containing the tables
- `extraSettings` The configuration settings for the connection (i.e. SSL Settings such as `"SSLKeyStorePwd=*****"`)
- `pathToDriver` The path to the folder containing the Impala JDBC driver JAR files.

To be able to use Windows authentication for SQL Server (and PDW), you have to install the JDBC driver. Download the .exe from [Microsoft](#) and run it, thereby extracting its contents to a folder. In the extracted folder you will find the file `sqljdbc_4.0/enu/auth/x64/sqljdbc_auth.dll` (64-bits) or `sqljdbc_4.0/enu/auth/x86/sqljdbc_auth.dll` (32-bits), which needs to be moved to location on the system path, for example to `c:/windows/system32`.

Examples

Not run:

```
conn <- connect(dbms = "postgresql",
               server = "localhost/postgres",
               user = "root",
               password = "xxx",
               schema = "cdm_v4")
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)
```

```
conn <- connect(dbms = "sql server", server = "RNDUSRDHIT06.jnj.com", schema = "Vocabulary")
dbGetQuery(conn, "SELECT COUNT(*) FROM concept")
disconnect(conn)
```

```
conn <- connect(dbms = "oracle",
               server = "127.0.0.1/xe",
               user = "system",
               password = "xxx",
               schema = "test",
```

```

        pathToDriver = "c:/temp")
dbGetQuery(conn, "SELECT COUNT(*) FROM test_table")
disconnect(conn)

conn <- connect(dbms = "postgresql",
               connectionString = "jdbc:postgresql://127.0.0.1:5432/cmd_database")
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)

```

```
createConnectionDetails
```

```
createConnectionDetails
```

Description

`createConnectionDetails` creates a list containing all details needed to connect to a database. There are three ways to call this function:

- `createConnectionDetails(dbms, user, password, server, port, schema, extraSettings, oracleDriver)`
- `createConnectionDetails(dbms, connectionString, pathToDriver)`
- `createConnectionDetails(dbms, connectionString, user, password, pathToDriver)`

Arguments

<code>dbms</code>	The type of DBMS running on the server. Valid values are <ul style="list-style-type: none"> • "oracle" for Oracle • "postgresql" for PostgreSQL • "redshift" for Amazon Redshift • "sql server" for Microsoft SQL Server • "pdw" for Microsoft Parallel Data Warehouse (PDW) • "netezza" for IBM Netezza • "bigquery" for Google BigQuery
<code>user</code>	The user name used to access the server.
<code>password</code>	The password for that user.
<code>server</code>	The name of the server.
<code>port</code>	(optional) The port on the server to connect to.
<code>schema</code>	(optional) The name of the schema to connect to.
<code>extraSettings</code>	(optional) Additional configuration settings specific to the database provider to configure things as security for SSL. These must follow the format for the JDBC connection for the RDBMS specified in <code>dbms</code> .
<code>oracleDriver</code>	Specify which Oracle drive you want to use. Choose between "thin" or "oci".
<code>connectionString</code>	The JDBC connection string. If specified, the <code>server</code> , <code>port</code> , <code>extraSettings</code> , and <code>oracleDriver</code> fields are ignored. If <code>user</code> and <code>password</code> are not specified, they are assumed to already be included in the connection string.
<code>pathToDriver</code>	Path to the JDBC driver JAR files. Currently only needed for Impala and Netezza. See jdbcDrivers for details on how to get the drivers.

Details

This function creates a list containing all details needed to connect to a database. The list can then be used in the [connect](#) function.

Value

A list with all the details needed to connect to a database.

DBMS parameter details

Depending on the DBMS, the function arguments have slightly different interpretations: Oracle:

- **user.** The user name used to access the server
- **password.** The password for that user
- **server.** This field contains the SID, or host and servicename, SID, or TNSName: '`<sid>`', '`<host>/<sid>`', '`<host>/<service name>`', or '`<tnsname>`'
- **port.** Specifies the port on the server (default = 1521)
- **schema.** This field contains the schema (i.e. 'user' in Oracle terms) containing the tables
- **extraSettings** The configuration settings for the connection (i.e. SSL Settings such as "`(PROTOCOL=tcps)`")
- **oracleDriver** The driver to be used. Choose between "thin" or "oci".

Microsoft SQL Server:

- **user.** The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server
- **port.** Not used for SQL Server
- **schema.** The database containing the tables. If both database and schema are specified (e.g. '`my_database.dbo`'), then only the database part is used, the schema is ignored.
- **extraSettings** The configuration settings for the connection (i.e. SSL Settings such as "`encrypt=true; trustServerCertificate=false;`")

Microsoft PDW:

- **user.** The user used to log in to the server. If the user is not specified, Windows Integrated Security will be used, which requires the SQL Server JDBC drivers to be installed (see details below).
- **password.** The password used to log on to the server
- **server.** This field contains the host name of the server
- **port.** Not used for SQL Server
- **schema.** The database containing the tables
- **extraSettings** The configuration settings for the connection (i.e. SSL Settings such as "`encrypt=true; trustServerCertificate=false;`")

PostgreSQL:

- **user.** The user used to log in to the server

- password. The password used to log on to the server
- server. This field contains the host name of the server and the database holding the relevant schemas: <host>/<database>
- port. Specifies the port on the server (default = 5432)
- schema. The schema containing the tables.
- extraSettings The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")

Redshift:

- user. The user used to log in to the server
- password. The password used to log on to the server
- server. This field contains the host name of the server and the database holding the relevant schemas: <host>/<database>
- port. Specifies the port on the server (default = 5439)
- schema. The schema containing the tables.
- extraSettings The configuration settings for the connection (i.e. SSL Settings such as "ssl=true&sslfactory=com.amazon.redshift.ssl.NonValidatingFactory")

Netezza:

- user. The user used to log in to the server
- password. The password used to log on to the server
- server. This field contains the host name of the server and the database holding the relevant schemas: <host>/<database>
- port. Specifies the port on the server (default = 5480)
- schema. The schema containing the tables.
- extraSettings The configuration settings for the connection (i.e. SSL Settings such as "ssl=true")
- pathToDriver The path to the folder containing the Netezza JDBC driver JAR file (nzjdbc.jar).

Impala:

- user. The user name used to access the server
- password. The password for that user
- server. The host name of the server
- port. Specifies the port on the server (default = 21050)
- schema. The database containing the tables
- extraSettings The configuration settings for the connection (i.e. SSL Settings such as "SSLKeyStorePwd=*****")
- pathToDriver The path to the folder containing the Impala JDBC driver JAR files.

To be able to use Windows authentication for SQL Server (and PDW), you have to install the JDBC driver. Download the .exe from [Microsoft](#) and run it, thereby extracting its contents to a folder. In the extracted folder you will find the file sqljdbc_4.0/enu/auth/x64/sqljdbc_auth.dll (64-bits) or sqljdbc_4.0/enu/auth/x86/sqljdbc_auth.dll (32-bits), which needs to be moved to location on the system path, for example to c:/windows/system32.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(dbms = "postgresql",
                                             server = "localhost/postgres",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v4")

conn <- connect(connectionDetails)
dbGetQuery(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

DatabaseConnector	<i>DatabaseConnector</i>
-------------------	--------------------------

Description

DatabaseConnector

DatabaseConnectorDriver	<i>Create a DatabaseConnectorDriver object</i>
-------------------------	--

Description

Create a DatabaseConnectorDriver object

Usage

DatabaseConnectorDriver()

dbClearResult, DatabaseConnectorResult-method	<i>Clear a result set</i>
---	---------------------------

Description

Frees all resources (local and remote) associated with a result set. In some cases (e.g., very large result sets) this can be a critical step to avoid exhausting resources (memory, file descriptors, etc.)

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbClearResult(res, ...)
```

Arguments

res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

dbClearResult() returns TRUE, invisibly, for result sets obtained from both dbSendQuery() and dbSendStatement(). An attempt to close an already closed result set issues a warning in both cases.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbColumnInfo, DatabaseConnectorResult-method

Information about result types

Description

Produces a data.frame that describes the output of a query. The data.frame should have as many rows as there are output fields in the result set, and each column in the data.frame should describe an aspect of the result set field (field name, type, etc.)

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbColumnInfo(res, ...)
```

Arguments

res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

A data.frame with one row per output field in res. Methods MUST include name, field.type (the SQL type), and data.type (the R data type) columns, and MAY contain other database specific information like scale and precision or whether the field can store NULLs.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbConnect, DatabaseConnectorDriver-method
Create a connection to a DBMS

Description

Connect to a database. This function is synonymous with the [connect](#) function. except a dummy driver needs to be specified

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
dbConnect(drv, ...)
```

Arguments

drv	The result of the <code>link{DatabaseConnectorDriver}</code> function
...	Other parameters. These are the same as expected by the connect function.

Value

Returns a `DatabaseConnectorConnection` object that can be used with most of the other functions in this package.

Examples

```
## Not run:
conn <- dbConnect(DatabaseConnectorDriver(),
  dbms = "postgresql",
  server = "localhost/ohdsi",
  user = "joe",
  password = "secret")
querySql(conn, "SELECT * FROM cdm_synpuf.person")
dbDisconnect(conn)

## End(Not run)
```

dbDisconnect, DatabaseConnectorConnection-method
Disconnect (close) a connection

Description

This closes the connection, discards all pending work, and frees resources (e.g., memory, sockets).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbDisconnect(conn)
```

Arguments

conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).

Value

dbDisconnect() returns TRUE, invisibly.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbExecute, DatabaseConnectorConnection, character-method

Execute an update statement, query number of rows affected, and then close result set

Description

Executes a statement and returns the number of rows affected. `dbExecute()` comes with a default implementation (which should work with most backends) that calls [dbSendStatement\(\)](#), then [dbGetRowsAffected\(\)](#), ensuring that the result is always free-d by [dbClearResult\(\)](#).

Methods in other packages:

- [DBI::dbExecute\("DBIConnection", "character"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbExecute(conn, statement,
  ...)
```

Arguments

conn A [DBIConnection](#) object, as returned by [dbConnect\(\)](#).

statement a character string containing SQL.

... Other parameters passed on to methods.

Value

`dbExecute()` always returns a scalar numeric that specifies the number of rows affected by the statement. An error is raised when issuing a statement over a closed or invalid connection, if the syntax of the statement is invalid, or if the statement is not a non-NA string.

See Also

For queries: [dbSendQuery\(\)](#) and [dbGetQuery\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbExistsTable, DatabaseConnectorConnection, character-method
Does a table exist?

Description

Returns if a table given by name exists in the database.

Methods in other packages:

- [DBI::dbExistsTable\("DBIConnection", "Id"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbExistsTable(conn, name,
  database = NULL, schema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying a DBMS table name.
database	Name of the database.
schema	Name of the schema.
...	Other parameters passed on to methods.

Value

dbExistsTable() returns a logical scalar, TRUE if the table or view specified by the name argument exists, FALSE otherwise. This includes temporary tables if supported by the database.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with [dbQuoteIdentifier\(\)](#) or if this results in a non-scalar.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbFetch, DatabaseConnectorResult-method

Fetch records from a previously executed query

Description

Fetch the next *n* elements (rows) from the result set and return them as a `data.frame`.

Methods in other packages:

- [DBI::dbFetch\("DBIResult"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbFetch(res, datesAsString = FALSE, ...)
```

Arguments

<code>res</code>	An object inheriting from DBIResult , created by dbSendQuery() .
<code>datesAsString</code>	Should dates be represented as strings? (instead of Date objects)
<code>...</code>	Other arguments passed on to methods.

Details

`fetch()` is provided for compatibility with older DBI clients - for all new code you are strongly encouraged to use `dbFetch()`. The default implementation for `dbFetch()` calls `fetch()` so that it is compatible with existing code. Modern backends should implement for `dbFetch()` only.

Value

`dbFetch()` always returns a [data.frame](#) with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows. An attempt to fetch from a closed result set raises an error. If the *n* argument is not an atomic whole number greater or equal to -1 or Inf, an error is raised, but a subsequent call to `dbFetch()` with proper *n* argument succeeds. Calling `dbFetch()` on a result set from a data manipulation query created by [dbSendStatement\(\)](#) can be fetched and return an empty data frame, with a warning.

See Also

Close the result set with [dbClearResult\(\)](#) as soon as you finish retrieving the records you want.

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbGetQuery, DatabaseConnectorConnection, character-method

Send query, retrieve results and then clear result set

Description

Returns the result of a query as a data frame. `dbGetQuery()` comes with a default implementation (which should work with most backends) that calls `dbSendQuery()`, then `dbFetch()`, ensuring that the result is always free-d by `dbClearResult()`.

Methods in other packages:

- `DBI::dbGetQuery("DBIConnection", "character")`

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbGetQuery(conn, statement,
  ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>statement</code>	a character string containing SQL.
<code>...</code>	Other parameters passed on to methods.

Details

This method is for SELECT queries only. Some backends may support data manipulation statements through this method for compatibility reasons. However, callers are strongly advised to use [dbExecute\(\)](#) for data manipulation statements.

Value

`dbGetQuery()` always returns a [data.frame](#) with as many rows as records were fetched and as many columns as fields in the result set, even if the result is a single value or has one or zero rows. An error is raised when issuing a query over a closed or invalid connection, if the syntax of the query is invalid, or if the query is not a non-NA string. If the `n` argument is not an atomic whole number greater or equal to -1 or Inf, an error is raised, but a subsequent call to `dbGetQuery()` with proper `n` argument succeeds.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbGetRowCount, DatabaseConnectorResult-method

The number of rows fetched so far

Description

Returns the total number of rows actually fetched with calls to [dbFetch\(\)](#) for this result set.

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbGetRowCount(res, ...)
```

Arguments

<code>res</code>	An object inheriting from DBIResult .
<code>...</code>	Other arguments passed on to methods.

Value

`dbGetRowCount()` returns a scalar number (integer or numeric), the number of rows fetched so far. After calling [dbSendQuery\(\)](#), the row count is initially zero. After a call to [dbFetch\(\)](#) without limit, the row count matches the total number of rows returned. Fetching a limited number of rows increases the number of rows by the number of rows returned, even if fetching past the end of the result set. For queries with an empty result set, zero is returned even after fetching. For data manipulation statements issued with [dbSendStatement\(\)](#), zero is returned before and after calling [dbFetch\(\)](#). Attempting to get the row count for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbGetRowsAffected, DatabaseConnectorResult-method

The number of rows affected

Description

This method returns the number of rows that were added, deleted, or updated by a data manipulation statement.

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbGetRowsAffected(res, ...)
```


Arguments

res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

dbGetRowsAffected() returns a scalar number (integer or numeric), the number of rows affected by a data manipulation statement issued with [dbSendStatement\(\)](#). The value is available directly after the call and does not change after calling [dbFetch\(\)](#). For queries issued with [dbSendQuery\(\)](#), zero is returned before and after the call to [dbFetch\(\)](#). Attempting to get the rows affected for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

 dbGetStatement, DatabaseConnectorResult-method

Get the statement associated with a result set

Description

Returns the statement that was passed to [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbGetStatement(res, ...)
```

Arguments

res An object inheriting from [DBIResult](#).
 ... Other arguments passed on to methods.

Value

dbGetStatement() returns a string, the query used in either [dbSendQuery\(\)](#) or [dbSendStatement\(\)](#). Attempting to query the statement for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbHasCompleted, DatabaseConnectorResult-method
Completion status

Description

This method returns if the operation has completed. A SELECT query is completed if all rows have been fetched. A data manipulation statement is always completed.

Usage

```
## S4 method for signature 'DatabaseConnectorResult'
dbHasCompleted(res, ...)
```

Arguments

res	An object inheriting from DBIResult .
...	Other arguments passed on to methods.

Value

dbHasCompleted() returns a logical scalar. For a query initiated by [dbSendQuery\(\)](#) with non-empty result set, dbHasCompleted() returns FALSE initially and TRUE after calling [dbFetch\(\)](#) without limit. For a query initiated by [dbSendStatement\(\)](#), dbHasCompleted() always returns TRUE. Attempting to query completion status for a result set cleared with [dbClearResult\(\)](#) gives an error.

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbIsValid, DatabaseConnectorConnection-method
Is this DBMS object still valid?

Description

This generic tests whether a database object is still valid (i.e. it hasn't been disconnected or cleared).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbIsValid(dbObj, ...)
```

Arguments

dbObj	An object inheriting from DBIObject , i.e. DBIDriver , DBIConnection , or a DBIResult
...	Other arguments to methods.

Value

dbIsValid() returns a logical scalar, TRUE if the object specified by dbObj is valid, FALSE otherwise. A [DBIConnection](#) object is initially valid, and becomes invalid after disconnecting with [dbDisconnect\(\)](#). For an invalid connection object (e.g., for some drivers if the object is saved to a file and then restored), the method also returns FALSE. A [DBIResult](#) object is valid after a call to [dbSendQuery\(\)](#), and stays valid even after all rows have been fetched; only clearing it with [dbClearResult\(\)](#) invalidates it. A [DBIResult](#) object is also valid after a call to [dbSendStatement\(\)](#), and stays valid after querying the number of rows affected; only clearing it with [dbClearResult\(\)](#) invalidates it. If the connection to the database system is dropped (e.g., due to connectivity problems, server failure, etc.), dbIsValid() should return FALSE. This is not tested automatically.

See Also

Other DBIDriver generics: [DBIDriver-class](#), [dbConnect](#), [dbDataType](#), [dbDriver](#), [dbGetInfo](#), [dbListConnections](#)

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbListFields, DatabaseConnectorConnection, character-method
List field names of a remote table

Description

List field names of a remote table

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbListFields(conn, name,
  database = NULL, schema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	a character string with the name of the remote table.
database	Name of the database.
schema	Name of the schema.
...	Other parameters passed on to methods.

Value

a character vector

See Also

[dbColumnInfo\(\)](#) to get the type of the fields.

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbListTables, DatabaseConnectorConnection-method

List remote tables

Description

Returns the unquoted names of remote tables accessible through this connection. This should include views and temporary objects, but not all database backends (in particular **RMariaDB** and **RMySQL**) support this.

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
dbListTables(conn, database = NULL,
             schema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
database	Name of the database.
schema	Name of the schema.
...	Other parameters passed on to methods.

Value

`dbListTables()` returns a character vector that enumerates all tables and views in the database. Tables added with [dbWriteTable\(\)](#) are part of the list, including temporary tables if supported by the database. As soon a table is removed from the database, it is also removed from the list of database tables.

The returned names are suitable for quoting with `dbQuoteIdentifier()`. An error is raised when calling this method for a closed or invalid connection.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbQuoteIdentifier, DatabaseConnectorConnection, character-method
Quote identifiers

Description

Call this method to generate a string that is suitable for use in a query as a column or table name, to make sure that you generate valid SQL and protect against SQL injection attacks. The inverse operation is [dbUnquoteIdentifier\(\)](#).

Methods in other packages:

- [DBI::dbQuoteIdentifier\("DBIConnection", "ANY"\)](#)
- [DBI::dbQuoteIdentifier\("DBIConnection", "Id"\)](#)
- [DBI::dbQuoteIdentifier\("DBIConnection", "SQL"\)](#)
- [DBI::dbQuoteIdentifier\("DBIConnection", "character"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbQuoteIdentifier(conn, x,
  ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	A character vector, SQL or Id object to quote as identifier.
...	Other arguments passed on to methods.

Value

dbQuoteIdentifier() returns an object that can be coerced to [character](#), of the same length as the input. For an empty character vector this function returns a length-0 object. The names of the input argument are preserved in the output. An error is raised if the input contains NA, but not for an empty string.

When passing the returned object again to dbQuoteIdentifier() as x argument, it is returned unchanged. Passing objects of class [SQL](#) should also return them unchanged. (For backends it may be most convenient to return [SQL](#) objects to achieve this behavior, but this is not required.)

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteLiteral](#), [dbQuoteString](#), [dbUnquoteIdentifier](#)

dbQuoteString, DatabaseConnectorConnection, character-method
Quote literal strings

Description

Call this method to generate a string that is suitable for use in a query as a string literal, to make sure that you generate valid SQL and protect against SQL injection attacks.

Methods in other packages:

- [DBI::dbQuoteString\("DBIConnection", "ANY"\)](#)
- [DBI::dbQuoteString\("DBIConnection", "SQL"\)](#)
- [DBI::dbQuoteString\("DBIConnection", "character"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbQuoteString(conn, x, ...)
```

Arguments

conn	A subclass of DBIConnection , representing an active connection to an DBMS.
x	A character vector to quote as string.
...	Other arguments passed on to methods.

Value

dbQuoteString() returns an object that can be coerced to [character](#), of the same length as the input. For an empty character vector this function returns a length-0 object.

When passing the returned object again to dbQuoteString() as x argument, it is returned unchanged. Passing objects of class [SQL](#) should also return them unchanged. (For backends it may be most convenient to return [SQL](#) objects to achieve this behavior, but this is not required.)

See Also

Other DBIResult generics: [DBIResult-class](#), [dbBind](#), [dbClearResult](#), [dbColumnInfo](#), [dbFetch](#), [dbGetInfo](#), [dbGetRowCount](#), [dbGetRowsAffected](#), [dbGetStatement](#), [dbHasCompleted](#), [dbIsValid](#), [dbQuoteIdentifier](#), [dbQuoteLiteral](#), [dbUnquoteIdentifier](#)

dbReadTable, DatabaseConnectorConnection, character-method
Copy data frames from database tables

Description

Reads a database table to a data frame, optionally converting a column to row names and converting the column names to valid R identifiers.

Methods in other packages:

- `DBI::dbReadTable("DBIConnection", "Id")`
- `DBI::dbReadTable("DBIConnection", "character")`

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbReadTable(conn, name,
  database = NULL, schema = NULL, oracleTempSchema = NULL, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>name</code>	A character string specifying the unquoted DBMS table name, or the result of a call to dbQuoteIdentifier() .
<code>database</code>	Name of the database.
<code>schema</code>	Name of the schema.
<code>oracleTempSchema</code>	Specifically for Oracle, a schema with write privileges where temp tables can be created.
<code>...</code>	Other parameters passed on to methods.

Value

`dbReadTable()` returns a data frame that contains the complete data from the remote table, effectively the result of calling [dbGetQuery\(\)](#) with `SELECT * FROM <name>`. An error is raised if the table does not exist. An empty table is returned as a data frame with zero rows.

The presence of [rownames](#) depends on the `row.names` argument, see [sqlColumnToRownames\(\)](#) for details:

- If `FALSE` or `NULL`, the returned data frame doesn't have row names.
- If `TRUE`, a column named "row_names" is converted to row names, an error is raised if no such column exists.
- If `NA`, a column named "row_names" is converted to row names if it exists, otherwise no translation occurs.
- If a string, this specifies the name of the column in the remote table that contains the row names, an error is raised if no such column exists.

The default is `row.names = FALSE`.

If the database supports identifiers with special characters, the columns in the returned data frame are converted to valid R identifiers if the `check.names` argument is `TRUE`, otherwise non-syntactic column names can be returned unquoted.

An error is raised when calling this method for a closed or invalid connection. An error is raised if name cannot be processed with `dbQuoteIdentifier()` or if this results in a non-scalar. Unsupported values for `row.names` and `check.names` (non-scalars, unsupported data types, NA for `check.names`) also raise an error.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbRemoveTable, DatabaseConnectorConnection, character-method
Remove a table from the database

Description

Remove a remote table (e.g., created by `dbWriteTable()`) from the database.

Methods in other packages:

- `DBI::dbRemoveTable("DBIConnection", "Id")`

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbRemoveTable(conn, name,
  database = NULL, schema = NULL, oracleTempSchema = NULL, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>name</code>	A character string specifying a DBMS table name.
<code>database</code>	Name of the database.
<code>schema</code>	Name of the schema.
<code>oracleTempSchema</code>	Specifically for Oracle, a schema with write privileges where temp tables can be created.
<code>...</code>	Other parameters passed on to methods.

Value

`dbRemoveTable()` returns `TRUE`, invisibly. If the table does not exist, an error is raised. An attempt to remove a view with this function may result in an error.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with `dbQuoteIdentifier()` or if this results in a non-scalar.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbSendQuery](#), [dbSendStatement](#), [dbWriteTable](#)

dbSendQuery, DatabaseConnectorConnection, character-method

Execute a query on a given database connection

Description

The `dbSendQuery()` method only submits and synchronously executes the SQL query to the database engine. It does *not* extract any records — for that you need to use the [dbFetch\(\)](#) method, and then you must call [dbClearResult\(\)](#) when you finish fetching the records you need. For interactive use, you should almost always prefer [dbGetQuery\(\)](#).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbSendQuery(conn, statement,
  ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>statement</code>	a character string containing SQL.
<code>...</code>	Other parameters passed on to methods.

Details

This method is for SELECT queries only. Some backends may support data manipulation queries through this method for compatibility reasons. However, callers are strongly encouraged to use [dbSendStatement\(\)](#) for data manipulation statements.

The query is submitted to the database server and the DBMS executes it, possibly generating vast amounts of data. Where these data live is driver-specific: some drivers may choose to leave the output on the server and transfer them piecemeal to R, others may transfer all the data to the client – but not necessarily to the memory that R manages. See individual drivers' `dbSendQuery()` documentation for details.

Value

`dbSendQuery()` returns an S4 object that inherits from [DBIResult](#). The result set can be used with [dbFetch\(\)](#) to extract records. Once you have finished using a result, make sure to clear it with [dbClearResult\(\)](#). An error is raised when issuing a query over a closed or invalid connection, if the syntax of the query is invalid, or if the query is not a non-NA string.

See Also

For updates: [dbSendStatement\(\)](#) and [dbExecute\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendStatement](#), [dbWriteTable](#)

dbSendStatement, DatabaseConnectorConnection, character-method

Execute a data manipulation statement on a given database connection

Description

The `dbSendStatement()` method only submits and synchronously executes the SQL data manipulation statement (e.g., UPDATE, DELETE, INSERT INTO, DROP TABLE, ...) to the database engine. To query the number of affected rows, call [dbGetRowsAffected\(\)](#) on the returned result object. You must also call [dbClearResult\(\)](#) after that. For interactive use, you should almost always prefer [dbExecute\(\)](#).

Methods in other packages:

- [DBI::dbSendStatement\("DBIConnection", "character"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character'
dbSendStatement(conn,
  statement, ...)
```

Arguments

<code>conn</code>	A DBIConnection object, as returned by dbConnect() .
<code>statement</code>	a character string containing SQL.
<code>...</code>	Other parameters passed on to methods.

Details

[dbSendStatement\(\)](#) comes with a default implementation that simply forwards to [dbSendQuery\(\)](#), to support backends that only implement the latter.

Value

`dbSendStatement()` returns an S4 object that inherits from [DBIResult](#). The result set can be used with [dbGetRowsAffected\(\)](#) to determine the number of rows affected by the query. Once you have finished using a result, make sure to clear it with [dbClearResult\(\)](#). An error is raised when issuing a statement over a closed or invalid connection, if the syntax of the statement is invalid, or if the statement is not a non-NA string.

See Also

For queries: [dbSendQuery\(\)](#) and [dbGetQuery\(\)](#).

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbWriteTable](#)

dbUnloadDriver, DatabaseConnectorDriver-method

Load and unload database drivers

Description

These methods are deprecated, please consult the documentation of the individual backends for the construction of driver instances.

`dbDriver()` is a helper method used to create a new driver object given the name of a database or the corresponding R package. It works through convention: all DBI-extending packages should provide an exported object with the same name as the package. `dbDriver()` just looks for this object in the right places: if you know what database you are connecting to, you should call the function directly.

`dbUnloadDriver()` is not implemented for modern backends.

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
dbUnloadDriver(drv, ...)
```

Arguments

<code>drv</code>	an object that inherits from <code>DBIDriver</code> as created by <code>dbDriver</code> .
<code>...</code>	any other arguments are passed to the driver <code>drvName</code> .

Details

The client part of the database communication is initialized (typically dynamically loading C code, etc.) but note that connecting to the database engine itself needs to be done through calls to `dbConnect`.

Value

In the case of `dbDriver`, a driver object whose class extends `DBIDriver`. This object may be used to create connections to the actual DBMS engine.

In the case of `dbUnloadDriver`, a logical indicating whether the operation succeeded or not.

See Also

Other `DBIDriver` generics: [DBIDriver-class](#), [dbConnect](#), [dbDataType](#), [dbGetInfo](#), [dbIsValid](#), [dbListConnections](#)

Other `DBIDriver` generics: [DBIDriver-class](#), [dbConnect](#), [dbDataType](#), [dbGetInfo](#), [dbIsValid](#), [dbListConnections](#)

dbWriteTable, DatabaseConnectorConnection, character, data.frame-method
Copy data frames to database tables

Description

Writes, overwrites or appends a data frame to a database table, optionally converting row names to a column and specifying SQL data types for fields.

Methods in other packages:

- [DBI::dbWriteTable\("DBIConnection", "Id"\)](#)

Usage

```
## S4 method for signature 'DatabaseConnectorConnection,character,data.frame'
dbWriteTable(conn,
  name, value, overwrite = FALSE, append = FALSE, temporary = FALSE,
  oracleTempSchema = NULL, ...)
```

Arguments

conn	A DBIConnection object, as returned by dbConnect() .
name	A character string specifying the unquoted DBMS table name, or the result of a call to dbQuoteIdentifier() .
value	a data.frame (or coercible to data.frame).
overwrite	Overwrite an existing table (if exists)?
append	Append to existing table?
temporary	Should the table created as a temp table?
oracleTempSchema	Specifically for Oracle, a schema with write privileges where temp tables can be created.
...	Other parameters passed on to methods.

Value

dbWriteTable() returns TRUE, invisibly. If the table exists, and both append and overwrite arguments are unset, or append = TRUE and the data frame with the new data has different column names, an error is raised; the remote table remains unchanged.

An error is raised when calling this method for a closed or invalid connection. An error is also raised if name cannot be processed with [dbQuoteIdentifier\(\)](#) or if this results in a non-scalar. Invalid values for the additional arguments row.names, overwrite, append, field.types, and temporary (non-scalars, unsupported data types, NA, incompatible values, duplicate or missing names, incompatible columns) also raise an error.

See Also

Other DBIConnection generics: [DBIConnection-class](#), [dbDataType](#), [dbDisconnect](#), [dbExecute](#), [dbExistsTable](#), [dbGetException](#), [dbGetInfo](#), [dbGetQuery](#), [dbIsValid](#), [dbListFields](#), [dbListObjects](#), [dbListResults](#), [dbListTables](#), [dbReadTable](#), [dbRemoveTable](#), [dbSendQuery](#), [dbSendStatement](#)

disconnect	<i>Disconnect from the server</i>
------------	-----------------------------------

Description

This function sends SQL to the server, and returns the results in an ffdF object.

Usage

```
disconnect(connection)
```

Arguments

connection The connection to the database server.

Examples

```
## Not run:
library(ffbase)
connectionDetails <- createConnectionDetails(dbms = "postgresql",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v4")

conn <- connect(connectionDetails)
count <- querySql.ffdf(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

executeSql	<i>Execute SQL code</i>
------------	-------------------------

Description

This function executes SQL consisting of one or more statements.

Usage

```
executeSql(connection, sql, profile = FALSE, progressBar = TRUE,
            reportOverallTime = TRUE)
```

Arguments

connection	The connection to the database server.
sql	The SQL to be executed
profile	When true, each separate statement is written to file prior to sending to the server, and the time taken to execute a statement is displayed.
progressBar	When true, a progress bar is shown based on the statements in the SQL code.
reportOverallTime	When true, the function will display the overall time taken to execute all statements.

Details

This function splits the SQL in separate statements and sends it to the server for execution. If an error occurs during SQL execution, this error is written to a file to facilitate debugging. Optionally, a progress bar is shown and the total time taken to execute the SQL is displayed. Optionally, each separate SQL statement is written to file, and the execution time per statement is shown to aid in detecting performance issues.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(dbms = "mysql",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v4")

conn <- connect(connectionDetails)
executeSql(conn, "CREATE TABLE x (k INT); CREATE TABLE y (k INT);")
disconnect(conn)

## End(Not run)
```

getTableNames	<i>List all tables in a database schema.</i>
---------------	--

Description

This function returns a list of all tables in a database schema.

Usage

```
getTableNames(connection, databaseSchema)
```

Arguments

connection The connection to the database server.

databaseSchema The name of the database schema. See details for platform-specific details.

Details

The databaseSchema argument is interpreted differently according to the different platforms: SQL Server and PDW: The databaseSchema schema should specify both the database and the schema, e.g. 'my_database.dbo'. PostgreSQL and Redshift: The databaseSchema should specify the schema. Oracle: The databaseSchema should specify the Oracle 'user'. MySql and Impala: The databaseSchema should specify the database.

Value

A character vector of table names. To ensure consistency across platforms, these table names are in upper case.

insertTable	<i>Insert a table on the server</i>
-------------	-------------------------------------

Description

This function sends the data in a data frame or ffd to a table on the server. Either a new table is created, or the data is appended to an existing table.

Usage

```
insertTable(connection, tableName, data, dropTableIfExists = TRUE,
            createTable = TRUE, tempTable = FALSE, oracleTempSchema = NULL,
            useMppBulkLoad = FALSE)
```

Arguments

connection	The connection to the database server.
tableName	The name of the table where the data should be inserted.
data	The data frame or ffd containing the data to be inserted.
dropTableIfExists	Drop the table if the table already exists before writing?
createTable	Create a new table? If false, will append to existing table.
tempTable	Should the table created as a temp table?
oracleTempSchema	Specifically for Oracle, a schema with write privileges where temp tables can be created.
useMppBulkLoad	If using Redshift or PDW, use more performant bulk loading techniques. Setting the system environment variable "USE_MPP_BULK_LOAD" to TRUE is another way to enable this mode. Please note, Redshift requires valid S3 credentials; PDW requires valid DWLoader installation. This can only be used for permanent tables, and cannot be used to append to an existing table.

Details

This function sends the data in a data frame to a table on the server. Either a new table is created, or the data is appended to an existing table. If using Redshift or PDW, bulk uploading techniques may be more performant than relying upon a batch of insert statements, depending upon data size and network throughput. Redshift: The MPP bulk loading relies upon the CloudyR S3 library to test a connection to an S3 bucket using AWS S3 credentials. Credentials are configured either directly into the System Environment using the following keys: Sys.setenv("AWS_ACCESS_KEY_ID" = "some_access_key_id", "AWS_SECRET_ACCESS_KEY" = "some_secret_access_key", "AWS_DEFAULT_REGION" = "some_aws_region", "AWS_BUCKET_NAME" = "some_bucket_name", "AWS_OBJECT_KEY" = "some_object_key", "AWS_SSE_TYPE" = "server_side_encryption_type") PDW: The MPP bulk loading relies upon the client having a Windows OS and the DWLoader exe installed, and the following permissions granted: -Grant BULK Load permissions - needed at a server level USE master; GRANT ADMINISTER BULK OPERATIONS TO user; -Grant Staging database permissions - we will use the user db. USE scratch; EXEC sp_addrolemember 'db_ddladmin', user; Set the R environment variable DWLOADER_PATH to the location of the binary.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(dbms = "mysql",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v5")

conn <- connect(connectionDetails)
data <- data.frame(x = c(1, 2, 3), y = c("a", "b", "c"))
insertTable(conn, "my_table", data)
disconnect(conn)

## bulk data insert with Redshift or PDW
connectionDetails <- createConnectionDetails(dbms = "redshift",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v5")

conn <- connect(connectionDetails)
data <- data.frame(x = c(1, 2, 3), y = c("a", "b", "c"))
insertTable(connection = connection,
            tableName = "scratch.somedata",
            data = data,
            dropTableIfExists = TRUE,
            createTable = TRUE,
            tempTable = FALSE,
            useMppBulkLoad = TRUE) # or, Sys.setenv('USE_MPP_BULK_LOAD' = TRUE)

## End(Not run)
```

jdbcDrivers

How to download JDBC drivers for the various data platforms.

Description

How to download JDBC drivers for the various data platforms.

PostgresSql

Go to [the PostgreSQL JDBC site](#) and download the current version. The file is called something like 'postgresql-42.2.2.jar'.

Oracle

Go to [the Oracle JDBC site](#). Select 'Accept License Agreement' and download the jar file. The file is called something like 'ojdbc7.jar'.

SQL Server and PDW

Go to [the Microsoft SQL Server JDBC site](#), click 'Download' and select the tar.gz file. Click 'Next' to start the download. Decompress the file and find a file called something like 'sqljdbc41.jar' in the a folder named something like 'sqljdbc_6.0/enu/jre7'.

RedShift

Go to the [Amazon RedShift JDBC driver page](#) and download the latest JDBC driver. The file is called something like 'RedshiftJDBC42-1.2.12.1017.jar'.

Netezza

Read the instructions [here](#) on how to obtain the Netezza JDBC driver.

BigQuery

Go to [Google's site](#) and download the latest JDBC driver. Unzip the file, and locate the appropriate jar files.

Impala

Go to [Cloudera's site](#), pick your OS version, and click "GET IT NOW!". Register, and you should be able to download the driver.

lowLevelExecuteSql	<i>Execute SQL code</i>
--------------------	-------------------------

Description

This function executes a single SQL statement.

Usage

```
lowLevelExecuteSql(connection, sql)
```

Arguments

connection	The connection to the database server.
sql	The SQL to be executed

lowLevelQuerySql	<i>Low level function for retrieving data to a data frame</i>
------------------	---

Description

This is the equivalent of the [querySql](#) function, except no error report is written when an error occurs.

Usage

```
lowLevelQuerySql(connection, query = "", datesAsString = FALSE)
```

Arguments

connection	The connection to the database server.
query	The SQL statement to retrieve the data
datesAsString	Should dates be imported as character vectors, our should they be converted to R's date format?

Details

Retrieves data from the database server and stores it in a data frame.

Value

A data frame containing the data retrieved from the server

`lowLevelQuerySql.ffdf` *Low level function for retrieving data to an ffdf object*

Description

This is the equivalent of the `querySql.ffdf` function, except no error report is written when an error occurs.

Usage

```
lowLevelQuerySql.ffdf(connection, query = "", datesAsString = FALSE)
```

Arguments

connection	The connection to the database server.
query	The SQL statement to retrieve the data
datesAsString	Should dates be imported as character vectors, our should they be converted to R's date format?

Details

Retrieves data from the database server and stores it in an ffdf object. This allows very large data sets to be retrieved without running out of memory.

Value

A ffdf object containing the data. If there are 0 rows, a regular data frame is returned instead (ffdf cannot have 0 rows)

querySql	<i>Retrieve data to a data.frame</i>
----------	--------------------------------------

Description

This function sends SQL to the server, and returns the results.

Usage

```
querySql(connection, sql)
```

Arguments

connection	The connection to the database server.
sql	The SQL to be send.

Details

This function sends the SQL to the server and retrieves the results. If an error occurs during SQL execution, this error is written to a file to facilitate debugging.

Value

A data frame.

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(dbms = "mysql",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v4")

conn <- connect(connectionDetails)
count <- querySql(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

querySql.ffdf	<i>Retrieves data to an ffdf object</i>
---------------	---

Description

This function sends SQL to the server, and returns the results in an ffdf object.

Usage

```
querySql.ffdf(connection, sql)
```

Arguments

connection	The connection to the database server.
sql	The SQL to be send.

Details

Retrieves data from the database server and stores it in an ffdof object. This allows very large data sets to be retrieved without running out of memory. If an error occurs during SQL execution, this error is written to a file to facilitate debugging.

Value

A ffdof object containing the data. If there are 0 rows, a regular data frame is returned instead (ffdf cannot have 0 rows)

Examples

```
## Not run:
library(ffbase)
connectionDetails <- createConnectionDetails(dbms = "mysql",
                                             server = "localhost",
                                             user = "root",
                                             password = "blah",
                                             schema = "cdm_v4")

conn <- connect(connectionDetails)
count <- querySql.ffdf(conn, "SELECT COUNT(*) FROM person")
disconnect(conn)

## End(Not run)
```

show,DatabaseConnectorConnection-method

Show an Object

Description

Display the object, by printing, plotting or whatever suits its class. This function exists to be specialized by methods. The default method calls [showDefault](#).

Formal methods for show will usually be invoked for automatic printing (see the details).

Usage

```
## S4 method for signature 'DatabaseConnectorConnection'
show(object)
```

Arguments

object	Any R object
--------	--------------

Details

Objects from an S4 class (a class defined by a call to [setClass](#)) will be displayed automatically if by a call to `show`. S4 objects that occur as attributes of S3 objects will also be displayed in this form; conversely, S3 objects encountered as slots in S4 objects will be printed using the S3 convention, as if by a call to [print](#).

Methods defined for `show` will only be inherited by simple inheritance, since otherwise the method would not receive the complete, original object, with misleading results. See the `simpleInheritanceOnly` argument to [setGeneric](#) and the discussion in [setIs](#) for the general concept.

Value

`show` returns an invisible NULL.

See Also

[showMethods](#) prints all the methods for one or more functions.

Examples

```
## following the example shown in the setMethod documentation ...
setClass("track", slots = c(x="numeric", y="numeric"))
setClass("trackCurve", contains = "track", slots = c(smooth = "numeric"))

t1 <- new("track", x=1:20, y=(1:20)^2)

tc1 <- new("trackCurve", t1)

setMethod("show", "track",
  function(object)print(rbind(x = object@x, y=object@y))
)
## The method will now be used for automatic printing of t1

t1

## Not run:      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10] [,11] [,12]
x      1   2   3   4   5   6   7   8   9  10  11  12
y      1   4   9  16  25  36  49  64  81 100 121 144
      [,13] [,14] [,15] [,16] [,17] [,18] [,19] [,20]
x      13  14  15  16  17  18  19  20
y     169 196 225 256 289 324 361 400

## End(Not run)
## and also for tc1, an object of a class that extends "track"
tc1

## Not run:      [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10] [,11] [,12]
x      1   2   3   4   5   6   7   8   9  10  11  12
y      1   4   9  16  25  36  49  64  81 100 121 144
      [,13] [,14] [,15] [,16] [,17] [,18] [,19] [,20]
x      13  14  15  16  17  18  19  20
y     169 196 225 256 289 324 361 400

## End(Not run)
```

show, DatabaseConnectorDriver-method
Show an Object

Description

Display the object, by printing, plotting or whatever suits its class. This function exists to be specialized by methods. The default method calls [showDefault](#).

Formal methods for show will usually be invoked for automatic printing (see the details).

Usage

```
## S4 method for signature 'DatabaseConnectorDriver'
show(object)
```

Arguments

object Any R object

Details

Objects from an S4 class (a class defined by a call to [setClass](#)) will be displayed automatically if by a call to show. S4 objects that occur as attributes of S3 objects will also be displayed in this form; conversely, S3 objects encountered as slots in S4 objects will be printed using the S3 convention, as if by a call to [print](#).

Methods defined for show will only be inherited by simple inheritance, since otherwise the method would not receive the complete, original object, with misleading results. See the [simpleInheritanceOnly](#) argument to [setGeneric](#) and the discussion in [setIs](#) for the general concept.

Value

show returns an invisible NULL.

See Also

[showMethods](#) prints all the methods for one or more functions.

Examples

```
## following the example shown in the setMethod documentation ...
setClass("track", slots = c(x="numeric", y="numeric"))
setClass("trackCurve", contains = "track", slots = c(smooth = "numeric"))

t1 <- new("track", x=1:20, y=(1:20)^2)

tc1 <- new("trackCurve", t1)

setMethod("show", "track",
  function(object)print(rbind(x = object@x, y=object@y))
)
## The method will now be used for automatic printing of t1
```

t1

```
## Not run:  [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10] [,11] [,12]
x    1    2    3    4    5    6    7    8    9   10   11   12
y    1    4    9   16   25   36   49   64   81  100  121  144
      [,13] [,14] [,15] [,16] [,17] [,18] [,19] [,20]
x    13   14   15   16   17   18   19   20
y   169  196  225  256  289  324  361  400
```

End(Not run)

and also for tc1, an object of a class that extends "track"
tc1

```
## Not run:  [,1] [,2] [,3] [,4] [,5] [,6] [,7] [,8] [,9] [,10] [,11] [,12]
x    1    2    3    4    5    6    7    8    9   10   11   12
y    1    4    9   16   25   36   49   64   81  100  121  144
      [,13] [,14] [,15] [,16] [,17] [,18] [,19] [,20]
x    13   14   15   16   17   18   19   20
y   169  196  225  256  289  324  361  400
```

End(Not run)

Index

character, [21, 22](#)
connect, [2, 7, 11](#)
createConnectionDetails, [3, 6](#)

data.frame, [14, 15, 28](#)
DatabaseConnector, [9](#)
DatabaseConnector-package
(DatabaseConnector), [9](#)
DatabaseConnectorDriver, [9](#)
dbBind, [10, 14, 16–19, 21, 22](#)
dbClearResult, [10, 14, 16–19, 21, 22](#)
dbClearResult(), [12, 14–19, 25, 26](#)
dbClearResult, DatabaseConnectorResult-method,
[9](#)
dbColumnInfo, [10, 14, 16–19, 21, 22](#)
dbColumnInfo(), [20](#)
dbColumnInfo, DatabaseConnectorResult-method,
[10](#)
dbConnect, [19, 27](#)
dbConnect(), [12, 13, 15, 19, 20, 23–26, 28](#)
dbConnect, DatabaseConnectorDriver-method,
[11](#)
dbDataType, [12, 13, 15, 19, 20, 24–28](#)
dbDisconnect, [12, 13, 15, 19, 20, 24–28](#)
dbDisconnect(), [19](#)
dbDisconnect, DatabaseConnectorConnection-method,
[11](#)
dbDriver, [19](#)
dbExecute, [12, 13, 15, 19, 20, 24–28](#)
dbExecute(), [15, 26](#)
dbExecute, DatabaseConnectorConnection, character-method,
[12](#)
dbExistsTable, [12, 15, 19, 20, 24–28](#)
dbExistsTable, DatabaseConnectorConnection, character-method,
[13](#)
dbFetch, [10, 16–19, 21, 22](#)
dbFetch(), [15–18, 25](#)
dbFetch, DatabaseConnectorResult-method,
[14](#)
dbGetException, [12, 13, 15, 19, 20, 24–28](#)
dbGetInfo, [10, 12–22, 24–28](#)
dbGetQuery, [12, 13, 19, 20, 24–28](#)
dbGetQuery(), [12, 23, 25, 27](#)
dbGetQuery, DatabaseConnectorConnection, character-method,
[15](#)
dbGetRowCount, [10, 14, 17–19, 21, 22](#)
dbGetRowCount, DatabaseConnectorResult-method,
[16](#)
dbGetRowsAffected, [10, 14, 16–19, 21, 22](#)
dbGetRowsAffected(), [12, 26](#)
dbGetRowsAffected, DatabaseConnectorResult-method,
[16](#)
dbGetStatement, [10, 14, 16–19, 21, 22](#)
dbGetStatement, DatabaseConnectorResult-method,
[17](#)
dbHasCompleted, [10, 14, 16, 17, 19, 21, 22](#)
dbHasCompleted, DatabaseConnectorResult-method,
[18](#)
DBI::dbFetch(DBIResult), [14](#)
DBIConnection, [12, 13, 15, 18–26, 28](#)
DBIDriver, [18](#)
DBIObject, [18](#)
DBIResult, [10, 14, 16–19, 25, 26](#)
dbIsValid, [10, 12–18, 20–22, 24–28](#)
dbIsValid, DatabaseConnectorConnection-method,
[18](#)
dbListConnections, [19, 27](#)
dbListFields, [12, 13, 15, 19, 20, 24–28](#)
dbListFields, DatabaseConnectorConnection, character-method,
[19](#)
dbListObjects, [12, 13, 15, 19, 20, 24–28](#)
dbListResults, [12, 13, 15, 19, 20, 24–28](#)
dbListTables, [12, 13, 15, 19, 20, 24–28](#)
dbListTables, DatabaseConnectorConnection-method,
[20](#)
dbQuoteIdentifier, [10, 14, 16–19, 22](#)
dbQuoteIdentifier(), [13, 23, 24, 28](#)
dbQuoteIdentifier, DatabaseConnectorConnection, character-method,
[21](#)
dbQuoteLiteral, [10, 14, 16–19, 21, 22](#)
dbQuoteString, [10, 14, 16–19, 21](#)
dbQuoteString, DatabaseConnectorConnection, character-method,
[22](#)
dbReadTable, [12, 13, 15, 19, 20, 25–28](#)
dbReadTable, DatabaseConnectorConnection, character-method,
[23](#)

dbRemoveTable, [12](#), [13](#), [15](#), [19](#), [20](#), [24](#), [26–28](#)
dbRemoveTable, DatabaseConnectorConnection, character-method,
[24](#)
dbSendQuery, [12](#), [13](#), [15](#), [19](#), [20](#), [24](#), [25](#), [27](#), [28](#)
dbSendQuery(), [12](#), [14–19](#), [26](#), [27](#)
dbSendQuery, DatabaseConnectorConnection, character-method,
[25](#)
dbSendStatement, [12](#), [13](#), [15](#), [19](#), [20](#), [24–26](#),
[28](#)
dbSendStatement(), [12](#), [14–19](#), [25](#), [26](#)
dbSendStatement, DatabaseConnectorConnection, character-method,
[26](#)
dbUnloadDriver, DatabaseConnectorDriver-method,
[27](#)
dbUnquoteIdentifier, [10](#), [14](#), [16–19](#), [21](#), [22](#)
dbUnquoteIdentifier(), [21](#)
dbWriteTable, [12](#), [13](#), [15](#), [19](#), [20](#), [24–27](#)
dbWriteTable(), [20](#), [24](#)
dbWriteTable, DatabaseConnectorConnection, character, data.frame-method,
[28](#)
disconnect, [29](#)
executeSql, [29](#)
getTableNames, [30](#)
Id, [21](#)
insertTable, [31](#)
jdbcDrivers, [3](#), [6](#), [32](#)
lowLevelExecuteSql, [33](#)
lowLevelQuerySql, [33](#)
lowLevelQuerySql.ffdf, [34](#)
print, [37](#), [38](#)
querySql, [33](#), [35](#)
querySql.ffdf, [34](#), [35](#)
rownames, [23](#)
setClass, [37](#), [38](#)
setGeneric, [37](#), [38](#)
setIs, [37](#), [38](#)
show, DatabaseConnectorConnection-method,
[36](#)
show, DatabaseConnectorDriver-method,
[38](#)
showDefault, [36](#), [38](#)
showMethods, [37](#), [38](#)
SQL, [21](#), [22](#)
sqlColumnToRownames(), [23](#)