

Package ‘SqlRender’

June 7, 2017

Type Package

Title Rendering Parameterized SQL and Translation to Dialects

Version 1.4.0

Date 2017-05-29

Maintainer Martijn Schuemie <schuemie@ohdsi.org>

Description A rendering tool for parameterized SQL that also translates into different SQL dialects. These dialects include Sql Server, Oracle, PostgreSQL, Amazon RedShift, Impala, IBM Netezza, Google BigQuery, and Microsoft PDW.

License Apache License 2.0

VignetteBuilder knitr

URL <https://github.com/OHDSI/SqlRender>

BugReports <https://github.com/OHDSI/SqlRender/issues>

Imports rJava

Suggests testthat,
knitr,
rmarkdown,
formatR

LazyData false

RoxygenNote 6.0.1

R topics documented:

camelCaseToSnakeCase	2
createRWrapperForSql	2
loadRenderTranslateSql	3
readSql	4
renderSql	4
renderSqlFile	5
snakeCaseToCamelCase	6
splitSql	7
translateSql	7
translateSqlFile	8
writeSql	9
Index	10

`camelCaseToSnakeCase` *Convert a camel case string to snake case*

Description

Convert a camel case string to snake case

Usage

```
camelCaseToSnakeCase(string)
```

Arguments

`string` The string to be converted

Value

A string

Examples

```
camelCaseToSnakeCase("cdmDatabaseSchema")
# > 'cdm_database_schema'
```

`createRWrapperForSql` *Create an R wrapper for SQL*

Description

`createRWrapperForSql` creates an R wrapper for a parameterized SQL file. The created R script file will contain a single function, that executes the SQL, and accepts the same parameters as specified in the SQL.

Usage

```
createRWrapperForSql(sqlFilename, rFilename, packageName,
  createRoxygenTemplate = TRUE)
```

Arguments

`sqlFilename` The SQL file.

`rFilename` The name of the R file to be generated. Defaults to the name of the SQL file with the extension reset to R.

`packageName` The name of the package that will contains the SQL file.

`createRoxygenTemplate` If true, a template of Roxygen comments will be added.

Details

This function reads the declarations of defaults in the parameterized SQL file, and creates an R function that exposes the parameters. It uses the `loadRenderTranslateSql` function, and assumes the SQL will be used inside a package. To use inside a package, the SQL file should be placed in the `inst/sql/sql_server` folder of the package.

Examples

```
## Not run:
# This will create a file called CohortMethod.R:
createRWrapperForSql("CohortMethod.sql", packageName = "CohortMethod")

## End(Not run)
```

```
loadRenderTranslateSql
```

Load, render, and translate a SQL file in a package

Description

`loadRenderTranslateSql` Loads a SQL file contained in a package, renders it and translates it to the specified dialect

Usage

```
loadRenderTranslateSql(sqlFilename, packageName, dbms = "sql server", ...,
  oracleTempSchema = NULL)
```

Arguments

<code>sqlFilename</code>	The source SQL file
<code>packageName</code>	The name of the package that contains the SQL file
<code>dbms</code>	The target dialect. Currently 'sql server', 'oracle', 'postgres', and 'redshift' are supported
<code>...</code>	Parameter values used for <code>renderSql</code>
<code>oracleTempSchema</code>	A schema that can be used to create temp tables in when using Oracle.

Details

This function looks for a SQL file with the specified name in the `inst/sql/<dbms>` folder of the specified package. If it doesn't find it in that folder, it will try and load the file from the `inst/sql/sql_server` folder and use the `translateSql` function to translate it to the requested dialect. It will subsequently call the `renderSql` function with any of the additional specified parameters.

Value

Returns a string containing the rendered SQL.

Examples

```
## Not run:
renderedSql <- loadRenderTranslateSql("CohortMethod.sql",
                                     packageName = "CohortMethod",
                                     dbms = connectionDetails$dbms,
                                     CDM_schema = "cdmSchema")

## End(Not run)
```

readSql	<i>Reads a SQL file</i>
---------	-------------------------

Description

readSql loads SQL from a file

Usage

```
readSql(sourceFile)
```

Arguments

sourceFile The source SQL file

Details

readSql loads SQL from a file

Value

Returns a string containing the SQL.

Examples

```
## Not run:
readSql("myParamStatement.sql")

## End(Not run)
```

renderSql	<i>renderSql</i>
-----------	------------------

Description

renderSql Renders SQL code based on parameterized SQL and parameter values.

Usage

```
renderSql(sql = "", ...)
```

Arguments

sql	The parameterized SQL
...	Parameter values

Details

This function takes parameterized SQL and a list of parameter values and renders the SQL that can be send to the server. Parameterization syntax:

@parameterName Parameters are indicated using a @ prefix, and are replaced with the actual values provided in the renderSql call.

{DEFAULT @parameterName = parameterValue} Default values for parameters can be defined using curly and the DEFAULT keyword.

{if}?{then}:{else} The if-then-else pattern is used to turn on or off blocks of SQL code.

Value

A list containing the following elements:

parameterizedSql The original parameterized SQL code

sql The rendered sql

Examples

```
renderSql("SELECT * FROM @a;", a = "myTable")
renderSql("SELECT * FROM @a {@b}?{WHERE x = 1};", a = "myTable", b = "true")
renderSql("SELECT * FROM @a {@b == ''}?{WHERE x = 1}:{ORDER BY x};", a = "myTable", b = "true")
renderSql("SELECT * FROM @a {@b != ''}?{WHERE @b = 1};", a = "myTable", b = "y")
renderSql("SELECT * FROM @a {1 IN (@c)}?{WHERE @b = 1};",
  a = "myTable",
  b = "y",
  c = c(1, 2, 3, 4))
renderSql("{DEFAULT @b = \"someField\"}SELECT * FROM @a {@b != ''}?{WHERE @b = 1};",
  a = "myTable")
renderSql("SELECT * FROM @a {@a == 'myTable' & @b != 'x'}?{WHERE @b = 1};",
  a = "myTable",
  b = "y")
```

renderSqlFile

Render a SQL file

Description

renderSqlFile Renders SQL code in a file based on parameterized SQL and parameter values, and writes it to another file.

Usage

```
renderSqlFile(sourceFile, targetFile, ...)
```

Arguments

sourceFile	The source SQL file
targetFile	The target SQL file
...	Parameter values

Details

This function takes parameterized SQL and a list of parameter values and renders the SQL that can be send to the server. Parameterization syntax:

@parameterName Parameters are indicated using a @ prefix, and are replaced with the actual values provided in the renderSql call.

{DEFAULT @parameterName = parameterValue} Default values for parameters can be defined using curly and the DEFAULT keyword.

{if}?{then}:{else} The if-then-else pattern is used to turn on or off blocks of SQL code.

Examples

```
## Not run:
renderSqlFile("myParamStatement.sql", "myRenderedStatement.sql", a = "myTable")

## End(Not run)
```

snakeCaseToCamelCase *Convert a snake case string to camel case*

Description

Convert a snake case string to camel case

Usage

```
snakeCaseToCamelCase(string)
```

Arguments

string	The string to be converted
--------	----------------------------

Value

A string

Examples

```
snakeCaseToCamelCase("cdm_database_schema")
# > 'cdmDatabaseSchema'
```

`splitSql`*splitSql*

Description

`splitSql` splits a string containing multiple SQL statements into a vector of SQL statements

Usage

```
splitSql(sql)
```

Arguments

<code>sql</code>	The SQL string to split into separate statements
------------------	--

Details

This function is needed because some DBMSs (like ORACLE) do not accept multiple SQL statements being sent as one execution.

Value

A vector of strings, one for each SQL statement

Examples

```
splitSql("SELECT * INTO a FROM b; USE x; DROP TABLE c;")
```

`translateSql`*translateSql*

Description

`translateSql` translates SQL from one dialect to another

Usage

```
translateSql(sql = "", targetDialect, oracleTempSchema = NULL,  
  sourceDialect)
```

Arguments

<code>sql</code>	The SQL to be translated
<code>targetDialect</code>	The target dialect. Currently "oracle", "postgresql", "pdw", "impala", "netezza", "bigquery", and "redshift" are supported
<code>oracleTempSchema</code>	A schema that can be used to create temp tables in when using Oracle or Impala.
<code>sourceDialect</code>	Deprecated: The source dialect. Currently, only "sql server" for Microsoft SQL Server is supported

Details

This function takes SQL in one dialect and translates it into another. It uses simple pattern replacement, so its functionality is limited.

Value

A list containing the following elements:

originalSql The original parameterized SQL code

sql The translated SQL

Examples

```
translateSql("USE my_schema;", targetDialect = "oracle")
```

translateSqlFile	<i>Translate a SQL file</i>
------------------	-----------------------------

Description

This function takes SQL and translates it to a different dialect.

Usage

```
translateSqlFile(sourceFile, targetFile, sourceDialect, targetDialect,  
  oracleTempSchema = NULL)
```

Arguments

sourceFile	The source SQL file
targetFile	The target SQL file
sourceDialect	Deprecated: The source dialect. Currently, only 'sql server' for Microsoft SQL Server is supported
targetDialect	The target dialect. Currently 'oracle', 'postgresql', and 'redshift' are supported
oracleTempSchema	A schema that can be used to create temp tables in when using Oracle.

Details

This function takes SQL and translates it to a different dialect.

Examples

```
## Not run:
translateSqlFile("myRenderedStatement.sql",
  "myTranslatedStatement.sql",
  targetDialect = "postgresql")

## End(Not run)
```

writeSql	<i>Write SQL to a SQL (text) file</i>
----------	---------------------------------------

Description

writeSql writes SQL to a file

Usage

```
writeSql(sql, targetFile)
```

Arguments

sql	A string containing the sql
targetFile	The target SQL file

Details

writeSql writes SQL to a file

Examples

```
## Not run:  
sql <- "SELECT * FROM @table_name"  
writeSql(sql, "myParamStatement.sql")  
  
## End(Not run)
```

Index

camelCaseToSnakeCase, [2](#)
createRWrapperForSql, [2](#)

loadRenderTranslateSql, [3](#)

readSql, [4](#)
renderSql, [4](#)
renderSqlFile, [5](#)

snakeCaseToCamelCase, [6](#)
splitSql, [7](#)

translateSql, [7](#)
translateSqlFile, [8](#)

writeSql, [9](#)