

# Package ‘MF’

December 21, 2018

**Type** Package

**Title** Mitigated Fraction

**Version** 4.3.5

**Date** 21 December 2018

**Author** David Siev

**Maintainer** Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

**Description** Calculate MF (mitigated fraction) with clustering and bootstrap options. See <http://goo.gl/pcXYVr> for definition of MF. No endorsement, claim, or warranty is implied for this package. It is made available for investigational or pedagogical use only

**License** MIT + file LICENSE

**LazyLoad** yes

**LazyData** yes

**Depends** R (>= 3.4.4)

**Imports** methods, dplyr (>= 0.7.1), plyr, stringr, tidyr, forcats,  
purrr

**Collate** 'aaa.r' 'classes.r' 'generic\_methods.r' 'MF-package.r'  
'HLBoot.r' 'MFBoot.r' 'MFClus.r' 'MFClusBoot.r' 'MFClusHier.R'  
'MFmp.r' 'MFnestBoot.r' 'MFr.r' 'MFSubj.r' 'MFHier-wrappers.r'

**RoxygenNote** 6.0.1

**NeedsCompilation** no

## R topics documented:

MF-package . . . . .	2
calflung . . . . .	3
HLBoot . . . . .	3
mf-class . . . . .	5
MFBoot . . . . .	6
mfboot-class . . . . .	7
mfbootcluster-class . . . . .	8
MFClus . . . . .	9
MFClusBoot . . . . .	10
MFClusBootHier . . . . .	12
mfclusboothier-class . . . . .	13
MFClusHier . . . . .	14

mfclushier-class . . . . .	15
mfcluster-class . . . . .	16
mfcomponents-class . . . . .	16
MFh . . . . .	17
MFhBoot . . . . .	18
mfhierdata-class . . . . .	20
mfhlboot-class . . . . .	20
MFmp . . . . .	21
mfmp-class . . . . .	23
MFnest . . . . .	23
MFnestBoot . . . . .	26
MFr . . . . .	27
MFSbj . . . . .	28
mlesions . . . . .	29
piglung . . . . .	30

<b>Index</b>	<b>31</b>
--------------	-----------

---

MF-package	<i>MF Package</i>
------------	-------------------

---

## Description

Includes functions related to mitigated fraction.

For internal use only at the USDA Center for Veterinary Biologics.

## Details

Package:	MF-package
Type:	Package
Version:	4.3.5
Date:	21-Dec-2018
License:	MIT
LazyLoad:	yes

## Author(s)

David Siev <David.Siev@aphis.usda.gov>

## Examples

```
#-----
# Checking MF package
#-----
example(MFr)
#-----
# End examples
```

```
#-----
invisible()
```

calflung

*calflung dataset***Description**

Post-mortem examination of the lungs of groups of calves.

**Format**

a data frame with 50 observations of the following 2 variables, no NAs

**group** Treatment group. One of con = control or vac = vaccinate

**lesion** Fraction of lungs with gross lesions.

HLBoot

*Bootstrap CI for MF, HL, and Qdif***Description**

Estimates bootstrap confidence intervals for MF, HL, and Qdif.

**Usage**

```
HLBoot(formula, data, compare = c("con", "vac"), b = 100, B = 100,
        alpha = 0.05, hpd = TRUE, bca = FALSE, return.boot = FALSE,
        trace.it = FALSE, seed = sample(1:1e+05, 1))
```

**Arguments**

formula	Formula of the form $y \sim x + \text{cluster}(w)$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $w$ is a factor indicating the clusters.
data	Data frame
compare	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared
b	Number of bootstrap samples to take with each cycle
B	Number of cycles, giving the total number of samples = $B * b$
alpha	Complement of the confidence level
hpd	Boolean whether to estimate highest density intervals for MF and HL.
bca	Boolean whether to estimate BCa intervals for MF.
return.boot	Boolean whether to save the bootstrap samples of the statistics.
trace.it	Boolean whether to display verbose tracking of the cycles.
seed	to initialize random number generator for reproducibility. Passed to <code>set.seed</code> .

## Details

Estimates bootstrap confidence intervals for the mitigated fraction (MF), Hodge-Lehmann estimator (HL), and the difference of medians and quartiles (Qdif). Equal tailed intervals are provided for all three, highest density intervals are optionally provided for MF and HL, and BCa intervals are optionally provided for MF. The Hodges-Lehmann estimator is the median difference; it assumes that the two distributions have the same shape and differ by a constant shift. Assumes data is single pool (no nesting).

## Value

a `mflboot-class` data object

## Author(s)

David Siev <david.siev@aphis.usda.gov>

## References

Hodges JL, Lehmann EL, (1963). Estimates of location based on rank tests. *Annals of Mathematical Statistics*. **34:598–611**.

Siev D, (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4:500–508**.

Efron B, Tibshirani RJ. *An Introduction to the Bootstrap*. Chapman and Hall, New York, 1993.

## See Also

`mflboot-class`

## Examples

```
HLBoot(lesion~group, calflung, seed = 12345)

# Bootstrapping
# . . . . .
# . . . . .
# . . . . .
#
# 10000 bootstrap samples
# 95% confidence intervals
# Comparing vac to con
#
#
# Mitigated Fraction
#
# observed median lower upper
# Equal Tailed      0.44 0.4496 0.152 0.7088
# Highest Density    0.44 0.4496 0.152 0.7088
#
#
# Hodges-Lehmann
#
# observed median lower upper
# Equal Tailed      -0.07335 -0.07615 -0.17220 -0.01565000
```

```
# Highest Density -0.07335 -0.07615 -0.15635 -0.00850065
#
#
# Quartile Differences (quartiles of vac - quartiles of con)
#
# observed    median    lower    upper
# Q25 -0.041500 -0.041500 -0.10340 -0.000905
# Q50 -0.112525 -0.111175 -0.28115  0.019350
# Q75 -0.168000 -0.170425 -0.38890  0.005300
#
#
# Quartiles of con
# observed    median    lower    upper
# Q25 0.054000 0.054000 0.021005 0.11275
# Q50 0.139275 0.139275 0.061400 0.31000
# Q75 0.315000 0.315000 0.173000 0.44625
#
#
# Quartiles of vac
# observed    median    lower    upper
# Q25 0.01250 0.01250 0.00125 0.026000
# Q50 0.02675 0.02675 0.01665 0.144575
# Q75 0.14700 0.14700 0.02810 0.219250
```

mf-class

*Class mf*

## Description

Parent class for package MF data objects.

## Usage

```
mf$new(nboot, alpha, seed, compare, rng)
```

## Fields

- `nboot`: numeric value specifying number of samples
- `alpha`: numeric value specifying complement of confidence interval
- `seed`: vector of integers specifying seed for pseudo-random number generator used
- `compare`: vector of character strings naming groups compared
- `rng`: character string naming type of random number generator

## Author(s)

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

## See Also

Other mf: [mfboot-class](#), [mfbootcluster-class](#), [mfhlboot-class](#)

MFBoot

*Bootstrap MF CI***Description**

Estimates bootstrap confidence intervals for the mitigated fraction.

**Usage**

```
MFBoot(formula, data, compare = c("con", "vac"), b = 100, B = 100,
       alpha = 0.05, hpd = TRUE, bca = FALSE, return.boot = FALSE, trace.it = FALSE,
       seed = sample(1:100000, 1))
```

**Arguments**

formula	Formula of the form $y \sim x$ , where $y$ is a continuous response and $x$ is a factor with two levels.
data	Data frame
compare	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared
b	Number of bootstrap samples to take with each cycle
B	Number of cycles, giving the total number of samples = $B * b$
alpha	Complement of the confidence level
hpd	Estimate highest density intervals?
bca	Estimate BCa intervals?
return.boot	Save the bootstrap sample of the MF statistic?
trace.it	Verbose tracking of the cycles?
seed	to initialize random number generator for reproducibility. Passed to <code>set.seed</code> .

**Details**

Resamples the data and produces bootstrap confidence intervals. Equal tailed intervals are estimated by the percentile method. Highest density intervals are estimated by selecting the shortest of all possible intervals. For BCa intervals, see Efron and Tibshirani section 14.3.

**Value**

a `mfboot-class` data object

**Author(s)**

David Siev <david.siev@aphis.usda.gov>

**References**

Siev D. (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4:500–508**

Efron B, Tibshirani RJ. *An Introduction to the Bootstrap*. Chapman and Hall, New York, 1993.

**See Also**[mfboot-class](#)**Examples**

```

MfBoot(lesion~group, calflung, seed = 12345)

# 10000 bootstrap samples
# 95% confidence interval
# Seed = 12345
#
# Comparing vac to con
# observed median lower upper
# Equal Tailed      0.44 0.4496 0.152 0.7088
# Highest Density    0.44 0.4496 0.152 0.7088

```

---

mfboot-class	<i>Class mfboot</i>
--------------	---------------------

---

**Description**

class for data objects produced by MfBoot, contains class mf with the two additional fields *stat* and *stuff*.

**Usage**

```
mfboot$new(nboot, alpha, seed, compare, rng, sample, stat, stuff)
```

**Fields**

- *nboot*: numeric value specifying number of samples
- *alpha*: numeric value specifying complement of confidence interval
- *seed*: vector of integers specifying seed for pseudo-random number generator used
- *compare*: vector of character strings naming groups compared
- *rng*: character string naming type of random number generator
- *sample*: what is this?
- *stat*: matrix of estimates

**Contains**[mf-class](#)**Author(s)**

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

**See Also**[MfBoot](#)

Other mf: [mf-class](#), [mfbootcluster-class](#), [mfhlboot-class](#)

---

mfbootcluster-class     *Class mfbootcluster*

---

## Description

Class mfbootcluster is created from output of function MFClusBoot

## Usage

```
mfbootcluster$new(nboot, alpha, seed, compare, rng, stat, what, excludedClusters,  
call, sample)
```

## Fields

- nboot: numeric value specifying number of samples
- alpha: numeric value specifying complement of confidence interval
- seed: vector of integers specifying seed for pseudo-random number generator used
- compare: vector of character strings naming groups compared
- rng: character string naming type of random number generator
- stat: matrix matrix with columns *observed*, *median*, *lower*, *upper* for estimates
- what: character vector naming what was resampled: *clusters*, *units*, *both*
- excludedClusters: character vector naming clusters excluded because of missing treatment(s)
- call: the call to MFClusBoot
- sample: what is this?
- All: Field "All" from MFClus call.

## Contains

[mf-class](#)

## Author(s)

Marie Vendettuoli <[marie.c.vendettuoli@aphis.usda.gov](mailto:marie.c.vendettuoli@aphis.usda.gov)>

## See Also

[MFClusBoot](#)

Other mf: [mf-class](#), [mfboot-class](#), [mfhlboot-class](#)



---

MFClus	<i>Clustered mitigated fraction</i>
--------	-------------------------------------

---

## Description

Estimates mitigated fraction from clustered or stratified data.

## Usage

```
MFClus(formula, data, compare = c("con", "vac"), trace.it = FALSE)
```

## Arguments

formula	Formula of the form $y \sim x + \text{cluster}(w)$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $w$ is a factor indicating the clusters.
data	Data frame. See Note for handling of input data with more than two levels.
compare	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared
trace.it	Verbose tracking of the cycles? Default FALSE.

## Details

Averages the U statistic over the clusters and computes MF from it. Clusters are excluded if they do not include both treatments.

## Value

a [mfcluster-class](#) data object

## Note

If input data contains more than two levels of treatment, rows associated with unused treatment levels will be removed.  
 Factor levels for treatments not present in the input data will be ignored.  
 Clusters with missing treatments will be excluded. See [mfbootcluster-class](#) or use `trace.it` to identify excluded clusters.

## Author(s)

David Siev <david.siev@aphis.usda.gov>

## References

Siev D. (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4**:500–508

## See Also

[mfcluster-class](#)

## Examples

```
## Not run:
MFClus(lesion ~ group + cluster(litter), piglung)

# Comparing vac to con
#
# MF = 0.3533835
#
# By Cluster
#   w  u      r n1 n2      mf
# U 25 10 0.4000000 5 5 -0.2000000
# K 12  2 0.2500000 4 2 -0.5000000
# Z 16 10 0.8333333 3 4  0.6666667
# D  3  2 1.0000000 1 2  1.0000000
# N  1  0 0.0000000 1 3 -1.0000000
# T  8  5 0.8333333 2 3  0.6666667
# P  4  1 0.5000000 2 1  0.0000000
# L  3  2 0.6666667 1 3  0.3333333
# G 15  9 0.7500000 3 4  0.5000000
# J 15  9 1.0000000 3 3  1.0000000
# W  6  3 0.7500000 2 2  0.5000000
# A  9  3 0.3333333 3 3 -0.3333333
# X 12  6 1.0000000 3 2  1.0000000
# F 13  7 0.7777778 3 3  0.5555556
# S 21 11 0.9166667 4 3  0.8333333
# H 14  8 0.8888889 3 3  0.7777778
# Y  2  1 1.0000000 1 1  1.0000000
# E  2  1 1.0000000 1 1  1.0000000
#
# All
#   w  u      r n1 n2      mf
# All 181 90 0.6766917 50 52 0.3533835
#
# Excluded Clusters
# [1] M, Q, R, B, O, V, I, C

## End(Not run)
```

---

MFClusBoot

*Bootstrap MF CI from clustered data*


---

## Description

Estimates bootstrap confidence intervals for the mitigated fraction from clustered or stratified data.

## Usage

```
MFClusBoot(formula, data, compare = c("con", "vac"), boot.cluster = TRUE,
  boot.unit = TRUE, b = 100, B = 100, alpha = 0.05, hpd = TRUE,
  return.boot = FALSE, trace.it = FALSE, seed = sample(1:1e+05, 1))
```

**Arguments**

<code>formula</code>	Formula of the form $y \sim x + \text{cluster}(w)$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $w$ is a factor indicating the clusters.
<code>data</code>	Data frame. See Note for handling of input data with more than two levels.
<code>compare</code>	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared
<code>boot.cluster</code>	Boolean whether to resample the clusters.
<code>boot.unit</code>	Boolean whether to resample the units within cluster.
<code>b</code>	Number of bootstrap samples to take with each cycle
<code>B</code>	Number of cycles, giving the total number of samples = $B * b$
<code>alpha</code>	Complement of the confidence level
<code>hpd</code>	Boolean whether to estimate highest density intervals.
<code>return.boot</code>	Boolean whether to save the bootstrap sample of the MF statistic.
<code>trace.it</code>	Boolean whether to display verbose tracking of the cycles.
<code>seed</code>	to initialize random number generator for reproducibility. Passed to <code>set.seed</code> .

**Details**

Resamples the data and produces bootstrap confidence intervals. Equal tailed intervals are estimated by the percentile method. Highest density intervals are estimated by selecting the shortest of all possible intervals.

**Value**

a `mfbootcluster-class` data object

**Note**

If input data contains more than two levels of treatment, rows associated with unused treatment levels will be removed.

Factor levels for treatments not present in the input data will be ignored.

Clusters with missing treatments will be excluded. See `mfbootcluster-class` or use `trace.it` to identify excluded clusters.

**Author(s)**

David Siev <david.siev@aphis.usda.gov>

**References**

Siev D. (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4:500–508**

Efron B, Tibshirani RJ. *An Introduction to the Bootstrap*. Chapman and Hall, New York, 1993.

## Examples

```
## Not run:
MFclusBoot(lesion ~ group + cluster(litter), piglung, seed = 12345)
Bootstrapping clusters. . . . .

Bootstrapping units. . . . .

10000 bootstrap samples of clusters and units in treatment in cluster
Comparing vac to con

95% confidence interval

observed   median      lower      upper
Equal Tailed  0.3533835 0.3648649 -0.01409471 0.7109966
Highest Density 0.3533835 0.3648649  0.00000000 0.7236842

Excluded Clusters
M, Q, R, B, O, V, I, C

## End(Not run)
```

---

MFclusBootHier

---

*MFclusBootHier*


---

## Description

Combines [MFhBoot](#) and [MFnestBoot](#) into a single function.

## Usage

```
MFclusBootHier(formula, data, compare = c("con", "vac"), nboot = 10000,
  boot.unit = TRUE, boot.cluster = TRUE, which.factor = "All",
  alpha = 0.05, seed = sample(1:1e+05, 1))
```

## Arguments

formula	formula Formula of the form $y \sim x + a/b/c$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $a/b/c$ are grouping variables corresponding to the clusters. Nesting is assumed to be in order, left to right, highest to lowest. So a single level of "a" will contain multiple levels of "b" and a single level of "b" will contain multiple levels of "c".
data	a data.frame or tibble with the variables specified in formula. Additional variables will be ignored.
compare	Text vector stating the factor levels - compare[1] is the control or reference group to which compare[2] is compared.
nboot	number of bootstrapping events
boot.unit	Boolean whether to sample observations from within those of the same core.
boot.cluster	Boolean whether to sample which cores are present. If TRUE, some trees have all the cores while others only have a subset.
which.factor	Which variables to include in the mitigated fraction summation. Default is $\hat{\epsilon}^{\text{TM}}\text{All}\hat{\epsilon}^{\text{TM}}$ , to sum over entire tree.

alpha	Passed to <a href="#">emp.hpd</a> to calculate high tailed upper and high tailed lower of mitigated fraction.
seed	Passed to <a href="#">MFhBoot</a> to initialize random number generator for reproducibility.

### Value

A list with the following elements:

- **MFhBoot** as output from [MFhBoot](#).
- **MFnestBoot** as output from [MFnestBoot](#).

### Note

Core variable is the variable corresponding to the lowest nodes of the hierarchical tree. Nest variables are those above the core. All refers to a summary of the entire tree.

### See Also

[MFhBoot](#), [MFnestBoot](#).

### Examples

```
a <- data.frame(
  room = paste('Room',rep(c('W','Z'),each=24)),
  pen = paste('Pen',rep(LETTERS[1:6],each=8)),
  litter = paste('Litter',rep(11:22,each=4)),
  tx = rep(rep(c('vac','con'),each=2),12),
  stringsAsFactors = FALSE
)
set.seed(76153)
a$lung[a$tx=='vac'] <- rnorm(24,5,1.3)
a$lung[a$tx=='con'] <- rnorm(24,7,1.3)
set.seed(12345)
thismf1 <- MFclusBootHier(lung ~ tx + room/pen/litter, a, nboot = 10000,
  boot.cluster = TRUE, boot.unit = TRUE)
thismf1
```

---

mfclusboothier-class    *Class mfclusboothier*

---

### Description

Class mfclusboothier is created from output of function MFclusBootHier.

### Usage

```
mfclusboothier$new(MFhBoot, MFnestBoot)
```

### Fields

- MFhBoot: output from MFhBoot. A list.
- MFnestBoot: output from MFnestBoot. A list.

Author(s)

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

See Also

[MFhBoot](#), [MFnestBoot](#)

---

MFClusHier	<i>MFClusHier</i>
------------	-------------------

---

Description

Calculate mitigated fraction directly from hierarchial nested data. Combines [MFh](#) and [MFnest](#) into a single function.

Usage

```
MFClusHier(formula, data, compare = c("con", "vac"), which.factor = "All")
```

Arguments

formula	Formula of the form $y \sim x + a/b/c$ , where y is a continuous response, x is a factor with two levels of treatment, and a/b/c are grouping variables corresponding to the clusters. Nesting is assumed to be in order, left to right, highest to lowest. So a single level of "a" will contain multiple levels of "b" and a single level of "b" will contain multiple levels of "c".
data	a data.frame or tibble with the variables specified in formula. Additional variables will be ignored.
compare	Text vector stating the factor levels - compare[1] is the control or reference group to which compare[2] is compared.
which.factor	one or more variable(s) of interest. This can be any of the core or nest variables from the data set. If none or NULL is specified, MF will be calculated for the whole tree.

Value

A list with the following elements:

- **MFh** as output from [MFh](#).
- **MFnest** as output from [MFnest](#).

Note

Core variable is the variable corresponding to the lowest nodes of the hierarchical tree. Nest variables are those above the core. All refers to a summary of the entire tree.

See Also

[MFh](#), [MFnest](#)

**Examples**

```

a <- data.frame(
  room = paste('Room',rep(c('W','Z'),each=24)),
  pen = paste('Pen',rep(LETTERS[1:6],each=8)),
  litter = paste('Litter',rep(11:22,each=4)),
  tx = rep(rep(c('vac','con'),each=2),12),
  stringsAsFactors = FALSE
)
set.seed(76153)
a$lung[a$tx=='vac'] <- rnorm(24,5,1.3)
a$lung[a$tx=='con'] <- rnorm(24,7,1.3)
thismf <- MFClusHier(lung ~ tx + room/pen/litter,a)
thismf$MFnest
aCore <- thismf$MFh
aCore
aCore$data
aCore$formula
aCore$compare

```

mfclushier-class

*Class mfclushier***Description**

Class mfclushier is created from output of function MFClusHier

**Usage**

```
mfclushier$new(MFh, MFnest)
```

**Fields**

- MFh: output from MFh. A [mfhierdata](#) object.
- MFnest: output from MFnest. A tibble.

**Author(s)**

Marie Vendettuoli <[marie.c.vendettuoli@aphis.usda.gov](mailto:marie.c.vendettuoli@aphis.usda.gov)>

**See Also**

[MFh](#), [MFnest](#)

---

mfcluster-class	<i>Class mfcluster</i>
-----------------	------------------------

---

### Description

Class mfcluster is created from output of function MFClus

### Usage

```
mfcluster$new(All, bycluster, excludedClusters, call, compare)
```

### Fields

- All: vector with elements:
  - *w* Wilcoxon statistic
  - *u* Mann-Whitney statistic
  - *r* mean ridit
  - *n1* size of group 1
  - *n2* size of group 2
  - *mf* mitigated fraction
- byCluster: As for All, by clusters
- excludedClusters: character vector naming clusters excluded because of missing treatment
- call: the call to MFClus
- compare: character vector naming groups compared

### Author(s)

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

### See Also

[MFClus](#)

---

mfcomponents-class	<i>Class mfcomponents</i>
--------------------	---------------------------

---

### Description

Class mfcomponents is created from output of function MFSubj

### Usage

```
mfcomponents$new(mf, x, y, subj, compare)
```



**Fields**

- `mf`: numeric estimator for mitigated fraction
- `x`: numeric vector containing responses of group 1
- `y`: numeric vector containing responses of group 2
- `subj`: matrix where `mf.j` are the subject components
- `compare`: character vector naming groups being compared

**Author(s)**

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

**See Also**

[MFSubj](#)

---

MFh	<i>Identify ranks for use when evaluating MF for nested hierarchy.</i>
-----	--

---

**Usage**

```
MFh(formula, data, compare = c("con", "vac"))
```

**Arguments**

<code>formula</code>	Formula of the form $y \sim x + a/b/c$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $a/b/c$ are vgrouping variables corresponding to the clusters. Nesting is assumed to be in order, left to right, highest to lowest. So a single level of "a" will contain multiple levels of "b" and a single level of "b" will contain multiple levels of "c".
<code>data</code>	a data.frame or tibble with the variables specified in formula. Additional variables will be ignored.
<code>compare</code>	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared.

**Value**

A [mfhierdata](#) object, which is a list of three items.

**coreTbl** A [tibble](#) with one row for each unique core level showing values for:

- `con_n` & `vac_n` - counts of observations for each treatment level in the core level.
- `con_medResp` & `vac_medResp` - median of the  $y$  continuous response for each treatment level.
- `n1n2` - product of the counts, `con_n * vac_n`.
- `w` - Wilcoxon statistic
- `u` - Mann-Whitney statistic

**data** A [tibble](#) of the restructured input data used for calculations.

**compare** The compare variables as input by user.

**formula** The formula as input by user.

**Note**

Core variable is the variable corresponding to the lowest nodes of the hierarchial tree. Nest variables are those above the core.

**See Also**

[MFnest](#) for calculation of MF for nest, core and all variables. [mfhierdata](#) for returned object.MFClusHier for a wrapper.

**Examples**

```
a <- data.frame(
  room = paste('Room',rep(c('W','Z'),each=24)),
  pen = paste('Pen',rep(LETTERS[1:6],each=8)),
  litter = paste('Litter',rep(11:22,each=4)),
  tx = rep(rep(c('vac','con'),each=2),12),
  stringsAsFactors = FALSE
)
set.seed(76153)
a$lung[a$tx=='vac'] <- rnorm(24,5,1.3)
a$lung[a$tx=='con'] <- rnorm(24,7,1.3)

aCore <- MFh(lung ~ tx + room/pen/litter,a)
aCore
# A tibble: 12 x 10
#   room   pen litter con_medResp con_n     w vac_medResp vac_n n1n2     u
#   <chr> <chr> <chr>      <dbl> <dbl> <dbl>      <dbl> <dbl> <dbl> <dbl>
# 1 Room W Pen A Litter 11      8.24     2     7        5.13     2     4     4
# 2 Room W Pen A Litter 12      4.91     2     5        3.81     2     4     2
# 3 Room W Pen B Litter 13      8.10     2     7        5.23     2     4     4
# 4 Room W Pen B Litter 14      8.11     2     7        5.59     2     4     4
# 5 Room W Pen C Litter 15      8.09     2     7        5.26     2     4     4
# 6 Room W Pen C Litter 16      6.77     2     7        4.50     2     4     4
# 7 Room Z Pen D Litter 17      5.58     2     7        4.26     2     4     4
# 8 Room Z Pen D Litter 18      7.44     2     6        6.33     2     4     3
# 9 Room Z Pen E Litter 19      7.98     2     7        4.58     2     4     4
# 10 Room Z Pen E Litter 20      6.78     2     7        4.86     2     4     4
# 11 Room Z Pen F Litter 21      6.82     2     7        5.36     2     4     4
# 12 Room Z Pen F Litter 22      7.27     2     7        5.13     2     4     4
```

---

MFhBoot	<i>MFhBoot</i>
---------	----------------

---

**Description**

Calculate rank tables for MF using bootstrapping.

**Usage**

```
MFhBoot(formula, data, compare = c("con", "vac"), nboot = 10000,
  boot.unit = TRUE, boot.cluster = TRUE, seed = sample(1:1e+05, 1))
```

## Arguments

formula	Formula of the form $y \sim x + a/b/c$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $a/b/c$ are grouping variables corresponding to the clusters. Nesting is assumed to be in order, left to right, highest to lowest. So a single level of "a" will contain multiple levels of "b" and a single level of "b" will contain multiple levels of "c".
data	a data.frame or tibble with the variables specified in formula. Additional variables will be ignored.
compare	Text vector stating the factor levels - compare[1] is the control or reference group to which compare[2] is compared.
nboot	number of bootstrapping events
boot.unit	Boolean whether to sample observations from within those of the same core.
boot.cluster	Boolean whether to sample which cores are present. If TRUE, some trees have all the cores while others only have a subset.
seed	to initialize random number generator for reproducibility. Passed to set.seed.

## Value

A list with the following elements:

**bootmfh** Rank table for the bootstrapped values as output from [MFh](#). Includes a new bootID variable to distinguish each bootstrapped incidence.

**clusters** Table of unique nodes with an ID.

**compare** Compare vector as specified by user.

**mfh** MFh run on original data input.

## See Also

[MFclusBootHier](#), [MFnestBoot](#)

## Examples

```
set.seed(76153)
a <- data.frame(room = paste('Room', rep(c('W','Z'), each = 24)),
                pen = paste('Pen', rep(LETTERS[1:6], each = 8)),
                litter = paste('Litter', rep(11:22, each = 4)),
                tx = rep(rep(c('vac', 'con'), each = 2), 12),
                stringsAsFactors = FALSE)
a[a$tx == 'vac', 'lung'] <- rnorm(24, 5, 1.3)
a[a$tx == 'con', 'lung'] <- rnorm(24, 7, 1.3)
a

formula <- lung ~ tx + room/pen/litter
nboot <- 10000
boot.cluster <- TRUE
boot.unit <- TRUE
which.factors <- c('All', 'room', 'pen', 'litter')

system.time(test1 <- MFhBoot(formula, a,
                             nboot = 10000,
```

```

                                boot.cluster = TRUE, boot.unit = TRUE, seed = 12345))
test1$bootmfh

```

---

mfhierdata-class	<i>Class mfhierdata</i>
------------------	-------------------------

---

## Description

Class mfhierdata is created from output of function MFh

## Usage

```
mfhierdata$new(coreTbl, data)
```

## Fields

- `coreTbl`: data.frame with one row for each unique core level showing values for `nx`, `ny`, `N`, `w`, `u`, and median observed response.
- `data`: data.frame is the restructured input data used for calculations in MFh and MFnest.
- `compare`: character vector naming groups being compared.
- `formula`: formula that was called by user.

## Author(s)

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

## See Also

[MFh](#)

---

mfhlboot-class	<i>Class mfhlboot</i>
----------------	-----------------------

---

## Description

class for data objects produced by HLBoot, contains class mf with additional fields *MFstat*, *HLstat*, *QDIFstat*, *QXstat*, *QYstat*

## Usage

```
mfhlboot$new(nboot, alpha, seed, compare, rng, sample, MFstat, HLstat,
             QDIFstat, QXstat, QYstat)
```

**Fields**

- `nboot`: Numeric value specifying number of samples.
- `alpha`: Numeric value specifying complement of confidence interval.
- `seed`: Vector of integers specifying seed for pseudo-random number generator used.
- `compare`: Vector of character strings naming groups compared.
- `rng`: Character string naming type of random number generator.
- `sample`: The bootstrapped values.
- `MFstatMatrix` with columns *observed*, *median*, *lower*, *upper* for Equal Tailed and Highest Density estimates of mitigated fraction (MF).
- `HLstatMatrix` with columns *observed*, *median*, *lower*, *upper* for Equal Tailed and Highest Density estimates of Hodge-Lehmann estimator (HL).
- `QDIFstatMatrix` with columns *observed*, *median*, *lower*, *upper* for estimates of Quartile Differences.
- `QXstatMatrix` with columns *observed*, *median*, *lower*, *upper* for quartiles of treatments, equal tailed.
- `QYstatMatrix` with columns *observed*, *median*, *lower*, *upper* for quartiles of response, equal tailed.

**Contains**

[mf-class](#)

**Author(s)**

Marie Vendettuoli <[marie.c.vendettuoli@aphis.usda.gov](mailto:marie.c.vendettuoli@aphis.usda.gov)>

**See Also**

[HLBoot](#)

Other mf: [mf-class](#), [mfboot-class](#), [mfbootcluster-class](#)

---

MFmp

*Mitigated fraction from matched pairs*

---

**Description**

Estimates mitigated fraction from matched pairs.

**Usage**

```
MFmp(formula=NULL, data=NULL, compare = c("con", "vac"), x=NULL, alpha=0.05, df=NULL, tdist=T)
```

**Arguments**

formula	Formula of the form $y \sim x + \text{cluster}(w)$ , where $y$ is a continuous response, $x$ is a factor with two levels of treatment, and $w$ is a factor indicating the clusters.
data	Data frame
compare	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared
x	Trinomial vector $\{\Sigma I(x < y), \Sigma I(x = y), \Sigma I(x > y)\}$
alpha	Complement of the confidence level.
df	Degrees of freedom. Default N-2
tdist	Use quantiles of t or Gaussian distribution for confidence interval? Default t distribution.

**Details**

Estimates  $MF$  from matched pairs by the difference of multinomial fractions  $(\Sigma I(x < y) - \Sigma I(x > y))/N$ . The trinomial vector is  $\{\Sigma I(x < y), \Sigma I(x = y), \Sigma I(x > y)\}$

**Value**

a `mfmp-class` data object

**Note**

upper confidence interval is truncated to 1; lower confidence interval is truncated to -1. Point estimate of 1.0 indicates complete separation.

**Author(s)**

David Siev <david.siev@aphis.usda.gov>

**References**

Siev D. (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4:500–508**

**See Also**

`mfmp-class`

**Examples**

```
MFmp(les ~ tx + cluster(cage), mlesions, compare = c('con', 'vac'))
MFmp(x = c(12, 12, 2))
```

mfmp-class

*Class mfmp***Description**

Class mfmp is created from output of function MFmp

**Usage**

```
mfmp$new(ci, x, what, alpha, tdist, df)
```

**Fields**

- ci: numeric vector of point and interval estimates
- x: numeric vector of length three holding data
- what: text string describing interval type
- alpha: numeric value specifying complement of confidence interval
- tdist: Logical indicating if t distribution(TRUE) or gaussian (FALSE)
- df: numeric value indicating degrees freedom

**Author(s)**

Marie Vendettuoli <marie.c.vendettuoli@aphis.usda.gov>

**See Also**

[MFmp](#)

MFnest

*Summations to calculate the MF for nested data from a rank table.*

**Usage**

```
MFnest(Y, which.factor = "All")
```

**Arguments**

- |              |   |
|--------------|---|
| Y            | rank table (tibble or data.frame), structured as \$scoreTbl output from <a href="#">MFh</a> or returned object from <a href="#">MFh()</a> .   |
| which.factor | one or more grouping variable(s) of interest. This can be any of the core or nest variables from the data set. If none or All is specified, a summary MF will be calculated for the whole tree. |

**Value**

A tibble with each unique level of a variable as a row. Other values include:

MF Mitigated fraction for the particular level of the variable in this row.

N1N2 Sum of the n1n2 variable in \$coreTbl field of `mfhierdata` object output by `MFh` for this particular variable-level combination.

U Sum of u variable in \$coreTbl field of `mfhierdata` object output by `MFh` for this particular variable-level combination.

\_N Sum of the \_n variable in \$coreTbl field of `mfhierdata` object output by `MFh` for this particular variable-level combination.

\_medResp Median of observed responses for each comparison group for this particular variable-level combination.

**Note**

Core variable is the variable corresponding to the lowest nodes of the hierarchical tree. Nest variables are those above the core. All refers to a summary of the entire tree.

**See Also**

[MFh](#)

**Examples**

```
a <- data.frame(
  room = paste('Room',rep(c('W','Z'),each=24)),
  pen = paste('Pen',rep(LETTERS[1:6],each=8)),
  litter = paste('Litter',rep(11:22,each=4)),
  tx = rep(rep(c('vac','con'),each=2),12),
  stringsAsFactors = FALSE
)
set.seed(76153)
a$lung[a$tx=='vac'] <- rnorm(24,5,1.3)
a$lung[a$tx=='con'] <- rnorm(24,7,1.3)

aCore <- MFh(lung ~ tx + room/pen/litter,a)
MFnest(aCore)
# # A tibble: 1 x 9
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
# 1 All      All    0.875   48   45   24   24          7.24       4.91

MFnest(aCore$coreTbl)
# Skipping median summary, no response data provided.
# # A tibble: 1 x 7
#   variable level    MF  N1N2    U con_N vac_N
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>
# 1 All      All    0.875   48   45   24   24

MFnest(aCore, 'room')
# # A tibble: 2 x 9
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
```



```
# 1 room    Room W 0.833    24    22    12    12        7.79        4.85
# 2 room    Room Z 0.917    24    23    12    12        6.71        4.98
```

```
MFnest(aCore, 'pen')
```

```
# Complete separation observed for variable(s): pen
```

```
# # A tibble: 6 x 9
```

```
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
# 1 pen      Pen A  0.5     8     6     4     4        6.79        4.24
# 2 pen      Pen B  1       8     8     4     4        8.11        5.59
# 3 pen      Pen C  1       8     8     4     4        7.69        4.85
# 4 pen      Pen D 0.75     8     7     4     4        6.10        4.98
# 5 pen      Pen E  1       8     8     4     4        6.86        4.86
# 6 pen      Pen F  1       8     8     4     4        6.88        5.13
```

```
MFnest(aCore, c('All', 'litter'))
```

```
# Complete separation observed for variable(s): litter
```

```
# # A tibble: 13 x 9
```

```
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
# 1 All      All    0.875   48   45   24   24        7.24        4.91
# 2 litter   Litter 11 1     4     4     2     2        8.24        5.13
# 3 litter   Litter 12 0     4     2     2     2        4.91        3.81
# 4 litter   Litter 13 1     4     4     2     2        8.10        5.23
# 5 litter   Litter 14 1     4     4     2     2        8.11        5.59
# 6 litter   Litter 15 1     4     4     2     2        8.09        5.26
# 7 litter   Litter 16 1     4     4     2     2        6.77        4.50
# 8 litter   Litter 17 1     4     4     2     2        5.58        4.26
# 9 litter   Litter 18 0.5   4     3     2     2        7.44        6.33
# 10 litter  Litter 19 1     4     4     2     2        7.98        4.58
# 11 litter  Litter 20 1     4     4     2     2        6.78        4.86
# 12 litter  Litter 21 1     4     4     2     2        6.82        5.36
# 13 litter  Litter 22 1     4     4     2     2        7.27        5.13
```

```
MFnest(aCore, 'litter')
```

```
# Complete separation observed for variable(s): litter
```

```
# # A tibble: 12 x 9
```

```
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
# 1 litter   Litter 11 1     4     4     2     2        8.24        5.13
# 2 litter   Litter 12 0     4     2     2     2        4.91        3.81
# 3 litter   Litter 13 1     4     4     2     2        8.10        5.23
# 4 litter   Litter 14 1     4     4     2     2        8.11        5.59
# 5 litter   Litter 15 1     4     4     2     2        8.09        5.26
# 6 litter   Litter 16 1     4     4     2     2        6.77        4.50
# 7 litter   Litter 17 1     4     4     2     2        5.58        4.26
# 8 litter   Litter 18 0.5   4     3     2     2        7.44        6.33
# 9 litter   Litter 19 1     4     4     2     2        7.98        4.58
# 10 litter  Litter 20 1     4     4     2     2        6.78        4.86
# 11 litter  Litter 21 1     4     4     2     2        6.82        5.36
# 12 litter  Litter 22 1     4     4     2     2        7.27        5.13
```

```
MFnest(aCore, c('room', 'pen', 'litter'))
```

```
# # A tibble: 20 x 9
```

```
#   variable level    MF  N1N2    U con_N vac_N con_medResp vac_medResp
#   <fct>      <chr> <dbl> <dbl> <dbl> <dbl> <dbl>      <dbl>      <dbl>
# 1 room      Room W  0.833   24   22   12   12        7.79        4.85
```

# 2 room	Room Z	0.917	24	23	12	12	6.71	4.98
# 3 pen	Pen A	0.5	8	6	4	4	6.79	4.24
# 4 pen	Pen B	1	8	8	4	4	8.11	5.59
# 5 pen	Pen C	1	8	8	4	4	7.69	4.85
# 6 pen	Pen D	0.75	8	7	4	4	6.10	4.98
# 7 pen	Pen E	1	8	8	4	4	6.86	4.86
# 8 pen	Pen F	1	8	8	4	4	6.88	5.13
# 9 litter	Litter 11	1	4	4	2	2	8.24	5.13
# 10 litter	Litter 12	0	4	2	2	2	4.91	3.81
# 11 litter	Litter 13	1	4	4	2	2	8.10	5.23
# 12 litter	Litter 14	1	4	4	2	2	8.11	5.59
# 13 litter	Litter 15	1	4	4	2	2	8.09	5.26
# 14 litter	Litter 16	1	4	4	2	2	6.77	4.50
# 15 litter	Litter 17	1	4	4	2	2	5.58	4.26
# 16 litter	Litter 18	0.5	4	3	2	2	7.44	6.33
# 17 litter	Litter 19	1	4	4	2	2	7.98	4.58
# 18 litter	Litter 20	1	4	4	2	2	6.78	4.86
# 19 litter	Litter 21	1	4	4	2	2	6.82	5.36
# 20 litter	Litter 22	1	4	4	2	2	7.27	5.13

MFnestBoot

MFnestBoot

**Description**

MFnest using bootstrapping

**Usage**

MFnestBoot(x, which.factor = "All", alpha = 0.05)

**Arguments**

x	output from <a href="#">MFhBoot</a>
which.factor	one or more grouping variable(s) of interest. This can be any of the core or nest variables from the data set. A MF value will be calculated for each level of the variable(s) specified. Default is $\hat{\epsilon}^{\text{TM}}\text{All}\hat{\epsilon}^{\text{TM}}$ , to sum over entire tree.
alpha	Passed to <a href="#">emp.hpd</a> to calculate eq tailed upper and high lower of mitigated fraction

**Value**

A list with the following elements:

**mfnest\_details** The MF and summary statistics as calculated for each bootstrap event. Variables as in [MFnest](#) output.**mfnest\_summary** Statistical summary of bootstrapped MF with each unique level of a core or nest variable passed to which.factor as a row. Other variables include:

- median Median of MFs from all of the bootstrap events.
- etlower Lower value of equal tailed range.

- `etupper` Upper value of equal tailed range.
- `hdlower` Lower value of the highest posterior density range.
- `hdupper` Upper value of the highest posterior density range.
- `mf.obs` MF calculated from data using [MFh](#).

### See Also

[MFclusBootHier](#), [MFhBoot](#)

### Examples

```
set.seed(76153)
a <- data_frame(room = paste('Room', rep(c('W','Z'), each = 24)),
                pen = paste('Pen', rep(LETTERS[1:6], each = 8)),
                litter = paste('Litter', rep(11:22, each = 4)),
                tx = rep(rep(c('vac', 'con'), each = 2), 12)) %>%
  mutate(lung = ifelse(tx == 'vac', rnorm(24, 5, 1.3), rnorm(24, 7, 1.3)))
a

formula <- lung ~ tx + room/pen/litter
nboot <- 10000
boot.cluster <- TRUE
boot.unit <- TRUE
which.factors <- c('All', 'room', 'pen', 'litter')

#####

test1 <- MFhBoot(formula, a,
                 nboot = 10000,
                 boot.cluster = TRUE, boot.unit = TRUE, seed = 12345)
MFnestBoot(test1, c('All', 'litter'))

## Not run:
system.time(test2 <- MFnestBoot(test1, which.factors))
test2
system.time(test3 <- MFnestBoot(test1, which.factors[1]))
test3
system.time(test4 <- MFnestBoot(test1, which.factors[2]))
test4
system.time(test5 <- MFnestBoot(test1, which.factors[2:3]))
test5
system.time(test6 <- MFnestBoot(test1, which.factors[2:4]))
test6

## End(Not run)
```

---

MFr

*Mitigated fraction*


---

### Description

Mitigated fraction comparing treatment to control.

**Usage**

```
MFr(formula, data, compare = c("con", "vac"))
```

**Arguments**

formula	Formula of the form $y \sim x$ , where $y$ is a continuous response and $x$ is a factor with two levels
data	Data frame
compare	Text vector stating the factor levels – <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared

**Details**

The mitigated fraction is an estimator that quantifies an intervention's effect on reducing the severity of a condition. Since its units are on the probability scale, it is often a good idea to accompany it with an estimator on the original scale of measurement.

**Value**

The estimated mitigated fraction.

**Author(s)**

David Siev

**References**

Siev D, 2005. An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. 4:500-508

**Examples**

```
MFr(lesion~group,calflung)
# [1] 0.44
```

---

MFSubj

*Subject components of mitigated fraction*


---

**Description**

Estimates the subject components of the mitigated fraction.

**Usage**

```
MFSubj(formula, data, compare = c("con", "vac"))
```

**Arguments**

formula	Formula of the form $y \sim x$ , where $y$ is a continuous response and $x$ is a factor with two levels
data	Data frame
compare	Text vector stating the factor levels - <code>compare[1]</code> is the control or reference group to which <code>compare[2]</code> is compared

## Details

The mitigated fraction is an estimator that quantifies an intervention's effect on reducing the severity of a condition. Since its units are on the probability scale, it is often a good idea to accompany it with an estimator on the original scale of measurement.

The subject components are the individual contributions of the treated subjects to  $MF$ , which is the average of the subject components.

## Value

a `mfcomponents-class` data object

## Author(s)

David Siev <david.siev@aphis.usda.gov>

## References

Siev D. (2005). An estimator of intervention effect on disease severity. *Journal of Modern Applied Statistical Methods*. **4:500–508**

## Examples

```
x <- MFSubj(lesion ~ group, calflung)
x

# MF = 0.44 comparing vac to con
#
# MF Subject Components
#
#   mf.j freq   min.y   max.y
#   1.00   6 0.000030 0.00970
#   0.84   1 0.012500 0.01250
#   0.76   3 0.016650 0.02030
#   0.68   6 0.023250 0.03190
#   0.04   1 0.132100 0.13210
#  -0.04   3 0.144575 0.16325
#  -0.20   2 0.210000 0.21925
#  -0.36   1 0.292000 0.29200
#  -0.52   1 0.356500 0.35650
#  -0.84   1 0.461500 0.46150

mean(x$subj[, 'mf.j'])

# [1] 0.44
```

---

mlesions

mlesions dataset

---

## Description

Post-mortem examination of the lungs of dogs housed in cages by pairs.

**Format**

A data frame with 52 observations of the following 3 variables, no NAs.

**cage** Cage ID. 1 - 26.

**tx** Treatment. One of 'con' or 'vac'.

**les** Percent gross lung lesions.

---

*piglung*

*piglung dataset*

---

**Description**

Post-mortem examination of the lungs of pigs in litters.

**Format**

A data frame with 102 observations of the following 3 variables, no NAs.

**lesion** Percent gross lung lesions.

**group** Treatment group. One of 'con' or 'vac'.

**litter** Litter ID.

# Index

## \*Topic **datasets**

calflung, [3](#)  
mlesions, [29](#)  
piglung, [30](#)

## \*Topic **documentation**

mf-class, [5](#)  
mfboot-class, [7](#)  
mfbootcluster-class, [8](#)  
mfclusboothier-class, [13](#)  
mfclushier-class, [15](#)  
mfcluster-class, [16](#)  
mfcomponents-class, [16](#)  
mfhierdata-class, [20](#)  
mfhlboot-class, [20](#)  
mfmp-class, [23](#)

calflung, [3](#)  
calflung-data (calflung), [3](#)

emp.hpd, [13](#), [26](#)

HLBoot, [3](#), [21](#)

MF (MF-package), [2](#)  
mf (mf-class), [5](#)  
mf-class, [5](#)  
MF-package, [2](#)  
MFBoot, [6](#), [7](#)  
mfboot (mfboot-class), [7](#)  
mfboot-class, [7](#)  
mfbootcluster (mfbootcluster-class), [8](#)  
mfbootcluster-class, [8](#)  
MFClus, [9](#), [16](#)  
MFClusBoot, [8](#), [10](#)  
MFClusBootHier, [12](#), [19](#), [27](#)  
mfclusboothier (mfclusboothier-class),  
[13](#)  
mfclusboothier-class, [13](#)  
MFClusHier, [14](#), [18](#)  
mfclushier (mfclushier-class), [15](#)  
mfclushier-class, [15](#)  
mfcluster (mfcluster-class), [16](#)  
mfcluster-class, [16](#)  
mfcomponents (mfcomponents-class), [16](#)

mfcomponents-class, [16](#)  
MFh, [14](#), [15](#), [17](#), [19](#), [20](#), [23](#), [24](#), [27](#)  
MFhBoot, [12–14](#), [18](#), [26](#), [27](#)  
mfhierdata, [15](#), [17](#), [18](#), [24](#)  
mfhierdata (mfhierdata-class), [20](#)  
mfhierdata-class, [20](#)  
mfhlboot (mfhlboot-class), [20](#)  
mfhlboot-class, [20](#)  
MFmp, [21](#), [23](#)  
mfmp (mfmp-class), [23](#)  
mfmp-class, [23](#)  
MFnest, [14](#), [15](#), [18](#), [23](#), [26](#)  
MFnestBoot, [12–14](#), [19](#), [26](#)  
MFr, [27](#)  
MFSubj, [17](#), [28](#)  
mlesions, [29](#)  
mlesions-data (mlesions), [29](#)  
  
piglung, [30](#)  
piglung-data (piglung), [30](#)  
  
tibble, [17](#)