Introduction to Database Systems (CSD202)

Lab Assignment#2

Date: 25/01/19

1.

```
mysql> insert into Customer1
    -> select customer_id, store_id, first_name, last_name from customer
    -> where customer_id>=11 and customer_id<=20;
Query OK, 10 rows affected (0.03 sec)
Records: 10  Duplicates: 0  Warnings: 0
```

2.

```
mysql> select * from customer1;
+-------------+----------+------------+-----------+
| Customer_ID | Store_ID | First_Name | Last_Name |
+-------------+----------+------------+-----------+
|          11 |        2 | LISA       | ANDERSON  |
|          12 |        1 | NANCY      | THOMAS    |
|          13 |        2 | KAREN      | JACKSON   |
|          14 |        2 | BETTY      | WHITE     |
|          15 |        1 | HELEN      | HARRIS    |
|          16 |        2 | SANDRA     | MARTIN    |
|          17 |        1 | DONNA      | THOMPSON  |
|          18 |        2 | CAROL      | GARCIA    |
|          19 |        1 | RUTH       | MARTINEZ  |
|          20 |        2 | SHARON     | ROBINSON  |
+-------------+----------+------------+-----------+
10 rows in set (0.00 sec)

mysql> describe customer1;
+-------------+-------------+------+-----+---------+-------+
| Field       | Type        | Null | Key | Default | Extra |
+-------------+-------------+------+-----+---------+-------+
| Customer_ID | int(11)     | YES  |     | NULL    |       |
| Store_ID    | int(11)     | YES  |     | NULL    |       |
| First_Name  | varchar(20) | YES  |     | NULL    |       |
| Last_Name   | varchar(20) | YES  |     | NULL    |       |
+-------------+-------------+------+-----+---------+-------+
4 rows in set (0.02 sec)
```

3.

```
mysql> select customer_id, concat(first_name," ",last_name) as Name from customer1;
+-------------+-----------------+
| customer_id | Name            |
+-------------+-----------------+
|          11 | LISA ANDERSON   |
|          12 | NANCY THOMAS    |
|          13 | KAREN JACKSON   |
|          14 | BETTY WHITE     |
|          15 | HELEN HARRIS    |
|          16 | SANDRA MARTIN   |
|          17 | DONNA THOMPSON  |
|          18 | CAROL GARCIA    |
|          19 | RUTH MARTINEZ   |
|          20 | SHARON ROBINSON |
+-------------+-----------------+
10 rows in set (0.00 sec)
```

4.

```
mysql> select store_id, count(*) as No_of_Visits from customer1 group by store_id;
+----------+--------------+
| store_id | No_of_Visits |
+----------+--------------+
|        1 |            4 |
|        2 |            6 |
+----------+--------------+
2 rows in set (0.00 sec)
```

Alter Operation's: -

1. *A)*

```
mysql> select * from customer1;
+-------------+----------+------------+-----------+--------+
| Customer_ID | Store_ID | First_Name | Last_Name | Amount |
+-------------+----------+------------+-----------+--------+
|          11 |        2 | LISA       | ANDERSON  |   0.00 |
|          12 |        1 | NANCY      | THOMAS    |   0.00 |
|          13 |        2 | KAREN      | JACKSON   |   0.00 |
|          14 |        2 | BETTY      | WHITE     |   0.00 |
|          15 |        1 | HELEN      | HARRIS    |   0.00 |
|          16 |        2 | SANDRA     | MARTIN    |   0.00 |
|          17 |        1 | DONNA      | THOMPSON  |   0.00 |
|          18 |        2 | CAROL      | GARCIA    |   0.00 |
|          19 |        1 | RUTH       | MARTINEZ  |   0.00 |
|          20 |        2 | SHARON     | ROBINSON  |   0.00 |
+-------------+----------+------------+-----------+--------+
10 rows in set (0.00 sec)

mysql> describe customer1;
+-------------+--------------+------+-----+---------+-------+
| Field       | Type         | Null | Key | Default | Extra |
+-------------+--------------+------+-----+---------+-------+
| Customer_ID | int(11)      | YES  |     | NULL    |       |
| Store_ID    | int(11)      | YES  |     | NULL    |       |
| First_Name  | varchar(20)  | YES  |     | NULL    |       |
| Last_Name   | varchar(20)  | YES  |     | NULL    |       |
| Amount      | decimal(8,2) | NO   |     | NULL    |       |
+-------------+--------------+------+-----+---------+-------+
5 rows in set (0.01 sec)
```

B)

```
mysql> insert into customer1 values
    -> (21,2,'Alex', 'Berg', 8500.52);
Query OK, 1 row affected (0.02 sec)

mysql> insert into customer1 values
    -> (22,2,'Grace', 'Robert', 6053.52);
Query OK, 1 row affected (0.03 sec)

mysql> insert into customer1 values
    -> (23,1,'ABC', 'Betty', 7963.52);
Query OK, 1 row affected (0.02 sec)

mysql> insert into customer1 values
    -> (24,2,'DEF', 'XYZ', 8523.6);
Query OK, 1 row affected (0.03 sec)
```

```
mysql> select * from customer1;
+-------------+----------+------------+-----------+---------+
| Customer_ID | Store_ID | First_Name | Last_Name | Amount  |
+-------------+----------+------------+-----------+---------+
|          11 |        2 | LISA       | ANDERSON  |    0.00 |
|          12 |        1 | NANCY      | THOMAS    |    0.00 |
|          13 |        2 | KAREN      | JACKSON   |    0.00 |
|          14 |        2 | BETTY      | WHITE     |    0.00 |
|          15 |        1 | HELEN      | HARRIS    |    0.00 |
|          16 |        2 | SANDRA     | MARTIN    |    0.00 |
|          17 |        1 | DONNA      | THOMPSON  |    0.00 |
|          18 |        2 | CAROL      | GARCIA    |    0.00 |
|          19 |        1 | RUTH       | MARTINEZ  |    0.00 |
|          20 |        2 | SHARON     | ROBINSON  |    0.00 |
|          21 |        2 | Alex       | Berg      | 8500.52 |
|          22 |        2 | Grace      | Robert    | 6053.52 |
|          23 |        1 | ABC        | Betty     | 7963.52 |
|          24 |        2 | DEF        | XYZ       | 8523.60 |
+-------------+----------+------------+-----------+---------+
14 rows in set (0.00 sec)

mysql> describe customer1;
+-------------+--------------+------+-----+---------+-------+
| Field       | Type         | Null | Key | Default | Extra |
+-------------+--------------+------+-----+---------+-------+
| Customer_ID | int(11)      | YES  |     | NULL    |       |
| Store_ID    | int(11)      | YES  |     | NULL    |       |
| First_Name  | varchar(20)  | YES  |     | NULL    |       |
| Last_Name   | varchar(20)  | YES  |     | NULL    |       |
| Amount      | decimal(8,2) | NO   |     | NULL    |       |
+-------------+--------------+------+-----+---------+-------+
5 rows in set (0.01 sec)
```

2

```
mysql> alter table customer1
    -> modify column customer_id int(7);
Query OK, 0 rows affected (0.06 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> describe customer1;
+-------------+--------------+------+-----+---------+-------+
| Field       | Type         | Null | Key | Default | Extra |
+-------------+--------------+------+-----+---------+-------+
| customer_id | int(7)       | YES  |     | NULL    |       |
| Store_ID    | int(11)      | YES  |     | NULL    |       |
| First_Name  | varchar(20)  | YES  |     | NULL    |       |
| Last_Name   | varchar(20)  | YES  |     | NULL    |       |
| Amount      | decimal(8,2) | NO   |     | NULL    |       |
+-------------+--------------+------+-----+---------+-------+
5 rows in set (0.00 sec)
```

3.

```
mysql> alter table customer1
    -> drop amount;
Query OK, 0 rows affected (0.31 sec)
Records: 0  Duplicates: 0  Warnings: 0

mysql> describe customer1;
+-------------+-------------+------+-----+---------+-------+
| Field       | Type        | Null | Key | Default | Extra |
+-------------+-------------+------+-----+---------+-------+
| customer_id | int(7)      | YES  |     | NULL    |       |
| Store_ID    | int(11)     | YES  |     | NULL    |       |
| First_Name  | varchar(20) | YES  |     | NULL    |       |
| Last_Name   | varchar(20) | YES  |     | NULL    |       |
+-------------+-------------+------+-----+---------+-------+
4 rows in set (0.02 sec)
```