



GAMEDNA™

# GOOGLE ANALYTICS

## PLUGIN FOR UE4 SECOND EDITION



# Contents

1. License .....	3
2. Introduction.....	4
3. Getting started .....	5
4. Example project.....	7
5. Recording events in Blueprints .....	8
6. Supported Analytics Provider Nodes .....	11
7. Recording events in C++ .....	12

# 1. License

Copyright © 2017 gameDNA. All rights reserved.

gameDNA grants you a non-exclusive, non-transferable, non-sublicensable license for a single User to use, reproduce, display, perform, and modify the Google Analytics Plugin for Unreal Engine 4 ® for any lawful purpose (the "License"). The License becomes effective on the date you buy Google Analytics Plugin for Unreal Engine 4 ®. The License does not grant you any title or ownership in the Licensed Technology.

You may Distribute the Google Analytics Plugin for Unreal Engine 4 ® incorporated in object code format only as an inseparable part of a Product to end users. The Product may not contain any Plugin Content in uncooked source format.

Unreal ® is a trademark or registered trademark of Epic Games, Inc. in the United States of America and elsewhere. Unreal ® Engine, Copyright 1998 – 2017, Epic Games, Inc. All rights reserved.

Google Analytics is a trademark of Google, Inc.

## 2. Introduction

**Google Analytics Provider** plugin for Unreal Engine 4 ® lets you integrate out-of-the-box Google Analytics into your Unreal Engine project for all platforms. It fully implements Unreal Analytics Provider system so you can use all available features exposed by this (including Analytics Blueprint Library).

Required Unreal Engine 4.10 or above because of Android Plugin support!

**Current plugin version: 2.1.1**

**Support:** [support@gamednastudio.com](mailto:support@gamednastudio.com)

### FEATURES:


- Four special nodes only for Google Analytics Provider plugin: *Record Google Event*, *Record Google Screen*, *Record Google Social Interaction*, *Record Google User Timing*
- Implements Unreal Analytics Provider system
- All features are exposed to Blueprints
- Real-time sessions tracking (you can see who is currently playing your game!)
- Tracking events and screens
- Registering In-App Purchases
- Registering user progression
- Sending info about age, gender, location and interests
- Automatic errors, exceptions and crash reporting
- Automatic system info tracking (e. g. device, operating system, app version)
- Automatic caching events when user is offline and send them to Google Analytics when user is online
- Campaign measurement
- Social interactions
- User timing
- And more features provided by Google Analytics

### WHAT YOU GET:

- Full source code
- Compatible with all UE4 platforms (all-in-one)
- Easy plugin setup
- All future updates
- Support via e-mail ([support@gamednastudio.com](mailto:support@gamednastudio.com))

### 3. Getting started

1. Unpack the plugin archive to *Plugins* folder in your UE4 project folder (for project plugins) or *Engine/Plugins/Marketplace* (for engine plugins) and start the editor.




2. [Only for IOS] Download the official Google Analytics IOS SDK:  
[https://dl.google.com/googleanalyticservices/GoogleAnalyticsServicesiOS\\_3.17.zip](https://dl.google.com/googleanalyticservices/GoogleAnalyticsServicesiOS_3.17.zip)


Unpack the downloaded archive and copy following files to the location `[PLUGIN_FOLDER]/Source/ThirdParty/IOS`:

- `libGoogleAnalyticsServices.a`
- `libAdIdAccess.a`
- `GoogleAnalytics/Library/*` (all files)


Finally, `[PLUGIN_FOLDER]/Source/ThirdParty/IOS` should look like this:



3. Enable *Google Analytics Provider in Edit -> Plugins -> Analytics -> Project -> Google Analytics Provider*.



4. If you want to use Blueprint nodes for *Google Analytics Provider*, go to *Edit -> Plugins -> Built-In -> Analytics* and enable *Analytics Blueprint Library*.



5. Open *Config/DefaultEngine.ini* file and add following lines:

```
[Analytics]
ProviderModuleName=GoogleAnalytics
TrackingIdAndroid=<ENTER YOUR TRACKING ID FOR ANDROID>
TrackingIdIOS=<ENTER YOUR TRACKING ID FOR IOS>
TrackingIdUniversal=<ENTER YOUR TRACKING ID FOR PLATFORMS OTHER THAN
IOS OR ANDROID>

[AnalyticsDevelopment]
ProviderModuleName=GoogleAnalytics
TrackingIdAndroid=<ENTER YOUR TRACKING ID FOR ANDROID>
TrackingIdIOS=<ENTER YOUR TRACKING ID FOR IOS>
TrackingIdUniversal=<ENTER YOUR TRACKING ID FOR PLATFORMS OTHER THAN
IOS OR ANDROID>

[AnalyticsTest]
ProviderModuleName=GoogleAnalytics
TrackingIdAndroid=<ENTER YOUR TRACKING ID FOR ANDROID>
TrackingIdIOS=<ENTER YOUR TRACKING ID FOR IOS>
TrackingIdUniversal=<ENTER YOUR TRACKING ID FOR PLATFORMS OTHER THAN
IOS OR ANDROID>
```


**TIP:** *Google Analytics* account for platforms other than iOS & Android should be set as website.

6. That's all! *Google Analytics Provider* works now! 😊

## 4. Example project

You can download example project at the following address:

<https://gamednastudio.com/plugins/example/TestGoogleAnalytics.zip>



Credentials to Google Analytics Dashboard (<https://analytics.google.com>):


Login: [gameDNAtest@gmail.com](mailto:gameDNAtest@gmail.com)

Password: unrealengine

Please don't change password! ;)

## 5. Recording events in Blueprints

Before recording any events you have to call the *Start Session* function. You should do it before any other Google Analytics function.




This plugin implements four special nodes only for Google Analytics.

- a) **Record Google Event** - events are a useful way to collect data about a user's interaction with interactive components of your game, like button presses or the use of a particular item in a game.




- b) **Record Google Screen** - screens in Google Analytics represent content users are viewing within your game. The equivalent concept in web analytics is a pageview. Measuring screen views allows you to see which content is being viewed most by your users, and how they are navigating between different pieces of content. A screen view consists of a single string field that will be used as the screen name in your Google Analytics reports.






- c) **Record Google Social Interaction** – social interaction measurement allows you to measure a user's interactions with various social network sharing and recommendation widgets embedded in your content.



- d) **Record Google User Timing** – measuring user timings provides a native way to measure a period of time in Google Analytics. This can be useful to measure resource load times, for example.



Google Analytics Provider plugin fully implements Unreal Analytics Provider system so you can use all available features exposed by this (including Analytics Blueprint Library).

You can learn more about Unreal Analytics Provider here:

<https://docs.unrealengine.com/latest/INT/Gameplay/Analytics/index.html>

and about Analytics Blueprint Library here:


<https://docs.unrealengine.com/latest/INT/Gameplay/Analytics/Blueprints/index.html>

## LIMITATIONS:

Google Analytics supports only following attributes for events:

- Event Category (String)
- Event Action (String) – known as Event Name in Unreal Analytics Provider system
- Event Label (String)
- Event Value (Integer)

So if you are using standard Unreal Analytics Provider functions, you can make something like this and that's exactly what special Record Google Event node is.



## 6. Supported Analytics Provider Nodes

### SUPPORTED ANALYTICS PROVIDER NODES

**f Record Google Event**  
▷ ◁  
Event Category   
Event Action   
Event Label   
Event Value

**f Record Google Social Interaction**  
▷ ◁  
Social Network   
Social Action   
Social Target

**f Record Google User Timing**  
▷ ◁  
Timing Category   
Timing Value   
Timing Name

**f Record Google Screen**  
▷ ◁  
Screen Name

### SPECIAL FOR GOOGLE ANALYTICS PLUGIN

**f Start Session**  
▷ ◁  
Return Value

**f Get User Id**  
▷ ◁  
Return Value

**f Set User Id**  
▷ ◁  
User Id

**f Set Age**  
▷ ◁  
Age

**f Set Gender**  
▷ ◁  
Gender

**f Start Session with Attributes**  
▷ ◁  
Attributes  Return Value

**f Make Event Attribute**  
Attribute Name  Return Value   
Attribute Value

**f Set Location**  
▷ ◁  
Location

**f Record Error**  
▷ ◁  
Error

**f Record Currency Given**  
▷ ◁  
Game Currency Type   
Game Currency Amount

**f Record Currency Purchase**  
▷ ◁  
Game Currency Type   
Game Currency Amount   
Real Currency Type   
Real Money Cost   
Payment Provider

**f Record Item Purchase**  
▷ ◁  
Item Id   
Currency   
Per Item Cost   
Item Quantity

**f End Session**  
▷ ◁

**f Record Event**  
▷ ◁  
Event Name

**f Record Progress with Full Hierarchy and Attributes**  
▷ ◁  
Progress Type   
Progress Names   
Attributes

**f Record Simple Item Purchase**  
▷ ◁  
Item Id   
Item Quantity

**f Record Progress**  
▷ ◁  
Progress Type   
Progress Name

**f Record Currency Given with Attributes**  
▷ ◁  
Game Currency Type   
Game Currency Amount   
Attributes

**f Record Progress with Attributes**  
▷ ◁  
Progress Type   
Progress Name   
Attributes

**f Record Simple Currency Purchase**  
▷ ◁  
Game Currency Type   
Game Currency Amount

**f Record Event with Attribute**  
▷ ◁  
Event Name   
Attribute Name   
Attribute Value

**f Record Event with Attributes**  
▷ ◁  
Event Name   
Attributes

## 7. Recording events in C++

You can use Unreal Analytics Provider for C++ or simply call special functions for Google Analytics Provider plugin.

Add the following to your *\*.Build.cs* file private dependency module name:

```
PrivateDependencyModuleNames.AddRange(new string[] { "GoogleAnalytics" });
```

Import these headers anywhere in source code project:

```
#include "GoogleAnalyticsBlueprintLibrary.h"  
#include "Runtime/Analytics/Analytics/Public/Analytics.h"  
#include  
"Runtime/Analytics/Analytics/Public/Interfaces/IAalyticsProvider.h"
```

### a) Start session:

```
FAnalytics::Get().GetDefaultConfiguredProvider()->StartSession();
```

### b) Record Google Event:

```
UGoogleAnalyticsBlueprintLibrary::RecordGoogleEvent(TEXT("Event Category"),  
TEXT("Event Action"), TEXT("Event Label"), <INTEGER VALUE>);
```

### c) Record Google Social Interaction:

```
UGoogleAnalyticsBlueprintLibrary::RecordGoogleSocialInteraction(TEXT("Social  
Network"), TEXT("Social Action"), TEXT("Social Target"));
```

### d) Record Google User Timing:

```
UGoogleAnalyticsBlueprintLibrary::RecordGoogleUserTiming(TEXT("Timing  
Category"), <INTEGER VALUE>, TEXT("Timing Name"));
```

### e) Record Google Screen:

```
UGoogleAnalyticsBlueprintLibrary::RecordGoogleScreen(TEXT("Screen Name"));
```