

09-DaskBag

August 10, 2020

1 Dask bag

Dask proposes "big data" collections with a small set of high-level primitives like `map`, `filter`, `groupby`, and `join`. With these common patterns we can often handle computations that are more complex than `map`, but are still structured.

- Dask-bag excels in processing data that can be represented as a sequence of arbitrary inputs ("messy" data)
- When you encounter a set of data with a format that does not enforce strict structure and datatypes.

Related Documentation

- [Bag Documentation](#)
- [Bag API](#)

```
[1]: data = list(range(1,9))  
data
```

```
[1]: [1, 2, 3, 4, 5, 6, 7, 8]
```

```
[2]: import dask.bag as db  
  
b = db.from_sequence(data)
```

```
[3]: b.compute() # Gather results back to local process
```

```
[3]: [1, 2, 3, 4, 5, 6, 7, 8]
```

```
[4]: b.map(lambda x : x//2).compute() # compute length of each element and collect  
    ↪ results
```

```
[4]: [0, 1, 1, 2, 2, 3, 3, 4]
```

```
[5]: from time import sleep  
  
def slow_half( x):  
    sleep(1)  
    return x // 2
```

```
res = b.map(slow_half)
res
```

```
[5]: dask.bag<slow_half, npartitions=8>
```

```
[6]: %%time
res.compute()
```

```
CPU times: user 16.6 ms, sys: 9.32 ms, total: 25.9 ms
Wall time: 4.39 s
```

```
[6]: [0, 1, 1, 2, 2, 3, 3, 4]
```

```
[7]: res.visualize()
```

```

└─
└─-----
FileNotFoundError                                Traceback (most recent call
└─last)

  /usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
└─backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
    165     try:
--> 166         proc = subprocess.Popen(cmd, startupinfo=get_startupinfo(),
└─**kwargs)
    167     except OSError as e:

  /usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in
└─__init__(self, args, bufsize, executable, stdin, stdout, stderr, preexec_fn,
└─close_fds, shell, cwd, env, universal_newlines, startupinfo, creationflags,
└─restore_signals, start_new_session, pass_fds, encoding, errors, text)
    853
--> 854         self._execute_child(args, executable, preexec_fn,
└─close_fds,
    855                                     pass_fds, cwd, env,

  /usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in
└─_execute_child(self, args, executable, preexec_fn, close_fds, pass_fds, cwd,
└─env, startupinfo, creationflags, shell, p2cread, p2cwrite, c2pread, c2pwrite,
└─errread, errwrite, restore_signals, start_new_session)
   1701                                     err_msg = os.strerror(errno_num)
```

```

-> 1702                                raise child_exception_type(errno_num, err_msg,
↳err_filename)
    1703                                raise child_exception_type(err_msg)

```

FileNotFoundError: [Errno 2] No such file or directory: 'dot'

During handling of the above exception, another exception occurred:

```

ExecutableNotFound                      Traceback (most recent call
↳last)

```

```

<ipython-input-7-2dde28612c67> in <module>
----> 1 res.visualize()

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(self, filename, format, optimize_graph, **kwargs)
    91         https://docs.dask.org/en/latest/optimize.html
    92         """
---> 93         return visualize(
    94             self,
    95             filename=filename,

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(*args, **kwargs)
    551         raise NotImplementedError("Unknown value color=%s" % color)
    552
--> 553         return dot_graph(dsk, filename=filename, **kwargs)
    554
    555

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
↳py in dot_graph(dsk, filename, format, **kwargs)
    270         """
    271         g = to_graphviz(dsk, **kwargs)
--> 272         return graphviz_to_file(g, filename, format)
    273
    274

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
↳py in graphviz_to_file(g, filename, format)

```

```

282         format = "png"
283
--> 284     data = g.pipe(format=format)
285     if not data:
286         raise RuntimeError(

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳files.py in pipe(self, format, renderer, formatter, quiet)
134         data = text_type(self.source).encode(self._encoding)
135
--> 136         out = backend.pipe(self._engine, format, data,
137                             renderer=renderer, formatter=formatter,
138                             quiet=quiet)

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳backend.py in pipe(engine, format, data, renderer, formatter, quiet)
244     """
245     cmd, _ = command(engine, format, None, renderer, formatter)
--> 246     out, _ = run(cmd, input=data, capture_output=True, check=True,
↳quiet=quiet)
247     return out
248

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
167     except OSError as e:
168         if e.errno == errno.ENOENT:
--> 169             raise ExecutableNotFound(cmd)
170         else:
171             raise

ExecutableNotFound: failed to execute ['dot', '-Tpng'], make sure the
↳Graphviz executables are on your systems' PATH

```

```
[8]: b.topk
```

```
[8]: <bound method Bag.topk of dask.bag<from_sequence, npartitions=8>>
```

```
[9]: b.product(b).compute() # Cartesian product of each pair
# of elements in two sequences (or the same sequence in this case)
```

[9] : [(1, 1),
(1, 2),
(1, 3),
(1, 4),
(1, 5),
(1, 6),
(1, 7),
(1, 8),
(2, 1),
(2, 2),
(2, 3),
(2, 4),
(2, 5),
(2, 6),
(2, 7),
(2, 8),
(3, 1),
(3, 2),
(3, 3),
(3, 4),
(3, 5),
(3, 6),
(3, 7),
(3, 8),
(4, 1),
(4, 2),
(4, 3),
(4, 4),
(4, 5),
(4, 6),
(4, 7),
(4, 8),
(5, 1),
(5, 2),
(5, 3),
(5, 4),
(5, 5),
(5, 6),
(5, 7),
(5, 8),
(6, 1),
(6, 2),
(6, 3),
(6, 4),
(6, 5),
(6, 6),
(6, 7),

```
(6, 8),
(7, 1),
(7, 2),
(7, 3),
(7, 4),
(7, 5),
(7, 6),
(7, 7),
(7, 8),
(8, 1),
(8, 2),
(8, 3),
(8, 4),
(8, 5),
(8, 6),
(8, 7),
(8, 8)]
```

Chain operations to construct more complex computations

```
[10]: (b.filter(lambda x: x % 2 > 0)
      .product(b)
      .filter(lambda v : v[0] % v[1] == 0 and v[0] != v[1])
      .compute())
```

```
[10]: [(3, 1), (5, 1), (7, 1)]
```

```
[ ]:
```

1.1 Daily stock example

Let's use the bag interface to read the json files containing time series.

Each line is a JSON encoded dictionary with the following keys - timestamp: Day. - close: Stock value at the end of the day. - high: Highest value. - low: Lowest value. - open: Opening price.

```
[11]: # preparing data
import os # library to get directory and file paths
import tarfile # this module makes possible to read and write tar archives

def extract_data(name, where):
    datadir = os.path.join(where,name)
    if not os.path.exists(datadir):
        print("Extracting data...")
        tar_path = os.path.join(where, name+'.tgz')
        with tarfile.open(tar_path, mode='r:gz') as data:
            data.extractall(where)
```

```
extract_data('daily-stock','data') # this function call will extract json files
```

Extracting data...

```
[12]: %ls data/daily-stock/*.json
```

```
data/daily-stock/aet.json  data/daily-stock/hpq.json
data/daily-stock/afl.json  data/daily-stock/ibm.json
data/daily-stock/aig.json  data/daily-stock/jbl.json
data/daily-stock/al.json   data/daily-stock/jpm.json
data/daily-stock/amgn.json data/daily-stock/luv.json
data/daily-stock/avy.json  data/daily-stock/met.json
data/daily-stock/b.json    data/daily-stock/pcg.json
data/daily-stock/bwa.json  data/daily-stock/tgt.json
data/daily-stock/ge.json   data/daily-stock/usb.json
data/daily-stock/hal.json  data/daily-stock/xom.json
data/daily-stock/hp.json
```

```
[13]: import dask.bag as db
import json
stocks = db.read_text('data/daily-stock/*.json')
```

```
[14]: stocks.npartitions
```

```
[14]: 22
```

```
[15]: stocks.visualize()
```

```
↳ -----
FileNotFoundError                                Traceback (most recent call↳
↳last)

  /usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
    165     try:
--> 166         proc = subprocess.Popen(cmd, startupinfo=get_startupinfo(),↳
↳**kwargs)
    167     except OSError as e:

  /usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in↳
↳__init__(self, args, bufsize, executable, stdin, stdout, stderr, preexec_fn,↳
↳close_fds, shell, cwd, env, universal_newlines, startupinfo, creationflags,↳
↳restore_signals, start_new_session, pass_fds, encoding, errors, text)
```

```

853
--> 854             self._execute_child(args, executable, preexec_fn,
↳close_fds,
855                                     pass_fds, cwd, env,

/usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in
↳_execute_child(self, args, executable, preexec_fn, close_fds, pass_fds, cwd,
↳env, startupinfo, creationflags, shell, p2cread, p2cwrite, c2pread, c2pwrite,
↳errread, errwrite, restore_signals, start_new_session)
1701                 err_msg = os.strerror(errno_num)
-> 1702                 raise child_exception_type(errno_num, err_msg,
↳err_filename)
1703                 raise child_exception_type(err_msg)

```

FileNotFoundError: [Errno 2] No such file or directory: 'dot'

During handling of the above exception, another exception occurred:

```

ExecutableNotFound                                Traceback (most recent call
↳last)

<ipython-input-15-a27501b2e8e0> in <module>
----> 1 stocks.visualize()

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(self, filename, format, optimize_graph, **kwargs)
91         https://docs.dask.org/en/latest/optimize.html
92         """
---> 93         return visualize(
94             self,
95             filename=filename,

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(*args, **kwargs)
551         raise NotImplementedError("Unknown value color='%s' % color)
552
--> 553         return dot_graph(dsk, filename=filename, **kwargs)
554
555

```



```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
py in dot_graph(dsk, filename, format, **kwargs)
270     """
271     g = to_graphviz(dsk, **kwargs)
--> 272     return graphviz_to_file(g, filename, format)
273
274

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
py in graphviz_to_file(g, filename, format)
282     format = "png"
283
--> 284     data = g.pipe(format=format)
285     if not data:
286         raise RuntimeError(

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
files.py in pipe(self, format, renderer, formatter, quiet)
134     data = text_type(self.source).encode(self._encoding)
135
--> 136     out = backend.pipe(self._engine, format, data,
137                        renderer=renderer, formatter=formatter,
138                        quiet=quiet)

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
backend.py in pipe(engine, format, data, renderer, formatter, quiet)
244     """
245     cmd, _ = command(engine, format, None, renderer, formatter)
--> 246     out, _ = run(cmd, input=data, capture_output=True, check=True,
quiet=quiet)
247     return out
248

```

```

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
167     except OSError as e:
168         if e.errno == errno.ENOENT:
--> 169             raise ExecutableNotFound(cmd)
170         else:
171             raise

```

ExecutableNotFound: failed to execute ['dot', '-Tpng'], make sure the
↳ Graphviz executables are on your systems' PATH

```
[16]: import json
js = stocks.map(json.loads)
```

```
[17]: import os, sys
from glob import glob
import pandas as pd
import json

here = os.getcwd() # get the current directory
filenames = sorted(glob(os.path.join(here, 'data', 'daily-stock', '*.json')))
filenames
```

```
[17]: ['/home/runner/work/big-data/big-data/notebooks/data/daily-stock/aet.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/afl.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/aig.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/al.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/amgn.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/avy.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/b.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/bwa.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/ge.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hal.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hp.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hpq.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/ibm.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/jbl.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/jpm.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/luv.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/met.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/pcg.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/tgt.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/usb.json',
'/home/runner/work/big-data/big-data/notebooks/data/daily-stock/xom.json']
```

```
[18]: %rm data/daily-stock/*.h5
```

rm: cannot remove 'data/daily-stock/*.h5': No such file or directory

```
[19]: from tqdm.notebook import tqdm
for fn in tqdm(filenames):
    with open(fn) as f:
        data = [json.loads(line) for line in f]
```

```
df = pd.DataFrame(data)

out_filename = fn[:-5] + '.h5'
df.to_hdf(out_filename, '/data')
```

```
HBox(children=(FloatProgress(value=0.0, max=21.0), HTML(value='')))
```

```
[20]: filenames = sorted(glob(os.path.join(here, 'data', 'daily-stock', '*.h5')))
      filenames
```

```
[20]: ['/home/runner/work/big-data/big-data/notebooks/data/daily-stock/aet.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/afl.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/aig.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/al.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/amgn.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/avy.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/b.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/bwa.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/ge.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hal.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hp.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/hpq.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/ibm.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/jbl.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/jpm.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/luv.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/met.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/pcg.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/tgt.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/usb.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/xom.h5']
```

1.1.1 Serial version

```
[21]: %%time
      series = {}
      for fn in filenames:    # Simple map over filenames
          series[fn] = pd.read_hdf(fn)['close']

      results = {}

      for a in filenames:     # Doubly nested loop over the same collection
          for b in filenames:
              if a != b:      # Filter out bad elements
```

```

        results[a, b] = series[a].corr(series[b]) # Apply function

((a, b), corr) = max(results.items(), key=lambda kv: kv[1]) # Reduction

```

CPU times: user 997 ms, sys: 42.6 ms, total: 1.04 s
 Wall time: 1.04 s

```
[22]: a, b, corr
```

```
[22]: ('/home/runner/work/big-data/big-data/notebooks/data/daily-stock/aet.h5',
      '/home/runner/work/big-data/big-data/notebooks/data/daily-stock/luv.h5',
      0.9413176064560881)
```

1.2 Dask.bag methods

We can construct most of the above computation with the following dask.bag methods:

- `collection.map(function)`: apply function to each element in collection
- `collection.product(collection)`: Create new collection with every pair of inputs
- `collection.filter(predicate)`: Keep only elements of collection that match the predicate function
- `collection.max()`: Compute maximum element

```
[23]: %%time

import dask.bag as db

b = db.from_sequence(filenamees)
series = b.map(lambda fn: pd.read_hdf(fn)['close'])

corr = (series.product(series)
        .filter(lambda ab: not (ab[0] == ab[1]).all())
        .map(lambda ab: ab[0].corr(ab[1])).max())

```

CPU times: user 6.17 ms, sys: 0 ns, total: 6.17 ms
 Wall time: 5.84 ms

```
[24]: %%time

result = corr.compute()

```

CPU times: user 1.96 s, sys: 697 ms, total: 2.65 s
 Wall time: 4.68 s

```
[25]: result
```

```
[25]: 0.9413176064560881
```

1.2.1 Wordcount with Dask bag

```
[26]: import lorem
```

```
lorem.text()
```

```
[26]: 'Dolorem aliquam tempora adipisci sit. Quisquam sed non etincidunt. Quiquia voluptatem labore consectetur. Amet magnam ipsum ipsum ut. Tempora etincidunt dolorem sed. Porro numquam neque dolor labore. Quaerat dolor velit dolor non amet.\n\nAliquam aliquam labore tempora porro aliquam ut. Dolor non amet voluptatem. Neque tempora neque quaerat ut ut. Aliquam quiquia etincidunt etincidunt ipsum ipsum modi ipsum. Dolor dolor dolore aliquam etincidunt porro consectetur tempora. Modi dolor adipisci aliquam tempora quisquam. Est est numquam etincidunt adipisci.\n\nMagnam velit sit aliquam magnam aliquam aliquam. Ipsum porro velit amet ut non numquam dolor. Modi numquam aliquam etincidunt porro ut quaerat consectetur. Ut aliquam consectetur ipsum dolore etincidunt amet eius. Numquam est tempora dolor non. Magnam labore tempora voluptatem voluptatem quaerat velit quiquia. Ut etincidunt dolore velit porro tempora.\n\nConsectetur porro dolore consectetur. Est velit velit dolorem quisquam dolor. Quisquam neque porro dolor. Dolorem etincidunt ut dolorem velit magnam quaerat etincidunt. Velit consectetur quiquia modi dolorem neque. Amet ut velit quiquia magnam consectetur. Magnam quaerat eius tempora non eius. Etincidunt dolorem neque porro. Neque neque quiquia dolorem eius voluptatem magnam. Magnam etincidunt labore voluptatem quisquam.'
```

```
[27]: import lorem
```

```
for i in range(20):  
    with open(f"sample-{i:02d}.txt", "w") as f:  
        f.write(lorem.text())
```

```
[28]: %ls *.txt
```

```
sample00.txt  sample04.txt  sample08.txt  sample12.txt  sample16.txt  
sample01.txt  sample05.txt  sample09.txt  sample13.txt  sample17.txt  
sample02.txt  sample06.txt  sample10.txt  sample14.txt  sample18.txt  
sample03.txt  sample07.txt  sample11.txt  sample15.txt  sample19.txt
```

```
[29]: import glob
```

```
glob.glob('sample*.txt')
```

```
[29]: ['sample13.txt',  
      'sample01.txt',  
      'sample14.txt',  
      'sample00.txt',  
      'sample17.txt',  
      'sample19.txt',
```

```
'sample07.txt',
'sample09.txt',
'sample08.txt',
'sample16.txt',
'sample02.txt',
'sample04.txt',
'sample11.txt',
'sample10.txt',
'sample05.txt',
'sample06.txt',
'sample18.txt',
'sample03.txt',
'sample15.txt',
'sample12.txt']
```

```
[30]: import dask.bag as db
import glob
b = db.read_text(glob.glob('sample*.txt'))

wordcount = (b.str.replace(".", "") # remove dots
             .str.lower()           # lower text
             .str.strip()           # remove \n and trailing spaces
             .str.split()           # split into words
             .flatten()             # chain all words lists
             .frequencies()         # compute occurrences
             .topk(10, lambda x: x[1])) # sort and return top 10 words

wordcount.compute() # Run all tasks and return result
```

```
[30]: [('est', 185),
       ('magnam', 168),
       ('velit', 166),
       ('ipsum', 164),
       ('ut', 161),
       ('voluptatem', 157),
       ('amet', 156),
       ('sit', 155),
       ('eius', 153),
       ('quisquam', 151)]
```

1.3 Genome example

We will use a Dask bag to calculate the frequencies of sequences of five bases, and then sort the sequences into descending order ranked by their frequency.

- First we will define some functions to split the bases into sequences of a certain size

1.3.1 Exercise 9.1

- Implement a function `group_characters(line, n=5)` to group `n` characters together and return a iterator. `line` is a text line in `genome.txt` file.

```
>>> line = "abcdefghijklmno"
>>> for seq in group_character(line, 5):
    print(seq)
```

```
"abcde"
"efghi"
"klmno"
```

- Implement `group_and_split(line)`

```
>>> group_and_split('abcdefghijklmno')
['abcde', 'fghij', 'klmno']
```

- Use the `dask bag` to compute the frequencies of sequences of five bases.

```
[31]: from string import ascii_lowercase as alphabet
alphabet
```

```
[31]: 'abcdefghijklmnopqrstuvwxyz'
```

```
[32]: def reverse(text):
    k = len(text)
    while k > 0:
        k = k-1
        yield text[k]

reverse_alphabet = reverse(alphabet)
print(*reverse_alphabet)
```

```
z y x w v u t s r q p o n m l k j i h g f e d c b a
```

```
[33]: class Reverse:

    def __init__(self, data):
        self.data = data
        self.index = len(data)

    def __iter__(self):
        return self

    def __next__(self):
        self.index = self.index-1
        if self.index < 0:
            raise StopIteration
        else:
```

```
return self.data[self.index]
```

```
[34]: class Fibonacci:

    def __init__(self, n):
        self.n = n
        self.f0 = 0
        self.f1 = 1

    def __iter__(self):
        return self

    def __next__(self):
        self.n = self.n - 1
        if self.n < 0:
            raise StopIteration
        else:
            self.f0, self.f1 = self.f1, self.f0 + self.f1
        return self.f1

print(*Fibonacci(7))
```

1 2 3 5 8 13 21

```
[35]: for c in Reverse(alphabet):
        print(c, end="")
```

zyxwvutsrqponmlkjihgfedcba

```
[36]: for c in reverse(alphabet):
        print(c, end="")
```

zyxwvutsrqponmlkjihgfedcba

```
[37]: def group_character( line, n=5):
        bases = ''
        for i, b in enumerate(line):
            bases += b
            if (i+1) % n == 0:
                yield bases
            bases = ''
```

```
[38]: line = "abcdefghijklmno"
        for seq in group_character(line, 5):
            print(seq)
```

abcde


```
fghij  
klmno
```

```
[39]: def group_and_split( line, n):  
       return [seq for seq in group_character(line,n)]
```

```
[40]: %ls data
```

```
daily-stock/      genome04.txt  
monthly.land.90S.90N.df_1901-2000mean.dat.txt  
daily-stock.tgz  genome05.txt      nucleotide-sample.txt  
genome.txt       genome06.txt      nycflights.tar.gz  
genome00.txt     genome07.txt      people.json  
genome01.txt     irmar.csv         philadelphia-crime-data-2015-ytd.csv  
genome02.txt     irmar.json  
genome03.txt     latinbooks.tgz
```

```
[41]: import os  
      from glob import glob  
  
      data_path = os.path.join("data")  
      with open(os.path.join(data_path,"genome.txt")) as g:  
          data = g.read()  
          for i in range(8):  
              file = os.path.join(data_path,f"genome{i:02d}.txt")  
              with open(file,"w") as f:  
                  f.write(data)  
  
      glob("data/genome0*.txt")
```

```
[41]: ['data/genome00.txt',  
      'data/genome01.txt',  
      'data/genome07.txt',  
      'data/genome06.txt',  
      'data/genome02.txt',  
      'data/genome05.txt',  
      'data/genome03.txt',  
      'data/genome04.txt']
```

```
[42]: from operator import itemgetter  
  
      import dask.bag as db  
  
      b = db.read_text("data/genome0*.txt")  
  
      result = (b.filter(lambda line: not line.startswith(">"))  
                .map(lambda line: line.strip()))
```

```
.map(lambda line : group_and_split(line,5))
.flatten()
.frequencies()
.topk(10,lambda v : v[1]))
```

```
[43]: result.visualize()
```

```

      □
↳ -----

FileNotFoundError                                Traceback (most recent call↳
↳ last)

  /usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳ backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
      165     try:
--> 166         proc = subprocess.Popen(cmd, startupinfo=get_startupinfo(),↳
↳ **kwargs)
      167     except OSError as e:

  /usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in↳
↳ __init__(self, args, bufsize, executable, stdin, stdout, stderr, preexec_fn,↳
↳ close_fds, shell, cwd, env, universal_newlines, startupinfo, creationflags,↳
↳ restore_signals, start_new_session, pass_fds, encoding, errors, text)
      853
--> 854         self._execute_child(args, executable, preexec_fn,↳
↳ close_fds,
      855                                pass_fds, cwd, env,

  /usr/share/miniconda3/envs/big-data/lib/python3.8/subprocess.py in↳
↳ _execute_child(self, args, executable, preexec_fn, close_fds, pass_fds, cwd,↳
↳ env, startupinfo, creationflags, shell, p2cread, p2cwrite, c2pread, c2pwrite,↳
↳ errread, errwrite, restore_signals, start_new_session)
      1701             err_msg = os.strerror(errno_num)
-> 1702             raise child_exception_type(errno_num, err_msg,↳
↳ err_filename)
      1703             raise child_exception_type(err_msg)

FileNotFoundError: [Errno 2] No such file or directory: 'dot'
```

During handling of the above exception, another exception occurred:

```

ExecutableNotFound                                Traceback (most recent call
↳last)

<ipython-input-43-dc769738af30> in <module>
----> 1 result.visualize()

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(self, filename, format, optimize_graph, **kwargs)
    91         https://docs.dask.org/en/latest/optimize.html
    92         """
--> 93         return visualize(
    94             self,
    95             filename=filename,

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/
↳base.py in visualize(*args, **kwargs)
    551         raise NotImplementedError("Unknown value color=%s" % color)
    552
--> 553         return dot_graph(dsk, filename=filename, **kwargs)
    554
    555

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
↳py in dot_graph(dsk, filename, format, **kwargs)
    270         """
    271         g = to_graphviz(dsk, **kwargs)
--> 272         return graphviz_to_file(g, filename, format)
    273
    274

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/dask/dot.
↳py in graphviz_to_file(g, filename, format)
    282         format = "png"
    283
--> 284         data = g.pipe(format=format)
    285         if not data:
    286             raise RuntimeError(

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳files.py in pipe(self, format, renderer, formatter, quiet)
    134         data = text_type(self.source).encode(self._encoding)

```

```

135
--> 136         out = backend.pipe(self._engine, format, data,
137                                renderer=renderer, formatter=formatter,
138                                quiet=quiet)

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳ backend.py in pipe(engine, format, data, renderer, formatter, quiet)
244         """
245         cmd, _ = command(engine, format, None, renderer, formatter)
--> 246         out, _ = run(cmd, input=data, capture_output=True, check=True,
↳ quiet=quiet)
247         return out
248

/usr/share/miniconda3/envs/big-data/lib/python3.8/site-packages/graphviz/
↳ backend.py in run(cmd, input, capture_output, check, encoding, quiet, **kwargs)
167     except OSError as e:
168         if e.errno == errno.ENOENT:
--> 169             raise ExecutableNotFound(cmd)
170         else:
171             raise

ExecutableNotFound: failed to execute ['dot', '-Tpng'], make sure the
↳ Graphviz executables are on your systems' PATH

```

```
[44]: result.compute()
```

```
[44]: [('CTGTG', 472),
      ('CCCAG', 440),
      ('CCTGG', 416),
      ('AAAAA', 392),
      ('TGCTG', 336),
      ('TGTGT', 328),
      ('CCACC', 312),
      ('GGCTG', 304),
      ('CACCA', 296),
      ('GGTGG', 296)]
```

1.3.2 Exercise 9.2

The [FASTA](#) file format is used to write several genome sequences.

- Create a function that can read a [FASTA file](#) and compute the frequencies for $n = 5$ of a

given sequence.

1.3.3 Exercise 9.3

Write a program that uses the function implemented above to read several FASTA files stored in a Dask bag.

2 Some remarks about bag

- Higher level dask collections include functions for common patterns
- Move data to collection, construct lazy computation, trigger at the end
- Use `Dask.bag (product + map)` to handle nested for loop

Bags have the following known limitations

1. Bag operations tend to be slower than array/dataframe computations in the same way that Python tends to be slower than NumPy/Pandas
2. `Bag.groupby` is slow. You should try to use `Bag.foldby` if possible.
3. Check the [API](#)
4. `dask.dataframe` can be faster than `dask.bag`. But sometimes it is easier to load and clean messy data with a bag. We will see later how to transform a bag into a `dask.dataframe` with the [to_dataframe](#) method.