

macOS Tier 1 Troubleshooting Guide

Overview

This guide covers common macOS troubleshooting procedures performed by Help Desk and Desktop Support technicians. It demonstrates practical knowledge of incident resolution, user support, and system administration in enterprise environments.

Tier 1 Troubleshooting

1. Verify Basic Information


- Confirm the user's issue and gather symptoms.
- Identify affected applications, devices, and users.
- Determine when the issue started.
- Check for recent changes or updates.

2. Network Connectivity Issues

Verify Connection

ping google.com

In macOS Terminal, ping google.com is commonly used as a basic test of internet connectivity and network functionality. IT professionals frequently use this command because Google's infrastructure is highly reliable and globally accessible. If the ping request fails, it often indicates an issue with the local device, network configuration, or internet connection rather than a problem with Google's servers.



```
macbookair@Austins-MacBook-Air ~ % ping google.com
PING google.com (172.253.135.100): 56 data bytes
64 bytes from 172.253.135.100: icmp_seq=0 ttl=105 time=27.936 ms
64 bytes from 172.253.135.100: icmp_seq=1 ttl=105 time=29.484 ms
64 bytes from 172.253.135.100: icmp_seq=2 ttl=105 time=27.963 ms
64 bytes from 172.253.135.100: icmp_seq=3 ttl=105 time=28.859 ms
64 bytes from 172.253.135.100: icmp_seq=4 ttl=105 time=29.666 ms
64 bytes from 172.253.135.100: icmp_seq=5 ttl=105 time=28.159 ms
64 bytes from 172.253.135.100: icmp_seq=6 ttl=105 time=28.607 ms
^C
--- google.com ping statistics ---
7 packets transmitted, 7 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 27.936/28.668/29.666/0.654 ms
macbookair@Austins-MacBook-Air ~ %
```

Check IP Address

Ifconfig

In macOS Terminal, the ifconfig command-line tool is used as a key network diagnostic utility to view, inspect, and troubleshoot active network interfaces and system connectivity.




```
[macbookair@Austins-MacBook-Air ~]$ ifconfig
lo0: flags=8049<UP,LOOPBACK,RUNNING,MULTICAST> mtu 16384
    options=1283<RXCSUM, TXCSUM, TXSTATUS, SW_TIMESTAMP>
    inet 127.0.0.1 netmask 0xff000000
    inet6 ::1 prefixlen 128
    nd6 options=201<PERFORMNUD,DAD>
gif0: flags=8010<POINTOPOINT,MULTICAST> mtu 1280
stf0: flags=0<> mtu 1280
en0: flags=8863<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    options=400<CHANNEL_IO>
    ether c8:69:cd:be:62:92
    inet6 fe80::18dd:dda0:70e4:1ee0:0 prefixlen 64 secured scopeid 0x4
    inet6 2400::1700:14b0:b480:86b:faa1:c396:61d1 prefixlen 64 autoconf secured
    inet6 2400::1700:14b0:b480:a4a3:d566:9ea4:c35a prefixlen 64 autoconf temporary
    inet 192.168.1.67 netmask 0xfffff000 broadcast 192.168.1.255
    inet6 2400::1700:14b0:b480::2b prefixlen 64 dynamic
    nd6 options=201<PERFORMNUD,DAD>
    media: autoselect
    status: active
en1: flags=8963<UP,BROADCAST,SMART,RUNNING,PROMISC,SIMPLEX,MULTICAST> mtu 1500
    options=460<TSO4,TSO6,CHANNEL_IO>
    ether 82:1b:17:4b:49:80
    media: autoselect <full-duplex>
    status: inactive
bridge0: flags=8822<BROADCAST,SMART,SIMPLEX,MULTICAST> mtu 1500
    options=43<RXCSUM, TXCSUM, TSO4, TSO6>
    ether 82:1b:17:4b:49:80
    Configuration:
        id 0:0:0:0:0:0 priority 0 hellotime 0 fwddelay 0
        maxage 0 holdcnt 0 proto stp maxaddr 100 timeout 1200
        root id 0:0:0:0:0:0 priority 0 ifcost 0 port 0
        ipfilter disabled flags 0x0
        member: en1 flags=3<LEARNING,DISCOVER>
            ifmaxaddr 0 port 5 priority 0 path cost 0
    media: <unknown type>
    status: inactive
p2p0: flags=8843<UP,BROADCAST,RUNNING,SIMPLEX,MULTICAST> mtu 2304
    options=400<CHANNEL_IO>
    ether 0a:69:cd:be:62:92
    media: autoselect
    status: inactive
awdl0: flags=8943<UP,BROADCAST,RUNNING,PROMISC,SIMPLEX,MULTICAST> mtu 1484
    options=400<CHANNEL_IO>
    ether 76:97:f2:28:89:31
    inet6 fe80::7497:f2ff:fe28:8931:awdl0 prefixlen 64 scopeid 0x8
    nd6 options=201<PERFORMNUD,DAD>
    media: autoselect
    status: active
llw0: flags=8863<UP,BROADCAST,SMART,RUNNING,SIMPLEX,MULTICAST> mtu 1500
    options=400<CHANNEL_IO>
    ether 76:97:f2:28:89:31
    inet6 fe80::7497:f2ff:fe28:8931:llw0 prefixlen 64 scopeid 0x9
    nd6 options=201<PERFORMNUD,DAD>
    media: autoselect
    status: active
utun0: flags=8051<UP,POINTOPOINT,RUNNING,MULTICAST> mtu 1300
    inet6 fe80::7df:4613:c901:7f53:utun0 prefixlen 64 scopeid 0xa
    nd6 options=201<PERFORMNUD,DAD>
utun1: flags=8051<UP,POINTOPOINT,RUNNING,MULTICAST> mtu 2000
    inet6 fe80::7756:cfb8:85bb:d81b:utun1 prefixlen 64 scopeid 0xb
    nd6 options=201<PERFORMNUD,DAD>
utun2: flags=8051<UP,POINTOPOINT,RUNNING,MULTICAST> mtu 1000
    inet6 fe80::ce81:b1c:bd2c:69e:utun2 prefixlen 64 scopeid 0xc
```

Renew DHCP Lease

1. System Settings
2. Network
3. Select Network Adapter
4. TCP/IP

5. Renew DHCP Lease



Flush DNS Cache

```
sudo dscacheutil -flushcache  
sudo killall -HUP mDNSResponder
```

3. Printer Troubleshooting



Check Printer Status

1. System Settings
2. Printers & Scanners

Remove and Re-Add Printer

1. Delete existing printer

2. Add printer again
3. Test print



Sat May 30 4:45 PM

Add Printer

Address: 0.0.0.0
Valid and complete host name or address.

Protocol: Line Printer Daemon - LPD

Queue:
Leave blank for default queue.

Name: 0.0.0.0

Location:

Use: Generic PostScript Printer
The selected printer software isn't from the manufacturer and may not let you use all the features of your printer.

?

Add

Sat May 30 4:45 PM

Add Printer

Address: 0.0.0.0
Valid and complete host name or address.

Protocol: Line Printer Daemon - LPD

Queue:
Leave blank for default queue.

Name: 0.0.0.0

Location:

Use: Generic PostScript Printer
The selected printer software isn't from the manufacturer and may not let you use all the features of your printer.

?


Add



Unable to communicate with the printer at this time.

Unable to connect to '0.0.0.0' due to an error. Would you still like to create the printer?

Cancel Continue



Reset Printing System

1. Open Printers & Scanners
2. Right-click printer list
3. Select "Reset Printing System"

4. Application Issues


Force Quit Application

Command + Option + Esc

Monitor Resource Usage

Activity Monitor

The Activity Monitor is macOS's built-in task management tool. It is a valuable resource for diagnosing performance issues, identifying applications that consume excessive battery power, and handling unresponsive programs, while providing detailed insight into how system resources are being used.



Restart Application

- Force quit application
 - Reopen application
 - Verify functionality
-

5. Password and Account Issues

Reset Password

System Settings > Users & Groups

Verify Account Lockout

- Confirm login attempts
 - Check directory service status
 - Unlock account if applicable
-

6. Software Installation Verification

Check Installed Applications

Applications Folder

Verify Version

About This Mac

Confirm Licensing

- Verify assigned license
 - Ensure application activation
-

Troubleshooting Methodology

1. Identify the problem.
 2. Establish a theory of probable cause.
 3. Test the theory.
 4. Establish a plan of action.
 5. Implement the solution.
 6. Verify full system functionality.
 7. Document findings and resolution.
-

Skills Demonstrated

- macOS Administration
- End User Support
- Network Troubleshooting
- Printer Support
- User Account Management
- Terminal Operations
- Log Analysis
- Incident Documentation
- Tier 1 Help Desk Support