

POLITECNICO
MILANO 1863

Best Bike Paths – RASD Document

RASD document for the
Software Engineering 2 course assignment

Authors: **Alessandro Burato, Gabriele Crimella, Davide Faccini**

Teacher: Elisabetta Di Nitto
Academic Year: 2025-26

Contents

Contents **i**

1 Introduction **1**
1.1 Purpose . . . 1
1.1.1 Goals . . . 1
1.2 Scope . . . 2
1.2.1 World Phenomena . . . 2
1.2.2 Machine Phenomena . . . 3
1.2.3 Shared Phenomena . . . 3
1.3 Definitions, Acronyms, Abbreviations . . . 4
1.4 Reference Documents . . . 4
1.5 Document Structure . . . 4

2 Overall Description **5**

3 Specific Requirements **7**
3.1 Functional Requirements . . . 7
3.1.1 Requirements . . . 7
3.1.2 Use Cases Diagrams . . . 9
3.1.3 Use Cases . . . 10

4 Formal Analysis Using Alloy **29**
4.1 Signatures . . . 29
4.1.1 Status . . . 29
4.1.2 Segment . . . 29
4.1.3 Path . . . 30
4.1.4 Statistics . . . 30
4.1.5 Trip . . . 30
4.1.6 RegisteredUser . . . 31

5 Effort Spent **33**

6 References **35**

List of Figures **37**

List of Tables **39**

1 Introduction

1.1. Purpose

The primary purpose of this project, initiated by a leading Bike Association, is to develop and deploy an advanced support system for the cycling community designed to thrive within a transport landscape dominated by cars.

The core idea is to foster a collaborative digital environment where cyclists can actively record, consult, and publish both their own and other users' riding paths.

This platform will serve as the definitive centralized resource for finding highly recommended routes tailored precisely to the user's specific experience, preferences, and safety considerations.

Ultimately, the system aims to significantly enhance the quality of the cycling experience by providing verified, community-rated routes, thereby connecting riders and making high-quality path discovery universally accessible

1.1.1. Goals

Here are the goals that BBP has to fulfill. BBP has to:

Goal	Description
G1	Recognize suitable bike paths
G2	Allow the user to browse different bike paths
G3	Allow the user to see bike paths statistics
G4	Allow the user to search for paths between two locations
G5	Allow the user to see paths optimality based on other registered users' reviews
G6	Allow user to see weather information when available
G7	Allow users to register to the application using credentials
G8	Allow registered user to review published bike paths
G9	Allow registered user to confirm or reject false positives in track recording
G10	Allow registered user to let the system automatically record suitable bike paths
G11	Allow registered user to manually create suitable bike paths
G12	Allow registered user to publish bike paths
G13	Allow the store of bike paths data for registered users
G14	Allow registered user to add publishable information about bike paths

Table 1.1: List of Goals

1.2. Scope

1.2.1. World Phenomena

WP	Description
WP1	A user physically moves through space using a bicycle
WP2	The physical conditions of a bike path or street change (e.g., presence of potholes, road maintenance status, or obstacles)
WP3	The meteorological conditions in the geographic area vary (e.g., temperature, wind speed)
WP4	A user intends to reach a specific destination starting from a specific origin point

Table 1.2: World Phenomena

1.2.2. Machine Phenomena

MP	Description
MP1	The system guesses that the user is biking by analyzing the detected speed
MP2	The system computes statistics related to a trip (e.g., total distance covered, average speed, performance metrics)
MP3	The system identifies potential anomalies (e.g., potholes) by processing raw data from the device sensors (accelerometer and gyroscope)
MP4	The system computes the score of a path based on its status and its effectiveness in reaching the destination
MP5	The system merges path information incoming from multiple users, evaluating data freshness and the number of confirmations received
MP6	The system stores trip history and path information in the database for future retrieval

Table 1.3: Machine Phenomena

1.2.3. Shared Phenomena

World-Controlled Phenomena

SP_WC	Description
SP_WC1	The user sends a command to start or stop recording a trip
SP_WC2	The mobile device sensors (GPS, accelerometer, gyroscope) transmit position and movement data to the system
SP_WC3	The user manually inserts data regarding a street (e.g., street name, status)
SP_WC4	The user confirms or corrects information automatically detected by the system (e.g., confirming a pothole)
SP_WC5	The user inputs search parameters for a path (origin and destination)
SP_WC6	The external weather service transmits current condition data (e.g., temperature, wind) to the system

Table 1.4: Shared Phenomena – World-Controlled

Machine-Controlled Phenomena

SP_MC	Description
SP_MC1	The system visualizes available bike paths between two points on a map, highlighting those with better scores
SP_MC2	The system displays trip statistics to the user (speed, distance, etc.)
SP_MC3	The system presents a confirmation request to the user regarding automatically detected information

Table 1.5: Shared Phenomena – Machine-Controlled

1.3. Definitions, Acronyms, Abbreviations

- BBP: Bike Buddy Project
- RASD: Requirements Analysis and Specification Document
- WP: World Phenomenon
- MP: Machine Phenomenon
- SP_WC: Shared Phenomenon - World Controlled
- SP_MC: Shared Phenomenon - Machine Controlled

1.4. Reference Documents

- Specification document assignment
- IEEE standard documentation for RASD
- Materials for the Software Engineering 2 course made available on WeBeep

1.5. Document Structure

2 | Overall Description

Chapter 2

3 Specific Requirements

3.1. Functional Requirements

3.1.1. Requirements

ID	Description
R1	The system shall allow new users to register an account
R2	The system shall allow user not registered to access without an account if they don't want to register
R3	The system shall allow registered users to log in to the application
R4	The system shall allow registered users to view and update their personal profile information
R5	The system shall allow users to log out of their current session
R6	The system shall allow registered users to record their cycling trips
R7	The system shall store recorded trips to maintain a history of the user's cycling activities
R8	The system shall compute and display total distance covered for each trip
R9	The system shall compute and display average speed for each trip
R10	The system shall compute and display total time spent speed for each trip
R11	The system shall compute and display elevation gain for each trip
R12	The system shall compute and display calories spent for each trip
R13	The system shall compute and display additional performance metrics for the trips
R14	The system shall retrieve meteorological data (weather conditions, temperature, wind speed) from an external service and enrich the trip data when available
R15	The system shall allow registered users to insert information about bike paths
R16	The system shall allow registered users to make publishable information about bike paths
R17	The system shall allow registered users to add info about the status of a bike path
R18	The system shall allow registered users to add the presence of relevant obstacles on the bike path
R19	The system shall recognise if the users are cycling on an exists bike path

Continue in the next page...

ID	Description
R20	The system shall recognise if the users are cycling on a path where cars are rare and speed limits under 50kmh
R21	The system shall calculate the distance of a path
R22	The system shall allow registered users to manually insert bike path data by specifying the names of the streets included in the path
R23	The system shall allow registered users to manually specify the status of the street
R24	The system shall allow users to manually report the presence of obstacles on the street
R25	The system shall automatically infer that the registered user is cycling based on their speed
R26	The system shall collect GPS data to reconstruct the path followed by the user during the ride
R27	The system shall acquire data from the mobile device's accelerometer and gyroscope to detect basic metrics
R28	The system shall analyze sensor data to identify potential path irregularities
R29	The system shall require the user to confirm or correct the automatically acquired data
R30	The system shall allow registered users to mark their inserted data as "publishable" to make it available to the community
R31	The system shall merge information about the same path from multiple users
R32	The system shall prioritize data based on timeframe of execution and the number of confirmations to determine the current status
R33	The system shall allow any user to search for bike paths by specifying an origin and a destination
R34	The system shall find for its data bike paths where an origin and a destination are specified by any users
R35	The system shall visualize the bike paths connecting the specified origin and destination on a map
R36	The system shall compute a score for each path based on its status and its effectiveness in reaching the destination from the origin
R37	If multiple paths exist, from the user's request the system shall display them sorted by their calculated score

Table 3.1: Requirements List

3.1.2. Use Cases Diagrams




Figure 3.1: Use Cases

3.1.3. Use Cases

In this section, they are explained and represented the main identified use cases. For each Use Case, the documentation follows a two-step structure:

- 1. Use Case Table: A structured table detailing specific fields
- 2. Diagram: A Sequence Diagram visualizing the steps described in the table

UC1. Sign in to BBP

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.2: Sign in to BBP




Figure 3.2: Sign in to BBP

UC2. Login to BBP

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.3: Login to BBP




Figure 3.3: Login to BBP

UC3. Logout to BBP

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.4: Logout to BBP




Figure 3.4: Logout to BBP

UC4. Recording with Manual Mode

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.5: Recording with Manual Mode




Figure 3.5: Recording with Manual Mode

UC5. Recording with Automated Mode

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.6: Recording with Automated Mode




Figure 3.6: Recording with Automated Mode

UC6. Personal Trip Storage

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.7: Personal Trip Storage




Figure 3.7: Personal Trip Storage

UC7. Search Path

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.8: Search Path




Figure 3.8: Search Path

UC8. Look Publish Path

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.9: Look Publish Path




Figure 3.9: Look Publish Path

UC9. Account Settings

Actor	abc
Entry conditions	abc
Event Flow	• abc
Exit condition	abc
Exceptions	• abc

Table 3.10: Account Settings




Figure 3.10: Account Settings

4 | Formal Analysis Using Alloy

For readability and simplicity motivations we decided to insert the most important objects of the model simplifying the complex ones (for example, individual nodes of streets are not modeled) and we kept what we thought was essential to verify simple assertions.

4.1. Signatures

4.1.1. Status

```
abstract sig Status{}
one sig Clear extends Status{}
one sig RoadWork extends Status{}
one sig Pothole extends Status{}
```

Listing 4.1: Status signature

An object Status is used to be associated with a street segment, therefore allowing us to better describe streets and to introduce potholes. The actual signature is abstract since we wanted to make the object expandable with more variants (we added Clear, RoadWork and Pothole as examples).

4.1.2. Segment

```
sig Segment{
        nextSegment: lone Segment,
        status: some Status
}{
        // a segment cannot point to itself as next
        // (but cycles are allowed)
        nextSegment != this

        // if status is clear then its the only status possible
        Clear in status implies #status = 1
}
```

Listing 4.2: Segment signature

An object Segment is used to model street segments: every segment is connected to at most another segment (forming what actively is a chain of streets). To have consistent segments, they are to be considered as a part of a physical street and they also model direction of said street: therefore two different segments can be the same street segment but traversed in opposite direction, this implies that a necessary condition that we need to add is that a segment cannot connect to itself.

4.1.3. Path

```
sig Path{
        start: Segment,
        score: Int
}{
        // Paths are saved only if associated with
        // at least a Trip
        some t: Trip| t.path = this
}
```

Listing 4.3: Path signature

Following the definition of a Segment, a Path is simply an objects that keeps the first segment of an arbitrarily long chain of segments. Paths also have a score and, since paths are discovered and inserted by RegisteredUsers, it is necessary that a Trip (see Trip signature) has said Path associated to it.

4.1.4. Statistics

```
sig Statistics{}{
        // Statistics are saved only if associated
        // with at least a trip
        some t: Trip| t.averageSpeed = this
        or t.duration = this
        or t.externalStats = this
}
```

Listing 4.4: Statistics signature

4.1.5. Trip

```
sig Trip{
        path: one Path,
        averageSpeed: one Statistics,
        duration: one Statistics,
        externalStats: lone Statistics
}{
        // statistics are different
        averageSpeed != duration and duration != externalStats

        // Trips are saved only if associated with
        // at least a registered user
        one u: RegisteredUser| this in u.registeredTrips
}
```

Listing 4.5: Trip signature

A Trip is an object that has one single path, the statistics associated with the trip itself inserted by the user and the statistics retrieved from the external service. Because Trips are created by the user, it is necessary that every Trip has exactly one Path and that one RegisteredUser has registered said Trip.

4.1.6. RegisteredUser

```
sig RegisteredUser {
        registeredTrips: set Trip,
        publishedTrips: set Trip
}{
        // published trips are a subset of all registered trips
        publishedTrips in registeredTrips
}
```

Listing 4.6: RegisteredUser signature

5 Effort Spent

A table representing the total hours of work is shown here.

Work Areas	Alessandro Burato	Gabriele Crimella	Davide Faccin
Introduction	1.5h	1.5h	0h
Overall Description	0h	0h	0h
Specific Requirements	0h	0h	0h
Alloy	0h	0h	0h
Group Meetings and Reviews	8h	8h	8h

Table 5.1: Table of Effort

6 | References

Chapter 6

List of Figures

3.1 Use Cases 9
3.2 Sign in to BBP 11
3.3 Login to BBP 13
3.4 Logout to BBP 15
3.5 Recording with Manual Mode 17
3.6 Recording with Automated Mode 19
3.7 Personal Trip Storage 21
3.8 Search Path 23
3.9 Look Publish Path 25
3.10 Account Settings 27

List of Tables

1.1 List of Goals 2
1.2 World Phenomena 2
1.3 Machine Phenomena 3
1.4 Shared Phenomena – World-Controlled 3
1.5 Shared Phenomena – Machine-Controlled 4

3.1 Requirements List 8
3.2 Sign in to BBP 10
3.3 Login to BBP 12
3.4 Logout to BBP 14
3.5 Recording with Manual Mode 16
3.6 Recording with Automated Mode 18
3.7 Personal Trip Storage 20
3.8 Search Path 22
3.9 Look Publish Path 24
3.10 Account Settings 26

5.1 Table of Effort 33